

MMSE Approximation for the Sparse Prior


Dror Simon

Computer Science, Technion, Israel

January 16, 2019

Joint work with Jeremias Sulam, Yaniv Romano, Yue M. Lu and Michael Elad

Noise Removal



Noise Removal




Noise Removal



Why denoising?


Noise Removal



Why denoising?

- A simple testing ground for novel concepts in signal processing.

Noise Removal



Why denoising?

- A simple testing ground for novel concepts in signal processing.
- Can be generalized to other, more complicated applications.



**Noisy
Signal**

Noise Removal


**Noisy
Signal**

**Clean
Estimate**

Noise Removal



Noise Removal




Noise Removal – Bayesian Standpoint

Noise Removal – Bayesian Standpoint




Denoising


Noise Removal – Bayesian Standpoint




Noise Removal – Bayesian Standpoint




Noise Removal – Bayesian Standpoint



Noise Removal – Bayesian Standpoint



Noise Removal – Bayesian Standpoint




- 1 Bayesian Framework
 - The Generative Model
 - Bayesian Estimators
- 2 MMSE Approximation
 - Previous Work
- 3 Stochastic Resonance
 - Can Noise Help Denoising?
- 4 Our Proposed Method
 - The Algorithm
 - Unitary Case Analysis
 - The General Dictionary Case
 - Image Denoising
- 5 Conclusions

- 1 Bayesian Framework
 - The Generative Model
 - Bayesian Estimators
- 2 MMSE Approximation
 - Previous Work
- 3 Stochastic Resonance
 - Can Noise Help Denoising?
- 4 Our Proposed Method
 - The Algorithm
 - Unitary Case Analysis
 - The General Dictionary Case
 - Image Denoising
- 5 Conclusions


The Generative Model

$\mathbf{D} \in \mathbb{R}^{n \times m}$ is a dictionary with normalized columns.




The Generative Model

Each element i in α is non zero with probability $p_i \ll 1$.




The Generative Model

The non-zero elements of the sparse representation, denoted by α_s , are sampled from a Gaussian distribution $\alpha_s | s \sim \mathcal{N}(\mathbf{0}, \sigma_\alpha^2 \mathbf{I}_{|s|})$.




The Generative Model

The product $\mathbf{D}\alpha$ leads to a signal \mathbf{x} .




The Generative Model

We are given noisy measurements $\mathbf{y} = \mathbf{D}\boldsymbol{\alpha} + \boldsymbol{\nu}$, where $\boldsymbol{\nu}$ is a white Gaussian noise $\boldsymbol{\nu} \sim \mathcal{N}(\mathbf{0}, \sigma_{\nu}^2 \mathbf{I}_n)$.




The Generative Model – Results

¹Turek, Javier S., Irad Yavneh, and Michael Elad, 2011. "On MMSE and MAP denoising under sparse representation modeling over a unitary dictionary." 

The Generative Model – Results


- The prior probability of a support (Bernoulli):

$$p(s) = \prod_{i \in s} p_i \prod_{j \notin s} (1 - p_j).$$

¹Turek, Javier S., Irad Yavneh, and Michael Elad, 2011. "On MMSE and MAP denoising under sparse representation modeling over a unitary dictionary." 


The Generative Model – Results

- The prior probability of a support (Bernoulli):
 $p(s) = \prod_{i \in s} p_i \prod_{j \notin s} (1 - p_j).$
- When the support is known, \mathbf{y} and $\boldsymbol{\alpha}_s$ are jointly Gaussian
 $\mathbf{y} = \mathbf{D}_s \boldsymbol{\alpha}_s + \boldsymbol{\nu}$, leading to¹

¹Turek, Javier S., Irad Yavneh, and Michael Elad, 2011. "On MMSE and MAP denoising under sparse representation modeling over a unitary dictionary." 


The Generative Model – Results

- The prior probability of a support (Bernoulli):
 $p(s) = \prod_{i \in s} p_i \prod_{j \notin s} (1 - p_j).$
- When the support is known, \mathbf{y} and $\boldsymbol{\alpha}_s$ are jointly Gaussian
 $\mathbf{y} = \mathbf{D}_s \boldsymbol{\alpha}_s + \boldsymbol{\nu}$, leading to¹
 - $\mathbf{y}|s$ is Gaussian: $\mathbf{y}|s \sim \mathcal{N}(\mathbf{0}, \mathbf{C}_s).$

¹Turek, Javier S., Irad Yavneh, and Michael Elad, 2011. "On MMSE and MAP denoising under sparse representation modeling over a unitary dictionary." 

The Generative Model – Results


- The prior probability of a support (Bernoulli):
 $p(s) = \prod_{i \in s} p_i \prod_{j \notin s} (1 - p_j).$
- When the support is known, \mathbf{y} and α_s are jointly Gaussian
 $\mathbf{y} = \mathbf{D}_s \alpha_s + \nu$, leading to¹
 - $\mathbf{y}|s$ is Gaussian: $\mathbf{y}|s \sim \mathcal{N}(\mathbf{0}, \mathbf{C}_s).$
 - $\mathbf{y}|\alpha_s, s$ is Gaussian: $\mathbf{y}|\alpha_s, s \sim \mathcal{N}(\mathbf{D}_s \alpha_s, \sigma_\nu^2 \mathbf{I}_n).$

¹Turek, Javier S., Irad Yavneh, and Michael Elad, 2011. "On MMSE and MAP denoising under sparse representation modeling over a unitary dictionary." 

The Generative Model – Results

- The prior probability of a support (Bernoulli):
 $p(s) = \prod_{i \in s} p_i \prod_{j \notin s} (1 - p_j).$
- When the support is known, \mathbf{y} and α_s are jointly Gaussian
 $\mathbf{y} = \mathbf{D}_s \alpha_s + \nu$, leading to¹
 - $\mathbf{y}|s$ is Gaussian: $\mathbf{y}|s \sim \mathcal{N}(\mathbf{0}, \mathbf{C}_s).$
 - $\mathbf{y}|\alpha_s, s$ is Gaussian: $\mathbf{y}|\alpha_s, s \sim \mathcal{N}(\mathbf{D}_s \alpha_s, \sigma_\nu^2 \mathbf{I}_n).$
 - $\alpha_s|\mathbf{y}, s$ is Gaussian: $\alpha_s|\mathbf{y}, s \sim \mathcal{N}\left(\frac{1}{\sigma_\nu^2} \mathbf{Q}_s^{-1} \mathbf{D}_s^T \mathbf{y}, \mathbf{Q}_s^{-1}\right).$

$$\mathbf{C}_s = \sigma_\alpha^2 \mathbf{D}_s \mathbf{D}_s^T + \sigma_\nu^2 \mathbf{I}_n, \quad \mathbf{Q}_s = \frac{1}{\sigma_\alpha^2} \mathbf{I}_{|s|} + \frac{1}{\sigma_\nu} \mathbf{D}_s^T \mathbf{D}_s$$

¹Turek, Javier S., Irad Yavneh, and Michael Elad, 2011. "On MMSE and MAP denoising under sparse representation modeling over a unitary dictionary." 

- 1 Bayesian Framework
 - The Generative Model
 - Bayesian Estimators
- 2 MMSE Approximation
 - Previous Work
- 3 Stochastic Resonance
 - Can Noise Help Denoising?
- 4 Our Proposed Method
 - The Algorithm
 - Unitary Case Analysis
 - The General Dictionary Case
 - Image Denoising
- 5 Conclusions

The goal: Estimate α given the noisy measurements \mathbf{y} ,
i.e. denoise the signal.

The goal: Estimate α given the noisy measurements \mathbf{y} ,
i.e. denoise the signal.

Many estimators can be proposed. We focus our attention on three:

The goal: Estimate α given the noisy measurements \mathbf{y} ,
i.e. denoise the signal.

Many estimators can be proposed. We focus our attention on three:

- 1 The oracle estimator.

The goal: Estimate α given the noisy measurements \mathbf{y} ,
i.e. denoise the signal.

Many estimators can be proposed. We focus our attention on three:

- 1 The oracle estimator.
- 2 The Maximum A-posteriori Probability (MAP) estimator.

The goal: Estimate α given the noisy measurements \mathbf{y} ,
i.e. denoise the signal.

Many estimators can be proposed. We focus our attention on three:

- 1 The oracle estimator.
- 2 The Maximum A-posteriori Probability (MAP) estimator.
- 3 The Minimum Mean Square Error (MMSE) estimator.

The Bayesian Estimators

The Bayesian Estimators

Oracle Estimator

$$\hat{\alpha}_s^{\text{Oracle}} = \mathbb{E} \{ \alpha_s | s, \mathbf{y} \} = \frac{1}{\sigma_\nu^2} \mathbf{Q}_s^{-1} \mathbf{D}_s^T \mathbf{y}$$

MAP Support Estimator

$$\hat{s}_{\text{MAP}} = \arg \max_s p(s|\mathbf{y})$$

MAP Support Estimator

$$\hat{s}_{\text{MAP}} = \arg \max_s p(s|\mathbf{y}) = \arg \max_s p(s) p(\mathbf{y}|s)$$

MAP Support Estimator

$$\begin{aligned}\hat{s}_{\text{MAP}} &= \arg \max_s p(s|\mathbf{y}) = \arg \max_s p(s) p(\mathbf{y}|s) \\ &= \arg \max_s -\frac{1}{2} \mathbf{y}^T \mathbf{C}_s^{-1} \mathbf{y} - \frac{1}{2} \log \det(\mathbf{C}_s) \\ &\quad + \sum_{i \in s} \log(p_i) + \sum_{j \notin s} \log(1 - p_j)\end{aligned}$$

MAP Support Estimator

$$\begin{aligned}\hat{s}_{\text{MAP}} &= \arg \max_s p(s|\mathbf{y}) = \arg \max_s p(s) p(\mathbf{y}|s) \\ &= \arg \max_s -\frac{1}{2} \mathbf{y}^T \mathbf{C}_s^{-1} \mathbf{y} - \frac{1}{2} \log \det(\mathbf{C}_s) \\ &\quad + \sum_{i \in s} \log(p_i) + \sum_{j \notin s} \log(1 - p_j) \\ s &\in \{0, 1\}^m\end{aligned}$$

MMSE Estimator

$$\hat{\alpha}_{\text{MMSE}} = \arg \min_{\hat{\alpha}(\mathbf{y})} \mathbb{E} \left\{ \|\hat{\alpha}(\mathbf{y}) - \alpha\|_2^2 \middle| \mathbf{y} \right\}$$

MMSE Estimator

$$\hat{\alpha}_{\text{MMSE}} = \arg \min_{\hat{\alpha}(\mathbf{y})} \mathbb{E} \left\{ \|\hat{\alpha}(\mathbf{y}) - \alpha\|_2^2 \middle| \mathbf{y} \right\} = \mathbb{E} \{ \alpha | \mathbf{y} \}$$

MMSE Estimator

$$\begin{aligned}\hat{\alpha}_{\text{MMSE}} &= \arg \min_{\hat{\alpha}(\mathbf{y})} \mathbb{E} \left\{ \|\hat{\alpha}(\mathbf{y}) - \alpha\|_2^2 \middle| \mathbf{y} \right\} = \mathbb{E} \{ \alpha | \mathbf{y} \} \\ &= \mathbb{E}_{s|\mathbf{y}} \left\{ \mathbb{E}_{\alpha|\mathbf{y},s} \{ \alpha | \mathbf{y}, s \} \right\}\end{aligned}$$

MMSE Estimator

$$\begin{aligned}\hat{\alpha}_{\text{MMSE}} &= \arg \min_{\hat{\alpha}(\mathbf{y})} \mathbb{E} \left\{ \|\hat{\alpha}(\mathbf{y}) - \alpha\|_2^2 \middle| \mathbf{y} \right\} = \mathbb{E} \{ \alpha | \mathbf{y} \} \\ &= \mathbb{E}_{s|\mathbf{y}} \left\{ \mathbb{E}_{\alpha|\mathbf{y},s} \{ \alpha | \mathbf{y}, s \} \right\} = \sum_{s \in \{0,1\}^m} p(s|\mathbf{y}) \hat{\alpha}_s^{\text{Oracle}}\end{aligned}$$

Bayesian Estimators – Summary

- Both estimators are practically impossible to obtain.

Bayesian Estimators – Summary

- Both estimators are practically impossible to obtain.
 - MAP – compute the posterior probability of each of the 2^m supports and pick the most probable one.

Bayesian Estimators – Summary

- Both estimators are practically impossible to obtain.
 - MAP – compute the posterior probability of each of the 2^m supports and pick the most probable one.
 - MMSE – compute the posterior probability of each support and use them as weights for all the possible oracle estimators.

Bayesian Estimators – Summary

- Both estimators are practically impossible to obtain.
 - MAP – compute the posterior probability of each of the 2^m supports and pick the most probable one.
 - MMSE – compute the posterior probability of each support and use them as weights for all the possible oracle estimators.
- How is this issue resolved?

Bayesian Estimators – Summary

- Both estimators are practically impossible to obtain.
 - MAP – compute the posterior probability of each of the 2^m supports and pick the most probable one.
 - MMSE – compute the posterior probability of each support and use them as weights for all the possible oracle estimators.
- How is this issue resolved?
 - MAP – use an approximation algorithm (greedy or relaxed) to recover a likely support, and then use the oracle.

Bayesian Estimators – Summary

- Both estimators are practically impossible to obtain.
 - MAP – compute the posterior probability of each of the 2^m supports and pick the most probable one.
 - MMSE – compute the posterior probability of each support and use them as weights for all the possible oracle estimators.
- How is this issue resolved?
 - MAP – use an approximation algorithm (greedy or relaxed) to recover a likely support, and then use the oracle.
 - MMSE – usually avoided.

Bayesian Estimators – Summary

- Both estimators are practically impossible to obtain.
 - MAP – compute the posterior probability of each of the 2^m supports and pick the most probable one.
 - MMSE – compute the posterior probability of each support and use them as weights for all the possible oracle estimators.
- How is this issue resolved?
 - MAP – use an approximation algorithm (greedy or relaxed) to recover a likely support, and then use the oracle.
 - MMSE – usually avoided.
- Can we do better?

- 1 Bayesian Framework
 - The Generative Model
 - Bayesian Estimators
- 2 MMSE Approximation
 - Previous Work
- 3 Stochastic Resonance
 - Can Noise Help Denoising?
- 4 Our Proposed Method
 - The Algorithm
 - Unitary Case Analysis
 - The General Dictionary Case
 - Image Denoising
- 5 Conclusions

- 1 Bayesian Framework
 - The Generative Model
 - Bayesian Estimators
- 2 MMSE Approximation
 - Previous Work
- 3 Stochastic Resonance
 - Can Noise Help Denoising?
- 4 Our Proposed Method
 - The Algorithm
 - Unitary Case Analysis
 - The General Dictionary Case
 - Image Denoising
- 5 Conclusions

Elad, Michael, and Irad Yavneh, 2009. "A plurality of sparse representations is better than the sparsest one alone."

- A modified version of the OMP algorithm.

Elad, Michael, and Irad Yavneh, 2009. "A plurality of sparse representations is better than the sparsest one alone."

- A modified version of the OMP algorithm.
 - OMP: picks the atom most correlated with the current residual.

Elad, Michael, and Irad Yavneh, 2009. "A plurality of sparse representations is better than the sparsest one alone."

- A modified version of the OMP algorithm.
 - OMP: picks the atom most correlated with the current residual.
 - RandOMP: weights the unpicked atoms according to their correlation with the residual, and chooses randomly.

Elad, Michael, and Irad Yavneh, 2009. "A plurality of sparse representations is better than the sparsest one alone."

Random OMP

- A modified version of the OMP algorithm.
 - OMP: picks the atom most correlated with the current residual.
 - RandOMP: weights the unpicked atoms according to their correlation with the residual, and chooses randomly.
- Repeated many times leading to a variety of solutions.

Elad, Michael, and Irad Yavneh, 2009. "A plurality of sparse representations is better than the sparsest one alone."

Random OMP

- A modified version of the OMP algorithm.
 - OMP: picks the atom most correlated with the current residual.
 - RandOMP: weights the unpicked atoms according to their correlation with the residual, and chooses randomly.
- Repeated many times leading to a variety of solutions.
- Averages the solutions to retrieve a final estimate.

Elad, Michael, and Irad Yavneh, 2009. "A plurality of sparse representations is better than the sparsest one alone."

- A modified version of the OMP algorithm.
 - OMP: picks the atom most correlated with the current residual.
 - RandOMP: weights the unpicked atoms according to their correlation with the residual, and chooses randomly.
- Repeated many times leading to a variety of solutions.
- Averages the solutions to retrieve a final estimate.
- Asymptotically converges with the MMSE estimator when:
 - The dictionary is unitary.
 - The cardinality of the sparse representation is 1.

Elad, Michael, and Irad Yavneh, 2009. "A plurality of sparse representations is better than the sparsest one alone."

- A modified version of the OMP algorithm.
 - OMP: picks the atom most correlated with the current residual.
 - RandOMP: weights the unpicked atoms according to their correlation with the residual, and chooses randomly.
- Repeated many times leading to a variety of solutions.
- Averages the solutions to retrieve a final estimate.
- Asymptotically converges with the MMSE estimator when:
 - The dictionary is unitary.
 - The cardinality of the sparse representation is 1.
- Empirically achieves better MSE than OMP even when these conditions are not met.

Elad, Michael, and Irad Yavneh, 2009. "A plurality of sparse representations is better than the sparsest one alone."

MMSE Approximation Methods

Why do these methods work?

MMSE Approximation Methods

Why do these methods work?

- $p(s|\mathbf{y})$ has an exponential nature.

MMSE Approximation Methods

Why do these methods work?

- $p(s|\mathbf{y})$ has an exponential nature. \Rightarrow The estimator is dominated by a small set of solutions.

MMSE Approximation Methods

Why do these methods work?

- $p(s|\mathbf{y})$ has an exponential nature. \Rightarrow The estimator is dominated by a small set of solutions.

$$\hat{\alpha}_{\text{MMSE}} = \sum_{s \in \{0,1\}^m} p(s|\mathbf{y}) \hat{\alpha}_s^{\text{Oracle}} \approx \sum_{s \in \omega \subset \{0,1\}^m} p(s|\mathbf{y}) \hat{\alpha}_s^{\text{Oracle}}$$

MMSE Approximation Methods

Why do these methods work?

- $p(s|\mathbf{y})$ has an exponential nature. \Rightarrow The estimator is dominated by a small set of solutions.

$$\hat{\alpha}_{\text{MMSE}} = \sum_{s \in \{0,1\}^m} p(s|\mathbf{y}) \hat{\alpha}_s^{\text{Oracle}} \approx \sum_{s \in \omega \subset \{0,1\}^m} p(s|\mathbf{y}) \hat{\alpha}_s^{\text{Oracle}}$$

- These methods find a “dominant” subset ω of supports and approximate their weights (posterior probabilities).

MMSE Approximation Methods

Why do these methods work?

- $p(s|\mathbf{y})$ has an exponential nature. \Rightarrow The estimator is dominated by a small set of solutions.

$$\hat{\alpha}_{\text{MMSE}} = \sum_{s \in \{0,1\}^m} p(s|\mathbf{y}) \hat{\alpha}_s^{\text{Oracle}} \approx \sum_{s \in \omega \subset \{0,1\}^m} p(s|\mathbf{y}) \hat{\alpha}_s^{\text{Oracle}}$$

- These methods find a “dominant” subset ω of supports and approximate their weights (posterior probabilities).

Previously suggested algorithms operate in a greedy fashion.

MMSE Approximation Methods

Why do these methods work?

- $p(s|\mathbf{y})$ has an exponential nature. \Rightarrow The estimator is dominated by a small set of solutions.

$$\hat{\alpha}_{\text{MMSE}} = \sum_{s \in \{0,1\}^m} p(s|\mathbf{y}) \hat{\alpha}_s^{\text{Oracle}} \approx \sum_{s \in \omega \subset \{0,1\}^m} p(s|\mathbf{y}) \hat{\alpha}_s^{\text{Oracle}}$$

- These methods find a “dominant” subset ω of supports and approximate their weights (posterior probabilities).

Previously suggested algorithms operate in a greedy fashion.

\Rightarrow **They are impractical for high dimensional signals.**

- 1 Bayesian Framework
 - The Generative Model
 - Bayesian Estimators
- 2 MMSE Approximation
 - Previous Work
- 3 Stochastic Resonance
 - Can Noise Help Denoising?
- 4 Our Proposed Method
 - The Algorithm
 - Unitary Case Analysis
 - The General Dictionary Case
 - Image Denoising
- 5 Conclusions

- 1 Bayesian Framework
 - The Generative Model
 - Bayesian Estimators
- 2 MMSE Approximation
 - Previous Work
- 3 Stochastic Resonance
 - Can Noise Help Denoising?
- 4 Our Proposed Method
 - The Algorithm
 - Unitary Case Analysis
 - The General Dictionary Case
 - Image Denoising
- 5 Conclusions

Definition

- Originally, was suggested as an explanation to the periodic recurrence of ice ages.
- Today, broadly applied to describe a more general phenomenon where presence of noise in a *nonlinear* system provides a better response.

Definition

- Originally, was suggested as an explanation to the periodic recurrence of ice ages.
- Today, broadly applied to describe a more general phenomenon where presence of noise in a *nonlinear* system provides a better response.

Noise **improves** system performance?



Dither – Noise Has a Constructive Value


Dither

- In signal quantization, additive noise is used to create stochastic quantization error.
- For example in images, dither prevents color banding which creates unpleasant images.

Dither – Noise Has a Constructive Value

Dither



- In signal quantization, additive noise is used to create stochastic quantization error.
- For example in images, dither prevents color banding which creates unpleasant images.



Dither – Noise Has a Constructive Value

Dither



- In signal quantization, additive noise is used to create stochastic quantization error.
- For example in images, dither prevents color banding which creates unpleasant images.



Dither – Noise Has a Constructive Value

Dither



- In signal quantization, additive noise is used to create stochastic quantization error.
- For example in images, dither prevents color banding which creates unpleasant images.



Dither – Noise Has a Constructive Value

Dither

- In signal quantization, additive noise is used to create stochastic quantization error.
- For example in images, dither prevents color banding which creates unpleasant images.



Noise 

- 1 Bayesian Framework
 - The Generative Model
 - Bayesian Estimators
- 2 MMSE Approximation
 - Previous Work
- 3 Stochastic Resonance
 - Can Noise Help Denoising?
- 4 Our Proposed Method
 - The Algorithm
 - Unitary Case Analysis
 - The General Dictionary Case
 - Image Denoising
- 5 Conclusions

- 1 Bayesian Framework
 - The Generative Model
 - Bayesian Estimators
- 2 MMSE Approximation
 - Previous Work
- 3 Stochastic Resonance
 - Can Noise Help Denoising?
- 4 Our Proposed Method
 - The Algorithm
 - Unitary Case Analysis
 - The General Dictionary Case
 - Image Denoising
- 5 Conclusions

The Proposed Algorithm


y

The Proposed Algorithm


n

y


The Proposed Algorithm




The Proposed Algorithm




The Proposed Algorithm




The Proposed Algorithm



The Proposed Algorithm



The Proposed Algorithm



The Proposed Algorithm

Algorithm 1: Stochastic Resonance MMSE Approximation

input : \mathbf{y}, \mathbf{D} , PursuitMethod, σ_n, K

The Proposed Algorithm

Algorithm 1: Stochastic Resonance MMSE Approximation

input : \mathbf{y}, \mathbf{D} , PursuitMethod, σ_n, K

output: $\hat{\alpha}$

The Proposed Algorithm

Algorithm 1: Stochastic Resonance MMSE Approximation

input : \mathbf{y}, \mathbf{D} , PursuitMethod, σ_n, K

output: $\hat{\alpha}$

for $k \in 1 \dots K$ **do**

|

The Proposed Algorithm

Algorithm 1: Stochastic Resonance MMSE Approximation

input : \mathbf{y}, \mathbf{D} , PursuitMethod, σ_n, K

output: $\hat{\alpha}$

for $k \in 1 \dots K$ **do**

$\mathbf{n}_k \leftarrow \text{SampleNoise}(\sigma_n)$

The Proposed Algorithm

Algorithm 1: Stochastic Resonance MMSE Approximation

input : \mathbf{y}, \mathbf{D} , PursuitMethod, σ_n, K

output: $\hat{\alpha}$

for $k \in 1 \dots K$ **do**

$\mathbf{n}_k \leftarrow \text{SampleNoise}(\sigma_n)$

$\tilde{\alpha}_k \leftarrow \text{PursuitMethod}(\mathbf{y} + \mathbf{n}_k, \mathbf{D})$

The Proposed Algorithm

Algorithm 1: Stochastic Resonance MMSE Approximation

input : \mathbf{y}, \mathbf{D} , PursuitMethod, σ_n, K

output: $\hat{\alpha}$

for $k \in 1 \dots K$ **do**

$\mathbf{n}_k \leftarrow \text{SampleNoise}(\sigma_n)$

$\tilde{\alpha}_k \leftarrow \text{PursuitMethod}(\mathbf{y} + \mathbf{n}_k, \mathbf{D})$

$\hat{S}_k \leftarrow \text{Support}(\tilde{\alpha}_k)$

The Proposed Algorithm

Algorithm 1: Stochastic Resonance MMSE Approximation

input : \mathbf{y}, \mathbf{D} , PursuitMethod, σ_n, K

output: $\hat{\alpha}$

for $k \in 1 \dots K$ **do**

$\mathbf{n}_k \leftarrow \text{SampleNoise}(\sigma_n)$

$\tilde{\alpha}_k \leftarrow \text{PursuitMethod}(\mathbf{y} + \mathbf{n}_k, \mathbf{D})$

$\hat{S}_k \leftarrow \text{Support}(\tilde{\alpha}_k)$

$\hat{\alpha}_k \leftarrow \hat{\alpha}_{\hat{S}_k}^{\text{Oracle}}(\mathbf{y})$

end

The Proposed Algorithm

Algorithm 1: Stochastic Resonance MMSE Approximation

input : \mathbf{y}, \mathbf{D} , PursuitMethod, σ_n, K

output: $\hat{\alpha}$

for $k \in 1 \dots K$ **do**

$\mathbf{n}_k \leftarrow \text{SampleNoise}(\sigma_n)$

$\tilde{\alpha}_k \leftarrow \text{PursuitMethod}(\mathbf{y} + \mathbf{n}_k, \mathbf{D})$

$\hat{S}_k \leftarrow \text{Support}(\tilde{\alpha}_k)$

$\hat{\alpha}_k \leftarrow \hat{\alpha}_{\hat{S}_k}^{\text{Oracle}}(\mathbf{y})$

end

$\hat{\alpha} \leftarrow \frac{1}{K} \sum_{k=1}^K \hat{\alpha}_k$

The Proposed Algorithm – Does It Work?

- $\mathbf{D} \in \mathbb{R}^{50 \times 100}$ a normalized random dictionary.

The Proposed Algorithm – Does It Work?

- $\mathbf{D} \in \mathbb{R}^{50 \times 100}$ a normalized random dictionary.
- $\|\boldsymbol{\alpha}\|_0 = 1, \boldsymbol{\alpha}_s \sim \mathcal{N}(0, 1)$.

The Proposed Algorithm – Does It Work?


- $\mathbf{D} \in \mathbb{R}^{50 \times 100}$ a normalized random dictionary.
- $\|\boldsymbol{\alpha}\|_0 = 1, \boldsymbol{\alpha}_s \sim \mathcal{N}(0, 1)$.
- $\boldsymbol{\nu} \sim \mathcal{N}(\mathbf{0}, \sigma_\nu^2 \mathbf{I}_{50}), \sigma_\nu = 0.2$.

The Proposed Algorithm – Does It Work?

- $\mathbf{D} \in \mathbb{R}^{50 \times 100}$ a normalized random dictionary.
- $\|\boldsymbol{\alpha}\|_0 = 1, \boldsymbol{\alpha}_s \sim \mathcal{N}(0, 1)$.
- $\boldsymbol{\nu} \sim \mathcal{N}(\mathbf{0}, \sigma_\nu^2 \mathbf{I}_{50}), \sigma_\nu = 0.2$.
- 100 iterations of stochastic resonance.

The Proposed Algorithm – Does It Work?

- $\mathbf{D} \in \mathbb{R}^{50 \times 100}$ a normalized random dictionary.
- $\|\alpha\|_0 = 1, \alpha_s \sim \mathcal{N}(0, 1)$.
- $\nu \sim \mathcal{N}(\mathbf{0}, \sigma_\nu^2 \mathbf{I}_{50}), \sigma_\nu = 0.2$.
- 100 iterations of stochastic resonance.



- 1 Bayesian Framework
 - The Generative Model
 - Bayesian Estimators
- 2 MMSE Approximation
 - Previous Work
- 3 Stochastic Resonance
 - Can Noise Help Denoising?
- 4 Our Proposed Method
 - The Algorithm
 - Unitary Case Analysis
 - The General Dictionary Case
 - Image Denoising
- 5 Conclusions

Unitary Case - Estimators

When \mathbf{D} is a unitary matrix ($\mathbf{D}^T \mathbf{D} = \mathbf{I}$), the oracle, MAP and MMSE estimators are element-wise shrinkage operators:

c and λ_{MAP} depend on p_i, σ_α and σ_ν .

Unitary Case - Estimators

When \mathbf{D} is a unitary matrix ($\mathbf{D}^T \mathbf{D} = \mathbf{I}$), the oracle, MAP and MMSE estimators are element-wise shrinkage operators:

Oracle

$$\hat{\alpha}_s^{\text{Oracle}}(\mathbf{y}) = c^2 \mathbf{D}_s^T \mathbf{y} = c^2 \beta_s$$

c and λ_{MAP} depend on p_i, σ_α and σ_ν .

Unitary Case - Estimators

When \mathbf{D} is a unitary matrix ($\mathbf{D}^T \mathbf{D} = \mathbf{I}$), the oracle, MAP and MMSE estimators are element-wise shrinkage operators:

MAP

$$\hat{\alpha}_{\text{MAP}}(\mathbf{y}) = \mathcal{H}_{\lambda_{\text{MAP}}}(\mathbf{D}^T \mathbf{y}) = \mathcal{H}_{\lambda_{\text{MAP}}}(\boldsymbol{\beta})$$

c and λ_{MAP} depend on p_i, σ_α and σ_ν .

Unitary Case - Estimators

When \mathbf{D} is a unitary matrix ($\mathbf{D}^T \mathbf{D} = \mathbf{I}$), the oracle, MAP and MMSE estimators are element-wise shrinkage operators:

MAP

$$\hat{\alpha}_{\text{MAP}}(\mathbf{y}) = \mathcal{H}_{\lambda_{\text{MAP}}}(\mathbf{D}^T \mathbf{y}) = \mathcal{H}_{\lambda_{\text{MAP}}}(\boldsymbol{\beta})$$
$$\mathcal{H}_{\lambda_{\text{MAP}}}(\beta_i) = \begin{cases} c^2 \beta_i & \text{if } |\beta_i| \geq \lambda_{\text{MAP}}, \\ 0 & \text{else} \end{cases}$$

c and λ_{MAP} depend on p_i, σ_α and σ_ν .

Unitary Case - Estimators


When \mathbf{D} is a unitary matrix ($\mathbf{D}^T \mathbf{D} = \mathbf{I}$), the oracle, MAP and MMSE estimators are element-wise shrinkage operators:

MMSE

$$\hat{\alpha}_i^{MMSE}(\beta_i) = \frac{\exp\left(\frac{c^2}{2\sigma_\nu^2} \beta_i^2\right) \frac{p_i}{1-p_i} \sqrt{1-c^2}}{1 + \exp\left(\frac{c^2}{2\sigma_\nu^2} \beta_i^2\right) \frac{p_i}{1-p_i} \sqrt{1-c^2}} c^2 \beta_i$$

c and λ_{MAP} depend on p_i, σ_α and σ_ν .

Unitary Case – Estimators



Unitary Case – Stochastic Resonance

To use our proposed algorithm we need to provide a pursuit.

Algorithm 1

Unitary Case – Stochastic Resonance

To use our proposed algorithm we need to provide a pursuit.
The MAP is attainable.

Algorithm 1

Unitary Case – Stochastic Resonance

To use our proposed algorithm we need to provide a pursuit.
The MAP is attainable. \implies Use it!

Algorithm 1

Unitary Case – Stochastic Resonance

To use our proposed algorithm we need to provide a pursuit.
The MAP is attainable. \implies Use it!

Algorithm 1

Subtractive hard-thresholding $\mathcal{H}^{-}(\cdot)$

$$\mathcal{H}^{-}(\beta, \tilde{n}) = \begin{cases} & \text{if } |\beta + \tilde{n}| \geq \lambda_{\text{MAP}}, \\ 0 & \text{otherwise.} \end{cases}$$

Unitary Case – Stochastic Resonance

To use our proposed algorithm we need to provide a pursuit.
The MAP is attainable. \implies Use it!

Algorithm 1

Subtractive hard-thresholding $\mathcal{H}^- (\cdot)$

$$\mathcal{H}^- (\beta, \tilde{n}) = \begin{cases} c^2 \beta & \text{if } |\beta + \tilde{n}| \geq \lambda_{\text{MAP}}, \\ 0 & \text{otherwise.} \end{cases}$$

Unitary Case – Stochastic Resonance

To use our proposed algorithm we need to provide a pursuit.
The MAP is attainable. \implies Use it!

Algorithm 1

Subtractive hard-thresholding $\mathcal{H}^{-}(\cdot)$

$$\mathcal{H}^{-}(\beta, \tilde{n}) = \begin{cases} c^2 \beta & \text{if } |\beta + \tilde{n}| \geq \lambda_{\text{MAP}}, \\ 0 & \text{otherwise.} \end{cases}$$

Unitary Case – Stochastic Resonance

To use our proposed algorithm we need to provide a pursuit.
The MAP is attainable. \implies Use it!

Algorithm 1

Subtractive hard-thresholding $\mathcal{H}^{-}(\cdot)$

$$\mathcal{H}^{-}(\beta, \tilde{n}) = \begin{cases} c^2 \beta & \text{if } |\beta + \tilde{n}| \geq \lambda, \\ 0 & \text{otherwise.} \end{cases}$$

Unitary Case – Asymptotic Estimator

What happens as $K \rightarrow \infty$?

Unitary Case – Asymptotic Estimator

What happens as $K \rightarrow \infty$?

$$\hat{\alpha}_k(\beta, \tilde{n}_k) = \mathcal{H}^-(\beta, \tilde{n}_k) = \begin{cases} c^2\beta & \text{if } |\beta + \tilde{n}_k| \geq \lambda, \\ 0 & \text{otherwise.} \end{cases}$$

Unitary Case – Asymptotic Estimator

What happens as $K \rightarrow \infty$?

$$\hat{\alpha}_k(\beta, \tilde{n}_k) = \mathcal{H}^-(\beta, \tilde{n}_k) = \begin{cases} c^2\beta & \text{if } |\beta + \tilde{n}_k| \geq \lambda, \\ 0 & \text{otherwise.} \end{cases}$$

$$\hat{\alpha} = \lim_{K \rightarrow \infty} \frac{1}{K} \sum_{k=1}^K \hat{\alpha}_k = \mathbb{E}_n \{\hat{\alpha}_k\}$$

Unitary Case – Asymptotic Estimator

What happens as $K \rightarrow \infty$?

$$\hat{\alpha}_k(\beta, \tilde{n}_k) = \mathcal{H}^-(\beta, \tilde{n}_k) = \begin{cases} c^2\beta & \text{if } |\beta + \tilde{n}_k| \geq \lambda, \\ 0 & \text{otherwise.} \end{cases}$$

$$\hat{\alpha} = \lim_{K \rightarrow \infty} \frac{1}{K} \sum_{k=1}^K \hat{\alpha}_k = \mathbb{E}_n \{\hat{\alpha}_k\} = \int_{-\infty}^{\infty} \mathcal{H}^-(\beta, \tilde{n}) p(\tilde{n}) d\tilde{n}$$

Unitary Case – Asymptotic Estimator

What happens as $K \rightarrow \infty$?

$$\hat{\alpha}_k(\beta, \tilde{n}_k) = \mathcal{H}^-(\beta, \tilde{n}_k) = \begin{cases} c^2\beta & \text{if } |\beta + \tilde{n}_k| \geq \lambda, \\ 0 & \text{otherwise.} \end{cases}$$

$$\begin{aligned} \hat{\alpha} &= \lim_{K \rightarrow \infty} \frac{1}{K} \sum_{k=1}^K \hat{\alpha}_k = \mathbb{E}_n \{\hat{\alpha}_k\} = \int_{-\infty}^{\infty} \mathcal{H}^-(\beta, \tilde{n}) p(\tilde{n}) d\tilde{n} \\ &= \dots \end{aligned}$$

Unitary Case – Asymptotic Estimator

What happens as $K \rightarrow \infty$?

$$\hat{\alpha}_k(\beta, \tilde{n}_k) = \mathcal{H}^-(\beta, \tilde{n}_k) = \begin{cases} c^2\beta & \text{if } |\beta + \tilde{n}_k| \geq \lambda, \\ 0 & \text{otherwise.} \end{cases}$$

$$\begin{aligned} \hat{\alpha} &= \lim_{K \rightarrow \infty} \frac{1}{K} \sum_{k=1}^K \hat{\alpha}_k = \mathbb{E}_n \{ \hat{\alpha}_k \} = \int_{-\infty}^{\infty} \mathcal{H}^-(\beta, \tilde{n}) p(\tilde{n}) d\tilde{n} \\ &= \dots \\ &= c^2\beta \left[Q\left(\frac{\lambda + \beta}{\sigma_n}\right) + Q\left(\frac{\lambda - \beta}{\sigma_n}\right) \right] \end{aligned}$$


$$Q(x) = \int_x^{\infty} e^{-\frac{t^2}{2}} dt$$

Unitary Case – Empirical Performance

How does this estimator perform?


Unitary Case – Empirical Performance

How does this estimator perform?



Unitary Case – Empirical Performance

How does this estimator perform?



Stochastic Resonance vs. MMSE

Are the two the same?

Stochastic Resonance & MMSE

$$\hat{\alpha}_{\text{stochastic}} = c^2 \beta \left[Q \left(\frac{\lambda + \beta}{\sigma_n} \right) + Q \left(\frac{\lambda - \beta}{\sigma_n} \right) \right]$$

$$\hat{\alpha}_{\text{MMSE}} = \frac{\exp \left(\frac{c^2}{2\sigma_v^2} \beta^2 \right) \frac{p_i}{1-p_i} \sqrt{1-c^2}}{1 + \exp \left(\frac{c^2}{2\sigma_v^2} \beta^2 \right) \frac{p_i}{1-p_i} \sqrt{1-c^2}} c^2 \beta$$

Stochastic Resonance vs. MMSE

Are the two the same?

Stochastic Resonance & MMSE

$$\hat{\alpha}_{\text{stochastic}} = c^2 \beta \left[Q \left(\frac{\lambda + \beta}{\sigma_n} \right) + Q \left(\frac{\lambda - \beta}{\sigma_n} \right) \right]$$

$$\hat{\alpha}_{\text{MMSE}} = \frac{\exp \left(\frac{c^2}{2\sigma_v^2} \beta^2 \right) \frac{p_i}{1-p_i} \sqrt{1-c^2}}{1 + \exp \left(\frac{c^2}{2\sigma_v^2} \beta^2 \right) \frac{p_i}{1-p_i} \sqrt{1-c^2}} c^2 \beta$$

No... But are they close?

Stochastic Resonance vs. MMSE

Are the two the same?

Stochastic Resonance & MMSE

$$\hat{\alpha}_{\text{stochastic}} = c^2 \beta \left[Q \left(\frac{\lambda + \beta}{\sigma_n} \right) + Q \left(\frac{\lambda - \beta}{\sigma_n} \right) \right]$$

$$\hat{\alpha}_{\text{MMSE}} = \frac{\exp \left(\frac{c^2}{2\sigma_v^2} \beta^2 \right) \frac{p_i}{1-p_i} \sqrt{1-c^2}}{1 + \exp \left(\frac{c^2}{2\sigma_v^2} \beta^2 \right) \frac{p_i}{1-p_i} \sqrt{1-c^2}} c^2 \beta$$

No... But are they close?

Empirically yes, but for the right choice of parameters.

Stochastic Resonance vs. MMSE

Are the two the same?

Stochastic Resonance & MMSE

$$\hat{\alpha}_{\text{stochastic}} = c^2 \beta \left[Q \left(\frac{\lambda + \beta}{\sigma_n} \right) + Q \left(\frac{\lambda - \beta}{\sigma_n} \right) \right]$$

$$\hat{\alpha}_{\text{MMSE}} = \frac{\exp \left(\frac{c^2}{2\sigma_v^2} \beta^2 \right) \frac{p_i}{1-p_i} \sqrt{1-c^2}}{1 + \exp \left(\frac{c^2}{2\sigma_v^2} \beta^2 \right) \frac{p_i}{1-p_i} \sqrt{1-c^2}} c^2 \beta$$

No... But are they close?

Empirically yes, but for the right choice of parameters.

We can set the parameters by using SURE.

Stochastic Resonance vs. MMSE

Are the two the same?

Stochastic Resonance & MMSE

$$\hat{\alpha}_{\text{stochastic}} = c^2 \beta \left[Q \left(\frac{\lambda + \beta}{\sigma_n} \right) + Q \left(\frac{\lambda - \beta}{\sigma_n} \right) \right]$$

$$\hat{\alpha}_{\text{MMSE}} = \frac{\exp \left(\frac{c^2}{2\sigma_v^2} \beta^2 \right) \frac{p_i}{1-p_i} \sqrt{1-c^2}}{1 + \exp \left(\frac{c^2}{2\sigma_v^2} \beta^2 \right) \frac{p_i}{1-p_i} \sqrt{1-c^2}} c^2 \beta$$


No... But are they close?

Empirically yes, but for the right choice of parameters.


We can set the parameters by using SURE.

More information in our paper.

Unitary Case – Summary



Unitary Case – Summary



- 1 Bayesian Framework
 - The Generative Model
 - Bayesian Estimators
- 2 MMSE Approximation
 - Previous Work
- 3 Stochastic Resonance
 - Can Noise Help Denoising?
- 4 Our Proposed Method
 - The Algorithm
 - Unitary Case Analysis
 - The General Dictionary Case
 - Image Denoising
- 5 Conclusions

The General Dictionary Case

The General Dictionary Case

- The general case is harder to analyze.

The General Dictionary Case

- The general case is harder to analyze.
- The MAP estimator is exhaustive \implies use a pursuit algorithm instead.

The General Dictionary Case

- The general case is harder to analyze.
- The MAP estimator is exhaustive \implies use a pursuit algorithm instead.
- The performance (and the analysis) depends on the pursuit used.

The General Dictionary Case

- The general case is harder to analyze.
- The MAP estimator is exhaustive \implies use a pursuit algorithm instead.
- The performance (and the analysis) depends on the pursuit used.
- We separate to two cases:

The General Dictionary Case

- The general case is harder to analyze.
- The MAP estimator is exhaustive \implies use a pursuit algorithm instead.
- The performance (and the analysis) depends on the pursuit used.
- We separate to two cases:
 - The generative model's parameters are known.

The General Dictionary Case

- The general case is harder to analyze.
- The MAP estimator is exhaustive \implies use a pursuit algorithm instead.
- The performance (and the analysis) depends on the pursuit used.
- We separate to two cases:
 - The generative model's parameters are known.
 - The generative model's parameters are not known.

General Case – Known Parameters

General Case – Known Parameters

- The parameters are known \implies use them.

General Case – Known Parameters

- The parameters are known \implies use them.
- Replace the arithmetic mean in the proposed algorithm with a weighted sum.

General Case – Known Parameters

- The parameters are known \implies use them.
- Replace the arithmetic mean in the proposed algorithm with a weighted sum.
- The weights are obtained by:

General Case – Known Parameters

- The parameters are known \implies use them.
- Replace the arithmetic mean in the proposed algorithm with a weighted sum.
- The weights are obtained by:
 - The occurrence of each support.

General Case – Known Parameters

- The parameters are known \implies use them.
- Replace the arithmetic mean in the proposed algorithm with a weighted sum.
- The weights are obtained by:
 - The occurrence of each support.
 - The unnormalized posterior probability $p(s)p(\mathbf{y}|s)$.

General Case – Known Parameters

- The parameters are known \implies use them.
- Replace the arithmetic mean in the proposed algorithm with a weighted sum.
- The weights are obtained by:
 - The occurrence of each support.
 - The unnormalized posterior probability $p(s)p(\mathbf{y}|s)$.
- In our paper we prove it is equivalent to a Monte Carlo importance sampling simulation.

General Case – Known Parameters


- The parameters are known \implies use them.
- Replace the arithmetic mean in the proposed algorithm with a weighted sum.
- The weights are obtained by:
 - The occurrence of each support.
 - The unnormalized posterior probability $p(s)p(\mathbf{y}|s)$.
- In our paper we prove it is equivalent to a Monte Carlo importance sampling simulation.
 \implies Asymptotically converges to the MMSE!

General Case – Known Parameters

- $\mathbf{D} \in \mathbb{R}^{50 \times 100}$ a normalized random dictionary.
- $\|\boldsymbol{\alpha}\|_0 = 1, \boldsymbol{\alpha}_s \sim \mathcal{N}(0, 1)$.
- $\boldsymbol{\nu} \sim \mathcal{N}(\mathbf{0}, \sigma_\nu^2 \mathbf{I}_{50}), \sigma_\nu = 0.2$.
- 35 iterations of stochastic resonance.

General Case – Known Parameters

- $\mathbf{D} \in \mathbb{R}^{50 \times 100}$ a normalized random dictionary.
- $\|\alpha\|_0 = 1, \alpha_s \sim \mathcal{N}(0, 1)$.
- $\nu \sim \mathcal{N}(\mathbf{0}, \sigma_\nu^2 \mathbf{I}_{50}), \sigma_\nu = 0.2$.
- 35 iterations of stochastic resonance.



General Case – Unknown Parameters

- Parameters' values are lacking.

General Case – Unknown Parameters

- Parameters' values are lacking. \implies the same MMSE is no longer attainable.

General Case – Unknown Parameters

- Parameters' values are lacking. \implies the same MMSE is no longer attainable.
- How can we estimate a support?

General Case – Unknown Parameters

- Parameters' values are lacking. \implies the same MMSE is no longer attainable.
- How can we estimate a support? Use any pursuit (MAP approximation).


General Case – Unknown Parameters

- Parameters' values are lacking. \implies the same MMSE is no longer attainable.
- How can we estimate a support? Use any pursuit (MAP approximation).
- How can we obtain the oracle estimator?


General Case – Unknown Parameters

- Parameters' values are lacking. \implies the same MMSE is no longer attainable.
- How can we estimate a support? Use any pursuit (MAP approximation).
- How can we obtain the oracle estimator? Simply use least squares $\hat{\alpha}(s, \mathbf{y})_{\text{oracle}} = (\mathbf{D}_s^T \mathbf{D}_s)^{-1} \mathbf{D}_s^T \mathbf{y}$.

General Case – Unknown Parameters



General Case – Unknown Parameters




General Case – Unknown Parameters

- $\mathbf{D} \in \mathbb{R}^{50 \times 100}$ a normalized random dictionary.
- $\|\boldsymbol{\alpha}\|_0 = 1, \boldsymbol{\alpha}_s \sim \mathcal{N}(0, 1)$.
- $\boldsymbol{\nu} \sim \mathcal{N}(\mathbf{0}, \sigma_\nu^2 \mathbf{I}_{50}), \sigma_\nu = 0.2$.
- 100 iterations of stochastic resonance.

General Case – Unknown Parameters

- $\mathbf{D} \in \mathbb{R}^{50 \times 100}$ a normalized random dictionary.
- $\|\boldsymbol{\alpha}\|_0 = 1, \boldsymbol{\alpha}_s \sim \mathcal{N}(0, 1)$.
- $\boldsymbol{\nu} \sim \mathcal{N}(\mathbf{0}, \sigma_\nu^2 \mathbf{I}_{50}), \sigma_\nu = 0.2$.
- 100 iterations of stochastic resonance.



General Case – Unknown Parameters

- $\mathbf{D} \in \mathbb{R}^{50 \times 100}$ a normalized random dictionary.
- $\|\boldsymbol{\alpha}\|_0 = 1$ $p_i = 0.05$, $\boldsymbol{\alpha}_s \sim \mathcal{N}(0, 1)$.
- $\boldsymbol{\nu} \sim \mathcal{N}(\mathbf{0}, \sigma_\nu^2 \mathbf{I}_{50})$, $\sigma_\nu = 0.2$.
- 100 iterations of stochastic resonance.

General Case – Unknown Parameters

- $\mathbf{D} \in \mathbb{R}^{50 \times 100}$ a normalized random dictionary.
- $\|\alpha\|_0 = 1$ $p_i = 0.05$, $\alpha_s \sim \mathcal{N}(0, 1)$.
- $\nu \sim \mathcal{N}(\mathbf{0}, \sigma_\nu^2 \mathbf{I}_{50})$, $\sigma_\nu = 0.2$.
- 100 iterations of stochastic resonance.


Use bounded noise formulation for the pursuit:

$$(\text{OMP}) \quad \min_{\alpha} \|\alpha\|_0 \quad \text{s.t.} \quad \|\mathbf{y} - \mathbf{D}\alpha\|_2 \leq \epsilon,$$

$$(\text{BP}) \quad \min_{\alpha} \|\alpha\|_1 \quad \text{s.t.} \quad \|\mathbf{y} - \mathbf{D}\alpha\|_2 \leq \epsilon.$$

General Case – Unknown Parameters

- $\mathbf{D} \in \mathbb{R}^{50 \times 100}$ a normalized random dictionary.
- $\|\boldsymbol{\alpha}\|_0 = 1$ $p_i = 0.05$, $\boldsymbol{\alpha}_s \sim \mathcal{N}(\mathbf{0}, 1)$.
- $\boldsymbol{\nu} \sim \mathcal{N}(\mathbf{0}, \sigma_\nu^2 \mathbf{I}_{50})$, $\sigma_\nu = 0.2$.
- 100 iterations of stochastic resonance.



- 1 Bayesian Framework
 - The Generative Model
 - Bayesian Estimators
- 2 MMSE Approximation
 - Previous Work
- 3 Stochastic Resonance
 - Can Noise Help Denoising?
- 4 Our Proposed Method
 - The Algorithm
 - Unitary Case Analysis
 - The General Dictionary Case
 - Image Denoising
- 5 Conclusions

Method Used:

⁵Sulam, Jeremias, et al, 2016. "Trainlets: Dictionary learning in high dimensions."

⁶Dai, Wei, and Olga Milenkovic, 2009. "Subspace pursuit for compressive sensing signal reconstruction."

Image Denoising

Method Used:

- Dataset containing facial images.

⁵Sulam, Jeremias, et al, 2016. "Trainlets: Dictionary learning in high dimensions."

⁶Dai, Wei, and Olga Milenkovic, 2009. "Subspace pursuit for compressive sensing signal reconstruction."

Image Denoising

Method Used:

- Dataset containing facial images.
- Trained a Trainlet⁵ dictionary on clean facial images.

⁵Sulam, Jeremias, et al, 2016. "Trainlets: Dictionary learning in high dimensions."

⁶Dai, Wei, and Olgica Milenkovic, 2009. "Subspace pursuit for compressive sensing signal reconstruction."

Image Denoising

Method Used:

- Dataset containing facial images.
- Trained a Trainlet⁵ dictionary on clean facial images.
- Pursuit used: Subspace Pursuit (SP)⁶.

⁵Sulam, Jeremias, et al, 2016. "Trainlets: Dictionary learning in high dimensions."

⁶Dai, Wei, and Olga Milenkovic, 2009. "Subspace pursuit for compressive sensing signal reconstruction."

Image Denoising

Method Used:

- Dataset containing facial images.
- Trained a Trainlet⁵ dictionary on clean facial images.
- Pursuit used: Subspace Pursuit (SP)⁶.

Experiment:

⁵Sulam, Jeremias, et al, 2016. "Trainlets: Dictionary learning in high dimensions."

⁶Dai, Wei, and Olgica Milenkovic, 2009. "Subspace pursuit for compressive sensing signal reconstruction."

Image Denoising

Method Used:

- Dataset containing facial images.
- Trained a Trainlet⁵ dictionary on clean facial images.
- Pursuit used: Subspace Pursuit (SP)⁶.

Experiment:

- Added noise to an unseen image.

⁵Sulam, Jeremias, et al, 2016. "Trainlets: Dictionary learning in high dimensions."

⁶Dai, Wei, and Olga Milenkovic, 2009. "Subspace pursuit for compressive sensing signal reconstruction."

Image Denoising

Method Used:

- Dataset containing facial images.
- Trained a Trainlet⁵ dictionary on clean facial images.
- Pursuit used: Subspace Pursuit (SP)⁶.

Experiment:

- Added noise to an unseen image.
- Use the dictionary and SP to denoise. Tune L parameter to obtain optimal denoising performance.

⁵Sulam, Jeremias, et al, 2016. "Trainlets: Dictionary learning in high dimensions."

⁶Dai, Wei, and Olgica Milenkovic, 2009. "Subspace pursuit for compressive sensing signal reconstruction."

Image Denoising

Method Used:

- Dataset containing facial images.
- Trained a Trainlet⁵ dictionary on clean facial images.
- Pursuit used: Subspace Pursuit (SP)⁶.

Experiment:

- Added noise to an unseen image.
- Use the dictionary and SP to denoise. Tune L parameter to obtain optimal denoising performance.
- Use SR algorithm using the same SP configuration used in the previous step.

⁵Sulam, Jeremias, et al, 2016. "Trainlets: Dictionary learning in high dimensions."

⁶Dai, Wei, and Olga Milenkovic, 2009. "Subspace pursuit for compressive sensing signal reconstruction."

Image Denoising – Results



Clean Image.

Image Denoising – Results



Noisy image.
PSNR=16.1 dB.



Clean Image.

Image Denoising – Results



Noisy image.
PSNR=16.1 dB.



Subspace Pursuit.
PSNR=26.88 dB.



Clean Image.

Image Denoising – Results



Noisy image.
PSNR=16.1 dB.



Subspace Pursuit.
PSNR=26.88 dB.



Stochastic
Resonance.
PSNR=28.76 dB.



Clean Image.

Image Denoising – Results



Noisy image.
PSNR=16.1 dB.



Subspace Pursuit.
PSNR=26.88 dB.



Stochastic
Resonance.
PSNR=28.76 dB.



Clean Image.

~ 2dB better.

- 1 Bayesian Framework
 - The Generative Model
 - Bayesian Estimators
- 2 MMSE Approximation
 - Previous Work
- 3 Stochastic Resonance
 - Can Noise Help Denoising?
- 4 Our Proposed Method
 - The Algorithm
 - Unitary Case Analysis
 - The General Dictionary Case
 - Image Denoising
- 5 Conclusions

Conclusions

- MMSE estimator is desired, but involves an exhaustive computation.

Conclusions

- MMSE estimator is desired, but involves an exhaustive computation.
- MAP is hard as well, but many approximation methods are available.

- MMSE estimator is desired, but involves an exhaustive computation.
- MAP is hard as well, but many approximation methods are available.
- We can use synthetic noise and any MAP estimator approximation to achieve an MMSE estimator approximation.

- MMSE estimator is desired, but involves an exhaustive computation.
- MAP is hard as well, but many approximation methods are available.
- We can use synthetic noise and any MAP estimator approximation to achieve an MMSE estimator approximation.
- MMSE estimator approximation is attainable, even for large dimensions.

Thank You