

Parallel Computing for Science & Engineering CS395T

02/06/2018

Instructors:

Lars Koesterke, TACC

Charlie Dey, TACC

Example code



THE UNIVERSITY OF TEXAS AT AUSTIN
Texas Advanced Computing Center

Work-sharing Constructs and Implied Barriers

- Worksharing Constructs
 - Do/For
 - Sections
 - Single
- Constructs without a Barrier
 - Critical
 - etc.

```
!$OMP PARALLEL shared(a)
```

...

```
a = 5.
```

```
!$OMP DO  
do i=1, n  
    b(i) = a  
enddo
```

...

```
!$OMP END PARALLEL
```

Is this code correct?

All threads will execute a = 5.

How can we fix this?

!\$OMP PARALLEL shared(a)

...

!\$OMP CRITICAL

a = 5.

!\$OMP END CRITICAL

!\$OMP DO

do i=1, n

 b(i) = a

enddo

...

!\$OMP END PARALLEL

Is there a Barrier needed at the end of the Critical Region?

Why is this solution not optimal?



!\$OMP PARALLEL shared(a)

...

What is the implicit Barrier doing?

!\$OMP SINGLE

a = 5.

!\$OMP END SINGLE

!\$OMP DO

do i=1, n

 b(i) = a

enddo

...

!\$OMP END PARALLEL



```
!$OMP PARALLEL shared(a)
```

...

```
!$OMP MASTER
```

```
a = 5.
```

```
!$OMP END MASTER
```

```
!$OMP DO
```

```
do i=1, n
```

```
    b(i) = a
```

```
enddo
```

...

```
!$OMP END PARALLEL
```

Would this work, too?

