S.No: 4	Exp. Name: ***Dynamic To-Do List with Modals***	**Date: 2026-09-21**

Aim:

You have joined a front-end team building a productivity app. The HTML and CSS for a To-Do List app are already provided. Write the JavaScript in `script.js` to make the app interactive.

Your Task

1. Add Task

When the user types a task and clicks the `Add` button, add a new `<li>` to the list with `id="task-list"`. Each item must include:

- A `<span>` holding the task text
- Two buttons labelled `Edit` and `Delete`

2. Edit Task with Modal

Clicking `Edit` on a task should:

- Open `#edit-modal` by setting its `display` to `block`
- Show the current task text inside `#edit-input`
- Update the task text when the user clicks `Save`

The modal should close when:

- The user clicks `Save`
- The user clicks the close icon at the top right
- The user clicks outside the modal

3. Delete Task with Confirmation

Clicking `Delete` on a task should:

- Open `#delete-modal` by setting its `display` to `block`
- Remove the task if the user clicks `Yes`
- Close the modal without deleting if the user clicks `No`
- Close the modal if the user clicks outside the confirmation box

Note:

- Trigger the **Add** action when the user clicks the **Add** button. You may implement this using either the button's $click$ event or the form's submit event (using `event.preventDefault()` if needed).

Source Code:

index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8" />
  <meta name="viewport" content="width=device-width, initial-
scale=1.0"/>
  <title>Dynamic To-Do List</title>
  <link rel="stylesheet" href="style.css" />
</head>
<body>
  <div class="container">
    <h1>To-Do List</h1>
    <form id="task-form">
      <input type="text" id="task-input" placeholder="Add a new
task" required />
      <button type="submit" id="add-task">Add</button>
    </form>
    <ul id="task-list"></ul>
  </div>

  <!-- Edit Modal -->
  <div id="edit-modal" class="modal">
    <div class="modal-content">
      <span class="close-btn" id="close-edit-modal">&times;
</span>
      <h2>Edit Task</h2>
      <input type="text" id="edit-input" />
      <button id="save-edit">Save</button>
    </div>
  </div>

  <!-- Delete Confirmation Modal -->
  <div id="delete-modal" class="modal">
    <div class="modal-content">
      <p>Are you sure you want to delete this task?</p>
      <button id="confirm-delete">Yes</button>
      <button id="cancel-delete">No</button>
    </div>
  </div>

  <script src="script.js"></script>
</body>
</html>
```

script.js

```
const taskForm = document.getElementById("task-form");
const tasklist = document.getElementById("task-list");
const taskInput = document.getElementById("task-input");

const editModal = document.getElementById("edit-modal");
const editInput = document.getElementById("edit-input");
const saveEdit = document.getElementById("save-edit");
const CloseEditModal = document.getElementById("close-edit-
modal");

const deleteModal = document.getElementById("delete-modal");
const confirmDelete = document.getElementById("confirm-delete");
const cancelDelete = document.getElementById("cancel-delete");
let currentTask=null;
taskForm.addEventListener("submit",function(event){
        event.preventDefault();
        const taskText=taskInput.value.trim();
        if (taskText===""){
                return;
        }
        const li=document.createElement("li");
        const span=document.createElement("span");
        span.textContent = taskText;
        const editButton=document.createElement("button");
        editButton.textContent = "Edit";
        const deleteButton=document.createElement("button");
        deleteButton.textContent = "Delete";
        li.appendChild(span);
        li.appendChild(editButton);
        li.appendChild(deleteButton);
        tasklist.appendChild(li);
        taskInput.value="";
});
tasklist.addEventListener("click",function(event){
        if (event.target.textContent ==="Edit"){
                currentTask=event.target.parentElement;

editInput.value=currentTask.querySelector("span").textContent;
                editModal.style.display = "block";
        }
        if (event.target.textContent === "Delete"){
                currentTask=event.target.parentElement;
                deleteModal.style.display = "block";
        }
```

```
});
saveEdit.addEventListener("click",function(){
        const newTask=editInput.value.trim();
        if (newTask !=="" && currentTask){

currentTask.querySelector("span").textContent=newTask;
                editModal.style.display = "none";
                currentTask=null;
        }
});
CloseEditModal.addEventListener("click",function(){
        editModal.style.display = "none";
        currentTask=null;
});
confirmDelete.addEventListener("click",function(){
        if(currentTask){
                currentTask.remove();
        }
        deleteModal.style.display = "none";
        currentTask=null;
});
cancelDelete.addEventListener("click",function(){
        deleteModal.style.display = "none";
        currentTask=null;
});
window.addEventListener("click",function(event){
        if (event.target === editModal){
                editModal.style.display = "none";
                currentTask=null;
        }
        if(event.target === deleteModal){
                deleteModal.style.display = "none";
                currentTask=null;
        }
});
```