

API Integration: SMS Service

1. Connect to OAuth Server and Retrieve Access Token

This step demonstrates retrieving an OAuth 2.0 access token using the **Client Credentials Grant**.

1.1 Encode Client Credentials

Concatenate `clientId` and `clientSecret` using a colon (`:`) separator.

```
<clientId>:<clientSecret>
```

Base64 encode the resulting string.

Example:

	Value
Client ID	ho_client
Client Secret	h0!\$CL
Concatenated	ho_client:h0!\$CL
Base64 Encoded	aG9fY2xpZW50mhPISRDTA==

1.2 Send Token Request

- **HTTP Method:** `POST`
- **Endpoint:** `https://marigold.medplusindia.com:6728/oauth-server/oauth/token?grant_type=client_credentials`

Headers:

```
Authorization: Basic <Base64EncodedClientCredentials>
```

Example cURL Command:

```
curl -X POST \  
  "https://marigold.medplusindia.com:6728/oauth-server/oauth/token?grant_type=client_credentials" \  
  -H "Authorization: Basic aG9fY2xpZW50mhPISRDTA=="
```

Sample Response:

```
{  
  "access_token": "eyJhbGciOiJSUzI1NiIsInR5cCI6IkpXVCJ9...",  
  "token_type": "bearer",  
  "expires_in": 119,  
  "scope": "read",  
  "env": "marigold",  
  "issued_at": "2026-06-30 11:00:00",  
  "jti": "804c8465-dfa1-426e-8fdf-6f1920bb0fc0"  
}
```

Note: `access_token` is valid for `expires_in` seconds (here, 119 seconds). Always check expiry before making API calls.

2. Send SMS Using Access Token

Use this API to send an SMS to a customer. The request is enqueued asynchronously; the API returns immediately upon successful queue placement.

- **HTTP Method:** `POST`
- **Endpoint:** `/message-service/sms/send-sms`

Headers:

```
Authorization: Bearer <AccessToken>
Content-Type: application/json
```

Request Parameters

Request Body

Field	Type	Mandatory	Description
mobile	String	Yes	Customer mobile number. Must be a valid Indian mobile number (10 digits, starting with 6/7/8/9)
smsTemplate	String	Yes	Valid SMS template configured in the system. Example: <code>REGISTRATION_OTP</code>
smsParams	Array	No	List of parameters based on SMS template configuration. Example: <code>["123456", "2hr"]</code>
customerId	String	No	Customer ID for communication logging
referenceId	String	No	Reference ID (e.g., order ID) associated with this SMS
referenceType	String	No	Type of reference. Allowed values: <code>MART</code> , <code>LAB</code> , <code>DOCTORS</code> , <code>PRESCRIPTION</code> , <code>OPTICALS</code> , <code>PB_ORDER</code> , <code>REDEMPTION</code>
createdBy	String	No	Identifier of the caller initiating the SMS request
remarks	String	No	Optional remarks/reason for sending this SMS

Query Parameters

Field	Type	Mandatory	Description
mobileNumbers	String	No	Comma-separated list of mobile numbers for bulk SMS. Example: <code>9876543210,9876543211</code> . When provided, the <code>mobile</code> field in the body is ignored and SMS is sent to each number in the list

Important Notes

1. `smsTemplate` must already exist and be configured in the system.
2. `mobile` must be a valid Indian mobile number matching the pattern: starts with 6/7/8/9, 10 digits.
3. The API is **asynchronous** — it returns immediately after enqueueing the request. Actual SMS delivery happens via a background queue consumer.
4. A daily rate limit of **20 SMS per mobile number** is enforced (configurable).
5. For bulk send using `mobileNumbers`, failure on one number does not stop processing of remaining numbers.

Example Request Body

```
{
  "mobile": "9876543210",
  "smsTemplate": "REGISTRATION_OTP",
```

```
{
  "smsParams": [
    "123456",
    "2hr"
  ],
  "customerId": "CUST001",
  "referenceId": "ORD12345",
  "referenceType": "MART",
  "createdBy": "OTG01057",
  "remarks": "Registration OTP"
}
```

Example cURL Command

```
curl -X POST \
  "https://marigold.medplusindia.com:6728/message-service/sms/send-sms" \
  -H "Authorization: Bearer eyJhbGciOiJSUzI1NiIsInR5cCI6IkpXVCJ9..." \
  -H "Content-Type: application/json" \
  -d '{
    "mobile": "9876543210",
    "smsTemplate": "REGISTRATION_OTP",
    "smsParams": ["123456", "2hr"]
  }'
```

Example cURL Command (Bulk Send)

```
curl -X POST \
  "https://marigold.medplusindia.com:6728/message-service/sms/send-sms?mobileNumbers=9876543210,9876543210" \
  -H "Authorization: Bearer eyJhbGciOiJSUzI1NiIsInR5cCI6IkpXVCJ9..." \
  -H "Content-Type: application/json" \
  -d '{
    "smsTemplate": "REGISTRATION_OTP",
    "smsParams": ["123456", "2hr"]
  }'
```

Sample Response

```
{
  "status": "SUCCESS",
  "message": "null",
  "data": {
    "status": "SUCCESS",
    "message": "SmsRequest Received Successfully"
  },
  "error": null
}
```

Sample Error Response

```
{
  "status": "SUCCESS",
  "message": "null",
  "data": {
    "status": "ERROR",
    "message": "INVALID_MOBILE_NUMBER"
  },
}
```

```
"error": null
}
```

3. Decode SMS Text Using Access Token

Use this API to preview the final SMS text by substituting template placeholders with provided parameters.

- **HTTP Method:** `POST`
- **Endpoint:** `/message-service/sms/decode-sms-text`

Headers:

```
Authorization: Bearer <AccessToken>
Content-Type: application/json
```

Request Parameters

Field	Type	Mandatory	Description
smsTemplate	String	Yes	Valid SMS template configured in the system
smsParams	Array	Yes	List of parameters to substitute into the template

Example Request Body

```
{
  "smsTemplate": "REGISTRATION_OTP",
  "smsParams": [
    "123456",
    "2hr"
  ]
}
```

Example cURL Command

```
curl -X POST \
  "https://marigold.medplusindia.com:6728/message-service/sms/decode-sms-text" \
  -H "Authorization: Bearer eyJhbGciOiJSUzI1NiIsInR5cCI6IkpXVCJ9..." \
  -H "Content-Type: application/json" \
  -d '{
    "smsTemplate": "REGISTRATION_OTP",
    "smsParams": ["123456", "2hr"]
  }'
```

Sample Response

```
{
  "status": "SUCCESS",
  "message": "null",
  "data": "123456 is the authorisation code for your Medplus registration.
          Please use it within 2hr. Thanks, Customer Care 040-67006700",
  "error": null
}
```