



Computational Aspects of KD

- Data Access

- read.csv

- write.csv

- edit

- Visualization

- scatter plots

- Data Manipulation

- attribute-oriented approach

- observation-oriented approach

- Model Building and Evaluation

- Model Deployment



Data Manipulation

Recall that a data frame is a data table representation in R,

```
> mammals.df
  Legs Wings  Fur Feathers Mammal
1    4   no  yes      no   true
2    2  yes   no     yes  false
3    4   no   no     no  false
4    4  yes  yes     no   true
5    3   no   no     no  false
```



Data Manipulation

Attribute-oriented Approach

We can access any attribute in the mammals data frame with the `$` notation.

```
> mammals.df$Legs
[1] 4 2 4 4 3
> mammals.df$Mammal
[1] true  false false  true  false
Levels: false true
```

R allows us to select groups of attributes with the `subset` function,

```
> subset(mammals.df, select=Fur:Mammal)
  Fur Feathers Mammal
1 yes        no  true
2 no         yes false
3 no         no  false
4 yes        no  true
5 no         no  false
> subset(mammals.df, select=-Mammal)
  Legs Wings  Fur Feathers
1   4    no yes        no
2   2   yes  no        yes
3   4    no  no        no
4   4   yes yes        no
5   3    no  no        no
```



Data Manipulation

Observation-oriented Approach

We can use the *subset* function also for observation-oriented data manipulation.

```
> subset(mammals.df, Legs == 4)
  Legs Wings  Fur Feathers Mammal
1     4    no  yes        no   true
3     4    no   no        no  false
4     4   yes  yes        no   true
```

Another, slightly more complicated example,

```
> mammal.levels <- levels(mammals.df$Mammal)
> mammal.levels
[1] "false" "true"
> true.level <- mammal.levels[2]
> subset(mammals.df, Mammal == true.level)
  Legs Wings Fur Feathers Mammal
1     4    no  yes        no   true
4     4   yes  yes        no   true
```



Model Building and Evaluation

We use the library 'e1071' (don't ask :) for building support vector machine models. ^a

```
> library(e1071)
```

Now we can construct a support vector machine model of our mammals data with the `svm` function,

```
> model<-svm(Mammal ~ .,data=mammals.df,kernel="linear")
```

At this point we can evaluate our model by checking how it performs on the training set.

```
> mammals.df$Mammal == fitted(model)
[1] TRUE TRUE TRUE TRUE TRUE
```

^aThe library is available through the Package Installer.



Model Deployment

Model deployment means applying your model in an appropriate context. In R we use the `predict` function to compute the value of the dependent attribute for some object. Given that R is a programming language we could program appropriate functionality around the `predict` function.

```
> independent.df <- subset(mammals.df, select=-Mammal)
> predict(model, independent.df)
      1      2      3      4      5
 true false false  true  false
Levels: false  true
```

How could we test in R whether these predictions are correct with respect to the original data set `mammals.df`?