

99888-0151-01

Table of Contents

Specifications 1-2

1-2 99888-0151-01

Specifications

PERFORMANCE

Maximum Horsepower	33.4 kW (45 PS) @9 000 r/min (rpm) (ID, TH) 38.3 kW (52 PS) @10 000 r/min (rpm) (PH) 37.6 kW (51 PS) @10 000 r/min (rpm)
Maximum Torque	42.6 N·m (4.3 kgf·m, 31 ft·lb) @6 000 r/min (rpm) (ID, PH, TH) 42.6 N·m (4.3 kgf·m, 31 ft·lb) @7 500 r/min (rpm)
Minimum Turning Radius	2.7 m (8.9 ft)

DIMENSIONS

Overall Length	2 300 mm (90.55 in.)
Overall Width:	
KLE500C	940 mm (37.0 in.)
KLE500D	980 mm (38.6 in.)
Overall Height/High Position:	
KLE500C	1 355 mm (53.35 in.)/1 405 mm (55.31 in.)
KLE500D	1 460 mm (57.48 in.)/1 510 mm (59.45 in.)
Wheelbase	1 555 mm (61.22 in.)
Road Clearance	185 mm (7.28 in.)
Curb Mass:	
KLE500C	193 kg (426 lb) (MIDE, SEA-B3, TH) 194 kg (428 lb)
KLE500D	194 kg (428 lb) (MIDE, SEA-B3, TH) 195 kg (430 lb)

ENGINE

Type	DOHC, 2-cylinder, 4-stroke, liquid-cooled
Displacement	451 cm ³ (27.5 cu in.)
Bore × Stroke	70.0 × 58.6 mm (2.76 × 2.31 in.)
Compression Ratio	11.3:1
Starting System	Electric starter
Cylinder Numbering Method	Left to right, 1-2
Firing Order	1-2
Fuel System	FI (Fuel Injection)
Ignition System	Battery and coil (transistorized ignition)
Ignition Timing (Electronically advanced)	10.0° BTDC @1 300 r/min (rpm) – 55.0° BTDC @10 000 r/min (rpm) (ID, PH, TH) 10.0° BTDC @1 300 r/min (rpm) – 48.7° BTDC @10 000 r/min (rpm)
Spark Plug:	
Type	NGK LMAR9G
Gap	0.7 – 0.8 mm (0.028 – 0.031 in.)
Lubrication System	Forced lubrication (wet sump)
Engine Oil:	
Type	API SG, SH, SJ, SL or SM with JASO MA, MA1 or MA2
Viscosity	SAE 10W-40
Capacity	2.4 L (2.5 US qt)
Coolant Capacity	1.3 L (1.4 US qt)

Specifications

TRANSMISSION

Transmission Type	6-speed, constant mesh, return shift
Clutch Type	Wet, multi disc
Driving System	Chain drive
Primary Reduction Ratio	2.029 (69/34)
Final Reduction Ratio	3.067 (46/15)
Overall Drive Ratio	6.454 (Top gear)
Gear Ratio:	
1st	2.929 (41/14)
2nd	2.056 (37/18)
3rd	1.619 (34/21)
4th	1.333 (32/24)
5th	1.154 (30/26)
6th	1.037 (28/27)

FRAME

Caster	28.0°
Trail	104 mm (4.09 in.)
Tire Size:	
Front	90/90-21 M/C 54S
Rear	140/70-17 M/C 66S
Rim Size:	
Front	21 × 2.15
Rear	17M/C × MT4.00
Fuel Tank Capacity	16 L (4.2 US gal)
Brake Fluid:	
Front	DOT3 or 4
Rear	DOT4

ELECTRICAL EQUIPMENT

Battery	12 V 8.6 Ah (10 HR) (ID, PH, TH) 12 V 8 Ah (10 HR)
Headlight:	
High Beam	LED
Low Beam	LED
City Light	LED
Brake/Tail Light	LED
Turn Signal Light:	
KLE500C:	
Front	12 V 10 W (RY10W)
Rear	12 V 10 W (RY10W)
KLE500D:	
Front	LED
Rear	LED
License Plate Light	12 V 5 W (W5W)

1-4 99888-0151-01

Specifications

ID:	Indonesia model
PH:	Philippines model
TH:	Thailand model
MIDE:	Middle East (General) model
SEA-B3:	Southeast Asia B3 model

Even if any one element of LED (Light Emitting Diode) light does not go on, consult with an authorized Kawasaki dealer.

Specifications are subject to change without notice.