

Velocity Python API

Table of Contents

Table of Contents	2
Command Prompt and Python Interpreter Basics	6
Set-up Needed to Access Scripts	7
Using Scripts	8
Example Scripts	10
Writing Scripts	11
Viewing Documentation	16
<code>__builtin__.SwigPyObject</code>	17
Velocity Classes	18
BaseRegistrationSettingsStructure	21
BaseImageBasedRegistrationSettingsStructure	22
BSplineDeformableRegistrationSettingsStructure	23
RigidRegistrationSettingsStructure	25
ManualRegistrationSettingsStructure	27
BoolList	28
CharList	29
CropSettings	30
DoubleList	31
ExportOperations	32
FloatList	34
Image2DList	35
ImportOperations	36
IntList	37
MarginSettings	38
MatrixR22d	39
MatrixR22i	41
MatrixR33d	43
MatrixR33f	45
MatrixR44d	47
MatrixR44f	49

PatientDataItem	51
Image2D	52
Patient	54
Plan	56
Registration	59
RegistrationCommissioningMarkerList	61
Structure	63
StructureSet	66
Volume	69
PatientDataOperations	74
PatientList	76
PlanList	77
RegistrationCommissioningMarkerLists	78
RegistrationList	79
RegistrationMarker	80
RegistrationMarkerList	81
RegistrationOperations	82
ReportOperations	85
ScaledVolumeData	87
StringList	88
StructureGuidedRegistrationInformation	89
StructureList	91
StructureMap	92
StructureOperations	93
StructureSetList	96
SurfaceDistanceMetrics	97
SwigPyIterator	98
TransformedRegistrationMarker	99
VectorR2b	101
VectorR2bList	103
VectorR2d	104
VectorR2dList	106
VectorR2f	107
VectorR2fList	109
VectorR2i	110
VectorR2iList	112
VectorR2s	113

VectorR2sList	115
VectorR2ub	116
VectorR2ubList	118
VectorR2ui	119
VectorR2uiList	121
VectorR2us	122
VectorR2usList	124
VectorR3b	125
VectorR3bList	127
VectorR3d	128
VectorR3dList	130
VectorR3f	131
VectorR3fList	133
VectorR3i	134
VectorR3iList	136
VectorR3s	137
VectorR3sList	139
VectorR3ub	140
VectorR3ubList	142
VectorR3ui	143
VectorR3uiList	145
VectorR3us	146
VectorR3usList	148
VectorR4b	149
VectorR4bList	151
VectorR4d	152
VectorR4dList	154
VectorR4f	155
VectorR4fList	157
VectorR4i	158
VectorR4iList	160
VectorR4s	161
VectorR4sList	163
VectorR4ub	164
VectorR4ubList	166
VectorR4ui	167
VectorR4uiList	169

VectorR4us	170
VectorR4usList	172
VelocityEngine	173
VolumeList	179
VolumeOperations	180

Command Prompt and Python Interpreter Basics

- Using Command Prompt vs Python Interpreter
 - >
 - Indicates that the following should be typed into the command prompt
 - >>>
 - Indicates that the following should be typed into the python interpreter
- Command Prompt Commands
 - > cd
 - Allows the user to change their working directory
 - Absolute Path
 - A path that starts from the root directory
 - This path must be used if your working directory is not part of the path to get to the desired directory
 - Example
 - > cd C:\absolute\path\to\directory
 - Relative Path
 - A path that starts from the working directory
 - This path can be used if your working directory is part of the path to get to the desired directory
 - Example
 - > cd \relative\path\to\directory
 - > python
 - Allows the user to open the python interpreter
 - If the following command is followed by a .py file, the file will be executed (otherwise, it will just open the python interpreter)
 - Example
 - > python my_code.py
 - Arrow Keys
 - The up and down arrow keys can be used to navigate through previously entered commands
- Python Interpreter Commands
 - >>> quit()
 - Allows you to exit the python interpreter and return to the command prompt

Set-up Needed to Access Scripts

- Setting up python
 - Download latest version of Python 2.7 (currently 2.7.15)
 - <https://www.python.org/downloads/windows/>
 - Windows x86-64 MSI installer
- Setting up pip
 - Pip should already be downloaded with python
 - To check if pip is already downloaded
 - > pip --version
 - If pip is not already download
 - <https://pip.pypa.io/en/stable/installing/>
- Setting up virtualenv
 - To download virtualenv
 - > pip install virtualenv
 - To create a virtualenv (named “velocity-env”)
 - > virtualenv velocity-env
 - To activate the virtualenv
 - > velocity-env\Scripts\activate
- Downloading velocity
 - Place the following file in the directory C:\Users\your_user_directory
 - Velocity-4.0.0.794-cp27-cp27m-win_amd64.whl
 - Make sure that your working directory is the directory that you just put the file in
 - To install velocity
 - > pip install velocity-4.0.0.794-cp27-cp27m-win_amd64.whl

Using Scripts

- Editing scripts to run
 - Open the script you want to change in emacs
 - `> emacs script_name.py`
 - Find the variable DB_NAME and change it to the database name
 - Example


```
DB_NAME = 'VMS_GRID'
```
 - Find the DB_USER and DB_PASS and change it to your username and password
 - Example


```
DB_USER = 'script'
DB_PASS = 'script'
```
 - The DB_IP and DB_PORT should already be correct
 - `DB_IP = '127.0.0.1'`
 - `DB_PORT = 57000`
 - Save the file by pressing the save button at the top or using the shortcut C-x s
 - C-x s means that you should hold down the control key, press x and then press s
- Compile the script
 - Switch to the python interpreter
 - Type the following into the interpreter
 - `>>> import py_compile`
 - `>>> py_compile.compile("file_name.py")`
 - This will compile the code so that the changes made to the code will be updated
- Run the script
 - Type the following into the command prompt
 - `> python file_name.py`
 - This will allow the program to run
- Fixing errors
 - RuntimeError: Non-script users may not log in from scripts
 - Log into velocity and go to settings
 - Click on the users tab and create a new user
 - After creating the new user, change the user type to Script
 - Use the username and password created for this user for DB_USER and DB_PASS
 - RuntimeError: Could not connect to active database at : *DB_IP* (*DB_PORT*). DbName=*DB_NAME*
 - This means that the DB_NAME is incorrect
 - RuntimeError: No response from Grid database (*DB_IP*: *DB_PORT*: *DB_NAME*): Resource temporarily unavailable

- This means that the DB_IP is incorrect or the DB_PORT is incorrect
- RuntimeError: Could not find patient with id: *patientId*
 - The specific patient that the script is written for needs to be imported to velocity in order to get the script to run
 - The patientId specifies which patient the script is written for

Example Scripts

- BED.py
 - Running the script
 - Runs Biological Effective Dose (BED) calculation
- Liver_import.py
 - Running the script
 - Tests to see if a file can be imported properly
- Pet_ct_registrations.py
 - Running the script
 - Tests running a manual registration, rigid registration, and performing a deformable registration
- Print_patient.py
 - Running the script
 - Prints out all information and data on the patient
- Structure_metrics.py
 - Running the script
 - Copies structures using a deformable.
 - Calculates minimum, median, mean, and standard deviation values, comparing them across the deformable or with the proceeding rigid.

Writing Scripts

- Required components for writing velocity scripts
 - Import statements
 - import velocity
 - This statement will import all velocity classes
 - import atexit
 - This statement will import the atexit module, which assists with properly closing the program after the script has finished running
 - Attributes
 - DB_NAME
 - This attribute can be named whatever you choose, but it will represent the name of the database that is used to login to the velocity grid
 - This attribute should be a constant
 - Although it is not necessary put the name in all capitalization, it is suggested to use capitalization to signify that the attribute is a constant
 - Example
 - DB_NAME = r'VMS_GRID'
 - The r is used in order to ensure that if there any escape characters, (a backslash) these characters will be registered as is, rather than as an escape character
 - DB_USER
 - This attribute can be named whatever you choose, but it will represent the username that is used to log into the velocity grid
 - The username should not be the generic username used to login to velocity, but should be the username that was created when you created a Script user for velocity
 - This attribute should be a constant
 - Example
 - DB_USER = 'script'
 - DB_PASS
 - This attribute can be named whatever you choose, but it will represent the password that is used to log into the velocity grid
 - The password should not be the generic password used to login to velocity, but should be the password that was created when you created a Script user for velocity
 - This attribute should be a constant

- Example
 - DB_PASS = 'script'
- DB_IP
 - This attribute can be named whatever you choose, but it will represent the IP address for the velocity grid
 - Example
 - DB_IP = '127.0.0.1'
- DB_PORT
 - This attribute can be named whatever you choose, but it will represent the port number for the velocity grid
 - Example
 - DB_PORT = 57000
- PATIENT_ID
 - This attribute can be named whatever you chose, but it will represent the id of the patient that is being used to run the script
 - Example
 - PATIENT_ID = 'AW3Y6TA684'
- Creating the velocity engine
 - e = velocity.VelocityEngine()
 - def orThrow(c, e=e):
 - if not c or (hasattr(c, 'isValid') and not c.isValid()):
 - raise RuntimeError(e.getErrorMessage())
 - This block of code is used to create the velocity engine and checks any errors that occur when creating the engine
 - Determines if the attempt to create the engine is valid using the isValid() method from the [PatientDataItem](#) class
 - Uses the getErrorMessage() method from the [VelocityEngine](#) class if an error occurs when trying to create the engine
- Logging in to and out of the velocity grid
 - orThrow(e.loginToGrid(DB_USER, DB_PASS, DB_IP, DB_PORT, DB_NAME))
 - atexit.register(e.logout)
 - Logs into your velocity grid using the loginToGrid() method from the [VelocityEngine](#) class and using your username, password, ip address, port number, and grid database
 - The username, password, etc. must be in the exact same order as listed above in order to successfully login
 - Logs out of the velocity grid after the script has finished running using the register() method from the atexit module

- Other components for writing velocity scripts
 - Based on what you want your script to test, you will most likely need to include other attributes, methods, and print statements
 - Most of the additional methods you will need to use will be from the [VelocityEngine](#) class; however, other methods may be needed
 - Additional attributes will need to be created in order to fill the parameters of the methods that you are testing
 - Scripts can be used to test a singular method to make sure it works properly, or used to test the interaction between multiple methods
 - Examine other scripts in order to get an idea of what is needed to write additional scripts
 - An example script with comments is provided for you on the next page to help visualize how to write your own scripts
 - This script can be copied and pasted into emacs as a .py file, compiled, and then run in order to see what it does
 - A “#” is used to denote that the following information is a comment, not an actual part of the code

```

# The following script is used as an example script to show how to write a script.
# In order to create the script, you will need to create a .py file. You can name
# the .py file whatever you want. I have chosen to name my .py file MyScript.py.
# To create the .py file, go to the command prompt and navigate to the directory
# that you wish to place your script in. I am placing my script in the
# velocity-examples directory (C:\Users\fgm3919\velocity-env\velocity-examples)
# where the other example scripts are. Once you are in the desired directory,
# type the following:
#      emacs MyScript.py
# This will open an empty file in emacs where you can copy and paste this script.
# After you have copied and pasted the script, compile the script and run it.
#
# The following script uses a patient that has already been imported, loads the
# patient, and then prints out the patient's full name and date of birth. The
# script tests the loadPatient() and patientDataOps() methods from the
# VelocityEngine class, the getPatientByPatientId() method from the
# PatientDataOperations class, and the getFirstName() and getLastName() methods
# from the Patient class.

```

```

import velocity
import atexit

# Attributes
DB_NAME = r'VMS_GRID'
DB_USER = 'script'
DB_PASS = 'script'
DB_IP = '127.0.0.1'
DB_PORT = 57000

# O'Reilly, Bobby'O must be loaded for the script to work
PATIENT_ID = "O'ReillyID"

# Creates the velocity engine
e = velocity.VelocityEngine()
def orThrow(c, e=e):
    if not c or (hasattr(c, 'isValid') and not c.isValid()):
        raise RuntimeError(e.getErrorMessage())

# Login to velocity grid

```

```

orThrow(e.loginToGrid(DB_USER, DB_PASS, DB_IP, DB_PORT, DB_NAME))
# Logout of velocity grid when script is done running
atexit.register(e.logout)

# Loads the patient given the patient ID
orThrow(e.loadPatient(PATIENT_ID))
print('Loaded patient: {}'.format(PATIENT_ID))

# Allows the script to use the patient data operations
patientDataOps = e.getPatientDataOperations()
# Assigns the patient to a variable called patient
patient = patientDataOps.getPatientByPatientId(PATIENT_ID)
# Determines the patient's full name
patientFullName = patient.getFirstName() + " " + patient.getLastName()
print('Patient {} is named {}'.format(PATIENT_ID, patientFullName))
# Determines the patient's date of birth
patientDOB = patient.getDateOfBirth()
print('Patient {} was born {}'.format(PATIENT_ID, patientDOB))

```

Viewing Documentation

- Entire Velocity Documentation
 - `>>> import velocity`
 - `>>> help(velocity)`
- Specific Class Documentation
 - `>>> import velocity`
 - `>>> help(velocity.Class_Name)`

`__builtin__.SwigPyObject`

- SwigPyObject is an implementation detail. All Velocity classes inherit SwigPyObject but scripting API users **should not use** SwigPyObject methods. These methods are:
 - `acquire()`
 - `append()`
 - `disown()`
 - `next()`
 - `own()`

Velocity Classes

- List of all classes
 - [BaseRegistrationSettingsStructure](#)
 - [BaseImageBasedRegistrationSettingsStructure](#)
 - [BSplineDeformableRegistrationSettingsStructure](#)
 - [RigidRegistrationSettingsStructure](#)
 - [ManualRegistrationSettingsStructure](#)
 - [BoolList](#)
 - [CharList](#)
 - [CropSettings](#)
 - [DoubleList](#)
 - [ExportOperations](#)
 - [FloatList](#)
 - [Image2DList](#)
 - [ImportOperations](#)
 - [IntList](#)
 - [MarginSettings](#)
 - [MatrixR22d](#)
 - [MatrixR22i](#)
 - [MatrixR33d](#)
 - [MatrixR33f](#)
 - [MatrixR44d](#)
 - [MatrixR44f](#)
 - [PatientDataItem](#)
 - [Image2D](#)
 - [Patient](#)
 - [Plan](#)
 - [Registration](#)
 - [RegistrationCommissioningMarkerList](#)
 - [Structure](#)
 - [StructureSet](#)
 - [Volume](#)
 - [PatientDataOperations](#)
 - [PatientList](#)
 - [PlanList](#)
 - [RegistrationCommissioningMarkerLists](#)
 - [RegistrationList](#)
 - [RegistrationMarker](#)
 - [RegistrationMarkerList](#)

- [RegistrationOperations](#)
- [ReportOperations](#)
- [ScaledVolumeData](#)
- [StringList](#)
- [StructureGuidedRegistrationInformation](#)
- [StructureList](#)
- [StructureMap](#)
- [StructureOperations](#)
- [StructureSetList](#)
- [SurfaceDistanceMetrics](#)
- [SwigPyIterator](#)
- [TransformedRegistrationMarker](#)
- [VectorR2b](#)
- [VectorR2bList](#)
- [VectorR2d](#)
- [VectorR2dList](#)
- [VectorR2f](#)
- [VectorR2fList](#)
- [VectorR2i](#)
- [VectorR2iList](#)
- [VectorR2s](#)
- [VectorR2sList](#)
- [VectorR2ub](#)
- [VectorR2ubList](#)
- [VectorR2ui](#)
- [VectorR2uiList](#)
- [VectorR2us](#)
- [VectorR2usList](#)
- [VectorR3b](#)
- [VectorR3bList](#)
- [VectorR3d](#)
- [VectorR3dList](#)
- [VectorR3f](#)
- [VectorR3fList](#)
- [VectorR3i](#)
- [VectorR3iList](#)
- [VectorR3s](#)
- [VectorR3sList](#)
- [VectorR3ub](#)

- [VectorR3ubList](#)
- [VectorR3ui](#)
- [VectorR3uiList](#)
- [VectorR3us](#)
- [VectorR3usList](#)
- [VectorR4b](#)
- [VectorR4bList](#)
- [VectorR4d](#)
- [VectorR4dList](#)
- [VectorR4f](#)
- [VectorR4fList](#)
- [VectorR4i](#)
- [VectorR4iList](#)
- [VectorR4s](#)
- [VectorR4sList](#)
- [VectorR4ub](#)
- [VectorR4ubList](#)
- [VectorR4ui](#)
- [VectorR4uiList](#)
- [VectorR4us](#)
- [VectorR4usList](#)
- [VelocityEngine](#)
- [VolumeList](#)
- [VolumeOperations](#)

BaseRegistrationSettingsStructure

- Defined built-in methods
 - [Built-in: Set 1](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

BaseImageBasedRegistrationSettingsStructure

- Attributes and data descriptors
 - preprocessingMethods
 - Attribute type
 - PreprocessingFilterMethod object
 - Description
 - A image pre-processing filter
 - primaryEndLevel
 - Attribute type
 - Double
 - primaryStartLevel
 - Attribute type
 - Double
 - roiEnd
 - Attribute type
 - [VectorR3d](#) object
 - Description
 - Used to represent the ending point for the region of interest
 - roiStart
 - Attribute type
 - [VectorR3d](#) object
 - Description
 - Used to represent the starting point for the region of interest
 - secondaryEndLevel
 - Attribute type
 - Double
 - secondaryStartLevel
 - Attribute type
 - Double
- Defined built-in methods
 - [Built-in: Set 1](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

BSplineDeformableRegistrationSettingsStructure

- Attributes and data descriptors
 - applyBoundaryContinuityConstrains
 - Type
 - vector < bool >
 - applyTopologicalRegularizer
 - Type
 - vector < bool >
 - gradientMagnitudeTolerance
 - Attribute type
 - vector < double >
 - gridCellSize
 - Attribute type
 - vector < VectorR3d >
 - gridCellSizeType
 - Attribute type
 - vector < char >
 - maximumNumberOfConsecutiveOptimizerAttempts
 - Attribute type
 - vector < int >
 - maximumNumberOfIterations
 - Attribute type
 - vector < int >
 - maximumStepLength
 - Attribute type
 - vector < double >
 - metricValuePercentageDifferent
 - Attribute type
 - vector < double >
 - minimumStepLength
 - Attribute type
 - vector < double >
 - numberOfHistogramBins
 - Attribute type
 - vector < int >
 - numberOfMultiResolutionLevels
 - Attribute type
 - Integer
 - Description

- Represents the number of resolution levels
 - relaxationFactor
 - Attribute type
 - vector < double >
 - samplesDenominator
 - Attribute type
 - vector < int >
 - topologicalRegularizerDistanceLimitingCoefficient
 - Attribute type
 - vector < VectorR3d >
- Inherited data descriptors
 - From BaseImageBasedRegistrationSettingsStructure
 - preprocessingMethod
 - primaryEndLevel
 - primaryStartLevel
 - roiEnd
 - roiStart
 - secondaryEndLevel
 - secondaryStartLevel
- Defined built-in methods
 - [Built-in: Set 1](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

RigidRegistrationSettingsStructure

- Attributes and data descriptors
 - disableRotationsX
 - Attribute type
 - Boolean
 - disableRotationsY
 - Attribute type
 - Boolean
 - disableRotationsZ
 - Attribute type
 - Boolean
 - disableTranslationsX
 - Attribute type
 - Boolean
 - disableTranslationsY
 - Attribute type
 - Boolean
 - disableTranslationsZ
 - Attribute type
 - Boolean
 - maximumNumberOfIterations
 - Attribute type
 - Integer
 - maximumStepLength
 - Attribute type
 - Double
 - minimumStepLength
 - Attribute type
 - Double
 - numberOfHistogramBins
 - Attribute type
 - Integer
 - performInitialAutoAlignment
 - Attribute type
 - Boolean
 - samplesDenominator
 - Attribute type
 - Integer
- Inherited data descriptors

- From BaseImageBaswedRegistrationSettingsStructure
 - preprocessingMethod
 - primaryEndLevel
 - primaryStartLevel
 - roiEnd
 - roiStart
 - secondaryEndLevel
 - secondaryStartLevel
- Defined built-in methods
 - [Built-in: Set 1](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

ManualRegistrationSettingsStructure

- Attributes and data descriptors
 - registrationMatrix
 - Attribute type
 - [MatrixR44d](#) object
 - Description
 - Represents the rigid transformation matrix of the registration
- Defined built-in methods
 - [Built-in: Set 1](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

BoolList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

CharList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

CropSettings

- Data descriptors
 - margin
 - marginDirection
 - operation
- Defined built-in methods
 - [Built-in: Set 1](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

DoubleList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

ExportOperations

- Attributes
 - DICOM_REG
 - Value
 - 2
 - DICOM_RTPLAN
 - Value
 - 1
 - DICOM_RTSTRUCT
 - Value
 - 3
 - DICOM_VOLUME
 - Value
 - 0
- Defined built-in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - documentNameStrFilenameFormatted(reportRecordId)
 - Return type
 - String
 - Description
 - Returns the name of the specified document as a formatted string
 - Calls getErrorMessage() method and returns an empty string if there is an error
 - exportDicomObject(objectType, objectUID, folderPath, overrideWithInfoFromDB = false, encodingType = ORIGINAL_ENCODING)
 - Return type
 - Boolean
 - Description
 - Exports a dicom object to the specified folder path
 - exportReportDocument(reportRecordId, baseFilenameExport, baseFolderPathExport)
 - Return type
 - Boolean
 - Description
 - Exports the report to the specified folder path
 - Returns false if there is an error
 - getErrorMessage()
 - Return type

- String
 - Description
 - Returns a string displaying an error message
- getLocalizedMessage()
 - Return type
 - String
 - Description
 - Returns a string displaying an error message
- patientIdStrFilenameFormatted()
 - Return type
 - String
 - Description
 - Returns the patient id as a formatted string
 - Calls the getErrorMessage() method and returns an empty string if an error occurs
- registrationNameStrFilenameFormatted()
 - Return type
 - String
 - Description
 - Returns the name of the current registration object as a formatted string
 - Calls the getErrorMessage() method and returns an empty string if an error occurs
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

FloatList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

Image2DList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

ImportOperations

- Defined built-in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - getErrorMessage()
 - Return type
 - String
 - Description
 - Returns a string displaying an error message
 - getLocalizedMessage()
 - Return type
 - String
 - Description
 - Returns a string displaying an error message
 - importDirectory(path, recursive)
 - Return type
 - Boolean
 - Description
 - Imports DICOM files
 - importEclipseTrePointSet(fileLocation, registrationCommissioningName)
 - Return type
 - Integer
 - Description
 - Imports the TRE Point Set from the Eclipse database and returns the record id
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

IntList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

MarginSettings

- Data descriptors
 - marginDirection
 - marginType
 - marginValue
 - marginValueNegX
 - marginValueNegY
 - marginValueNegZ
 - marginValueX
 - marginValueY
 - marginValueZ
- Defined built-in methods
 - [Built-in: Set 1](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

MatrixR22d

- Attributes
 - num_cols
 - Attribute type
 - Integer
 - Constant
 - Value
 - 2
 - num_rows
 - Attribute type
 - Integer
 - Constant
 - Value
 - 2
- Defined built in methods
 - [Built-in: Set 1](#)
 - [Built-int: Set 3](#)
- Other defined methods
 - elements()
 - Return Type
 - E
 - Description
 - Returns a pointer to an array with the elements in the matrix
 - extractScale(scale)
 - Description
 - Extracts the scale from the matrix
 - extractTranslation(translation)
 - Description
 - Extracts the translation from the matrix
 - get()
 - identity()
 - Description
 - Sets the matrix back to identity
 - invert()
 - Description
 - Changes the matrix to its inverse
 - isRigid()
 - Return type
 - Boolean

- Description
 - Determines if a matrix is a pure Rigid
- set()
- setElements(elementArray)
 - Description
 - Copies the elements from an array into the matrix
- transpose(m)
 - Description
 - Returns the transpose of the matrix
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

MatrixR22i

- Attributes
 - num_cols
 - Attribute type
 - Integer
 - Constant
 - Value
 - 2
 - num_rows
 - Attribute type
 - Integer
 - Constant
 - Value
 - 2
- Defined built in methods
 - [Built-in: Set 1](#)
 - [Built-int: Set 3](#)
- Other defined methods
 - elements()
 - Return Type
 - E
 - Description
 - Returns a pointer to an array with the elements in the matrix
 - extractScale(scale)
 - Description
 - Extracts the scale from the matrix
 - extractTranslation(translation)
 - Description
 - Extracts the translation from the matrix
 - get()
 - identity()
 - Description
 - Sets the matrix back to identity
 - invert()
 - Description
 - Changes the matrix to its inverse
 - isRigid()
 - Return type
 - Boolean

- Description
 - Determines if a matrix is a pure Rigid
- set()
- setElements(elementArray)
 - Description
 - Copies the elements from an array into the matrix
- transpose(m)
 - Description
 - Returns the transpose of the matrix
- Inherited methods
 - From `__builtin__.SwigPyObject`)
 - [All `__builtin__.SwigPyObject` methods](#)

MatrixR33d

- Attributes
 - num_cols
 - Attribute type
 - Integer
 - Constant
 - Value
 - 3
 - num_rows
 - Attribute type
 - Integer
 - Constant
 - Value
 - 3
- Defined built in methods
 - [Built-in: Set 1](#)
 - [Built-int: Set 3](#)
- Other defined methods
 - elements()
 - Return Type
 - E
 - Description
 - Returns a pointer to an array with the elements in the matrix
 - extractScale(scale)
 - Description
 - Extracts the scale from the matrix
 - extractTranslation(translation)
 - Description
 - Extracts the translation from the matrix
 - get()
 - identity()
 - Description
 - Sets the matrix back to identity
 - invert()
 - Description
 - Changes the matrix to its inverse
 - isRigid()
 - Return type
 - Boolean

- Description
 - Determines if a matrix is a pure Rigid
- set()
- setElements(elementArray)
 - Description
 - Copies the elements from an array into the matrix
- transpose(m)
 - Description
 - Returns the transpose of the matrix
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

MatrixR33f

- Attributes
 - num_cols
 - Attribute type
 - Integer
 - Constant
 - Value
 - 3
 - num_rows
 - Attribute type
 - Integer
 - Constant
 - Value
 - 3
- Defined built in methods
 - [Built-in: Set 1](#)
 - [Built-int: Set 3](#)
- Other defined methods
 - elements()
 - Return Type
 - E
 - Description
 - Returns a pointer to an array with the elements in the matrix
 - extractScale(scale)
 - Description
 - Extracts the scale from the matrix
 - extractTranslation(translation)
 - Description
 - Extracts the translation from the matrix
 - get()
 - identity()
 - Description
 - Sets the matrix back to identity
 - invert()
 - Description
 - Changes the matrix to its inverse
 - isRigid()
 - Return type
 - Boolean

- Description
 - Determines if a matrix is a pure Rigid
- set()
- setElements(elementArray)
 - Description
 - Copies the elements from an array into the matrix
- transpose(m)
 - Description
 - Returns the transpose of the matrix
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

MatrixR44d

- Attributes
 - num_cols
 - Attribute type
 - Integer
 - Constant
 - Value
 - 4
 - num_rows
 - Attribute type
 - Integer
 - Constant
 - Value
 - 4
- Defined built in methods
 - [Built-in: Set 1](#)
 - [Built-int: Set 3](#)
- Other defined methods
 - elements()
 - Return Type
 - E
 - Description
 - Returns a pointer to an array with the elements in the matrix
 - extractScale(scale)
 - Description
 - Extracts the scale from the matrix
 - extractTranslation(translation)
 - Description
 - Extracts the translation from the matrix
 - get()
 - identity()
 - Description
 - Sets the matrix back to identity
 - invert()
 - Description
 - Changes the matrix to its inverse
 - isRigid()
 - Return type
 - Boolean

- Description
 - Determines if a matrix is a pure Rigid
- set()
- setElements(elementArray)
 - Description
 - Copies the elements from an array into the matrix
- transpose(m)
 - Description
 - Returns the transpose of the matrix
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

MatrixR44f

- Attributes
 - num_cols
 - Attribute type
 - Integer
 - Constant
 - Value
 - 4
 - num_rows
 - Attribute type
 - Integer
 - Constant
 - Value
 - 4
- Defined built in methods
 - [Built-in: Set 1](#)
 - [Built-int: Set 3](#)
- Other defined methods
 - elements()
 - Return Type
 - E
 - Description
 - Returns a pointer to an array with the elements in the matrix
 - extractScale(scale)
 - Description
 - Extracts the scale from the matrix
 - extractTranslation(translation)
 - Description
 - Extracts the translation from the matrix
 - get()
 - identity()
 - Description
 - Sets the matrix back to identity
 - invert()
 - Description
 - Changes the matrix to its inverse
 - isRigid()
 - Return type
 - Boolean

- Description
 - Determines if a matrix is a pure Rigid
- set()
- setElements(elementArray)
 - Description
 - Copies the elements from an array into the matrix
- transpose(m)
 - Description
 - Returns the transpose of the matrix
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

PatientDataItem

- Defined built in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - getVelocityId()
 - Return Type
 - Integer
 - Description
 - Returns the velocity id value of the object
 - isValid()
 - Return Type
 - Boolean
 - Description
 - Determines if the object is a valid object
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

Image2D

- Defined built in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - getDateCreated()
 - Return type
 - String
 - Description
 - Returns the date that the image was created
 - Formats the date in ISO format
 - getDateEdited()
 - Return type
 - String
 - Description
 - Returns the date that the image was edited
 - Formats the date in ISO format
 - getInstanceUID()
 - Return type
 - String
 - getModality()
 - Return type
 - String
 - getName()
 - Return type
 - String
 - Description
 - Returns the name
 - getPatient()
 - Return type
 - [Patient](#) object
 - Description
 - Returns the patient object
 - getSeriesUID()
 - Return type
 - String
 - getStudyDate()
 - Return type
 - String
 - Description

- Returns the date of the study
 - Formats the date in ISO format
 - getStudyUID()
 - Return type
 - String
 - getType()
 - Return type
 - String
 - isLocked()
 - Return type
 - Boolean
 - Description
 - Determines if the object is locked
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)
 - From `PatientDataItem`
 - `getVelocityId()`
 - Return Type
 - Integer
 - Description
 - Returns the velocity id value of the object
 - `isValid()`
 - Return Type
 - Boolean
 - Description
 - Determines if the object is a valid object

Patient

- Defined built in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - getDateCreated()
 - Return type
 - String
 - Description
 - Returns the date that the record was created
 - Formats the date in ISO format
 - getDateOfBirth()
 - Return type
 - String
 - Description
 - Returns the patient's date of birth
 - Formats the date in ISO format
 - getDateEdited()
 - Return type
 - String
 - Description
 - Returns the date that the record was edited
 - Formats the date in ISO format
 - getFirstName()
 - Return type
 - String
 - Description
 - Returns the patient's first name
 - getLastName()
 - Return type
 - String
 - Description
 - Returns the patient's last name
 - getPatientId()
 - Return type
 - String
 - Description
 - Returns the patient's id
 - getPlans()
 - Return type

- vector < Plan >
 - getSex()
 - Return type
 - String
 - Description
 - Returns the patient's sex
 - getVolumes()
 - Return type
 - vector < Volume >
 - Parameters
 - modalityToGet
 - isLocked()
 - Return type
 - Boolean
 - Description
 - Determines if the object is locked
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)
 - From `PatientDataItem`
 - `getVelocityId()`
 - Return Type
 - Integer
 - Description
 - Returns the velocity id value of the object
 - `isValid()`
 - Return Type
 - Boolean
 - Description
 - Determines if the object is a valid object

Plan

- Defined built in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - getDate()
 - Return type
 - String
 - Description
 - Returns the date the plan was created
 - Formats the date in ISO format
 - getDoseVolumeIds()
 - Return type
 - vector < int >
 - Description
 - Returns the id values of the dose volumes
 - getDoseVolumes()
 - Return type
 - vector < Volume >
 - Description
 - Returns the dose volumes
 - getEditDate()
 - Return type
 - String
 - Description
 - Returns the date that the plan was edited
 - Formats the date in ISO format
 - getInstanceUID()
 - Return type
 - String
 - Description
 - Returns the UID of the instance
 - getName()
 - Return type
 - String
 - Description
 - Returns the name of the plan
 - getSeriesUID()
 - Return type
 - String

- Description
 - Returns the UID of the series
- getStructureSet()
 - Return type
 - [StructureSet](#) object
 - Description
 - Returns the structure set
- getStructureSetUID()
 - Return type
 - String
 - Description
 - Returns the UID of the structure sets
- getStructureVelocityIds()
 - Return type
 - vector < int >
 - Description
 - Returns the velocity ids of the structures
- getStructures()
 - Return type
 - vector < Structure >
 - Description
 - Returns the structures
- getStudyDate()
 - Return type
 - String
 - Description
 - Returns the date the study was created
 - Formats the date in ISO format
- getStudyUID()
 - Return type
 - String
 - Description
 - Returns the UID of the study
- getVolume()
 - Return type
 - [Volume](#) object
 - Description
 - Returns the volume
- getVolumeVelocityId()

- Return type
 - Integer
 - Description
 - Returns the velocity id of the volume
- isLocked()
 - Return type
 - Boolean
 - Description
 - Determines if the current plan is locked
- Inherited methods
 - From `__builtin__.SwigPyObject`)
 - [All `__builtin__.SwigPyObject` methods](#)
 - From `PatientDataItem`
 - `getVelocityId()`
 - Return Type
 - Integer
 - Description
 - Returns the velocity id value of the object
 - `isValid()`
 - Return Type
 - Boolean
 - Description
 - Determines if the object is a valid object

Registration

- Defined built in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - getDate() **Deprecated**
 - Return type
 - String
 - Description
 - Returns the date that the registration was created
 - Formats the date in ISO format
 - getDicomRegistrationUID()
 - Return type
 - String
 - Description
 - Returns the UID of the DICOM registration
 - getEditDate()
 - Return type
 - String
 - Description
 - Returns the date that the registration was edited
 - Formats the date in ISO format
 - getInstanceUID()
 - Return type
 - String
 - Description
 - Returns the UID of the instance
 - getName()
 - Return type
 - String
 - Description
 - Returns the name of the registration
 - getSourceVolume()
 - Return type
 - [Volume](#) object
 - Description
 - Returns the source volume
 - getTargetVolume()
 - Return type
 - [Volume](#) object

- Description
 - Returns the target volume
 - getType()
 - Return type
 - String
 - Description
 - Returns the registration type
 - isLocked()
 - Return type
 - Boolean
 - Description
 - Determines if the registration is locked
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)
 - From `PatientDataItem`
 - `getVelocityId()`
 - Return Type
 - Integer
 - Description
 - Returns the velocity id value of the object
 - `isValid()`
 - Return Type
 - Boolean
 - Description
 - Determines if the object is a valid object

RegistrationCommissioningMarkerList

- Defined built in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - getDate()
 - Return type
 - String
 - Description
 - Returns the date that the registration commissioning marker was created
 - Formats the date in ISO format
 - getName()
 - Return type
 - String
 - Description
 - Returns the name of the registration commissioning marker
 - getPrimaryVolume()
 - Return type
 - [Volume](#) object
 - Description
 - Returns the primary volume
 - getRegistrationMarkerList()
 - Return type
 - vector < RegistrationMarker >
 - Description
 - Returns the list of registration markers
 - getSecondaryVolume()
 - Return type
 - [Volume](#) object
 - Description
 - Returns the secondary volume
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)
 - From `PatientDataItem`
 - `getVelocityId()`
 - Return Type
 - Integer
 - Description

- Returns the velocity id value of the object
- isValid()
 - Return Type
 - Boolean
 - Description
 - Determines if the object is a valid object

Structure

- Defined built in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - getDate()
 - Return type
 - String
 - Description
 - Returns the date that the structure was created
 - Formats the date in ISO format
 - getEditDate()
 - Return type
 - String
 - Description
 - Returns the date that the structure was edited
 - Formats the date in ISO format
 - getFrameOfReferenceUID()
 - Return type
 - String
 - Description
 - Returns the UID of the frame of reference
 - getInstanceUID()
 - Return type
 - String
 - Description
 - Returns the UID of the instance
 - getName()
 - Return type
 - String
 - Description
 - Returns the name of the structure
 - getROINumber()
 - Return type
 - String
 - Description
 - Returns the ROI number of the structure
 - getStructureSet()
 - Return type
 - [StructureSet](#) object

- Description
 - Returns the structure set
 - getType()
 - Return type
 - String
 - Description
 - Returns the type of the structure
 - getVolume()
 - Return type
 - [Volume](#) object
 - Description
 - Returns the volume of the structure
 - getVolumeId()
 - Return type
 - Integer
 - Description
 - Returns the id of the volume of the structure
 - getVolumetricSize()
 - Return type
 - Double
 - Description
 - Returns the size of the volume of the structure
 - isEditable()
 - Return type
 - Boolean
 - Description
 - Returns if the structure can be edited
 - isLocked()
 - Return type
 - Boolean
 - Description
 - Returns if the structure is locked
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)
 - From `PatientDataItem`
 - getVelocityId()
 - Return Type
 - Integer

- Description
 - Returns the velocity id value of the object
- isValid()
 - Return Type
 - Boolean
 - Description
 - Determines if the object is a valid object

StructureSet

- Defined built in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - getDate()
 - Return type
 - String
 - Description
 - Returns the date that the structure set was created
 - Formats the date in ISO format
 - getEditDate()
 - Return type
 - String
 - Description
 - Returns the date that the structure set was edited
 - Formats the date in ISO format
 - getInstanceUID()
 - Return type
 - String
 - Description
 - Returns the UID of the instance
 - getName()
 - Return type
 - String
 - Description
 - Returns the name of the structure set
 - getSeriesDescription()
 - Return type
 - String
 - Description
 - Returns the description of the structure set series
 - getSeriesUID()
 - Return type
 - String
 - Description
 - Returns the UID of the series
 - getStructures()
 - Return type
 - vector < Structure >

- Description
 - Returns the structures in the structure set
 - getStudyDate()
 - Return type
 - String
 - Description
 - Returns the date that the study was created
 - Formats the date in ISO format
 - getStudyUID()
 - Return type
 - String
 - Description
 - Returns UID of the study
 - getVolume()
 - Return type
 - [Volume](#) object
 - Description
 - Returns the volume of the structure set
 - getVolumeUID()
 - Return type
 - String
 - Description
 - Returns the UID of the volume
 - isLocked()
 - Return type
 - Boolean
 - Description
 - Returns if the structure set is locked
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)
 - From `PatientDataItem`
 - `getVelocityId()`
 - Return Type
 - Integer
 - Description
 - Returns the velocity id value of the object
 - `isValid()`
 - Return Type

- Boolean
- Description
 - Determines if the object is a valid object

Volume

- Defined built in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - getAccessionNumber()
 - Return type
 - String
 - Description
 - Returns the accession number of the volume
 - getAllStructures()
 - Return type
 - vector < Structure >
 - Description
 - Returns all of the structures
 - getCreateDate()
 - Return type
 - String
 - Description
 - Returns the date that the volume was created
 - Formats the date in ISO format
 - getDicomPatientDateOfBirth()
 - Return type
 - String
 - Description
 - Returns the date that the patient was born
 - Formats the date in ISO format
 - getDicomPatientId()
 - Return type
 - String
 - Description
 - Returns the patient id
 - getDicomPatientName()
 - Return type
 - String
 - Description
 - Returns the name of the patient
 - getDicomPatientSex()
 - Return type
 - String

- Description
 - Returns the sex of the patient
- getDicomReferringPhysicianName()
 - Return type
 - String
 - Description
 - Returns the name of the patient's physician
- getEditDate()
 - Return type
 - String
 - Description
 - Returns the date that the volume was edited
 - Formats the date in ISO format
- getFrameOfReferenceUID()
 - Return type
 - String
 - Description
 - Returns the UID of the frame of reference
- getLinkedPlans()
 - Return type
 - vector < Plan >
 - Description
 - Returns the plans linked to the volume
- getLinkedRegistrations()
 - Return type
 - vector < Registration >
 - Description
 - Returns the registrations linked to the volume
- getModality()
 - Return type
 - String
 - Description
 - Returns the modality
- getName()
 - Return type
 - String
 - Description
 - Returns the name of the volume
- getPatient()

- Return type
 - [Patient](#) object
- Description
 - Returns the patient
- getPlanUID()
 - Return type
 - String
 - Description
 - Returns the plan UID of the dose volumes
- getSeriesDate()
 - Return type
 - String
 - Description
 - Returns the date the series was created
 - Formats the date in ISO format
- getSeriesNumber()
 - Return type
 - String
 - Description
 - Returns the number of the series
- getSeriesTime()
 - Return type
 - String
 - Description
 - Returns the time the series was created
- getSeriesType()
 - Return type
 - String
 - Description
 - Returns the type of the series
- getSeriesUID()
 - Return type
 - String
 - Description
 - Returns the UID of the series
- getSourceType()
 - Return type
 - String
 - Description

- Returns the type of the source
- getStructureSets()
 - Return type
 - vector < StructureSet >
 - Description
 - Return the structure sets of the volume
- getStudyDate()
 - Return type
 - String
 - Description
 - Returns the date the study was created
 - Formats the date in ISO format
- getStudyDescription()
 - Return type
 - String
 - Description
 - Returns the description of the study
- getStudyId()
 - Return type
 - String
 - Description
 - Returns the id of the study
- getStudyInstanceUID()
 - Return type
 - String
 - Description
 - Returns the UID of the study instance
- getStudyTime()
 - Return type
 - String
 - Description
 - Returns the time the study was created
- getVolumeUID
 - Return type
 - String
 - Description
 - Returns the UID of the volume
- isLocked()
 - Return type

- Boolean
 - Description
 - Returns if the volume is locked
- registrationCommissioningMarkerLists()
 - Return type
 - vector < RegistrationCommissioningMarkerList >
 - Parameters
 - secondaryVolumeId
- Inherited methods
 - From __builtin__.SwigPyObject
 - [All __builtin__.SwigPyObject methods](#)
 - From PatientDataItem
 - getVelocityId()
 - Return Type
 - Integer
 - Description
 - Returns the velocity id value of the object
 - isValid()
 - Return Type
 - Boolean
 - Description
 - Determines if the object is a valid object

PatientDataOperations

- Defined built in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - getErrorMessage()
 - Return type
 - String
 - Description
 - Returns an error message based on the error that has occurred
 - getLocalizedMessage()
 - Return type
 - String
 - Description
 - Returns a localized error message based on the error that has occurred
 - getPatient(vscId)
 - Return type
 - [Patient](#) object
 - Description
 - Returns the patient of a given vsc id
 - getPatientByPatientId(patientId)
 - Return type
 - [Patient](#) object
 - Description
 - Returns the patient of a given patient id
 - getPatients()
 - Return type
 - vector < patientdata::Patient >
 - Description
 - Returns the patients
 - getPlan(velocityId)
 - Return type
 - [Plan](#) object
 - Description
 - Returns the plan of a given velocity id
 - getRegistration(velocityId)
 - Return type
 - [Registration](#) object
 - Description

- Returns the registration of a given velocity id
 - `getRegistrationCommissioningMarkerList(velocityId)`
 - Return type
 - [RegistrationCommissioningMarkerList](#) object
 - Description
 - Returns the registration commissioning marker list of a given velocity id
 - `getStructure(velocityId)`
 - Return type
 - [Structure](#) object
 - Description
 - Returns the structure of a given velocity id
 - `getStructureSet(velocityId)`
 - Return type
 - [StructureSet](#) object
 - Description
 - Returns the structure set of a given velocity id
 - `getStructureSetByUID(uid)`
 - Return type
 - [StructureSet](#) object
 - Description
 - Returns the structure set of a given UID
 - `getVolume(velocityId)`
 - Return type
 - [Volume](#) object
 - Description
 - Returns the volume of a given velocity id
 - `getVolumeByUID(uid)`
 - Return type
 - [Volume](#) object
 - Description
 - Returns the volume of a given UID
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

PatientList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

PlanList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

RegistrationCommissioningMarkerLists

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

RegistrationList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

RegistrationMarker

- Defined built in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - getName()
 - Return type
 - String
 - Description
 - Returns the name of the registration marker
 - getPrimaryLocation()
 - Return type
 - [VectorR3d](#) object
 - Description
 - Returns the primary location of the registration marker
 - getSecondaryLocation()
 - Return type
 - [VectorR3d](#) object
 - Description
 - Returns the secondary location of the registration marker
 - isConfirmed()
 - Return type
 - Boolean
 - Returns if the registration marker has been confirmed
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

RegistrationMarkerList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

RegistrationOperations

- Defined built in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - computeJacobian()
 - Return type
 - [ScaledVolumeData](#) object
 - Description
 - Calculates the Jacobian from loaded volumes and registrations
 - Will return an empty volume data if there is an error
 - createNewRegistration(name, progress = nullptr)
 - Return type
 - [Registration](#) object
 - Description
 - Creates a new rigid registration with a given name
 - exportRegistration(registrationId, progress = nullptr)
 - Description
 - Creates a DICOM file of the current registration
 - getErrorMessage()
 - Return value
 - String
 - Description
 - Returns an error message based on the error that has occurred
 - getLocalizedMessage()
 - Return value
 - String
 - Description
 - Returns a localized error message based on the error that has occurred
 - getTransformedRegistrationCommissioningMarkers(markerListId)
 - Return type
 - pair < bool, vector < TransformedRegistrationMarker > >
 - Description
 - Returns a list of registration commissioned markers
 - The registration commissioned markers will be converted to coordinate systems
 - performBsplineRegistration(settings)
 - Return type
 - Boolean

- Description
 - Performs a BSpline deformable registration of two loaded volumes
 - Requires coordinate and image values to exist in Velocity's coordinate space and units
 - Returns true if the deformable registration occurs successfully
- performBsplineRegistrationDICOM(settings)
 - Return type
 - Boolean
 - Description
 - Performs a BSpline deformable registration of two loaded volumes
 - Requires coordinate and image values to exist in DICOM coordinate space and units
 - Returns true if the deformable registration occurs successfully
- performManualAlignment(settings)
 - Return type
 - Boolean
 - Description
 - Performs a manual alignment of two loaded volumes
 - Requires coordinate and image values to exist in Velocity's coordinate space and units
 - Returns true if the manual alignment occurs successfully
- performManualAlignmentDICOM(settings)
 - Return type
 - Boolean
 - Description
 - Performs a manual alignment of two loaded volumes
 - Requires coordinate and image values to exist in DICOM coordinate space and units
 - Returns true if the manual alignment occurs successfully
- performRigidRegistration(settings)
 - Return type
 - Boolean
 - Description
 - Performs a rigid registration of two loaded volumes
 - Requires coordinate and image values to exist in Velocity's coordinate space and units
 - Returns true if the rigid registration occurs successfully
- performRigidRegistrationDICOM(settings)
 - Return type

- Boolean
- Description
 - Performs a rigid registration of two loaded volumes
 - Requires coordinate and image values to exist in DICOM coordinate space and units
 - Returns true if the rigid registration occurs successfully
- saveRegistration(progress = nullptr)
 - Return type
 - [Registration](#) object
 - Description
 - Saves loaded registration to the database
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

ReportOperations

- Defined built in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - appendToReport(htmlStreamDataToAppend, includePatientHeaderInformation = true)
 - Return type
 - Boolean
 - Description
 - Appends a specified html stream to the internal html report
 - Calls getErrorMessage() method and returns false if an error occurs
 - attachRegistrationCommissioningToReport(registrationCommissioningMarkerListRecord)
 - Return type
 - Boolean
 - Description
 - Attaches the specified registration commissioning marker to the internal report
 - Calls getErrorMessage() method and returns false if an error occurs
 - attachViewer3DToReport()
 - Return type
 - Boolean
 - Description
 - Attaches the viewer state to the internal report
 - clearReport()
 - Description
 - Clears the internal html report
 - getErrorMessage()
 - Return type
 - String
 - Description
 - Returns an error message based on the error that has occurred
 - getLocalizedErrorMessage()
 - Return type
 - String
 - Description

- Returns a localized error message based on the error that has occurred
 - `getReport()`
 - Return type
 - String
 - Description
 - Returns the internal html report
 - `loadPersistentCachedReport()`
 - Return type
 - Boolean
 - Description
 - Loads persistent reports for the current patient from the database
 - `loadReportFromDatabase(reportRecordId)`
 - Return type
 - Boolean
 - Description
 - Loads the specified report from the database
 - `persistCachedReport()`
 - Return type
 - Boolean
 - Description
 - Puts the internal html report into a temporary file in the database
 - `saveReportToDatabase(reportName)`
 - Return type
 - Integer
 - Description
 - Saves the internal html report into the database under the specified name
 - Returns the id number of the report if the save is successful, otherwise -1 is returned
 - Clears the internal report if the save is successful
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

ScaledVolumeData

- Attributes and data descriptors
 - data
 - Attribute type
 - vector < double >
 - indexTransform
 - Attribute type
 - [MatrixR44d](#) object
 - size
 - Attribute type
 - [VectorR3i](#) object
 - volume
 - Attribute type
 - [Volume](#) object
- Defined built in methods
 - [Built-in: Set 1](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

StringList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

StructureGuidedRegistrationInformation

- Attributes and data descriptors
 - burnInStructureVolume
 - Attribute type
 - ImageR3us object
 - burnInVolumeMember
 - Attribute type
 - SelectedVolumeMember object
 - burnInVoxelValue
 - Attribute type
 - Short
 - euclideanDistanceMapModelTransform
 - Attribute type
 - AffineTransformR3d object
 - euclideanDistanceMapOfStructure
 - Attribute type
 - EuclideanDistanceTransformR3 object
 - handleObjectCleanup
 - Attribute type
 - Boolean
 - internalStructurePointsSCE
 - Attribute type
 - vector < VectorR3d >
 - neighboringPointIndices
 - Attribute type
 - vector < vector < int > >
 - primarySurfacePointsSCE
 - Attribute type
 - vector < VectorR3d >
 - secondarySurfacePointsSCE
 - Attribute type
 - vector < VectorR3d >
 - structureGuidedMethod
 - Attribute type
 - StructureGuidedMethod object
 - structureSurfacePointsSCE
 - Attribute type
 - vector < VectorR3d >
 - structureWeightCoefficient

- Attribute type
 - Double
 - surfacePointsWeightCoefficients
 - Attribute type
 - vector < double >
- Defined built in methods
 - [Built-in: Set 1](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

StructureList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

StructureMap

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 2](#)
 - [Undocumented: Set 4](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

StructureOperations

- Defined built in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - conformality(structureId1, structureId2, reporter = nullptr)
 - Return type
 - Double
 - Description
 - Calculates the conformality of two structures
 - copyStructuresToPrimary(secondaryStructureIds, structureSetId)
 - Return type
 - map < int, Structure >
 - Description
 - Copies the structures in the secondary volume to the primary volume
 - copyStructuresToSecondary(primaryStructureIds, structureSetId)
 - Return type
 - map < int, Structure >
 - Description
 - Copies the structures in the primary volume to the secondary volume
 - createStructure(structureSetId, name, type = "Organ", color = nullptr)
 - Return type
 - [Structure](#) object
 - Description
 - Creates a new structure
 - Requires that the type parameter is a valid DICOM type
 - createStructureSet(name, onPrimary, studyUID = "", studyDate = "")
 - Return type
 - [StructureSet](#) object
 - Description
 - Creates a new structure set
 - crop(sourceStructureId, structureSetId, croppingStructureIds, cropSettings, targetName, targetColor = nullptr, reporter = nullptr)
 - Return type
 - [Structure](#) object
 - Description
 - Crops a structure
 - exportStructureSet(structureSetId, encodingType = "", reporter = nullptr)

- Return type
 - Boolean
 - Description
 - Creates the structure set as a RTSTRUCT DICOM file on the disk
- getErrorMessage()
 - Return type
 - String
 - Description
 - Returns an error message based on the error that has occurred
- getLocalizedErrorMessage()
 - Return type
 - String
 - Description
 - Returns a localized error message based on the error that has occurred
- getStructureDVH(structureId, bins)
 - Return type
 - pair < bool, vector < VectorR2d > >
 - Description
 - Calculates the dose volume histogram of a given structure
- getVolumetricStructure(structureId)
 - Return type
 - [ScaledVolumeData](#) object
 - Description
 - Returns the volumetric structure data
 - Requires that the structureId parameter is either the primary or secondary volume
 - Will change the secondary volume to the primary volume if the secondary volume is used
- intersectStructures(structureSetId, structureIds, targetName, targetColor = nullptr, reporter = nullptr)
 - Return type
 - [Structure](#) object
 - Description
 - Creates a structure based on the intersection of multiple structures
- margin(structureSetId, sourceId, targetId, settings, reporter = nullptr)
 - Return type
 - [Structure](#) object
 - Description

- Uses the margin operation on a structure
 - saveStructureSets(structureSetId, encodingType = "")
 - Return type
 - [StructureSet](#) object
 - Description
 - Saves changes to a structure set
 - Must be called after finishing a set of modifications to a structure set
 - smooth(structureId, structureSetId, targetName, reporter = nullptr)
 - Return type
 - [Structure](#) object
 - Description
 - Creates a new structure after smoothing the current structure
 - surfaceDistanceMetrics(structureId1, structureId2)
 - Return type
 - [SurfaceDistanceMetrics](#) object
 - Description
 - Calculates the surface distance between two structures
 - unionStructures(structureSetId, structureIds, targetName, targetColor = nullptr, reporter = nullptr)
 - Return type
 - [Structure](#) object
 - Description
 - Used the union from multiple structures to create a new structure
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

StructureSetList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

SurfaceDistanceMetrics

- Attributes and data descriptors
 - hausdorffDistance
 - Attribute type
 - Double
 - isValid
 - Attribute type
 - Boolean
 - mean
 - Attribute type
 - Double
 - median
 - Attribute type
 - Double
 - min
 - Attribute type
 - Double
 - standardDeviation
 - Attribute type
 - Double
 - structureName1
 - Attribute type
 - String
 - structureName2
 - Attribute type
 - String
- Defined built in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

SwigPyIterator

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 4](#)
 - [Built-in: Set 5](#)
 - `__iter__()`
- Other defined methods
 - [Undocumented: Set 3](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

TransformedRegistrationMarker

- Attributes and data descriptors
 - deformedSecondaryInPrimaryDICOM
 - Attribute type
 - [VectorR3d](#) object
 - deformedSecondaryInScene
 - Attribute type
 - [VectorR3d](#) object
 - deformedSecondaryInSecondaryDICOM
 - Attribute type
 - [VectorR3d](#) object
 - isConfirmed
 - Attribute type
 - Boolean
 - name
 - Attribute type
 - String
 - primaryInIndex
 - Attribute type
 - [VectorR3d](#) object
 - primaryInPrimaryDICOM
 - Attribute type
 - [VectorR3d](#) object
 - primaryInScene
 - Attribute type
 - [VectorR3d](#) object
 - rigidSecondaryInPrimaryDICOM
 - Attribute type
 - [VectorR3d](#) object
 - rigidSecondaryInSecondaryDICOM
 - Attribute type
 - [VectorR3d](#) object
 - secondaryInIndex
 - Attribute type
 - [VectorR3d](#) object
- Defined built in methods
 - [Built-in: Set 1](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`

- [All `__builtin__`.SwigPyObject methods](#)

VectorR2b

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 2
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - $\text{VectorR} < N, E >$
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR2bList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR2d

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 2
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR2dList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR2f

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 2
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR2fList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR2i

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 2
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR2iList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR2s

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 2
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR2sList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR2ub

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 2
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR2ubList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR2ui

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 2
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR2uiList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR2us

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 2
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR2usList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR3b

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 3
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR3bList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR3d

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 3
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR3dList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR3f

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 3
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR3fList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR3i

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 3
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR3iList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR3s

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 3
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR3sList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR3ub

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 3
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR3ubList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR3ui

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 3
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR3uiList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR3us

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 3
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR3usList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR4b

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 4
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR4bList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR4d

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 4
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR4dList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR4f

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 4
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR4fList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR4i

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 4
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR4iList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR4s

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 4
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR4sList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR4ub

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 4
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR4ubList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR4ui

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 4
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR4uiList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VectorR4us

- Attributes
 - SIZE
 - Attribute type
 - Integer
 - Constant
 - Value
 - 4
- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 5](#)
 - `__delitem__()`
 - `__getitem__()`
 - `__setitem__()`
- Other defined methods
 - `nonNegative()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is nonnegative
 - `normalized(epsilon = vsc::VSC_EPSILON)`
 - Return type
 - `VectorR < N, E >` object
 - Description
 - Returns a normalized vector
 - `positive()`
 - Return type
 - Boolean
 - Description
 - Determines if every element in the vector is positive
 - `set(element)`
 - Description
 - Changes all elements in the vector to the specified element
 - `setElements(elementArray)`
 - Description
 - Sets the elements in the vector equal to the elements in the array
 - The vector and array need to have the same number of elements
 - `size()`
 - Description

- Determines the size of the vector
 - xy()
 - Return type
 - VectorR < 2, E >
 - Description
 - Returns the first two components of the vector
 - Sets undefined coordinates to 0
 - xyz()
 - Return type
 - VectorR < 3, E >
 - Description
 - Returns the first three components of the vector
 - Sets undefined coordinates to 0
 - xyzw()
 - Return type
 - VectorR < 4, E >
 - Description
 - Returns the first three components of the vector
 - If the w coordinate is undefined, it is set to 1
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VectorR4usList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VelocityEngine

- Attributes
 - VSC_PRIMARY_VALUE
 - Value
 - 0
 - VSC_SECONDARY_VALUE
 - Value
 - 1
- Defined built-in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - deletePatient(patientId, forceDelete)
 - Return type
 - Boolean
 - Description
 - Deletes the patient with the specified patient id
 - If there are multiple patients with the same id, forceDelete must be true in order to delete the patients
 - Returns true if the patient is successfully deleted
 - getCurrentPatient()
 - Return type
 - [Patient](#) object
 - Description
 - Returns the patient that is currently loaded
 - Will print an error message if there is no patient loaded
 - getErrorMessage()
 - Return type
 - String
 - Description
 - Returns an error message based on the error that has occurred
 - If there is not an error, an empty string is returned
 - getExportOperations()
 - Return type
 - [ExportOperations](#) object
 - Description
 - Returns the export operations for the engine
 - Will return a null pointer if the engine is not connected to the database
 - getImportOperations()

- Return type
 - [ImportOperations](#) object
 - Description
 - Returns the import operations for the engine
 - Will return a null pointer if the engine is not connected to the database
- getLocalizedMessage()
 - Return type
 - String
 - Description
 - Returns a localized error message based on the error that has occurred
 - If there is not a localized error, and empty string is returned
- getPatientDataOperations()
 - Return type
 - [PatientDataOperations](#) object
 - Description
 - Returns the patient data operations for the engine
 - Will return a null pointer if the engine is not connected to the database
- getPatientVolumeUIDs(patientID, modality)
 - Return type
 - vector < string >
 - Description
 - Returns the volumeUIDs of a specified patient in the form of a vector
- getPrimaryVolume()
 - Return type
 - [Volume](#) object
 - Description
 - Returns the primary volume of the current patient
- getRegistrationOperations()
 - Return type
 - [RegistrationOperations](#) object
 - Description
 - Returns the registration operations for the engine
 - Will return a null pointer if the engine is not connected to the database
- getReportOperations()

- Return type
 - [ReportOperations](#) object
 - Description
 - Returns the report operations for the engine
 - Will return a null pointer if the engine is not connected to the database
- getSecondaryVolume()
 - Return type
 - [Volume](#) object
 - Description
 - Returns the secondary volume of the current patient
- getStructureOperations()
 - Return type
 - [StructureOperations](#) object
 - Description
 - Returns the structure operations for the engine
 - Will return a null pointer if the engine is not connected to the database
- getValueAtStructureCenter(volume, linearInterp = true)
 - Return type
 - Double
 - Description
 - Returns the value at the structure center of the primary and secondary volumes
- getVolumeOperations()
 - Return type
 - [VolumeOperations](#) object
 - Description
 - Returns the volume operations for the engine
 - Will return a null pointer if the engine is not connected to the database
- isLoggedIn()
 - Return type
 - Boolean
 - Description
 - Determines if the engine is currently logged in
- loadPatientByPatientId(patientId)
 - Return type
 - [Patient](#) object

- Description
 - Loads a patient based on the specified patient id
 - Returns true if the patient is loaded successfully
- loadPatient(patientId)
 - Return type
 - Boolean
 - Description
 - Load a patient based on the specified internal database id
 - Returns true if the patient is loaded successfully
- loadPlan(velocityId)
 - Return type
 - [Plan](#) object
 - Description
 - Loads a plan based on the specified patient id
- loadPlanByUID(uid)
 - Return type
 - [Plan](#) object
 - Description
 - Loads a plan based on the specified UID
- loadPrimaryVolumeByUID(volumeUID)
 - Return type
 - Boolean
 - Description
 - Loads a primary volume based on the specified volume UID
 - Returns true if the volume is loaded successfully
- loadPrimaryVolume(databaseId)
 - Return type
 - Boolean
- loadRegistration(registrationId)
 - Return type
 - [Registration](#) object
 - Description
 - Loads a registration based on the specified registration id
- loadRegistrationByName(name)
 - Return type
 - [Registration](#) object
 - Description
 - Loads a registration based on the specified registration name
- loadSecondaryVolumeByUID(volumeUID)

- Return type
 - Boolean
 - Description
 - Loads a volume based on the specified volume UID
 - Returns true if the volume is loaded successfully
- loadSecondaryVolume(databaseId)
 - Return type
 - Boolean
- loadStructure(velocityId)
 - Return type
 - [Structure](#) object
 - Description
 - Loads a structure based on the specified velocity id
- loadStructureByName(name, structureSetUID)
 - Return type
 - [Structure](#) object
 - Description
 - Loads a structure based on the specified structure name
 - The structure must have a unique name in the set in order to be loaded properly
- loadStructureByUID(uid)
 - Return type
 - [Structure](#) object
 - Description
 - Loads a structure based on the specified structure UID
- loginToGrid(username, password, ip, port, dbLabel)
 - Return type
 - Boolean
 - Description
 - Logs into the the specified Grid database
 - Returns true if the specified Grid database is successfully logged into
 - All parameters must be valid in order to successfully log in
- loginToWorkstation(username, password, path, force = false)
 - Return type
 - Boolean
 - Description
 - Logs into the specified workstation database

- Returns true if the specified workstation database is successfully logged into
 - All parameters must be valid in order to successfully log in
 - logout()
 - Return type
 - Boolean
 - Description
 - Logs out of the database
 - Logging out makes all Operations class instances invalid
 - unloadPatient()
 - Return type
 - Boolean
 - Description
 - Unloads the current patient
 - Will cause the primary and secondary volumes to also unload
 - unloadPrimaryVolume()
 - Return type
 - Boolean
 - Description
 - Unloads the current primary volume
 - Will cause the secondary volume to unload
 - unloadSecondaryVolume()
 - Return type
 - Boolean
 - Description
 - Unloads the current secondary volume
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All __builtin__.SwigPyObject methods](#)

VolumeList

- Defined built-in methods
 - [Built-in: Set 1](#)
 - [Built-in: Set 2](#)
- Other defined methods
 - [Undocumented: Set 1](#)
 - [Undocumented: Set 2](#)
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)

VolumeOperations

- Defined built-in methods
 - [Built-in: Set 1](#)
- Other defined methods
 - createBEDDose(fractions, structureNames, structureIds, structRatioVal, progress = nullptr)
 - Return type
 - Integer
 - Description
 - Performs the BED scaling for the loaded secondary volume based on the loaded primary volume
 - Returns the volume id of the created volume, unless there is an error, in which -1 is returned
 - createBEDDoseByStructureUIDs(fractions, structureNames, structureUIDs, structRatioVal, progress = nullptr)
 - Return type
 - Integer
 - Description
 - Performs the BED scaling for the loaded secondary volume based on the loaded primary volume
 - Returns the volume id of the created volume unless there is an error, in which -1 is returned
 - createResampledPrimaryVolume(elementOperation, name = "", scalingCoefficient = 1.0, progress = nullptr)
 - Return type
 - Integer
 - Description
 - Performs the resampling of the specified element operation for the loaded primary volume
 - An error will occur if the specified element operation must be performed on multiple volumes
 - getErrorMessage()
 - Return type
 - String
 - Description
 - Returns an error message based on the error that has occurred
 - getLocalizedErrorMessage()
 - Return type
 - String

- Description
 - Returns a localized error message based on the error that has occurred
- Inherited methods
 - From `__builtin__.SwigPyObject`
 - [All `__builtin__.SwigPyObject` methods](#)