MALWARE ANALYSIS / STATIC REVERSE ENGINEERING

REMUS

Infostealer

Go loader and native Windows payload

Reconstruction, collection capabilities, command protocol, and blockchain-based infrastructure discovery.

Family assessment	Remus / high confidence
Method	Offline static analysis
Execution / C2 contact	Not performed
Report date	October 23, 2026

SHA256
744F82ADDA79C794C3462DED64800CD9A50F47FB9F198C95E0235ABE341944F2

An independent sample investigation. This report is a public portfolio example, not a commissioned client investigation or evidence of a specific host compromise.

01

Executive summary

The recovered native executable supports a high-confidence Remus-family assessment. A Go-based loader reconstructs an embedded PE32+ payload with information-collection, HTTP command, upload, and Ethereum contract lookup code.

Key findings

Stage reconstruction	A 336,567-byte PE32+ payload was recovered from a 336,560-byte embedded data blob.
Collection	Static call paths support screen capture, Unicode clipboard access, and protected-data API use.
Transport	The payload contains step-indexed HTTP requests and a multipart upload builder.
Family corroboration	The decoded JSON-RPC request contains the exact Ethereum contract documented in independent Remus research.

Scope and limitations

The sample was not executed. This investigation did not observe a successful network exchange, file theft, an active off-chain C2 destination, persistence, or an affected host.

These findings establish static capabilities and configuration. They do not establish that the capabilities were exercised on a real system.

02

Loader reconstruction

The second-stage Windows executable was recovered and identified without running the original sample.

Reconstruction sequence

1. Go loader

Obfuscated Go application containing a decoding routine and Windows manual-mapping logic.

2. Embedded data

336,560 bytes extracted from the compiled program.

3. Decode and map

The loader transforms embedded data, parses PE headers, maps sections, and resolves imports.

4. Native payload

Recovered 336,567-byte PE32+ x64 Windows executable containing collection and communication functions.

Function references

main.arJGDJ	Decode routine	0x00593160
main.bw4zQ8ZgkM6qO	PE parser and mapper	0x00581400

Artifact identification

The full SHA-256 hashes for the outer loader and recovered payload are listed on page 7.

03

Collection capabilities

The following operations are supported by static call paths. Successful collection on a real host was not observed.

Screen capture

Calls GDI32.BitBlt at 0x140029EDF with SRCCOPY (0x00CC0020). Related code reaches GetDIBits at 0x14002AC39.

Clipboard access

At 0x140029290, the payload resolves OpenClipboard, GetClipboardData, and CloseClipboard. The requested format is CF_UNICODETEXT (0xD).

Protected-data decryption

A reachable function dynamically invokes CryptUnprotectData near 0x14000E67D. The exact target application and successful plaintext recovery remain unverified.

Obfuscated API resolution

The sample uses nonstandard reflected CRC32 hashing: polynomial 0xEDB88320, initial value 0x96577E78, and a final bitwise NOT. DLL names are case-folded; API export names retain case.

04

Command channel

The native payload contains a structured command protocol and upload implementation. Server responses and completed uploads were not observed.

Dispatcher: 0x140008970

access_token=<runtime value>&step=<1, 2, 3, ...>

Response fields: type, data, name, extensions.
Task cases: 0, 1, 2, 3, 4; special value: 5.

Resolved handler paths

Case	Address	Interpretation
0	0x1400099A0	Named handler; precise semantics unresolved
2	0x14000A2A0	Retrieved payload handler
3	0x14000A5F0	Payload plus extension argument
4	0x14000B4F0	Payload plus extension argument

Multipart upload

Function 0x140003950 constructs multipart/form-data with the fields access_token, type, and data. WinHTTP routines handle session creation and request transmission.

This is an exfiltration-capable code path. No evidence of a successful upload was collected.

05

Infrastructure discovery

Decoded constants show an Ethereum JSON-RPC lookup. The same contract is documented in independent Remus research.

Recovered request parameters

RPC host	https://rpc.mevblocker.io
Method	POST / JSON-RPC 2.0
RPC action	eth_call
Contract	0x999941b74F6bbc921D5174A5b29911562cd2D7CF
Selector	0xc2fb26a6
Block	latest

Interpretation

The decoded configuration supplies parameters for an eth_call request through a public Ethereum RPC provider. The contract response may supply a server address. No contract call was executed in this investigation, so the current off-chain C2 destination remains unresolved.

Attribution and infrastructure context

The contract matches published Remus findings from SpyCloud Labs and Iossefy. The gateway rpc.mevblocker.io is a legitimate public service; this analysis does not establish attacker control of that service. It should not be broadly blocked solely because this sample references it.

06

Indicators and investigative guidance

Separate sample-specific identifiers from shared infrastructure and unverified third-party observations.

Verified artifact hashes

Outer loader / SHA-256

744f82adda79c794c3462ded64800cd9
a50f47fb9f198c95e0235abe341944f2

Recovered stage 2 / SHA-256

4306d3d9c3c7563784c792d9e99d2afa
3c0e338fc109ea233af69c804ab94aa5

Infrastructure pivot

0x999941b74F6bbc921D5174A5b29911562cd2D7CF

Documented Ethereum contract; useful as an investigative pivot. Its legitimate RPC gateway is not a sample-specific malicious indicator.

Recommended follow-up

1. Search EDR and file inventories for the two verified SHA-256 hashes.
2. If execution is suspected, preserve host logs, process trees, and network telemetry.
3. Scope potential credential exposure using verified incident evidence.
4. Treat external sandbox domains as unverified leads, not automatic IOCs.

07

Methods, confidence, and sources

Analysis method

Offline static analysis of Ghidra exports, embedded blob decoding, and recovered native PE inspection. Function references, Windows API calls, deobfuscated strings, and independent family research were correlated. Neither executable was detonated.

Evidence labels

High confidence	Direct code or static literal, or an independently corroborated family match.
Inferred	Interpretation of reachable paths requiring further tracing.
Unobserved	No direct runtime evidence from this investigation.

Public corroboration

SpyCloud Labs / September 10, 2026

Remus: A New Infostealer Hunting Wallets, Passwords, and AI Credentials
spycloud.com/blog/remus-a-new-infostealer/

Iossefy / June 17, 2026

Inside Remus Stealer: Obfuscation, Direct Syscalls, and Blockchain-Based C2
iossefy.github.io/malware/remus-stealer

This public portfolio sample describes an offline investigation, not a customer engagement or a specific machine infection. Unverified third-party sandbox leads are excluded from the primary indicator set.