To Implement how to List Active Jobs, Display Status Information, Retrieve Job IDs, Format Output, Update State Information, Test Job Listings.

To design how to Identify Target Job, Transfer Terminal Control, Resume Processes, Wait for Completion, Update Job State, Test Foreground Switching.

```
[varnikakomali@VARNIKAs-MacBook-Air Skill % nano skill_17.c
[varnikakomali@VARNIKAs-MacBook-Air Skill % gcc skill_17.c -o skill_17 && ./skill_17
 === Part 1: Launching Tasks & Testing Job Listings ===

Starting Job 1: sleep 3 &
Starting Job 2: sleep 1 &
--- Active Jobs Listing ---
JID      PID      PGID     STATUS       COMMAND
[1]      66583    66583    Running      sleep 3 &
[2]      66584    66584    Running      sleep 1 &
--------------------------

Sleeping parent for 1.2 seconds to verify state updates...

--- Active Jobs Listing ---
JID      PID      PGID     STATUS       COMMAND
[1]      66583    66583    Running      sleep 3 &
[2]      66584    66584    Done         sleep 1 &
--------------------------

=== Part 2: Foreground Switching (fg) & Terminal Transfer ===

Bringing Job [1] into foreground using builtin_fg(1):
[fg] Bringing Job [1] (sleep 3 &) to foreground...
[fg] Job [1] completed.

Inspecting job listings after foreground completion:
--- Active Jobs Listing ---
JID      PID      PGID     STATUS       COMMAND
[1]      66583    66583    Done         sleep 3 &
[2]      66584    66584    Done         sleep 1 &
--------------------------

varnikakomali@VARNIKAs-MacBook-Air Skill %
```