To Store Commands, Maintain History Buffer, Handle Capacity Limits, Retrieve Entries, Display History, Validate Consistency.

To Create Pipeline Structures, Store Commands, Maintain Execution Order, Connect Processes, Validate Pipeline Layout, Test Configurations.

```
Pipeline layout validated and executed successfully.
varnikakomali@VARNIKAs-MacBook-Air Skill % nano skill_11.c
varnikakomali@VARNIKAs-MacBook-Air Skill % gcc skill_11.c -o skill_11 && ./skill_11
=== Part 1: Circular Command History Buffer ===

Initial 5 entries added (Buffer full):
--- Shell History Buffer (Capacity: 5, Stored: 5) ---
  1: ls -la
  2: cd /Users
  3: pwd
  4: export DEBUG=1
  5: echo $DEBUG
-----------------------------------------------------

Adding 6th and 7th commands (Testing capacity eviction):
--- Shell History Buffer (Capacity: 5, Stored: 5) ---
  3: pwd
  4: export DEBUG=1
  5: echo $DEBUG
  6: grep root /etc/passwd
  7: cat file.txt
-----------------------------------------------------

Retrieved entry #6: "grep root /etc/passwd"

=== Part 2: Multiprocess Pipeline Execution ===

Executing pipeline layout: printf "banana\napple\ncherry\n" | grep a | sort

apple
banana

Pipeline layout validated and executed successfully.
varnikakomali@VARNIKAs-MacBook-Air Skill %
```