

Assignment Name: Internet Explorer

Client–Server Architecture:

Client–Server Architecture is a network model where:

- A **client** requests services or resources
- A **server** processes the request and sends back the response.

Examples of Clients

Web browsers (Chrome, Edge, Firefox)

Mobile apps

Desktop applications

Examples of Servers

Web servers (store websites)

Database servers (store data)

Email server

Example

When you open **www.google.com**:

- Your browser = Client
- Google's data centre = Server

Diagram Explanation (Client–Server Model)



Flow:

1. Client sends request
2. Server receives request
3. Server processes it
4. Server sends response
5. Client displays output

3. What Happens When You Open a website?

Step 1: URL Entry

`https://www.example.com`
in the browser.

Step 2: DNS Resolution

- Browser asks **DNS server** for the IP address of the website
- Example:

`www.example.com` → `93.184.216.34`

Step 3: Client Sends Request

- Browser sends an **HTTP/HTTPS request** to the server's IP
- Request includes:
 - Page name
 - Browser details
 - User info (cookies, cache)

Step 4: Server Processes Request

- Web server:
 - Finds the requested page
 - Runs backend code (if any)
 - Fetches data from database

Step 5: Server Sends Response

- Server sends back:
 - HTML
 - CSS
 - JavaScript
 - Images

Step 6: Browser Renders Page

- Browser:
 - Builds page structure
 - Applies styles
 - Runs scripts
- Website is displayed on the screen