

[My courses](#) / [19CS404](#) / [Module Home Challenge](#) / [M4-Subqueries \(HC\)](#)

Started on	Monday, 24 August 2026, 9:40 AM
State	Finished
Completed on	Monday, 24 August 2026, 9:54 AM
Time taken	13 mins 57 secs
Grade	10.00 out of 10.00 (100%)

Question 1

Correct

Mark 1.00 out of 1.00

Write a SQL query that retrieves the all the columns from the Table Grades, where the grade is equal to the minimum grade achieved in each subject.

Sample table: GRADES (attributes: student_id, student_name, subject, grade)

student_id	student_name	subject	grade
1	Alice	Math	90
2	Bob	Math	85
3	Charlie	Math	95
4	David	Science	88
5	Emma	Science	92
6	Frank	Science	85
7	John	Social	85

For example:

Result			
student_id	student_name	subject	grade
2	Bob	Math	85
6	Frank	Science	85
7	John	Social	85

Answer: (penalty regime: 0 %)

```

1 SELECT *
2 FROM Grades g
3 WHERE grade = (
4     SELECT MIN(grade)
5     FROM Grades
6     WHERE subject = g.subject
7 );

```

	Expected				Got				
✓	student_id	student_name	subject	grade	student_id	student_name	subject	grade	✓
	-----	-----	-----	-----	-----	-----	-----	-----	
	2	Bob	Math	85	2	Bob	Math	85	
	6	Frank	Science	85	6	Frank	Science	85	
	7	John	Social	85	7	John	Social	85	

	Expected				Got				
✓	student_id	student_name	subject	grade	student_id	student_name	subject	grade	✓
	-----	-----	-----	----	-----	-----	-----	----	
	-----				-----				
	2	Bob	Math	85	2	Bob	Math	85	
	6	Frank	Science	85	6	Frank	Science	85	
	7	John	Social	85	7	John	Social	85	
	15	Sam	SOCIAL	92	15	Sam	SOCIAL	92	

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **2**

Correct

Mark 1.00 out of 1.00

Write a SQL query to List departments with names longer than the average length

Departments Table (attributes: department_id, department_name)

name	type
department_id	INT
department_name	VARCHAR(100)

For example:

Result	
depar	department_name
----	-----
5	Anesthesiologis

Answer: (penalty regime: 0 %)

```

1 SELECT department_id, department_name
2 FROM Departments
3 WHERE LENGTH(department_name) > (
4     SELECT AVG(LENGTH(department_name))
5     FROM Departments
6 );

```

	Expected		Got		
✓	depar	department_name	depar	department_name	✓
	----	-----	----	-----	
	2	Orthopedics	2	Orthopedics	
✓	depar	department_name	depar	department_name	✓
	----	-----	----	-----	
	5	Anesthesiologis	5	Anesthesiologis	
✓	depar	department_name	depar	department_name	✓
	----	-----	----	-----	
	4	gynaecologist	4	gynaecologist	

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 3

Correct

Mark 1.00 out of 1.00

Write a SQL query that retrieves the names of students and their corresponding grades, where the grade is equal to the maximum grade achieved in each subject.

Sample table: GRADES (attributes: student_id, student_name, subject, grade)

student_id	student_name	subject	grade
1	Alice	Math	90
2	Bob	Math	85
3	Charlie	Math	95
4	David	Science	88
5	Emma	Science	92
6	Frank	Science	85
7	John	Social	85

For example:

Result	
student_name	grade
Charlie	95
Emma	92
John	85

Answer: (penalty regime: 0 %)

```

1 SELECT student_name, grade
2 FROM Grades g
3 WHERE grade = (
4     SELECT MAX(grade)
5     FROM Grades
6     WHERE subject = g.subject
7 );

```

	Expected		Got		
✓	student_name	grade	student_name	grade	✓
	-----		-----		
	Charlie	95	Charlie	95	
	Emma	92	Emma	92	
	John	85	John	85	
✓	student_name	grade	student_name	grade	✓
	-----		-----		
	Charlie	95	Charlie	95	
	Emma	92	Emma	92	
	John	85	John	85	
	Sam	92	Sam	92	

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 4

Correct

Mark 1.00 out of 1.00

Write a SQL query to retrieve all columns from the **CUSTOMERS** table for customers whose Address as Delhi

Sample table: CUSTOMERS

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000
2	Khilan	25	Delhi	1500
3	Kaushik	23	Kota	2000
4	Chaitali	25	Mumbai	6500
5	Hardik	27	Bhopal	8500
6	Komal	22	Hyderabad	4500
7	Muffy	24	Indore	10000

For example:

Result				
ID	NAME	AGE	ADDRESS	SALARY
2	Khilan	25	Delhi	1500

Answer: (penalty regime: 0 %)

```
1 SELECT * FROM CUSTOMERS
2 WHERE ADDRESS = 'Delhi';
```

	Expected					Got					
✓	ID	NAME	AGE	ADDRESS	SALARY	ID	NAME	AGE	ADDRESS	SALARY	✓
	2	Khilan	25	Delhi	1500	2	Khilan	25	Delhi	1500	
✓	ID	NAME	AGE	ADDRESS	SALARY	ID	NAME	AGE	ADDRESS	SALARY	✓
	2	Khilan	25	Delhi	1500	2	Khilan	25	Delhi	1500	
	17	Ram	22	Delhi	1400	17	Ram	22	Delhi	1400	

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **5**

Correct

Mark 1.00 out of 1.00

Write a SQL query to retrieve all columns from the **CUSTOMERS** table for customers whose salary is greater than \$4500.

Sample table: CUSTOMERS

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000
2	Khilan	25	Delhi	1500
3	Kaushik	23	Kota	2000
4	Chaitali	25	Mumbai	6500
5	Hardik	27	Bhopal	8500
6	Komal	22	Hyderabad	4500
7	Muffy	24	Indore	10000

For example:

Result				
ID	NAME	AGE	ADDRESS	SALARY
4	Chaitali	25	Mumbai	6500
5	Hardik	27	Bhopal	8500
7	Muffy	24	Indore	10000

Answer: (penalty regime: 0 %)

```
1 | SELECT * FROM CUSTOMERS WHERE SALARY > 4500;
```

	Expected					Got					
✓	ID	NAME	AGE	ADDRESS	SALARY	ID	NAME	AGE	ADDRESS	SALARY	✓
	---	---	---	---	---		---	---	---	---	
	4	Chaitali	25	Mumbai	6500	4	Chaitali	25	Mumbai	6500	
	5	Hardik	27	Bhopal	8500	5	Hardik	27	Bhopal	8500	
	7	Muffy	24	Indore	10000	7	Muffy	24	Indore	10000	

	Expected					Got					
✓	ID	NAME	AGE	ADDRESS	SALARY	ID	NAME	AGE	ADDRESS	SALARY	✓
	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	
	--					--					
	4	Chaitali	25	Mumbai	6500	4	Chaitali	25	Mumbai	6500	
	5	Hardik	27	Bhopal	8500	5	Hardik	27	Bhopal	8500	
	7	Muffy	24	Indore	10000	7	Muffy	24	Indore	10000	
	17	Ram	22	Chennai	40000	17	Ram	22	Chennai	40000	

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 6

Correct

Mark 1.00 out of 1.00

From the following tables, write a SQL query to determine the commission of the salespeople in Paris. Return commission.

salesman table

name	type

salesman_id	numeric(5)
name	varchar(30)
city	varchar(15)
commission	decimal(5,2)

customer table

name	type

customer_id	int
cust_name	text
city	text
grade	int
salesman_id	int

For example:

Result

commission

0.14

Answer: (penalty regime: 0 %)

```

1 SELECT commission
2 FROM salesman
3 WHERE salesman_id IN (
4     SELECT salesman_id
5     FROM customer
6     WHERE city = 'Paris'
7 );

```

	Expected	Got	
✓	commission ----- 0.14	commission ----- 0.14	✓
✓	commission ----- 0.13 0.14	commission ----- 0.13 0.14	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 7

Correct

Mark 1.00 out of 1.00

From the following tables write a SQL query to find salespeople who had more than one customer. Return salesman_id and name.

salesman table

name	type
-----	-----
salesman_id	numeric(5)
name	varchar(30)
city	varchar(15)
commission	decimal(5,2)

customer table

name	type
-----	-----
customer_id	int
cust_name	text
city	text
grade	int
salesman_id	int

For example:

Result

salesman_id	name
-----	-----
5001	James Hoog
5002	Nail Knite

Answer: (penalty regime: 0 %)

```

1 SELECT salesman_id, name
2 FROM salesman
3 WHERE salesman_id IN (
4     SELECT salesman_id
5     FROM customer
6     GROUP BY salesman_id
7     HAVING COUNT(*) > 1
8 );

```

	Expected		Got		
✓	salesman_id	name	salesman_id	name	✓
	-----	-----	-----	-----	
	5001	James Hoog	5001	James Hoog	
	5002	Nail Knite	5002	Nail Knite	
✓	salesman_id	name	salesman_id	name	✓
	-----	-----	-----	-----	
	5002	Nail Knite	5002	Nail Knite	
	5006	Mc Lyon	5006	Mc Lyon	

	Expected		Got		
✓	salesman_id	name	salesman_id	name	✓
	-----	-----	-----	-----	
	5006	Mc Lyon	5006	Mc Lyon	
	5007	Paul Adam	5007	Paul Adam	

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **8**

Correct

Mark 1.00 out of 1.00

Write a SQL query to retrieve all columns from the **CUSTOMERS** table for customers whose AGE is LESS than \$30

Sample table: CUSTOMERS

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000
2	Khilan	25	Delhi	1500
3	Kaushik	23	Kota	2000
4	Chaitali	25	Mumbai	6500
5	Hardik	27	Bhopal	8500
6	Komal	22	Hyderabad	4500
7	Muffy	24	Indore	10000

For example:

Result				
ID	NAME	AGE	ADDRESS	SALARY
2	Khilan	25	Delhi	1500
3	Kaushik	23	Kota	2000
4	Chaitali	25	Mumbai	6500
5	Hardik	27	Bhopal	8500
6	Komal	22	Hyderabad	4500
7	Muffy	24	Indore	10000

Answer: (penalty regime: 0 %)

```
1 | SELECT *
2 | FROM CUSTOMERS
3 | WHERE AGE < 30;
```

	Expected					Got					
✓	ID	NAME	AGE	ADDRESS	SALARY	ID	NAME	AGE	ADDRESS	SALARY	✓
	---	---	---	---	---	---	---	---	---	---	
	--					--					
	2	Khilan	25	Delhi	1500	2	Khilan	25	Delhi	1500	
	3	Kaushik	23	Kota	2000	3	Kaushik	23	Kota	2000	
	4	Chaitali	25	Mumbai	6500	4	Chaitali	25	Mumbai	6500	
	5	Hardik	27	Bhopal	8500	5	Hardik	27	Bhopal	8500	
	6	Komal	22	Hyderabad	4500	6	Komal	22	Hyderabad	4500	
	7	Muffy	24	Indore	10000	7	Muffy	24	Indore	10000	
✓	ID	NAME	AGE	ADDRESS	SALARY	ID	NAME	AGE	ADDRESS	SALARY	✓
	---	---	---	---	---	---	---	---	---	---	
	--					--					
	2	Khilan	25	Delhi	1500	2	Khilan	25	Delhi	1500	
	3	Kaushik	23	Kota	2000	3	Kaushik	23	Kota	2000	
	4	Chaitali	25	Mumbai	6500	4	Chaitali	25	Mumbai	6500	
	5	Hardik	27	Bhopal	8500	5	Hardik	27	Bhopal	8500	
	6	Komal	22	Hyderabad	4500	6	Komal	22	Hyderabad	4500	
	7	Muffy	24	Indore	10000	7	Muffy	24	Indore	10000	
	17	Ram	22	Chennai	1400	17	Ram	22	Chennai	1400	

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 9

Correct

Mark 1.00 out of 1.00

Write a SQL query to Retrieve the names and cities of customers who have the same city as customers with IDs 3 and 7

SAMPLE TABLE: customer

name	type
-----	-----
id	INTEGER
name	TEXT
city	TEXT
email	TEXT
phone	INTEGER

For example:

Result	
name	city
-----	-----
Neha	Bangalore
Rohit	Bangalore
Manoj	Bangalore
Vivek	Chandigarh

Answer: (penalty regime: 0 %)

```

1 SELECT name, city
2 FROM customer
3 WHERE city IN (
4     SELECT city
5     FROM customer
6     WHERE id IN (3, 7)
7 );

```

	Expected		Got		
✓	name	city	name	city	✓
	-----	-----	-----	-----	
	Neha	Bangalore	Neha	Bangalore	
	Rohit	Bangalore	Rohit	Bangalore	
	Manoj	Bangalore	Manoj	Bangalore	
	Vivek	Chandigarh	Vivek	Chandigarh	
✓	name	city	name	city	✓
	-----	-----	-----	-----	
	Ravi	Chandigarh	Ravi	Chandigarh	
	Neha	Chandigarh	Neha	Chandigarh	
	Rohit	Bangalore	Rohit	Bangalore	
	Vivek	Chandigarh	Vivek	Chandigarh	

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **10**

Correct

Mark 1.00 out of 1.00

From the following tables write a SQL query to count the number of customers with grades above the average in New York City. Return grade and count.

customer table

name	type
customer_id	int
cust_name	text
city	text
grade	int
salesman_id	int

For example:

Result	
grade	COUNT(*)
300	2

Answer: (penalty regime: 0 %)

```

1 SELECT grade, COUNT(*)
2 FROM customer
3 GROUP BY grade
4 HAVING grade > (
5     SELECT AVG(grade)
6     FROM customer
7     WHERE city = 'New York'
8 );

```

	Expected		Got		
✓	grade	COUNT(*)	grade	COUNT(*)	✓
	-----	-----	-----	-----	
	300	2	300	2	
✓	grade	COUNT(*)	grade	COUNT(*)	✓
	-----	-----	-----	-----	
	200	2	200	2	
	300	2	300	2	

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[◀ Discussion Forum for Module 3](#)

Jump to...



[Discussion Forum for Module 4 ▶](#)

QUIZ						
☒	M3 - Aggregate,Group by,Having Clause (SEB) May'25	-	✓ 100.00	0-100	100.00 %	-
QUIZ						
☒	M4-Subqueries (SEB) May'25	-	✓ 100.00	0-100	100.00 %	-