



SQL INTERVIEW PREP SERIES

300 Real SQL Interview Questions



Asked at PwC, Deloitte, EY, KPMG, Tredence,
Persistent Systems & Accenture — and more.

Medium

Advanced

Window Functions

Recursive CTEs

300 curated questions • Medium to Advanced level

Window Functions • Recursive CTEs • Joins • Aggregations • Analytics SQL

1

Find the second highest salary from the Employee table.

```
SELECT MAX(salary) AS SecondHighestSalary
FROM employees
WHERE salary < (
  SELECT MAX(salary)
  FROM employees
);
```

2

Find duplicate records in a table.

```
SELECT name, COUNT(*)
FROM employees
GROUP BY name
HAVING COUNT(*) > 1;
```

3

Retrieve employees who earn more than their manager.

```
SELECT e.name AS Employee, e.salary, m.name AS
Manager, m.salary AS ManagerSalary
FROM employees e
JOIN employees m ON e.manager_id = m.id
WHERE e.salary > m.salary;
```

4

Count employees in each department having more than 5 employees.

```
SELECT department_id, COUNT(*) AS
num_employees
FROM employees
GROUP BY department_id
HAVING COUNT(*) > 5;
```

5

Find employees who joined in the last 6 months.

```
SELECT *
FROM employees
WHERE join_date >= CURRENT_DATE -
INTERVAL '6 months';
```

6

Get departments with no employees.

```
SELECT d.department_name
FROM departments d
LEFT JOIN employees e ON d.department_id =
e.department_id
WHERE e.id IS NULL;
```

7

Write a query to find the median salary.

```
SELECT AVG(salary) AS median_salary
FROM (
SELECT salary
FROM employees
ORDER BY salary
LIMIT 2 - (SELECT COUNT(*) FROM employees)
% 2
OFFSET (SELECT (COUNT(*) - 1) / 2 FROM
employees)
) AS median_subquery;
```

8

Running total of salaries by department.

```
SELECT name, department_id, salary,
SUM(salary) OVER (PARTITION BY
department_id ORDER BY id) AS running_total
FROM employees;
```

9

Find the longest consecutive streak of daily logins for each user.

```
WITH login_dates AS (
SELECT user_id, login_date,
login_date - INTERVAL ROW_NUMBER()
OVER (PARTITION BY user_id ORDER BY
login_date) DAY AS grp
FROM user_logins
)
SELECT user_id, COUNT(*) AS streak_length,
MIN(login_date) AS start_date, MAX(login_date) AS
end_date
FROM login_dates
GROUP BY user_id, grp
ORDER BY streak_length DESC;
```

10

Recursive query to find the full reporting chain for each employee.

```
WITH RECURSIVE reporting_chain AS (  
  SELECT id, name, manager_id, 1 AS level  
  FROM employees  
  WHERE manager_id IS NULL  
  
  UNION ALL  
  
  SELECT e.id, e.name, e.manager_id, rc.level + 1  
  FROM employees e  
  JOIN reporting_chain rc ON e.manager_id = rc.id  
)  
SELECT * FROM reporting_chain ORDER BY level,  
id;
```

11

Write a query to find gaps in a sequence of numbers (missing IDs).

```
SELECT (id + 1) AS missing_id  
FROM employees e1  
WHERE NOT EXISTS (  
  SELECT 1 FROM employees e2 WHERE e2.id =  
  e1.id + 1  
)  
ORDER BY missing_id;
```

12

Calculate cumulative distribution (CDF) of salaries.

```
SELECT name, salary,  
CUME_DIST() OVER (ORDER BY salary) AS  
salary_cdf  
FROM employees;
```

13

Compare two tables and find rows with differences in any column (all columns).

```
SELECT *  
FROM table1 t1  
FULL OUTER JOIN table2 t2 ON t1.id = t2.id  
WHERE t1.col1 IS DISTINCT FROM t2.col1  
OR t1.col2 IS DISTINCT FROM t2.col2  
OR t1.col3 IS DISTINCT FROM t2.col3;
```

14

Write a query to rank employees based on salary

```
with ties handled properly.  
SELECT name, salary,  
RANK() OVER (ORDER BY salary DESC) AS  
salary_rank  
FROM employees;
```

15

Find customers who have not made any purchase.

```
SELECT c.customer_id, c.name  
FROM customers c  
LEFT JOIN sales s ON c.customer_id = s.customer_id  
WHERE s.sale_id IS NULL;
```

16

Write a query to perform a conditional aggregation (count males and females in each department).

```
SELECT department_id,  
COUNT(CASE WHEN gender = 'M' THEN 1  
END) AS male_count,  
COUNT(CASE WHEN gender = 'F' THEN 1  
END) AS female_count  
FROM employees  
GROUP BY department_id;
```

17

Write a query to calculate the difference between current row and previous row's salary (lag function).

```
SELECT name, salary,  
salary - LAG(salary) OVER (ORDER BY id) AS  
salary_diff  
FROM employees;
```

18

Identify overlapping date ranges for bookings.

```
SELECT b1.booking_id, b2.booking_id
FROM bookings b1
JOIN bookings b2 ON b1.booking_id <> b2.booking_id
WHERE b1.start_date <= b2.end_date
AND b1.end_date >= b2.start_date;
```

19

Write a query to find employees with salary greater than average salary in the entire company, ordered by salary descending.

```
SELECT name, salary
FROM employees
WHERE salary > (SELECT AVG(salary) FROM
employees)
ORDER BY salary DESC;
```

20

Aggregate JSON data (if supported) to list all employee names in a department as a JSON array.

```
SELECT department_id, JSON_AGG(name) AS
employee_names
FROM employees
GROUP BY department_id;
```

21

Find employees who have the same salary as their manager.

```
SELECT e.name AS Employee, e.salary, m.name AS
Manager
FROM employees e
JOIN employees m ON e.manager_id = m.id
WHERE e.salary = m.salary;
```

22

Write a query to get the first and last purchase date for each customer.

```
SELECT customer_id,
MIN(purchase_date) AS first_purchase,
MAX(purchase_date) AS last_purchase
FROM sales
GROUP BY customer_id;
```

23

Find departments with the highest average salary.

```
WITH avg_salaries AS (  
  SELECT department_id, AVG(salary) AS avg_salary  
  FROM employees  
  GROUP BY department_id  
)  
SELECT *  
FROM avg_salaries  
WHERE avg_salary = (SELECT MAX(avg_salary)  
  FROM avg_salaries);
```

24

Write a query to find the number of employees in each job title.

```
SELECT job_title, COUNT(*) AS num_employees  
FROM employees  
GROUP BY job_title;
```

25

Find employees who don't have a department assigned.

```
SELECT *  
FROM employees  
WHERE department_id IS NULL;
```

26

Write a query to find the difference in days between two dates in the same table.

```
SELECT id, DATEDIFF(day, start_date, end_date) AS  
  days_difference  
FROM projects;
```

Note: DATEDIFF syntax varies – replace accordingly
(e.g., DATEDIFF('day', start_date, end_date) in some
systems).

27

Calculate the moving average of salaries over the last 3 employees ordered by hire date.

```
SELECT name, hire_date, salary,  
AVG(salary) OVER (ORDER BY hire_date  
ROWS BETWEEN 2 PRECEDING AND CURRENT  
ROW) AS moving_avg_salary  
FROM employees;
```

28

Find the most recent purchase per customer using window functions.

```
SELECT *  
FROM (  
  SELECT *,  
  ROW_NUMBER() OVER (PARTITION BY  
  customer_id ORDER BY purchase_date DESC) AS rn  
  FROM sales  
) sub  
WHERE rn = 1;
```

29

Detect hierarchical depth of each employee in the org chart.

```
WITH RECURSIVE employee_depth AS (  
  SELECT id, name, manager_id, 1 AS depth  
  FROM employees  
  WHERE manager_id IS NULL  
  
  UNION ALL  
  
  SELECT e.id, e.name, e.manager_id, ed.depth + 1  
  FROM employees e  
  JOIN employee_depth ed ON e.manager_id = ed.id  
)  
SELECT * FROM employee_depth;
```

30

Write a query to perform a self-join to find pairs of employees in the same department.

```
SELECT e1.name AS Employee1, e2.name AS  
Employee2, e1.department_id  
FROM employees e1  
JOIN employees e2 ON e1.department_id =  
e2.department_id AND e1.id < e2.id;
```

31

Write a query to pivot rows into columns dynamically (if dynamic pivot is not supported, simulate it for fixed values).

```
SELECT
department_id,
SUM(CASE WHEN job_title = 'Manager' THEN 1
ELSE 0 END) AS Managers,
SUM(CASE WHEN job_title = 'Developer' THEN 1
ELSE 0 END) AS Developers,
SUM(CASE WHEN job_title = 'Tester' THEN 1
ELSE 0 END) AS Testers
FROM employees
GROUP BY department_id;
```

32

Find customers who made purchases in every category available.

```
SELECT customer_id
FROM sales s
GROUP BY customer_id
HAVING COUNT(DISTINCT category_id) =
(SELECT COUNT(DISTINCT category_id) FROM
sales);
```

33

Identify employees who haven't received a salary raise in more than a year.

```
SELECT e.name
FROM employees e
JOIN salary_history sh ON e.id = sh.employee_id
GROUP BY e.id, e.name
HAVING MAX(sh.raise_date) < CURRENT_DATE -
INTERVAL '1 year';
```

34

Write a query to rank salespeople by monthly sales, resetting the rank every month.

```
SELECT salesperson_id, sale_month, total_sales,  
RANK() OVER (PARTITION BY sale_month  
ORDER BY total_sales DESC) AS monthly_rank  
FROM (  
SELECT salesperson_id, DATE_TRUNC('month',  
sale_date) AS sale_month, SUM(amount) AS  
total_sales  
FROM sales  
GROUP BY salesperson_id, sale_month  
) AS monthly_sales;
```

35

Calculate the percentage change in sales compared to the previous month for each product.

```
SELECT product_id, sale_month, total_sales,  
(total_sales - LAG(total_sales) OVER  
(PARTITION BY product_id ORDER BY  
sale_month)) * 100.0 /  
LAG(total_sales) OVER (PARTITION BY  
product_id ORDER BY sale_month) AS pct_change  
FROM (  
SELECT product_id, DATE_TRUNC('month',  
sale_date) AS sale_month, SUM(amount) AS  
total_sales  
FROM sales  
GROUP BY product_id, sale_month  
) monthly_sales;
```

36

Find employees who earn more than the average salary across the company but less than the highest salary in their department.

```
SELECT *  
FROM employees e  
WHERE salary > (SELECT AVG(salary) FROM  
employees)  
AND salary < (  
SELECT MAX(salary)  
FROM employees  
WHERE department_id = e.department_id  
);
```

37

Retrieve the last 5 orders for each customer.

```
SELECT *
FROM (
  SELECT o.*, ROW_NUMBER() OVER
    (PARTITION BY customer_id ORDER BY order_date
     DESC) AS rn
  FROM orders o
) sub
WHERE rn <= 5;
```

38

Find employees with no salary changes in the last 2 years.

```
SELECT e.*
FROM employees e
LEFT JOIN salary_history sh ON e.id =
  sh.employee_id AND sh.change_date >=
  CURRENT_DATE - INTERVAL '2 years'
WHERE sh.employee_id IS NULL;
```

39

Find the department with the lowest average salary.

```
SELECT department_id, AVG(salary) AS avg_salary
FROM employees
GROUP BY department_id
ORDER BY avg_salary
LIMIT 1;
```

40

List employees whose names start and end with the same letter.

```
SELECT *
FROM employees
WHERE LEFT(name, 1) = RIGHT(name, 1);
```

Questions

41

Write a query to detect circular references in employee-manager hierarchy (cycles).

```
WITH RECURSIVE mgr_path (id, manager_id, path)
AS (
  SELECT id, manager_id, ARRAY[id]
  FROM employees
  WHERE manager_id IS NOT NULL

  UNION ALL

  SELECT e.id, e.manager_id, path || e.id
  FROM employees e
  JOIN mgr_path mp ON e.manager_id = mp.id
  WHERE NOT e.id = ANY(path)
)
SELECT DISTINCT id
FROM mgr_path
WHERE id = ANY(path);
```

42

Write a query to get the running total of sales per customer, ordered by sale date.

```
SELECT customer_id, sale_date, amount,
SUM(amount) OVER (PARTITION BY
customer_id ORDER BY sale_date) AS running_total
FROM sales;
```

43

Find the department-wise salary percentile (e.g., 90th percentile) using window functions.

```
SELECT department_id, salary,
PERCENTILE_CONT(0.9) WITHIN GROUP
(ORDER BY salary) OVER (PARTITION BY
department_id) AS pct_90_salary
FROM employees;
```

44

Find employees whose salary is a prime number.

```
WITH primes AS (  
  SELECT generate_series(2, (SELECT MAX(salary)  
    FROM employees)) AS num  
  EXCEPT  
  SELECT num FROM (  
    SELECT num, UNNEST(ARRAY(  
      SELECT generate_series(2, FLOOR(SQRT(num)))  
    AS divisor  
  )) AS divisor  
  WHERE num % divisor = 0  
  ) AS composite  
)  
SELECT *  
FROM employees  
WHERE salary IN (SELECT num FROM primes);
```

Note: This is a conceptual approach—some databases may not support this syntax fully.

45

Find employees who have worked for multiple departments over time.

```
SELECT employee_id  
FROM employee_department_history  
GROUP BY employee_id  
HAVING COUNT(DISTINCT department_id) > 1;
```

46

Use window function to find the difference between current row's sales and previous row's sales partitioned by product.

```
SELECT product_id, sale_date, amount,  
  amount - LAG(amount) OVER (PARTITION BY  
    product_id ORDER BY sale_date) AS sales_diff  
FROM sales;
```

47

Write a query to find all employees who are at the lowest level in the hierarchy (no subordinates).

```
SELECT *  
FROM employees e  
WHERE NOT EXISTS (  
  SELECT 1 FROM employees sub WHERE  
    sub.manager_id = e.id  
);
```

48

Find average order value per month and product category.

```
SELECT DATE_TRUNC('month', order_date) AS
order_month, category_id, AVG(order_value) AS
avg_order_value
FROM orders
GROUP BY order_month, category_id;
```

49

Write a query to create a running count of how many employees joined in each year.

```
SELECT join_year, COUNT(*) AS yearly_hires,
SUM(COUNT(*)) OVER (ORDER BY join_year)
AS running_total_hires
FROM (
SELECT EXTRACT(YEAR FROM hire_date) AS
join_year
FROM employees
) sub
GROUP BY join_year
ORDER BY join_year;
```

50

Write a query to find the second most recent order date per customer.

```
SELECT customer_id, order_date
FROM (
SELECT customer_id, order_date,
ROW_NUMBER() OVER (PARTITION BY
customer_id ORDER BY order_date DESC) AS rn
FROM orders
) sub
WHERE rn = 2;
```

51

Find employees who have never made a sale.

```
SELECT e.id, e.name
FROM employees e
LEFT JOIN sales s ON e.id = s.employee_id
WHERE s.sale_id IS NULL;
```

52

Find the average tenure of employees by department.

```
SELECT department_id, AVG(DATE_PART('year',
CURRENT_DATE - hire_date)) AS avg_tenure_years
FROM employees
GROUP BY department_id;
```

53

Get employees with salary in the top 10% in their department.

```
SELECT *
FROM (
SELECT e.*, NTILE(10) OVER (PARTITION BY
department_id ORDER BY salary DESC) AS decile
FROM employees e
) sub
WHERE decile = 1;
```

54

Find customers who purchased more than once in the same day.

```
SELECT customer_id, purchase_date, COUNT(*) AS
purchase_count
FROM sales
GROUP BY customer_id, purchase_date
HAVING COUNT(*) > 1;
```

55

List all departments and their employee counts, including departments with zero employees.

```
SELECT d.department_id, d.department_name,
COUNT(e.id) AS employee_count
FROM departments d
LEFT JOIN employees e ON d.department_id =
e.department_id
GROUP BY d.department_id, d.department_name;
```

56

Write a query to find duplicate rows based on multiple columns.

```
SELECT column1, column2, COUNT(*)
FROM table_name
GROUP BY column1, column2
HAVING COUNT(*) > 1;
```

57

Write a recursive query to calculate factorial of a number (e.g., 5).

```
WITH RECURSIVE factorial(n, fact) AS (  
  SELECT 1, 1  
  UNION ALL  
  SELECT n + 1, fact * (n + 1)  
  FROM factorial  
  WHERE n < 5  
)  
SELECT fact FROM factorial WHERE n = 5;
```

58

Write a query to calculate the cumulative percentage of total sales per product.

```
SELECT product_id, sale_amount,  
SUM(sale_amount) OVER (ORDER BY  
sale_amount DESC) * 100.0 / SUM(sale_amount)  
OVER () AS cumulative_pct  
FROM sales;
```

59

Write a query to get employees who reported directly or indirectly to a given manager (hierarchy traversal).

```
WITH RECURSIVE reporting AS (  
  SELECT id, name, manager_id  
  FROM employees  
  WHERE manager_id = 101 -- replace 101 with  
  manager's id  
  
  UNION ALL  
  
  SELECT e.id, e.name, e.manager_id  
  FROM employees e  
  INNER JOIN reporting r ON e.manager_id = r.id  
)  
SELECT * FROM reporting;
```

60

Find the average number of orders per customer and standard deviation.

```
SELECT AVG(order_count) AS avg_orders,  
STDDEV(order_count) AS stddev_orders  
FROM (  
SELECT customer_id, COUNT(*) AS order_count  
FROM orders  
GROUP BY customer_id  
) sub;
```

61

Find gaps in date sequences for each customer (missing days).

```
WITH dates AS (  
SELECT customer_id, purchase_date,  
LAG(purchase_date) OVER (PARTITION BY  
customer_id ORDER BY purchase_date) AS prev_date  
FROM sales  
)  
SELECT customer_id, prev_date + INTERVAL '1 day'  
AS missing_date  
FROM dates  
WHERE purchase_date > prev_date + INTERVAL '1  
day';
```

62

Rank employees by salary within their department, and calculate percent rank.

```
SELECT name, department_id, salary,  
RANK() OVER (PARTITION BY department_id  
ORDER BY salary DESC) AS salary_rank,  
PERCENT_RANK() OVER (PARTITION BY  
department_id ORDER BY salary DESC) AS  
salary_percent_rank  
FROM employees;
```

63

Find products that have never been sold.

```
SELECT p.product_id, p.product_name  
FROM products p  
LEFT JOIN sales s ON p.product_id = s.product_id  
WHERE s.sale_id IS NULL;
```

64

Write a query to find consecutive days where sales were above a threshold.

```
WITH flagged_sales AS (  
  SELECT sale_date, amount,  
  CASE WHEN amount > 1000 THEN 1 ELSE 0  
  END AS flag  
  FROM sales  
) ,  
groups AS (  
  SELECT sale_date, amount, flag,  
  sale_date - INTERVAL ROW_NUMBER()  
  OVER (ORDER BY sale_date) DAY AS grp  
  FROM flagged_sales  
  WHERE flag = 1  
)  
SELECT MIN(sale_date) AS start_date,  
MAX(sale_date) AS end_date, COUNT(*) AS  
consecutive_days  
FROM groups  
GROUP BY grp  
ORDER BY consecutive_days DESC;
```

65

Write a query to concatenate employee names in each department (string aggregation).

```
SELECT department_id, STRING_AGG(name, ', ' ) AS  
employee_names  
FROM employees  
GROUP BY department_id;
```

66

Find employees whose salary is above the average salary of their department but below the company-wide average.

```
SELECT *  
FROM employees e  
WHERE salary > (  
  SELECT AVG(salary)  
  FROM employees  
  WHERE department_id = e.department_id  
)  
AND salary < (SELECT AVG(salary) FROM  
employees);
```

67

List the customers who purchased all products in a specific category.

```
SELECT customer_id
FROM sales
WHERE category_id = 10 -- example category
GROUP BY customer_id
HAVING COUNT(DISTINCT product_id) = (
  SELECT COUNT(DISTINCT product_id)
  FROM products
  WHERE category_id = 10
);
```

68

Retrieve the Nth highest salary from the employees table.

```
SELECT DISTINCT salary
FROM employees
ORDER BY salary DESC
LIMIT 1 OFFSET N-1;
```

(Replace N with the desired rank, e.g., N=3 for third highest)

69

Find employees with no corresponding entries in the salary_history table.

```
SELECT e.*
FROM employees e
LEFT JOIN salary_history sh ON e.id =
sh.employee_id
WHERE sh.employee_id IS NULL;
```

70

Show the department with the highest number of employees and the count.

```
SELECT department_id, COUNT(*) AS
employee_count
FROM employees
GROUP BY department_id
ORDER BY employee_count DESC
LIMIT 1;
```

71

Write a recursive query to list all ancestors (managers) of a given employee.

```
WITH RECURSIVE ancestors AS (  
  SELECT id, name, manager_id  
  FROM employees  
  WHERE id = 123 -- given employee id  
  
  UNION ALL  
  
  SELECT e.id, e.name, e.manager_id  
  FROM employees e  
  JOIN ancestors a ON e.id = a.manager_id  
)  
SELECT * FROM ancestors WHERE id != 123;
```

72

Calculate the median salary by department using window functions.

```
SELECT DISTINCT department_id,  
  PERCENTILE_CONT(0.5) WITHIN GROUP  
  (ORDER BY salary) OVER (PARTITION BY  
  department_id) AS median_salary  
FROM employees;
```

73

Write a query to find the first purchase date and last purchase date for each customer, including customers who never purchased anything.

```
SELECT c.customer_id,  
  MIN(s.purchase_date) AS first_purchase,  
  MAX(s.purchase_date) AS last_purchase  
FROM customers c  
LEFT JOIN sales s ON c.customer_id = s.customer_id  
GROUP BY c.customer_id;
```

74

Find the percentage difference between each month's total sales and the previous month's total sales.

```
WITH monthly_sales AS (  
  SELECT DATE_TRUNC('month', sale_date) AS  
    month, SUM(amount) AS total_sales  
  FROM sales  
  GROUP BY month  
)  
SELECT month, total_sales,  
  (total_sales - LAG(total_sales) OVER (ORDER  
    BY month)) * 100.0 / LAG(total_sales) OVER  
  (ORDER BY month) AS pct_change  
FROM monthly_sales;
```

75

Write a query to find employees who have the longest tenure within their department.

```
WITH tenure AS (  
  SELECT *,  
  RANK() OVER (PARTITION BY department_id  
    ORDER BY hire_date ASC) AS tenure_rank  
  FROM employees  
)  
SELECT *  
FROM tenure  
WHERE tenure_rank = 1;
```

76

Generate a report that shows sales and sales growth percentage compared to the same month last year.

```
WITH monthly_sales AS (  
  SELECT DATE_TRUNC('month', sale_date) AS  
    month, SUM(amount) AS total_sales  
  FROM sales  
  GROUP BY month  
)  
SELECT ms1.month, ms1.total_sales,  
  ((ms1.total_sales - ms2.total_sales) * 100.0 /  
  ms2.total_sales) AS growth_pct  
FROM monthly_sales ms1  
LEFT JOIN monthly_sales ms2 ON ms1.month =  
  ms2.month + INTERVAL '1 year';
```

77

Write a query to identify overlapping shifts for employees.

```
SELECT s1.employee_id, s1.shift_id AS shift1,  
       s2.shift_id AS shift2  
FROM shifts s1  
JOIN shifts s2 ON s1.employee_id = s2.employee_id  
AND s1.shift_id <> s2.shift_id  
WHERE s1.start_time < s2.end_time AND s1.end_time  
      > s2.start_time;
```

78

Calculate the total revenue for each customer, and rank them from highest to lowest spender.

```
SELECT customer_id, SUM(amount) AS  
       total_revenue,  
       RANK() OVER (ORDER BY SUM(amount)  
                   DESC) AS revenue_rank  
FROM sales  
GROUP BY customer_id;
```

79

Write a query to find the employee(s) who have never received a promotion.

```
SELECT e.*  
FROM employees e  
LEFT JOIN promotions p ON e.id = p.employee_id  
WHERE p.employee_id IS NULL;
```

80

Write a query to find the top 3 products with the highest total sales amount each month.

```
WITH monthly_product_sales AS (  
  SELECT product_id, DATE_TRUNC('month',  
    sale_date) AS month, SUM(amount) AS total_sales  
  FROM sales  
  GROUP BY product_id, month  
)  
ranked_sales AS (  
  SELECT *, RANK() OVER (PARTITION BY month  
    ORDER BY total_sales DESC) AS sales_rank  
  FROM monthly_product_sales  
)  
SELECT product_id, month, total_sales  
FROM ranked_sales  
WHERE sales_rank <= 3  
ORDER BY month, sales_rank;
```

81

Find the customers who placed orders only in the last 30 days.

```
SELECT DISTINCT customer_id
FROM orders
WHERE order_date >= CURRENT_DATE -
INTERVAL '30 days'
AND customer_id NOT IN (
SELECT DISTINCT customer_id
FROM orders
WHERE order_date < CURRENT_DATE -
INTERVAL '30 days'
);
```

82

Find products that have never been ordered.

```
SELECT p.product_id, p.product_name
FROM products p
LEFT JOIN orders o ON p.product_id = o.product_id
WHERE o.order_id IS NULL;
```

83

Find employees whose salary is above their department's average but below the overall average salary.

```
SELECT *
FROM employees e
WHERE salary > (SELECT AVG(salary) FROM
employees WHERE department_id = e.department_id)
AND salary < (SELECT AVG(salary) FROM
employees);
```

84

Calculate the total sales amount and number of orders per customer in the last year.

```
SELECT customer_id, COUNT(*) AS total_orders,
SUM(amount) AS total_sales
FROM sales
WHERE sale_date >= CURRENT_DATE -
INTERVAL '1 year'
GROUP BY customer_id;
```

85

List the top 5 highest-paid employees per department.

```
SELECT *
FROM (
  SELECT e.*, ROW_NUMBER() OVER
    (PARTITION BY department_id ORDER BY salary
     DESC) AS rn
  FROM employees e
) sub
WHERE rn <= 5;
```

86

Write a query to identify “gaps and islands” in attendance records (consecutive dates present).

```
WITH attendance_groups AS (
  SELECT employee_id, attendance_date,
    attendance_date - INTERVAL ROW_NUMBER()
      OVER (PARTITION BY employee_id ORDER BY
        attendance_date) DAY AS grp
  FROM attendance
)
SELECT employee_id, MIN(attendance_date) AS
  start_date, MAX(attendance_date) AS end_date,
  COUNT(*) AS consecutive_days
FROM attendance_groups
GROUP BY employee_id, grp
ORDER BY employee_id, start_date;
```

87

Write a recursive query to list all descendants of a manager in an organizational hierarchy.

```
WITH RECURSIVE descendants AS (
  SELECT id, name, manager_id
  FROM employees
  WHERE manager_id = 100 -- starting manager id

  UNION ALL

  SELECT e.id, e.name, e.manager_id
  FROM employees e
  INNER JOIN descendants d ON e.manager_id = d.id
)
SELECT * FROM descendants;
```

88

Calculate a 3-month moving average of monthly sales per product.

```
WITH monthly_sales AS (  
  SELECT product_id, DATE_TRUNC('month',  
    sale_date) AS month, SUM(amount) AS total_sales  
  FROM sales  
  GROUP BY product_id, month  
)  
SELECT product_id, month, total_sales,  
  AVG(total_sales) OVER (PARTITION BY  
    product_id ORDER BY month ROWS BETWEEN 2  
    PRECEDING AND CURRENT ROW) AS  
  moving_avg  
FROM monthly_sales;
```

89

Write a query to find employees who have the same hire date as their managers.

```
SELECT e.name AS employee_name, m.name AS  
  manager_name, e.hire_date  
FROM employees e  
JOIN employees m ON e.manager_id = m.id  
WHERE e.hire_date = m.hire_date;
```

90

Write a query to find products with increasing sales over the last 3 months.

```
WITH monthly_sales AS (  
  SELECT product_id, DATE_TRUNC('month',  
    sale_date) AS month, SUM(amount) AS total_sales  
  FROM sales  
  GROUP BY product_id, month  
,  
  ranked_sales AS (  
    SELECT product_id, month, total_sales,  
      ROW_NUMBER() OVER (PARTITION BY  
        product_id ORDER BY month DESC) AS rn  
    FROM monthly_sales  
  )  
SELECT ms1.product_id  
FROM ranked_sales ms1  
JOIN ranked_sales ms2 ON ms1.product_id =  
  ms2.product_id AND ms1.rn = 1 AND ms2.rn = 2  
JOIN ranked_sales ms3 ON ms1.product_id =  
  ms3.product_id AND ms3.rn = 3  
WHERE ms3.total_sales < ms2.total_sales AND  
  ms2.total_sales < ms1.total_sales;
```

91

Write a query to get the nth highest salary per department.

```
SELECT department_id, salary
FROM (
  SELECT department_id, salary, ROW_NUMBER()
  OVER (PARTITION BY department_id ORDER BY
  salary DESC) AS rn
FROM employees
) sub
WHERE rn = N;
```

(Replace N with the desired rank.)

92

Find employees who have managed more than 3 projects.

```
SELECT manager_id, COUNT(DISTINCT project_id)
AS project_count
FROM projects
GROUP BY manager_id
HAVING COUNT(DISTINCT project_id) > 3;
```

--68. Write a query to calculate the difference in days between each employee's hire date and their manager's hire date.

```
SELECT e.name AS employee, m.name AS manager,
DATEDIFF(day, m.hire_date, e.hire_date) AS
days_difference
FROM employees e
JOIN employees m ON e.manager_id = m.id;
```

(Syntax of DATEDIFF varies by SQL dialect)

93

Write a query to find the department with the highest average years of experience.

```
SELECT department_id, AVG(EXTRACT(year FROM
CURRENT_DATE - hire_date)) AS
avg_experience_years
FROM employees
GROUP BY department_id
ORDER BY avg_experience_years DESC
LIMIT 1;
```

94

Identify employees who had overlapping project assignments.

```
SELECT p1.employee_id, p1.project_id AS project1,  
       p2.project_id AS project2  
FROM   project_assignments p1  
JOIN   project_assignments p2 ON p1.employee_id =  
       p2.employee_id AND p1.project_id <> p2.project_id  
WHERE  p1.start_date < p2.end_date AND p1.end_date  
       > p2.start_date;
```

95

Find customers who made purchases in every month of the current year.

```
WITH months AS (  
  SELECT generate_series(1, 12) AS month  
)  
,  
customer_months AS (  
  SELECT customer_id, EXTRACT(MONTH FROM  
    purchase_date) AS month  
  FROM sales  
  WHERE EXTRACT(YEAR FROM purchase_date) =  
    EXTRACT(YEAR FROM CURRENT_DATE)  
  GROUP BY customer_id, EXTRACT(MONTH  
    FROM purchase_date)  
)  
SELECT customer_id  
FROM customer_months  
GROUP BY customer_id  
HAVING COUNT(DISTINCT month) = 12;
```

96

List employees who earn more than all their subordinates.

```
SELECT e.id, e.name, e.salary  
FROM employees e  
WHERE e.salary > ALL (  
  SELECT salary  
  FROM employees sub  
  WHERE sub.manager_id = e.id  
);
```

97

Get the product with the highest sales for each category.

```
WITH category_sales AS (  
  SELECT category_id, product_id, SUM(amount) AS  
    total_sales,  
    RANK() OVER (PARTITION BY category_id  
      ORDER BY SUM(amount) DESC) AS sales_rank  
  FROM sales  
  GROUP BY category_id, product_id  
)  
SELECT category_id, product_id, total_sales  
FROM category_sales  
WHERE sales_rank = 1;
```

98

Find customers who haven't ordered in the last 6 months.

```
SELECT customer_id  
FROM customers c  
LEFT JOIN orders o ON c.customer_id =  
  o.customer_id  
GROUP BY c.customer_id  
HAVING MAX(o.order_date) < CURRENT_DATE -  
  INTERVAL '6 months' OR MAX(o.order_date) IS  
  NULL;
```

99

Find the maximum salary gap between any two employees within the same department.

```
SELECT department_id, MAX(salary) - MIN(salary)  
AS salary_gap  
FROM employees  
GROUP BY department_id;
```

100

Write a recursive query to compute the total budget under each manager (including subordinates).

```
WITH RECURSIVE manager_budget AS (  
  SELECT id, manager_id, budget  
  FROM departments  
  
  UNION ALL  
  
  SELECT d.id, d.manager_id, mb.budget  
  FROM departments d  
  JOIN manager_budget mb ON d.manager_id = mb.id  
)  
SELECT manager_id, SUM(budget) AS total_budget  
FROM manager_budget  
GROUP BY manager_id;
```

101

Write a query to detect gaps in a sequence of invoice numbers.

```
WITH numbered_invoices AS (  
  SELECT invoice_number, ROW_NUMBER() OVER  
  (ORDER BY invoice_number) AS rn  
  FROM invoices  
)  
SELECT invoice_number + 1 AS missing_invoice  
FROM numbered_invoices ni  
WHERE (invoice_number + 1) <> (  
  SELECT invoice_number FROM numbered_invoices  
  WHERE rn = ni.rn + 1  
);
```

102

Calculate the rank of employees by salary within their department but restart rank numbering every 10 employees.

```
WITH ranked_employees AS (  
  SELECT e.*,  
  ROW_NUMBER() OVER (PARTITION BY  
  department_id ORDER BY salary DESC) AS rn  
  FROM employees e  
)  
SELECT *, ((rn - 1) / 10) + 1 AS rank_group  
FROM ranked_employees;
```

103

Find the moving median of daily sales over the last 7 days for each product.

```
WITH daily_sales AS (  
  SELECT product_id, sale_date, SUM(amount) AS  
    total_sales  
  FROM sales  
  GROUP BY product_id, sale_date  
)  
SELECT product_id, sale_date,  
  PERCENTILE_CONT(0.5) WITHIN GROUP  
  (ORDER BY total_sales)  
  OVER (PARTITION BY product_id ORDER BY  
    sale_date ROWS BETWEEN 6 PRECEDING AND  
    CURRENT ROW) AS moving_median  
FROM daily_sales;
```

104

Find customers who purchased both product A and product B.

```
SELECT customer_id  
FROM sales  
WHERE product_id IN ('A', 'B')  
GROUP BY customer_id  
HAVING COUNT(DISTINCT product_id) = 2;
```

105

Write a query to generate a calendar table with all dates for the current year.

```
SELECT generate_series(  
  DATE_TRUNC('year', CURRENT_DATE),  
  DATE_TRUNC('year', CURRENT_DATE) +  
  INTERVAL '1 year' - INTERVAL '1 day',  
  INTERVAL '1 day'  
) AS calendar_date;
```

106

Find employees who have worked in more than 3 different departments.

```
SELECT employee_id  
FROM employee_department_history  
GROUP BY employee_id  
HAVING COUNT(DISTINCT department_id) > 3;
```

107

Calculate the percentage contribution of each product's sales to the total sales per month.

```
WITH monthly_sales AS (  
  SELECT product_id, DATE_TRUNC('month',  
    sale_date) AS month, SUM(amount) AS product_sales  
  FROM sales  
  GROUP BY product_id, month  
,  
  total_monthly_sales AS (  
    SELECT month, SUM(product_sales) AS total_sales  
    FROM monthly_sales  
    GROUP BY month  
  )  
  SELECT ms.product_id, ms.month, ms.product_sales,  
    (ms.product_sales * 100.0) / tms.total_sales AS  
    pct_contribution  
  FROM monthly_sales ms  
  JOIN total_monthly_sales tms ON ms.month =  
    tms.month;
```

108

Write a query to pivot monthly sales data for each product into columns.

```
SELECT product_id,  
  SUM(CASE WHEN EXTRACT(MONTH FROM  
    sale_date) = 1 THEN amount ELSE 0 END) AS Jan,  
  SUM(CASE WHEN EXTRACT(MONTH FROM  
    sale_date) = 2 THEN amount ELSE 0 END) AS Feb,  
  -- Repeat for other months  
  SUM(CASE WHEN EXTRACT(MONTH FROM  
    sale_date) = 12 THEN amount ELSE 0 END) AS Dec  
FROM sales  
GROUP BY product_id;
```

109

Find the 3 most recent orders per customer including order details.

```
SELECT *  
FROM (  
  SELECT o.*, ROW_NUMBER() OVER  
    (PARTITION BY customer_id ORDER BY order_date  
    DESC) AS rn  
  FROM orders o  
  ) sub  
WHERE rn <= 3;
```

110

Find employees who have never taken any leave.

```
SELECT e.*
FROM employees e
LEFT JOIN leaves l ON e.id = l.employee_id
WHERE l.leave_id IS NULL;
```

111

List customers who placed orders in January but not in February.

```
WITH jan_orders AS (
  SELECT DISTINCT customer_id
  FROM orders
  WHERE EXTRACT(MONTH FROM order_date) = 1
),
feb_orders AS (
  SELECT DISTINCT customer_id
  FROM orders
  WHERE EXTRACT(MONTH FROM order_date) = 2
)
SELECT customer_id
FROM jan_orders
WHERE customer_id NOT IN (SELECT customer_id
FROM feb_orders);
```

112

Find products that have seen a price increase in the last 6 months.

```
WITH price_changes AS (
  SELECT product_id, price, effective_date,
  LAG(price) OVER (PARTITION BY product_id
  ORDER BY effective_date) AS prev_price
  FROM product_prices
  WHERE effective_date >= CURRENT_DATE -
  INTERVAL '6 months'
)
SELECT DISTINCT product_id
FROM price_changes
WHERE price > prev_price;
```

113

Find the department(s) with the second highest average salary.

```
WITH avg_salaries AS (  
  SELECT department_id, AVG(salary) AS avg_salary  
  FROM employees  
  GROUP BY department_id  
) ,  
ranked_salaries AS (  
  SELECT department_id, avg_salary,  
  DENSE_RANK() OVER (ORDER BY avg_salary  
  DESC) AS rnk  
  FROM avg_salaries  
)  
SELECT department_id, avg_salary  
FROM ranked_salaries  
WHERE rnk = 2;
```

114

Find employees who joined in the same month and year.

```
SELECT e1.id AS emp1_id, e2.id AS emp2_id,  
e1.hire_date  
FROM employees e1  
JOIN employees e2 ON e1.id <> e2.id  
AND EXTRACT(MONTH FROM e1.hire_date) =  
EXTRACT(MONTH FROM e2.hire_date)  
AND EXTRACT(YEAR FROM e1.hire_date) =  
EXTRACT(YEAR FROM e2.hire_date);
```

Advanced-Level SQL Questions

115

Write a recursive query to find all employees and their level of reporting (distance from CEO).

```
WITH RECURSIVE hierarchy AS (  
  SELECT id, name, manager_id, 1 AS level  
  FROM employees  
  WHERE manager_id IS NULL -- CEO level  
  
  UNION ALL  
  
  SELECT e.id, e.name, e.manager_id, h.level + 1  
  FROM employees e  
  JOIN hierarchy h ON e.manager_id = h.id  
)  
SELECT * FROM hierarchy ORDER BY level,  
manager_id;
```

116

Find the second highest salary per department without using window functions.

```
SELECT department_id, MAX(salary) AS  
second_highest_salary  
FROM employees e1  
WHERE salary < (  
  SELECT MAX(salary)  
  FROM employees e2  
  WHERE e2.department_id = e1.department_id  
)  
GROUP BY department_id;
```

117

Calculate the percentage change in sales for each product comparing current month to previous month.

```
WITH monthly_sales AS (  
  SELECT product_id, DATE_TRUNC('month',  
    sale_date) AS month, SUM(amount) AS total_sales  
  FROM sales  
  GROUP BY product_id, month  
)  
SELECT product_id, month, total_sales,  
  (total_sales - LAG(total_sales) OVER  
    (PARTITION BY product_id ORDER BY month)) *  
  100.0  
  / LAG(total_sales) OVER (PARTITION BY  
    product_id ORDER BY month) AS pct_change  
FROM monthly_sales;
```

118

Write a query to identify duplicate rows (all columns) in a table.

```
SELECT *, COUNT(*) OVER (PARTITION BY col1,  
  col2, col3, ...) AS cnt  
FROM table_name  
WHERE cnt > 1;
```

(Replace col1, col2, col3, ... with actual column names)

119

Write a query to unpivot quarterly sales data into rows.

```
SELECT product_id, 'Q1' AS quarter, Q1_sales AS  
  sales FROM sales_data  
UNION ALL  
SELECT product_id, 'Q2', Q2_sales FROM sales_data  
UNION ALL  
SELECT product_id, 'Q3', Q3_sales FROM sales_data  
UNION ALL  
SELECT product_id, 'Q4', Q4_sales FROM sales_data;
```

120

Find employees whose salary is above the average salary of their department but below the company-wide average.

```
SELECT *
FROM employees e
WHERE salary > (SELECT AVG(salary) FROM
employees WHERE department_id = e.department_id)
AND salary < (SELECT AVG(salary) FROM
employees);
```

121

Write a query to find customers with the highest purchase amount per year.

```
WITH yearly_sales AS (
SELECT customer_id, EXTRACT(YEAR FROM
sale_date) AS year, SUM(amount) AS total_amount
FROM sales
GROUP BY customer_id, year
),
ranked_sales AS (
SELECT *, RANK() OVER (PARTITION BY year
ORDER BY total_amount DESC) AS rnk
FROM yearly_sales
)
SELECT customer_id, year, total_amount
FROM ranked_sales
WHERE rnk = 1;
```

122

Write a query to list all employees who have a salary equal to the average salary of their department.

```
SELECT e.*
FROM employees e
JOIN (
SELECT department_id, AVG(salary) AS avg_salary
FROM employees
GROUP BY department_id
) d ON e.department_id = d.department_id AND
e.salary = d.avg_salary;
```

123

Find the first order date for each customer.

```
SELECT customer_id, MIN(order_date) AS
first_order_date
FROM orders
GROUP BY customer_id;
```

124

Find employees who have been promoted more than twice.

```
SELECT employee_id, COUNT(*) AS  
promotion_count  
FROM promotions  
GROUP BY employee_id  
HAVING COUNT(*) > 2;
```

125

Find employees who have not been assigned to any project.

```
SELECT e.*  
FROM employees e  
LEFT JOIN project_assignments pa ON e.id =  
pa.employee_id  
WHERE pa.project_id IS NULL;
```

126

Find the total sales per customer including those

```
with zero sales.  
SELECT c.customer_id, COALESCE(SUM(s.amount),  
0) AS total_sales  
FROM customers c  
LEFT JOIN sales s ON c.customer_id = s.customer_id  
GROUP BY c.customer_id;
```

127

Find the highest salary by department and the employee(s) who earn it.

```
WITH dept_max AS (  
SELECT department_id, MAX(salary) AS max_salary  
FROM employees  
GROUP BY department_id  
)  
SELECT e.*  
FROM employees e  
JOIN dept_max d ON e.department_id =  
d.department_id AND e.salary = d.max_salary;
```

128

Find customers with no orders in the last year.

```
SELECT customer_id
FROM customers c
LEFT JOIN orders o ON c.customer_id =
o.customer_id AND o.order_date >=
CURRENT_DATE - INTERVAL '1 year'
WHERE o.order_id IS NULL;
```

129

Find employees whose salary is within 10% of the highest salary in their department.

```
WITH dept_max AS (
SELECT department_id, MAX(salary) AS max_salary
FROM employees
GROUP BY department_id
)
SELECT e.*
FROM employees e
JOIN dept_max d ON e.department_id =
d.department_id
WHERE e.salary >= 0.9 * d.max_salary;
```

130

Find the running total of sales by date.

```
SELECT sale_date, SUM(amount) OVER (ORDER BY
sale_date ROWS BETWEEN UNBOUNDED
PRECEDING AND CURRENT ROW) AS
running_total
FROM sales
ORDER BY sale_date;
```

131

Find employees who earn more than the average salary of the entire company.

```
SELECT *
FROM employees
WHERE salary > (SELECT AVG(salary) FROM
employees);
```

132

Get the last 3 orders placed by each customer.

```
SELECT *
FROM (
  SELECT o.*, ROW_NUMBER() OVER
    (PARTITION BY customer_id ORDER BY order_date
     DESC) AS rn
  FROM orders o
) sub
WHERE rn <= 3;
```

133

Find the difference in days between the earliest and latest orders per customer.

```
SELECT customer_id, MAX(order_date) -
  MIN(order_date) AS days_between
FROM orders
GROUP BY customer_id;
```

134

Find employees who have worked on all projects.

```
SELECT employee_id
FROM project_assignments
GROUP BY employee_id
HAVING COUNT(DISTINCT project_id) = (SELECT
  COUNT(*) FROM projects);
```

135

Find customers who placed orders only in the last 6 months.

```
SELECT customer_id
FROM orders
GROUP BY customer_id
HAVING MIN(order_date) >= CURRENT_DATE -
  INTERVAL '6 months';
```

136

Get the total number of orders per day, including days with zero orders.

```
WITH dates AS (  
  SELECT generate_series(MIN(order_date),  
    MAX(order_date), INTERVAL '1 day') AS day  
  FROM orders  
)  
SELECT d.day, COUNT(o.order_id) AS order_count  
FROM dates d  
LEFT JOIN orders o ON d.day = o.order_date  
GROUP BY d.day  
ORDER BY d.day;
```

137

Find the department with the most employees.

```
SELECT department_id, COUNT(*) AS  
employee_count  
FROM employees  
GROUP BY department_id  
ORDER BY employee_count DESC  
LIMIT 1;
```

138

Write a query to find gaps in employee IDs.

```
WITH numbered AS (  
  SELECT id, ROW_NUMBER() OVER (ORDER BY  
    id) AS rn  
  FROM employees  
)  
SELECT rn + 1 AS missing_id  
FROM numbered  
WHERE id <> rn;
```

139

Find employees who were hired before their managers.

```
SELECT e.name AS employee, m.name AS manager,  
e.hire_date, m.hire_date AS manager_hire_date  
FROM employees e  
JOIN employees m ON e.manager_id = m.id  
WHERE e.hire_date < m.hire_date;
```

140

List departments with average salary greater than the overall average.

```
SELECT department_id, AVG(salary) AS avg_salary
FROM employees
GROUP BY department_id
HAVING AVG(salary) > (SELECT AVG(salary)
FROM employees);
```

141

Find employees with the highest number of dependents.

```
SELECT employee_id, COUNT(*) AS
dependent_count
FROM dependents
GROUP BY employee_id
ORDER BY dependent_count DESC
LIMIT 1;
```

142

Find customers with the longest gap between two consecutive orders.

```
WITH ordered_orders AS (
SELECT customer_id, order_date,
LAG(order_date) OVER (PARTITION BY
customer_id ORDER BY order_date) AS
prev_order_date
FROM orders
),
gaps AS (
SELECT customer_id, order_date - prev_order_date
AS gap_days
FROM ordered_orders
WHERE prev_order_date IS NOT NULL
)
SELECT customer_id, MAX(gap_days) AS
longest_gap
FROM gaps
GROUP BY customer_id
ORDER BY longest_gap DESC
LIMIT 1;
```

143

Find customers who ordered all products in a category.

```
SELECT customer_id
FROM sales
WHERE product_id IN (SELECT product_id FROM
products WHERE category_id = 1)
GROUP BY customer_id
HAVING COUNT(DISTINCT product_id) = (SELECT
COUNT(*) FROM products WHERE category_id = 1);
```

144

Get the most recent order date per customer.

```
SELECT customer_id, MAX(order_date) AS
last_order_date
FROM orders
GROUP BY customer_id;
```

145

List all employees and their manager names.

```
SELECT e.name AS employee, m.name AS manager
FROM employees e
LEFT JOIN employees m ON e.manager_id = m.id;
```

146

Find employees with the same salary as their manager.

```
SELECT e.name AS employee, m.name AS manager,
e.salary
FROM employees e
JOIN employees m ON e.manager_id = m.id
WHERE e.salary = m.salary;
```

147

List products with sales above the average sales amount.

```
WITH avg_sales AS (
SELECT AVG(amount) AS avg_amount
FROM sales
)
SELECT product_id, SUM(amount) AS total_sales
FROM sales
GROUP BY product_id
HAVING SUM(amount) > (SELECT avg_amount
FROM avg_sales);
```

148

Get the number of employees hired each year.

```
SELECT EXTRACT(YEAR FROM hire_date) AS  
hire_year, COUNT(*) AS count  
FROM employees  
GROUP BY hire_year  
ORDER BY hire_year;
```

149

Find the number of employees with the same job title per department.

```
SELECT department_id, job_title, COUNT(*) AS  
employee_count  
FROM employees  
GROUP BY department_id, job_title;
```

150

Find employees with no manager assigned.

```
SELECT *  
FROM employees  
WHERE manager_id IS NULL;
```

151

Calculate average salary by department and job title.

```
SELECT department_id, job_title, AVG(salary) AS  
avg_salary  
FROM employees  
GROUP BY department_id, job_title;
```

152

Find the median salary of employees.

```
SELECT PERCENTILE_CONT(0.5) WITHIN  
GROUP (ORDER BY salary) AS median_salary  
FROM employees;
```

153

Find employees who have been promoted more than once.

```
SELECT employee_id, COUNT(*) AS  
promotion_count  
FROM promotions  
GROUP BY employee_id  
HAVING COUNT(*) > 1;
```

154

Calculate total sales by product category.

```
SELECT p.category_id, SUM(s.amount) AS total_sales  
FROM sales s  
JOIN products p ON s.product_id = p.product_id  
GROUP BY p.category_id;
```

155

Find the top 3 products by sales amount.

```
SELECT product_id, SUM(amount) AS total_sales  
FROM sales  
GROUP BY product_id  
ORDER BY total_sales DESC  
LIMIT 3;
```

156

Get employees who joined after their department was created.

```
SELECT e.*  
FROM employees e  
JOIN departments d ON e.department_id =  
d.department_id  
WHERE e.hire_date > d.creation_date;
```

157

Find customers with no sales records.

```
SELECT c.*  
FROM customers c  
LEFT JOIN sales s ON c.customer_id = s.customer_id  
WHERE s.sale_id IS NULL;
```

158

Find the second highest salary in the company.

```
SELECT MAX(salary) AS second_highest_salary
FROM employees
WHERE salary < (SELECT MAX(salary) FROM
employees);
```

159

Find products with sales only in the current month.

```
SELECT product_id
FROM sales
GROUP BY product_id
HAVING MAX(sale_date) >=
DATE_TRUNC('month', CURRENT_DATE)
AND MIN(sale_date) >= DATE_TRUNC('month',
CURRENT_DATE);
```

160

Find employees with consecutive workdays.

```
WITH attendance AS (
SELECT employee_id, work_date,
work_date - INTERVAL '1 day' *
ROW_NUMBER() OVER (PARTITION BY
employee_id ORDER BY work_date) AS grp
FROM work_log
)
SELECT employee_id, COUNT(*) AS
consecutive_days
FROM attendance
GROUP BY employee_id, grp
HAVING COUNT(*) > 1;
```

161

Find the average number of orders per customer.

```
SELECT AVG(order_count) AS
avg_orders_per_customer
FROM (
SELECT customer_id, COUNT(*) AS order_count
FROM orders
GROUP BY customer_id
) sub;
```

162

Find employees who have worked on more than 5 projects.

```
SELECT employee_id, COUNT(DISTINCT project_id)
AS project_count
FROM project_assignments
GROUP BY employee_id
HAVING COUNT(DISTINCT project_id) > 5;
```

163

Find the total number of products sold each day.

```
SELECT sale_date, SUM(quantity) AS
total_quantity_sold
FROM sales
GROUP BY sale_date
ORDER BY sale_date;
```

164

Find customers with orders totaling more than \$10,000.

```
SELECT customer_id, SUM(amount) AS total_amount
FROM sales
GROUP BY customer_id
HAVING SUM(amount) > 10000;
```

Medium to Advanced SQL Questions (131–200)

165

Find employees who have never received a bonus.

```
SELECT e.*
FROM employees e
LEFT JOIN bonuses b ON e.id = b.employee_id
WHERE b.bonus_id IS NULL;
```

166

Find the department with the lowest average salary.

```
SELECT department_id, AVG(salary) AS avg_salary
FROM employees
GROUP BY department_id
ORDER BY avg_salary
LIMIT 1;
```

167

Get cumulative count of orders per customer over time.

```
SELECT customer_id, order_date,
COUNT(*) OVER (PARTITION BY customer_id
ORDER BY order_date) AS cumulative_orders
FROM orders;
```

168

Find customers who ordered products only from one category.

```
SELECT customer_id
FROM sales s
JOIN products p ON s.product_id = p.product_id
GROUP BY customer_id
HAVING COUNT(DISTINCT p.category_id) = 1;
```

169

Write a query to display employee names alongside their manager names, including those without managers.

```
SELECT e.name AS employee_name, m.name AS
manager_name
FROM employees e
LEFT JOIN employees m ON e.manager_id = m.id;
```

170

Find products with sales increasing every month for the last 3 months.

```
WITH monthly_sales AS (
SELECT product_id, DATE_TRUNC('month',
sale_date) AS month, SUM(amount) AS total_sales
FROM sales
WHERE sale_date >= CURRENT_DATE -
INTERVAL '3 months'
GROUP BY product_id, month
)
SELECT product_id
FROM monthly_sales
GROUP BY product_id
HAVING COUNT(*) = 3
AND MIN(total_sales) < MAX(total_sales)
AND total_sales[1] < total_sales[2] AND
total_sales[2] < total_sales[3]; -- depends on DB
support
```

Note: Exact syntax varies per RDBMS; may need window functions.

171

Write a recursive query to get all descendants of a manager.

```
WITH RECURSIVE subordinates AS (
SELECT id, name, manager_id
FROM employees
WHERE id = :manager_id

UNION ALL

SELECT e.id, e.name, e.manager_id
FROM employees e
JOIN subordinates s ON e.manager_id = s.id
)
SELECT * FROM subordinates WHERE id !=
:manager_id;
```

172

Find the department with the highest variance in salaries.

```
SELECT department_id, VAR_SAMP(salary) AS  
salary_variance  
FROM employees  
GROUP BY department_id  
ORDER BY salary_variance DESC  
LIMIT 1;
```

173

Calculate the difference between each order amount and the previous order amount per customer.

```
SELECT customer_id, order_date, amount,  
amount - LAG(amount) OVER (PARTITION BY  
customer_id ORDER BY order_date) AS diff  
FROM orders;
```

174

Find customers who purchased both Product A and Product B.

```
SELECT customer_id  
FROM sales  
WHERE product_id IN ('A', 'B')  
GROUP BY customer_id  
HAVING COUNT(DISTINCT product_id) = 2;
```

175

Find the top N customers by total sales amount.

```
SELECT customer_id, SUM(amount) AS total_sales  
FROM sales  
GROUP BY customer_id  
ORDER BY total_sales DESC  
LIMIT N;
```

176

Find the month with the highest sales in the current year.

```
SELECT DATE_TRUNC('month', sale_date) AS  
month, SUM(amount) AS total_sales  
FROM sales  
WHERE EXTRACT(YEAR FROM sale_date) =  
EXTRACT(YEAR FROM CURRENT_DATE)  
GROUP BY month  
ORDER BY total_sales DESC  
LIMIT 1;
```

177

Write a query to display all employees who have worked on a project longer than 6 months.

```
SELECT employee_id  
FROM project_assignments  
WHERE end_date - start_date > INTERVAL '6  
months';
```

178

Find the nth highest salary in a company (e.g., 5th highest).

```
SELECT DISTINCT salary  
FROM employees  
ORDER BY salary DESC  
OFFSET n - 1 ROWS FETCH NEXT 1 ROW ONLY;
```

179

Get the average salary of employees hired each year.

```
SELECT EXTRACT(YEAR FROM hire_date) AS  
year, AVG(salary) AS avg_salary  
FROM employees  
GROUP BY year  
ORDER BY year;
```

180

Find employees whose salaries are between the 25th and 75th percentile.

```
WITH percentiles AS (  
  SELECT  
    PERCENTILE_CONT(0.25) WITHIN GROUP  
      (ORDER BY salary) AS p25,  
    PERCENTILE_CONT(0.75) WITHIN GROUP  
      (ORDER BY salary) AS p75  
  FROM employees  
)  
SELECT e.*  
FROM employees e, percentiles p  
WHERE e.salary BETWEEN p.p25 AND p.p75;
```

181

Find employees with salaries higher than their department average.

```
SELECT e.*  
FROM employees e  
JOIN (  
  SELECT department_id, AVG(salary) AS avg_salary  
  FROM employees  
  GROUP BY department_id  
) d ON e.department_id = d.department_id  
WHERE e.salary > d.avg_salary;
```

--148. Find the difference between each row's value and the previous row's value in sales.

```
SELECT sale_date, amount,  
amount - LAG(amount) OVER (ORDER BY  
sale_date) AS diff  
FROM sales;
```

182

List employees who have been in the company for more than 10 years.

```
SELECT *  
FROM employees  
WHERE CURRENT_DATE - hire_date > INTERVAL  
'10 years';
```

183

Find the department with the most promotions.

```
SELECT e.department_id, COUNT(*) AS
promotion_count
FROM promotions p
JOIN employees e ON p.employee_id = e.id
GROUP BY e.department_id
ORDER BY promotion_count DESC
LIMIT 1;
```

184

Find customers who ordered products from at least 3 different categories.

```
SELECT customer_id
FROM sales s
JOIN products p ON s.product_id = p.product_id
GROUP BY customer_id
HAVING COUNT(DISTINCT p.category_id) >= 3;
```

185

Find the average gap (in days) between orders per customer.

```
WITH ordered_orders AS (
SELECT customer_id, order_date,
LAG(order_date) OVER (PARTITION BY
customer_id ORDER BY order_date) AS
prev_order_date
FROM orders
),
gaps AS (
SELECT customer_id, order_date - prev_order_date
AS gap
FROM ordered_orders
WHERE prev_order_date IS NOT NULL
)
SELECT customer_id, AVG(gap) AS avg_gap_days
FROM gaps
GROUP BY customer_id;
```

186

List all customers who have never ordered product X.

```
SELECT customer_id
FROM customers
WHERE customer_id NOT IN (
  SELECT DISTINCT customer_id
  FROM sales
  WHERE product_id = 'X'
);
```

187

Calculate total revenue and number of orders per country.

```
SELECT c.country, COUNT(o.order_id) AS
order_count, SUM(o.amount) AS total_revenue
FROM customers c
JOIN orders o ON c.customer_id = o.customer_id
GROUP BY c.country;
```

188

Find the employees who were hired on the same day as their managers.

```
SELECT e.name AS employee, m.name AS manager,
e.hire_date
FROM employees e
JOIN employees m ON e.manager_id = m.id
WHERE e.hire_date = m.hire_date;
```

189

Find the top 3 products by quantity sold in each category.

```
SELECT category_id, product_id, total_quantity
FROM (
  SELECT p.category_id, s.product_id,
  SUM(s.quantity) AS total_quantity,
  ROW_NUMBER() OVER (PARTITION BY
  p.category_id ORDER BY SUM(s.quantity) DESC) AS
  rn
  FROM sales s
  JOIN products p ON s.product_id = p.product_id
  GROUP BY p.category_id, s.product_id
) sub
WHERE rn <= 3;
```

190

Find the difference in days between the first and last order for each customer.

```
SELECT customer_id, MAX(order_date) -  
MIN(order_date) AS days_between  
FROM orders  
GROUP BY customer_id;
```

191

Find customers who have increased their order volume every month for the last 3 months.

```
WITH monthly_orders AS (  
  SELECT customer_id, DATE_TRUNC('month',  
    order_date) AS month, COUNT(*) AS orders_count  
  FROM orders  
  WHERE order_date >= CURRENT_DATE -  
    INTERVAL '3 months'  
  GROUP BY customer_id, month  
)  
SELECT customer_id  
FROM monthly_orders  
GROUP BY customer_id  
HAVING COUNT(*) = 3  
AND MIN(orders_count) < MAX(orders_count); --  
Needs detailed window check for strict increase
```

192

Find employees who have the same salary as the average salary in their job title.

```
SELECT e.*  
FROM employees e  
JOIN (  
  SELECT job_title, AVG(salary) AS avg_salary  
  FROM employees  
  GROUP BY job_title  
) j ON e.job_title = j.job_title  
WHERE e.salary = j.avg_salary;
```

193

Write a query to calculate the difference in salary between employees and their managers.

```
SELECT e.name, m.name AS manager_name, e.salary,  
m.salary AS manager_salary, e.salary - m.salary AS  
salary_diff  
FROM employees e  
JOIN employees m ON e.manager_id = m.id;
```

194

List the departments with no employees.

```
SELECT d.*
FROM departments d
LEFT JOIN employees e ON d.department_id =
e.department_id
WHERE e.id IS NULL;
```

195

Find the employee with the maximum salary in each department.

```
WITH dept_max AS (
SELECT department_id, MAX(salary) AS max_salary
FROM employees
GROUP BY department_id
)
SELECT e.*
FROM employees e
JOIN dept_max d ON e.department_id =
d.department_id AND e.salary = d.max_salary;
```

196

Find customers with orders on every day in the last week.

```
WITH days AS (
SELECT generate_series(CURRENT_DATE -
INTERVAL '6 days', CURRENT_DATE, INTERVAL
'1 day') AS day
)
SELECT customer_id
FROM orders o
JOIN days d ON o.order_date = d.day
GROUP BY customer_id
HAVING COUNT(DISTINCT o.order_date) = 7;
```

197

Find the product that has been sold in the highest quantity in a single order.

```
SELECT product_id, MAX(quantity) AS  
max_quantity_in_order  
FROM sales  
GROUP BY product_id  
ORDER BY max_quantity_in_order DESC  
LIMIT 1;
```

198

Find employees who joined before their department was created.

```
SELECT e.*  
FROM employees e  
JOIN departments d ON e.department_id =  
d.department_id  
WHERE e.hire_date < d.creation_date;
```

199

Find customers with sales in at least 3 different years.

```
SELECT customer_id  
FROM sales  
GROUP BY customer_id  
HAVING COUNT(DISTINCT EXTRACT(YEAR  
FROM sale_date)) >= 3;
```

200

Find employees whose salary is above the company's average but below their department's average.

```
WITH company_avg AS (SELECT AVG(salary) AS  
avg_salary FROM employees),  
dept_avg AS (  
SELECT department_id, AVG(salary) AS  
avg_salary  
FROM employees  
GROUP BY department_id  
)  
SELECT e.*  
FROM employees e, company_avg ca  
JOIN dept_avg da ON e.department_id =  
da.department_id  
WHERE e.salary > ca.avg_salary AND e.salary <  
da.avg_salary;
```

201

Find the average order amount per customer per year.

```
SELECT customer_id, EXTRACT(YEAR FROM
order_date) AS year, AVG(amount) AS
avg_order_amount
FROM orders
GROUP BY customer_id, year;
```

202

Find employees who have worked on at least one project with a budget over \$1,000,000.

```
SELECT DISTINCT pa.employee_id
FROM project_assignments pa
JOIN projects p ON pa.project_id = p.project_id
WHERE p.budget > 1000000;
```

203

Find the most recent promotion date per employee.

```
SELECT employee_id, MAX(promotion_date) AS
last_promotion_date
FROM promotions
GROUP BY employee_id;
```

204

Find customers who made orders totaling more than the average order amount.

```
WITH avg_order AS (
SELECT AVG(amount) AS avg_amount FROM
orders
)
SELECT customer_id, SUM(amount) AS total_amount
FROM orders
GROUP BY customer_id
HAVING SUM(amount) > (SELECT avg_amount
FROM avg_order);
```

205

Find products never ordered.

```
SELECT product_id
FROM products
WHERE product_id NOT IN (SELECT DISTINCT
product_id FROM sales);
```

206

Find the month with the lowest sales in the past year.

```
SELECT DATE_TRUNC('month', sale_date) AS
month, SUM(amount) AS total_sales
FROM sales
WHERE sale_date >= CURRENT_DATE -
INTERVAL '1 year'
GROUP BY month
ORDER BY total_sales
LIMIT 1;
```

207

Calculate the number of employees hired each month in the last year.

```
SELECT DATE_TRUNC('month', hire_date) AS
month, COUNT(*) AS hires
FROM employees
WHERE hire_date >= CURRENT_DATE -
INTERVAL '1 year'
GROUP BY month
ORDER BY month;
```

208

Find the department with the highest number of projects.

```
SELECT department_id, COUNT(*) AS project_count
FROM projects
GROUP BY department_id
ORDER BY project_count DESC
LIMIT 1;
```

209

Find employees who do not have dependents.

```
SELECT e.*
FROM employees e
LEFT JOIN dependents d ON e.id = d.employee_id
WHERE d.dependent_id IS NULL;
```

210

Get the total sales amount for each product category including categories with zero sales.

```
SELECT c.category_id, COALESCE(SUM(s.amount),
0) AS total_sales
FROM categories c
LEFT JOIN products p ON c.category_id =
p.category_id
LEFT JOIN sales s ON p.product_id = s.product_id
GROUP BY c.category_id;
```

211

Find employees who have been promoted but their salary didn't increase.

```
SELECT e.id, e.name
FROM employees e
JOIN promotions p ON e.id = p.employee_id
WHERE e.salary <= (SELECT salary_before FROM
promotion_history WHERE employee_id = e.id
ORDER BY promotion_date DESC LIMIT 1);
```

212

Find customers with average order amount above \$500.

```
SELECT customer_id, AVG(amount) AS
avg_order_amount
FROM orders
GROUP BY customer_id
HAVING AVG(amount) > 500;
```

213

Find orders where the total quantity exceeds 100 units.

```
SELECT order_id, SUM(quantity) AS total_quantity
FROM order_items
GROUP BY order_id
HAVING SUM(quantity) > 100;
```

214

Find products whose sales have doubled compared to the previous month.

```
WITH monthly_sales AS (  
  SELECT product_id, DATE_TRUNC('month',  
    sale_date) AS month, SUM(amount) AS total_sales  
  FROM sales  
  GROUP BY product_id, month  
) ,  
sales_comparison AS (  
  SELECT product_id, month, total_sales,  
    LAG(total_sales) OVER (PARTITION BY  
      product_id ORDER BY month) AS prev_month_sales  
  FROM monthly_sales  
)  
SELECT product_id, month  
FROM sales_comparison  
WHERE prev_month_sales IS NOT NULL AND  
  total_sales >= 2 * prev_month_sales;
```

215

Write a query to find employees who worked on more than 3 projects in 2023.

```
SELECT employee_id, COUNT(DISTINCT project_id)  
  AS project_count  
FROM project_assignments  
WHERE assignment_date BETWEEN '2023-01-01'  
  AND '2023-12-31'  
GROUP BY employee_id  
HAVING COUNT(DISTINCT project_id) > 3;
```

216

Find customers whose last order was placed more than 1 year ago.

```
SELECT customer_id, MAX(order_date) AS  
  last_order_date  
FROM orders  
GROUP BY customer_id  
HAVING MAX(order_date) < CURRENT_DATE -  
  INTERVAL '1 year';
```

217

Find the average salary increase percentage per department.

```
SELECT e.department_id, AVG((e.salary -  
p.old_salary) / p.old_salary * 100) AS avg_increase_pct  
FROM employees e  
JOIN promotions p ON e.id = p.employee_id  
GROUP BY e.department_id;
```

218

Find employees who have never been promoted.

```
SELECT *  
FROM employees  
WHERE id NOT IN (SELECT DISTINCT  
employee_id FROM promotions);
```

219

Find products ordered by all customers.

```
SELECT product_id  
FROM sales  
GROUP BY product_id  
HAVING COUNT(DISTINCT customer_id) =  
(SELECT COUNT(*) FROM customers);
```

220

Find customers with orders totaling more than \$5000 in the last 6 months.

```
SELECT customer_id, SUM(amount) AS total_amount  
FROM orders  
WHERE order_date >= CURRENT_DATE -  
INTERVAL '6 months'  
GROUP BY customer_id  
HAVING SUM(amount) > 5000;
```

221

Find the rank of employees based on salary within their department.

```
SELECT *, RANK() OVER (PARTITION BY  
department_id ORDER BY salary DESC) AS  
salary_rank  
FROM employees;
```

222

Find customers who purchased a product but never reordered it.

```
WITH order_counts AS (  
  SELECT customer_id, product_id, COUNT(*) AS  
    order_count  
  FROM sales  
  GROUP BY customer_id, product_id  
)  
SELECT customer_id, product_id  
FROM order_counts  
WHERE order_count = 1;
```

223

Find the day with the highest number of new hires.

```
SELECT hire_date, COUNT(*) AS hires  
FROM employees  
GROUP BY hire_date  
ORDER BY hires DESC  
LIMIT 1;
```

224

Find the number of employees who have worked in more than one department.

```
SELECT employee_id  
FROM employee_department_history  
GROUP BY employee_id  
HAVING COUNT(DISTINCT department_id) > 1;
```

225

Find customers who ordered the most products in 2023.

```
SELECT customer_id, SUM(quantity) AS  
  total_quantity  
FROM sales  
WHERE EXTRACT(YEAR FROM sale_date) = 2023  
GROUP BY customer_id  
ORDER BY total_quantity DESC  
LIMIT 1;
```

226

Find the average days taken to ship orders per shipping method.

```
SELECT shipping_method, AVG(shipping_date -  
order_date) AS avg_shipping_days  
FROM orders  
GROUP BY shipping_method;
```

227

Find employees with overlapping project assignments.

```
SELECT pa1.employee_id, pa1.project_id,  
pa2.project_id AS overlapping_project  
FROM project_assignments pa1  
JOIN project_assignments pa2 ON pa1.employee_id =  
pa2.employee_id AND pa1.project_id <>  
pa2.project_id  
WHERE pa1.start_date <= pa2.end_date AND  
pa1.end_date >= pa2.start_date;
```

228

Find the total number of unique customers per product category.

```
SELECT p.category_id, COUNT(DISTINCT  
s.customer_id) AS unique_customers  
FROM sales s  
JOIN products p ON s.product_id = p.product_id  
GROUP BY p.category_id;
```

229

Find customers whose orders increased by at least 20% compared to the previous month.

```
WITH monthly_orders AS (  
SELECT customer_id, DATE_TRUNC('month',  
order_date) AS month, COUNT(*) AS order_count  
FROM orders  
GROUP BY customer_id, month  
)  
,  
orders_comparison AS (  
SELECT customer_id, month, order_count,  
LAG(order_count) OVER (PARTITION BY  
customer_id ORDER BY month) AS prev_order_count  
FROM monthly_orders  
)  
SELECT customer_id, month  
FROM orders_comparison  
WHERE prev_order_count IS NOT NULL AND  
order_count >= 1.2 * prev_order_count;
```

230

Find employees with no projects assigned in the last 6 months.

```
SELECT e.*
FROM employees e
LEFT JOIN project_assignments pa ON e.id =
pa.employee_id AND pa.start_date >=
CURRENT_DATE - INTERVAL '6 months'
WHERE pa.project_id IS NULL;
```

231

Find the number of employees who have changed departments more than twice.

```
SELECT employee_id
FROM employee_department_history
GROUP BY employee_id
HAVING COUNT(DISTINCT department_id) > 2;
```

232

Find the product with the highest average rating.

```
SELECT product_id, AVG(rating) AS avg_rating
FROM product_reviews
GROUP BY product_id
ORDER BY avg_rating DESC
LIMIT 1;
```

233

Find customers who have placed orders but never used a discount.

```
SELECT DISTINCT customer_id
FROM orders
WHERE discount_used = FALSE;
```

Medium to Advanced SQL Questions (201–300)

234

Find employees who have worked on every project in their department.

```
SELECT e.id, e.name
FROM employees e
JOIN projects p ON e.department_id = p.department_id
LEFT JOIN project_assignments pa ON e.id =
pa.employee_id AND p.project_id = pa.project_id
GROUP BY e.id, e.name, p.department_id
HAVING COUNT(p.project_id) =
COUNT(pa.project_id);
```

235

Find the average order amount excluding the top 5% largest orders.

```
WITH ordered_orders AS (
  SELECT amount,
  NTILE(100) OVER (ORDER BY amount DESC)
  AS percentile
  FROM orders
)
SELECT AVG(amount)
FROM ordered_orders
WHERE percentile > 5;
```

236

Find the top 3 employees with the highest salary increase over last year.

```
WITH salary_last_year AS (  
  SELECT employee_id, salary AS last_year_salary  
  FROM salaries  
  WHERE year = EXTRACT(YEAR FROM  
    CURRENT_DATE) - 1  
),  
salary_this_year AS (  
  SELECT employee_id, salary AS this_year_salary  
  FROM salaries  
  WHERE year = EXTRACT(YEAR FROM  
    CURRENT_DATE)  
)  
SELECT t.employee_id, t.this_year_salary -  
  l.last_year_salary AS salary_increase  
FROM salary_this_year t  
JOIN salary_last_year l ON t.employee_id =  
  l.employee_id  
ORDER BY salary_increase DESC  
LIMIT 3;
```

237

Find employees with the longest consecutive workdays.

```
WITH workdays AS (  
  SELECT employee_id, work_date,  
    ROW_NUMBER() OVER (PARTITION BY  
      employee_id ORDER BY work_date) -  
    ROW_NUMBER() OVER (PARTITION BY  
      employee_id ORDER BY work_date) AS grp  
  FROM attendance  
),  
consecutive_days AS (  
  SELECT employee_id, COUNT(*) AS  
    consecutive_days  
  FROM workdays  
  GROUP BY employee_id, grp  
)  
SELECT employee_id, MAX(consecutive_days) AS  
  max_consecutive_days  
FROM consecutive_days  
GROUP BY employee_id;
```

238

Find all managers who do not manage any employee.

```
SELECT DISTINCT manager_id
FROM employees
WHERE manager_id NOT IN (SELECT DISTINCT id
FROM employees);
```

239

Find the average salary of employees hired each month.

```
SELECT EXTRACT(YEAR FROM hire_date) AS
year, EXTRACT(MONTH FROM hire_date) AS
month, AVG(salary) AS avg_salary
FROM employees
GROUP BY year, month
ORDER BY year, month;
```

--207. Find the first 5 orders after a customer's registration date.

```
SELECT order_id, customer_id, order_date
FROM (
SELECT order_id, customer_id, order_date,
ROW_NUMBER() OVER (PARTITION BY
customer_id ORDER BY order_date) AS rn
FROM orders
JOIN customers c ON orders.customer_id =
c.customer_id
WHERE order_date >= c.registration_date
) sub
WHERE rn <= 5;
```

240

Find customers who placed orders every month for the last 6 months.

```
WITH months AS (  
  SELECT generate_series(  
    DATE_TRUNC('month', CURRENT_DATE) -  
    INTERVAL '5 months',  
    DATE_TRUNC('month', CURRENT_DATE),  
    INTERVAL '1 month'  
  ) AS month  
,  
customer_months AS (  
  SELECT customer_id, DATE_TRUNC('month',  
    order_date) AS month  
  FROM orders  
  WHERE order_date >= CURRENT_DATE -  
    INTERVAL '6 months'  
  GROUP BY customer_id, month  
)  
SELECT customer_id  
FROM customer_months cm  
JOIN months m ON cm.month = m.month  
GROUP BY customer_id  
HAVING COUNT(DISTINCT cm.month) = 6;
```

241

Calculate the moving average of sales over the last 3 days.

```
SELECT sale_date, product_id, amount,  
  AVG(amount) OVER (PARTITION BY  
    product_id ORDER BY sale_date ROWS BETWEEN 2  
    PRECEDING AND CURRENT ROW) AS  
  moving_avg_3_days  
FROM sales;
```

242

Find the number of employees who share the same birthday.

```
SELECT birth_date, COUNT(*) AS count_employees  
FROM employees  
GROUP BY birth_date  
HAVING COUNT(*) > 1;
```

243

Find customers who ordered the same product multiple times in one day.

```
SELECT customer_id, product_id, order_date,  
COUNT(*) AS order_count  
FROM sales  
GROUP BY customer_id, product_id, order_date  
HAVING COUNT(*) > 1;
```

244

Find the total sales for each product including products with zero sales.

```
SELECT p.product_id, COALESCE(SUM(s.amount),  
0) AS total_sales  
FROM products p  
LEFT JOIN sales s ON p.product_id = s.product_id  
GROUP BY p.product_id;
```

245

List the top 5 employees by number of projects in each department.

```
SELECT department_id, employee_id, project_count  
FROM (  
SELECT e.department_id, pa.employee_id,  
COUNT(DISTINCT pa.project_id) AS project_count,  
ROW_NUMBER() OVER (PARTITION BY  
e.department_id ORDER BY COUNT(DISTINCT  
pa.project_id) DESC) AS rn  
FROM project_assignments pa  
JOIN employees e ON pa.employee_id = e.id  
GROUP BY e.department_id, pa.employee_id  
) sub  
WHERE rn <= 5;
```

246

Find the day with the largest difference between maximum and minimum temperature.

```
SELECT weather_date, MAX(temperature) -  
MIN(temperature) AS temp_diff  
FROM weather_data  
GROUP BY weather_date  
ORDER BY temp_diff DESC  
LIMIT 1;
```

247

Find the 3 most recent orders per customer.

```
SELECT order_id, customer_id, order_date
FROM (
  SELECT order_id, customer_id, order_date,
  ROW_NUMBER() OVER (PARTITION BY
  customer_id ORDER BY order_date DESC) AS rn
  FROM orders
) sub
WHERE rn <= 3;
```

248

Find products with sales only in a specific country.

```
SELECT product_id
FROM sales s
JOIN customers c ON s.customer_id = c.customer_id
GROUP BY product_id
HAVING COUNT(DISTINCT c.country) = 1;
```

249

Find employees with a salary greater than all employees in department 10.

```
SELECT *
FROM employees
WHERE salary > ALL (
  SELECT salary FROM employees WHERE
  department_id = 10
);
```

250

Find the percentage of employees in each department.

```
WITH total_employees AS (SELECT COUNT(*) AS
total FROM employees)
SELECT department_id, COUNT(*) * 100.0 /
(SELECT total FROM total_employees) AS percentage
FROM employees
GROUP BY department_id;
```

251

Find the median salary per department.

```
SELECT department_id,  
PERCENTILE_CONT(0.5) WITHIN GROUP  
(ORDER BY salary) AS median_salary  
FROM employees  
GROUP BY department_id;
```

252

Find the employee who worked the most hours in a project.

```
SELECT employee_id, project_id,  
MAX(hours_worked) AS max_hours  
FROM project_assignments  
GROUP BY employee_id, project_id  
ORDER BY max_hours DESC  
LIMIT 1;
```

253

Find the first order date for each customer.

```
SELECT customer_id, MIN(order_date) AS  
first_order_date  
FROM orders  
GROUP BY customer_id;
```

254

Find the second most expensive product per category.

```
SELECT category_id, product_id, price  
FROM (  
SELECT category_id, product_id, price,  
ROW_NUMBER() OVER (PARTITION BY  
category_id ORDER BY price DESC) AS rn  
FROM products  
) sub  
WHERE rn = 2;
```

255

Find employees with the highest salary in each job title.

```
WITH max_salary_per_job AS (  
  SELECT job_title, MAX(salary) AS max_salary  
  FROM employees  
  GROUP BY job_title  
)  
SELECT e.*  
FROM employees e  
JOIN max_salary_per_job m ON e.job_title =  
m.job_title AND e.salary = m.max_salary;
```

256

Calculate the ratio of males to females in each department.

```
SELECT department_id,  
SUM(CASE WHEN gender = 'M' THEN 1 ELSE 0  
END) * 1.0 / NULLIF(SUM(CASE WHEN gender = 'F'  
THEN 1 ELSE 0 END), 0) AS male_to_female_ratio  
FROM employees  
GROUP BY department_id;
```

257

Find customers who spent more than average in their country.

```
WITH avg_spent_per_country AS (  
  SELECT c.country, AVG(o.amount) AS avg_amount  
  FROM customers c  
  JOIN orders o ON c.customer_id = o.customer_id  
  GROUP BY c.country  
)  
SELECT c.customer_id, SUM(o.amount) AS  
total_spent  
FROM customers c  
JOIN orders o ON c.customer_id = o.customer_id  
JOIN avg_spent_per_country a ON c.country =  
a.country  
GROUP BY c.customer_id, c.country, a.avg_amount  
HAVING SUM(o.amount) > a.avg_amount;
```

258

Find employees who have not been assigned to any project in the last year.

```
SELECT e.*
FROM employees e
LEFT JOIN project_assignments pa ON e.id =
pa.employee_id AND pa.assignment_date >=
CURRENT_DATE - INTERVAL '1 year'
WHERE pa.project_id IS NULL;
```

259

Find the top 3 customers by total order amount in each region.

```
SELECT region, customer_id, total_amount
FROM (
SELECT c.region, o.customer_id, SUM(o.amount) AS
total_amount,
ROW_NUMBER() OVER (PARTITION BY
c.region ORDER BY SUM(o.amount) DESC) AS rn
FROM customers c
JOIN orders o ON c.customer_id = o.customer_id
GROUP BY c.region, o.customer_id
) sub
WHERE rn <= 3;
```

260

Find employees hired after their managers.

```
SELECT e.name AS employee_name, m.name AS
manager_name, e.hire_date, m.hire_date AS
manager_hire_date
FROM employees e
JOIN employees m ON e.manager_id = m.id
WHERE e.hire_date > m.hire_date;
```

261

Find customers who ordered all products from a specific category.

```
WITH category_products AS (  
  SELECT product_id  
  FROM products  
  WHERE category_id = :category_id  
)  
,  
customer_products AS (  
  SELECT customer_id, product_id  
  FROM sales  
  WHERE product_id IN (SELECT product_id FROM  
    category_products)  
  GROUP BY customer_id, product_id  
)  
SELECT customer_id  
FROM customer_products  
GROUP BY customer_id  
HAVING COUNT(DISTINCT product_id) = (SELECT  
  COUNT(*) FROM category_products);
```

262

Find employees with the highest number of direct reports.

```
SELECT manager_id, COUNT(*) AS report_count  
FROM employees  
WHERE manager_id IS NOT NULL  
GROUP BY manager_id  
ORDER BY report_count DESC  
LIMIT 1;
```

263

Calculate the retention rate of customers month- over-month.

```
WITH monthly_customers AS (  
  SELECT customer_id, DATE_TRUNC('month',  
    order_date) AS month  
  FROM orders  
  GROUP BY customer_id, month  
) ,  
retention AS (  
  SELECT current.month AS current_month,  
    current.customer_id  
  FROM monthly_customers current  
  JOIN monthly_customers previous ON  
    current.customer_id = previous.customer_id  
  AND current.month = previous.month + INTERVAL  
    '1 month'  
)  
SELECT current_month, COUNT(DISTINCT  
  customer_id) * 100.0 /  
(SELECT COUNT(DISTINCT customer_id)  
  FROM monthly_customers WHERE month =  
    current_month - INTERVAL '1 month') AS  
  retention_rate  
FROM retention  
GROUP BY current_month  
ORDER BY current_month;
```

264

Find the average time difference between order and delivery.

```
SELECT AVG(delivery_date - order_date) AS  
  avg_delivery_time  
FROM orders  
WHERE delivery_date IS NOT NULL;
```

265

Find the department with the youngest average employee age.

```
SELECT department_id, AVG(EXTRACT(YEAR  
  FROM AGE(CURRENT_DATE, birth_date))) AS  
  avg_age  
FROM employees  
GROUP BY department_id  
ORDER BY avg_age  
LIMIT 1;
```

266

Find products that were sold in every quarter of the current year.

```
WITH quarterly_sales AS (  
  SELECT product_id, DATE_TRUNC('quarter',  
    sale_date) AS quarter  
  FROM sales  
  WHERE EXTRACT(YEAR FROM sale_date) =  
    EXTRACT(YEAR FROM CURRENT_DATE)  
  GROUP BY product_id, quarter  
)  
SELECT product_id  
FROM quarterly_sales  
GROUP BY product_id  
HAVING COUNT(DISTINCT quarter) = 4;
```

267

Find customers whose orders decreased consecutively for 3 months.

```
WITH monthly_orders AS (  
  SELECT customer_id, DATE_TRUNC('month',  
    order_date) AS month, COUNT(*) AS order_count  
  FROM orders  
  GROUP BY customer_id, month  
,  
  orders_with_lag AS (  
    SELECT customer_id, month, order_count,  
      LAG(order_count, 1) OVER (PARTITION BY  
        customer_id ORDER BY month) AS prev_1,  
      LAG(order_count, 2) OVER (PARTITION BY  
        customer_id ORDER BY month) AS prev_2  
    FROM monthly_orders  
  )  
SELECT DISTINCT customer_id  
FROM orders_with_lag  
WHERE order_count < prev_1 AND prev_1 < prev_2;
```

268

Find the employee(s) with the highest number of late arrivals.

```
SELECT employee_id, COUNT(*) AS late_count  
FROM attendance  
WHERE arrival_time > scheduled_start_time  
GROUP BY employee_id  
ORDER BY late_count DESC  
LIMIT 1;
```

269

Find the most common product combinations in orders (pairs).

```
WITH order_pairs AS (  
  SELECT o1.order_id, o1.product_id AS product1,  
         o2.product_id AS product2  
  FROM order_items o1  
  JOIN order_items o2 ON o1.order_id = o2.order_id  
  AND o1.product_id < o2.product_id  
)  
SELECT product1, product2, COUNT(*) AS  
pair_count  
FROM order_pairs  
GROUP BY product1, product2  
ORDER BY pair_count DESC  
LIMIT 10;
```

270

Find employees who have worked more than 40 hours in a week.

```
WITH weekly_hours AS (  
  SELECT employee_id, DATE_TRUNC('week',  
    work_date) AS week_start, SUM(hours_worked) AS  
    total_hours  
  FROM work_logs  
  GROUP BY employee_id, week_start  
)  
SELECT employee_id, week_start, total_hours  
FROM weekly_hours  
WHERE total_hours > 40;
```

271

Find the total revenue generated per sales representative.

```
SELECT sales_rep_id, SUM(amount) AS total_revenue  
FROM sales  
GROUP BY sales_rep_id;
```

272

Find customers with no orders in the last year.

```
SELECT customer_id  
FROM customers  
WHERE customer_id NOT IN (  
  SELECT DISTINCT customer_id FROM orders  
  WHERE order_date >= CURRENT_DATE -  
    INTERVAL '1 year'  
);
```

273

Find products with an increasing sales trend over the last 3 months.

```
WITH monthly_sales AS (  
  SELECT product_id, DATE_TRUNC('month',  
    sale_date) AS month, SUM(amount) AS total_sales  
  FROM sales  
  WHERE sale_date >= CURRENT_DATE -  
    INTERVAL '3 months'  
  GROUP BY product_id, month  
) ,  
sales_ranked AS (  
  SELECT product_id, month, total_sales,  
    LAG(total_sales) OVER (PARTITION BY  
      product_id ORDER BY month) AS prev_month_sales,  
    LAG(total_sales, 2) OVER (PARTITION BY  
      product_id ORDER BY month) AS  
      prev_2_month_sales  
  FROM monthly_sales  
)  
SELECT DISTINCT product_id  
FROM sales_ranked  
WHERE total_sales > prev_month_sales AND  
prev_month_sales > prev_2_month_sales;
```

274

Find departments where average salary is higher than the company average.

```
WITH company_avg AS (  
  SELECT AVG(salary) AS avg_salary FROM  
    employees  
)  
SELECT department_id, AVG(salary) AS dept_avg  
FROM employees  
GROUP BY department_id  
HAVING AVG(salary) > (SELECT avg_salary FROM  
  company_avg);
```

275

Find customers with orders where no product quantity is less than 5.

```
SELECT DISTINCT order_id  
FROM order_items  
GROUP BY order_id  
HAVING MIN(quantity) >= 5;
```

276

Find products ordered only by customers from one country.

```
SELECT product_id
FROM sales s
JOIN customers c ON s.customer_id = c.customer_id
GROUP BY product_id
HAVING COUNT(DISTINCT c.country) = 1;
```

277

Find employees who have not submitted their timesheets in the last month.

```
SELECT e.id, e.name
FROM employees e
LEFT JOIN timesheets t ON e.id = t.employee_id AND
t.timesheet_date >= CURRENT_DATE - INTERVAL
'1 month'
WHERE t.timesheet_id IS NULL;
```

278

Find the total discount given in each month.

```
SELECT DATE_TRUNC('month', order_date) AS
month, SUM(discount_amount) AS total_discount
FROM orders
GROUP BY month
ORDER BY month;
```

279

Find customers who have placed orders but never paid by credit card.

```
SELECT DISTINCT customer_id
FROM orders
WHERE payment_method != 'Credit Card';
```

280

Find employees whose salaries are within 10% of their department's average salary.

```
WITH dept_avg AS (  
  SELECT department_id, AVG(salary) AS avg_salary  
  FROM employees  
  GROUP BY department_id  
)  
SELECT e.*  
FROM employees e  
JOIN dept_avg d ON e.department_id =  
d.department_id  
WHERE e.salary BETWEEN d.avg_salary * 0.9 AND  
d.avg_salary * 1.1;
```

281

Find customers who ordered the most products in each category.

```
WITH product_totals AS (  
  SELECT c.customer_id, p.category_id,  
  SUM(s.quantity) AS total_quantity,  
  RANK() OVER (PARTITION BY p.category_id  
  ORDER BY SUM(s.quantity) DESC) AS rank  
  FROM sales s  
  JOIN products p ON s.product_id = p.product_id  
  JOIN customers c ON s.customer_id = c.customer_id  
  GROUP BY c.customer_id, p.category_id  
)  
SELECT customer_id, category_id, total_quantity  
FROM product_totals  
WHERE rank = 1;
```

282

Find the top 5 longest projects.

```
SELECT project_id, start_date, end_date,  
end_date - start_date AS duration  
FROM projects  
ORDER BY duration DESC  
LIMIT 5;
```

283

Find employees who have not taken any leave in the last 6 months.

```
SELECT e.id, e.name
FROM employees e
LEFT JOIN leaves l ON e.id = l.employee_id AND
l.leave_date >= CURRENT_DATE - INTERVAL '6
months'
WHERE l.leave_id IS NULL;
```

284

Find the department with the most projects completed last year.

```
SELECT department_id, COUNT(*) AS
completed_projects
FROM projects
WHERE status = 'Completed' AND completion_date
BETWEEN DATE_TRUNC('year',
CURRENT_DATE) - INTERVAL '1 year' AND
DATE_TRUNC('year', CURRENT_DATE) -
INTERVAL '1 day'
GROUP BY department_id
ORDER BY completed_projects DESC
LIMIT 1;
```

285

Find customers who have increased their order frequency month-over-month for 3 consecutive months.

```
WITH monthly_orders AS (
SELECT customer_id, DATE_TRUNC('month',
order_date) AS month, COUNT(*) AS order_count
FROM orders
GROUP BY customer_id, month
),
orders_with_lag AS (
SELECT customer_id, month, order_count,
LAG(order_count, 1) OVER (PARTITION BY
customer_id ORDER BY month) AS prev_1,
LAG(order_count, 2) OVER (PARTITION BY
customer_id ORDER BY month) AS prev_2
FROM monthly_orders
)
SELECT DISTINCT customer_id
FROM orders_with_lag
WHERE order_count > prev_1 AND prev_1 > prev_2;
```

286

Find employees who have been assigned projects outside their department.

```
SELECT DISTINCT e.id, e.name
FROM employees e
JOIN project_assignments pa ON e.id =
pa.employee_id
JOIN projects p ON pa.project_id = p.project_id
WHERE e.department_id != p.department_id;
```

287

Calculate the average time to close tickets per support agent.

```
SELECT support_agent_id, AVG(closed_date -
opened_date) AS avg_close_time
FROM support_tickets
WHERE closed_date IS NOT NULL
GROUP BY support_agent_id;
```

288

Find the first and last login date for each user.

```
SELECT user_id, MIN(login_date) AS first_login,
MAX(login_date) AS last_login
FROM user_logins
GROUP BY user_id;
```

289

Find customers who made purchases only in one month of the year.

```
WITH customer_months AS (
SELECT customer_id, DATE_TRUNC('month',
order_date) AS month
FROM orders
GROUP BY customer_id, month
)
SELECT customer_id
FROM customer_months
GROUP BY customer_id
HAVING COUNT(*) = 1;
```

290

Find products with sales revenue above the average revenue per product.

```
WITH avg_revenue AS (  
  SELECT AVG(total_revenue) AS avg_rev  
  FROM (  
    SELECT product_id, SUM(amount) AS  
      total_revenue  
    FROM sales  
    GROUP BY product_id  
  ) sub  
)  
SELECT product_id, SUM(amount) AS total_revenue  
FROM sales  
GROUP BY product_id  
HAVING SUM(amount) > (SELECT avg_rev FROM  
  avg_revenue);
```

291

Find departments where more than 50% of employees have a salary above \$60,000.

```
SELECT department_id  
FROM employees  
GROUP BY department_id  
HAVING AVG(CASE WHEN salary > 60000 THEN 1  
  ELSE 0 END) > 0.5;
```

292

Find employees who worked on all projects in the company.

```
WITH total_projects AS (  
  SELECT COUNT(DISTINCT project_id) AS  
    project_count FROM projects  
)  
,  
employee_projects AS (  
  SELECT employee_id, COUNT(DISTINCT  
    project_id) AS projects_worked  
  FROM project_assignments  
  GROUP BY employee_id  
)  
SELECT ep.employee_id  
FROM employee_projects ep  
JOIN total_projects tp ON 1=1  
WHERE ep.projects_worked = tp.project_count;
```

293

Find customers who ordered products from all categories.

```
WITH category_count AS (  
  SELECT COUNT(DISTINCT category_id) AS  
  total_categories FROM products  
)  
customer_categories AS (  
  SELECT customer_id, COUNT(DISTINCT  
  p.category_id) AS categories_ordered  
  FROM sales s  
  JOIN products p ON s.product_id = p.product_id  
  GROUP BY customer_id  
)  
SELECT customer_id  
FROM customer_categories  
JOIN category_count ON 1=1  
WHERE categories_ordered = total_categories;
```

294

Find the average tenure of employees by department.

```
SELECT department_id, AVG(DATE_PART('year',  
CURRENT_DATE - hire_date)) AS avg_tenure_years  
FROM employees  
GROUP BY department_id;
```

295

Find the number of orders placed on weekends vs weekdays.

```
SELECT CASE  
  WHEN EXTRACT(DOW FROM order_date) IN  
  (0,6) THEN 'Weekend'  
  ELSE 'Weekday'  
  END AS day_type,  
  COUNT(*) AS order_count  
FROM orders  
GROUP BY day_type;
```

296

Find the percentage of orders with discounts per month.

```
SELECT DATE_TRUNC('month', order_date) AS  
month,  
100.0 * SUM(CASE WHEN discount > 0 THEN 1  
ELSE 0 END) / COUNT(*) AS discount_percentage  
FROM orders  
GROUP BY month  
ORDER BY month;
```

297

Find the employees who have never been late to work.

```
SELECT e.id, e.name
FROM employees e
LEFT JOIN attendance a ON e.id = a.employee_id
AND a.arrival_time > a.scheduled_start_time
WHERE a.employee_id IS NULL;
```

298

Find products with sales only during holiday seasons.

```
SELECT product_id
FROM sales s
JOIN holidays h ON s.sale_date = h.holiday_date
GROUP BY product_id
HAVING COUNT(*) = (SELECT COUNT(*) FROM
sales WHERE product_id = s.product_id);
```

299

Find the department with the largest increase in employee count compared to last year.

```
WITH current_year AS (
SELECT department_id, COUNT(*) AS emp_count
FROM employees
WHERE hire_date <= CURRENT_DATE AND
(termination_date IS NULL OR termination_date >=
CURRENT_DATE)
GROUP BY department_id
),
last_year AS (
SELECT department_id, COUNT(*) AS emp_count
FROM employees
WHERE hire_date <= CURRENT_DATE -
INTERVAL '1 year' AND (termination_date IS NULL
OR termination_date >= CURRENT_DATE -
INTERVAL '1 year')
GROUP BY department_id
)
SELECT c.department_id, c.emp_count -
COALESCE(l.emp_count,0) AS increase
FROM current_year c
LEFT JOIN last_year l ON c.department_id =
l.department_id
ORDER BY increase DESC
LIMIT 1;
```

300

Find the average order value per customer segment.

```
SELECT segment, AVG(o.amount) AS  
avg_order_value  
FROM customers c  
JOIN orders o ON c.customer_id = o.customer_id  
GROUP BY segment;
```

301

Find employees who manage more than 3 projects.

```
SELECT manager_id, COUNT(DISTINCT project_id)  
AS project_count  
FROM projects  
GROUP BY manager_id  
HAVING COUNT(DISTINCT project_id) > 3;
```

302

Find products that have never been returned.

```
SELECT p.product_id  
FROM products p  
LEFT JOIN returns r ON p.product_id = r.product_id  
WHERE r.return_id IS NULL;
```

303

Find customers with orders but no shipments.

```
SELECT DISTINCT o.customer_id  
FROM orders o  
LEFT JOIN shipments s ON o.order_id = s.order_id  
WHERE s.shipment_id IS NULL;
```

304

Find employees whose salaries increased every year.

```
WITH salary_diff AS (  
  SELECT employee_id, year, salary,  
    LAG(salary) OVER (PARTITION BY  
      employee_id ORDER BY year) AS prev_salary  
  FROM salaries  
)  
SELECT DISTINCT employee_id  
FROM salary_diff  
WHERE salary > prev_salary OR prev_salary IS NULL  
GROUP BY employee_id  
HAVING COUNT(*) = (SELECT COUNT(*) FROM  
  salaries s2 WHERE s2.employee_id =  
  salary_diff.employee_id);
```

305

Find the total number of unique products sold in the last quarter.

```
SELECT COUNT(DISTINCT product_id) AS  
unique_products_sold  
FROM sales  
WHERE sale_date >= DATE_TRUNC('quarter',  
  CURRENT_DATE) - INTERVAL '3 months'  
AND sale_date < DATE_TRUNC('quarter',  
  CURRENT_DATE);
```

306

Find the day with the highest sales in each month.

```
WITH daily_sales AS (  
  SELECT DATE(order_date) AS day, SUM(amount)  
  AS total_sales  
  FROM orders  
  GROUP BY day  
,  
  ranked_sales AS (  
  SELECT day, total_sales,  
    RANK() OVER (PARTITION BY  
      DATE_TRUNC('month', day) ORDER BY total_sales  
    DESC) AS sales_rank  
  FROM daily_sales  
)  
SELECT day, total_sales  
FROM ranked_sales  
WHERE sales_rank = 1;
```

307

Find the products with the highest sales increase compared to the previous month.

```
WITH monthly_sales AS (  
  SELECT product_id, DATE_TRUNC('month',  
    sale_date) AS month, SUM(amount) AS total_sales  
  FROM sales  
  GROUP BY product_id, month  
,  
  sales_diff AS (  
    SELECT product_id, month, total_sales,  
      LAG(total_sales) OVER (PARTITION BY  
        product_id ORDER BY month) AS prev_month_sales  
    FROM monthly_sales  
  )  
  SELECT product_id, month, total_sales -  
    prev_month_sales AS increase  
  FROM sales_diff  
  WHERE prev_month_sales IS NOT NULL  
  ORDER BY increase DESC  
  LIMIT 10;
```

308

Find the top 5 customers by total order value in the last year.

```
SELECT customer_id, SUM(amount) AS  
  total_order_value  
FROM orders  
WHERE order_date >= CURRENT_DATE -  
  INTERVAL '1 year'  
GROUP BY customer_id  
ORDER BY total_order_value DESC  
LIMIT 5;
```

309

Find the number of employees who changed departments in the last year.

```
SELECT COUNT(DISTINCT employee_id)  
FROM employee_department_history  
WHERE change_date >= CURRENT_DATE -  
  INTERVAL '1 year';
```

310

Find the average salary for each job title within each department.

```
SELECT department_id, job_title, AVG(salary) AS  
avg_salary  
FROM employees  
GROUP BY department_id, job_title;
```

311

Find customers who placed orders with multiple payment methods.

```
SELECT customer_id  
FROM orders  
GROUP BY customer_id  
HAVING COUNT(DISTINCT payment_method) > 1;
```

312

Find products with the lowest average rating per category.

```
SELECT category_id, product_id, AVG(rating) AS  
avg_rating  
FROM product_reviews  
GROUP BY category_id, product_id  
QUALIFY ROW_NUMBER() OVER (PARTITION  
BY category_id ORDER BY AVG(rating)) = 1;
```

313

Find employees who have never received a promotion.

```
SELECT e.id, e.name  
FROM employees e  
LEFT JOIN promotions p ON e.id = p.employee_id  
WHERE p.promotion_id IS NULL;
```

314

Find the total number of orders placed each day in the last week.

```
SELECT DATE(order_date) AS order_day, COUNT(*)  
AS orders_count  
FROM orders  
WHERE order_date >= CURRENT_DATE -  
INTERVAL '7 days'  
GROUP BY order_day  
ORDER BY order_day;
```

315

Find customers with orders in both online and in- store channels.

```
SELECT customer_id
FROM orders
GROUP BY customer_id
HAVING COUNT(DISTINCT order_channel) > 1;
```

316

Find the top 3 sales reps by number of deals closed this quarter.

```
SELECT sales_rep_id, COUNT(*) AS deals_closed
FROM sales_deals
WHERE deal_close_date >= DATE_TRUNC('quarter',
CURRENT_DATE)
GROUP BY sales_rep_id
ORDER BY deals_closed DESC
LIMIT 3;
```

317

Find products that have been discontinued but still have sales.

```
SELECT p.product_id
FROM products p
JOIN sales s ON p.product_id = s.product_id
WHERE p.discontinued = TRUE;
```

318

Find employees who report to a manager hired after them.

```
SELECT e.id, e.name, m.id AS manager_id, m.name
AS manager_name
FROM employees e
JOIN employees m ON e.manager_id = m.id
WHERE e.hire_date < m.hire_date;
```

319

Find the average delivery time by shipping method.

```
SELECT shipping_method, AVG(delivery_date -
order_date) AS avg_delivery_time
FROM shipments
GROUP BY shipping_method;
```

320

Find orders where the total quantity exceeds 100.

```
SELECT order_id, SUM(quantity) AS total_quantity
FROM order_items
GROUP BY order_id
HAVING SUM(quantity) > 100;
```

321

Find customers who made orders but never returned a product.

```
SELECT DISTINCT o.customer_id
FROM orders o
LEFT JOIN returns r ON o.order_id = r.order_id
WHERE r.return_id IS NULL;
```

322

Find products that have been ordered but never reviewed.

```
SELECT p.product_id
FROM products p
LEFT JOIN product_reviews pr ON p.product_id =
pr.product_id
JOIN sales s ON p.product_id = s.product_id
WHERE pr.review_id IS NULL
GROUP BY p.product_id;
```

323

Find employees who have worked on projects for more than 2 years.

```
SELECT employee_id
FROM project_assignments
GROUP BY employee_id
HAVING MAX(assignment_end_date) -
MIN(assignment_start_date) > INTERVAL '2 years';
```

324

Find the product with the highest sales for each month.

```
WITH monthly_sales AS (  
  SELECT product_id, DATE_TRUNC('month',  
    sale_date) AS month, SUM(amount) AS total_sales  
  FROM sales  
  GROUP BY product_id, month  
) ,  
ranked_sales AS (  
  SELECT product_id, month, total_sales,  
    ROW_NUMBER() OVER (PARTITION BY  
      month ORDER BY total_sales DESC) AS rn  
  FROM monthly_sales  
)  
SELECT product_id, month, total_sales  
FROM ranked_sales  
WHERE rn = 1;
```

325

Find customers with the highest order count in each region.

```
WITH customer_order_counts AS (  
  SELECT c.region, o.customer_id, COUNT(*) AS  
    order_count,  
    ROW_NUMBER() OVER (PARTITION BY  
      c.region ORDER BY COUNT(*) DESC) AS rn  
  FROM customers c  
  JOIN orders o
```

326

Flag customers with an increase in orders every month this year.

```
WITH monthly_counts AS (  
  SELECT customer_id, DATE_TRUNC('month',  
    order_date) AS month, COUNT(*) AS cnt  
  FROM orders  
  WHERE EXTRACT(YEAR FROM order_date) =  
    EXTRACT(YEAR FROM CURRENT_DATE)  
  GROUP BY customer_id, month  
)  
increase_check AS (  
  SELECT customer_id,  
    LAG(cnt) OVER (PARTITION BY customer_id  
      ORDER BY month) AS prev_cnt,  
    cnt  
  FROM monthly_counts  
)  
SELECT DISTINCT customer_id  
FROM increase_check  
WHERE cnt > prev_cnt AND prev_cnt IS NOT NULL;
```

327

Find employees whose hire date is the same weekday as their manager's.

```
SELECT e.id, e.name  
FROM employees e  
JOIN employees m ON e.manager_id = m.id  
WHERE EXTRACT(DOW FROM e.hire_date) =  
  EXTRACT(DOW FROM m.hire_date);
```

328

Get total working hours per employee per week.

```
SELECT employee_id, DATE_TRUNC('week',  
  work_date) AS week_start, SUM(hours_worked) AS  
  total_hours  
FROM work_logs  
GROUP BY employee_id, week_start;
```

329

Identify suppliers who delivered to all regions.

```
WITH total_regions AS (  
  SELECT COUNT(DISTINCT region) AS total FROM  
  suppliers  
)  
supplier_regions AS (  
  SELECT supplier_id, COUNT(DISTINCT  
  delivery_region) AS regions_served  
  FROM deliveries  
  GROUP BY supplier_id  
)  
SELECT supplier_id  
FROM supplier_regions  
JOIN total_regions ON regions_served = total;
```

330

Find products ordered on their launch date.

```
SELECT o.product_id  
FROM orders o  
JOIN products p ON o.product_id = p.product_id  
WHERE CAST(o.order_date AS DATE) =  
p.launch_date;
```

331

Retrieve employees with salary in top 5% company-wide.

```
WITH salary_ranks AS (  
  SELECT salary, PERCENT_RANK() OVER  
  (ORDER BY salary DESC) AS pr  
  FROM employees  
)  
SELECT e.*  
FROM employees e  
JOIN salary_ranks sr ON e.salary = sr.salary  
WHERE sr.pr <= 0.05;
```

332

List departments with no open positions.

```
SELECT d.department_id  
FROM departments d  
LEFT JOIN job_openings j ON d.department_id =  
j.department_id AND j.status = 'Open'  
WHERE j.job_id IS NULL;
```

You've completed all 300 questions.

Keep practicing window functions, recursive CTEs, and real-world business logic — that's what separates strong SQL candidates in interviews at top firms.