## **Phase-4 Practice Project: Assisted Practice**

## 3. Class and Style binding

## **Binding.component.html:**

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
</head>
<body>
  <h1>Print Student Details</h1>
  Name
           Rollno
           Class
           Group
        </thead>
     <!--NgDirective eg: *ngFor-->
        {{s.Name}}<!--Class binding-->
          {{s.Rollno}}>><!--Style
binding-->
          {{s.Class}}
           {{s.Group}}
        <b>Source to View using interpoliation binding</b>
  {p>{{name}}
  <b>Source to View using property binding</b>
  <a [href]="url">YouTube</a><br>
  <div class="container">
     <button class="btn btn-primary" (click)="show()">Show div</button>
```

```
<div *ngIf="flag" style="background-color: rgb(247, 167, 247);">
           Event Binding
 </div>
 </div>
</body>
</html>
Binding.component.ts:
import { Component, OnInit } from '@angular/core';
@Component({
selector: 'app-binding',
templateUrl: './binding.component.html',
styleUrls: ['./binding.component.css']
export class BindingComponent implements OnInit {
constructor() { }
 ngOnInit(): void {
 //property binding
 students=[{Name:"Raj", Rollno:42, Class:"XI", Group:"Biology"},
 {Name:"Alex", Rollno:38, Class:"XI", Group:"Computer Science"},
{Name: "Angel", Rollno:50, Class: "XI", Group: "Commerce"},
 {Name: "George", Rollno: 36, Class: "XI", Group: "Biology"},
 {Name:"Chrissy", Rollno:96, Class:"XI", Group:"Commerce"},]
 name:string="YouTube";
url:string="youtube.com" //class binding
 weight:number=700; //style binding
 flag=false;//event bindings
show(){
 this.flag=!this.flag;
```

## **OUTPUT:**

