## **Phase-4 Practice Project: Assisted Practice**

## 8.PIPES

<hr>

```
Pipes.component.html:
<h1>Pipes Demo</h1>
<div class="jumbotron">
   <div class="container">
    <h2>Inbuilt Pipes demo</h2>
       <hr>>
       <b>UPPERCASE DEMO: </b>{{name | uppercase}}
       <hr>
       <b>lowercase demo: </b>{{name | lowercase}}
   </div>
</div>
<div class="jumbotron">
   <div class="container">
       <h2>Number Pipes</h2>
       <hr>
       <b>pi: </b>{{pi | number:'5.5-5'}}
       <hr>>
       <b>pi: </b>{{pi | number:'.3-3'}}
       <hr>>
       <b>pi: </b>{{pi | number:'.10-10'}}
  </div>
</div>
<div class="jumbotron">
   <div class="container">
 <h1>Currency Pipes</h1>
   <hr>
       <b>USD : </b>{{a | currency : 'USD':true : '3.3-3'}}
```

```
<b>USD : </b>{{a | currency : 'USD':false :'.3-3'}}
      <hr>
      <b>EURO : </b>{{b | currency : 'EURO':false}}
   <hr>
     <b>EURO : </b>{{b | currency : 'EURO':true}}
      <hr>
      <b>INR : </b>{{a | currency : 'INR':true}}
      <b>INR : </b>{{a | currency : 'INR':true : '4.4-4'}}
 </div>
</div>
<div class="jumbotron">
   <div class="container">
     <h1>Date Pipes</h1>
      <hr>
   <b>Today is: </b>{{today}}
   <hr>
      <b>Today is: </b>{{today | date}}
      <b>Today is: </b>{{today | date: 'dd/MM/yyyy'}}
   </div>
</div>
<div class="jumbotron">
 <div class="container">
      <h1>JSON Pipes</h1>
      <hr>
      <b>Without JSON Pipe: </b>{{object}}
      <hr>
 <b>With JSON Pipe: </b>{{object | json}}
```

```
</div>
</div>
<div class="jumbotron" style="background-color: yellow;">
   <div class="container">
       <h1>Custom Pipes</h1>
       <b>Original String </b>{{cust}}
       <b>Custom Pipe : </b>{{cust | changestring: '}}
       <hr>
      <b>Inbuilt & Custom Pipe : </b>{{cust | uppercase| changestring:'
'}}
      <hr>
 </div>
</div>
Pipes.component.ts:
import { Component, OnInit } from '@angular/core';
@Component({
selector: 'app-pipes',
 templateUrl: './pipes.component.html',
styleUrls: ['./pipes.component.css']
export class PipesComponent implements OnInit {
constructor() { }
ngOnInit(): void {
 name:string="JAVA FULL STACK TRAINING";
 pi: number=3.1415927;
 a=0.12345;
 b=9876.5432;
 today=new Date();
 object= {name:"Alex",email:"Alex@gmail.com",address:"Mumbai"};
 //custompipes
 cust:string="Welcome to the world of customPipes";
```

## **OUTPUT:**







