United College of Engineering and Research, Naini

Computer Science and Engineering Department

Unit 3
Compiler Design
Synatx Directed Translation

Prepared By Prabhat Shukla


SDT rule for Control Statements

 $S \rightarrow if E then S1$

 $S \rightarrow if E then S1 else S2$

 $S \rightarrow$ while E do S1

```
Write the 3AC for the expression
if(a>b)
      x=1;
1. if(a>b) goto (3)
2. goto(4)
3. x=1
4. exit
```



$S \rightarrow \text{if } E \text{ then } S_1$

```
E.true := newlabel;
```

$$E.false := S.next;$$

$$S_1.next := S.next;$$


$$S.code := E.code \mid\mid gen(E.true ':') \mid\mid S_1.code$$

Write the 3AC for the expression if(a>b) x=1;

else

$$x=0;$$

- 1. if(a>b) goto (4)
- 2. x=0
- 3. goto(5)
- 4. x=1
- 5. exit



$S \rightarrow \text{if } E \text{ then } S_1 \text{ else } S_2$

```
E.true : = newlabel;

E.false : = newlabel;

S_1.next := S.next;

S_2.next := S.next;

S.code : = E.code || gen(E.true ':') || S_1.code ||


gen('goto' S.next) ||

gen(E.false ':') || S_2.code
```

Write the 3AC for the expression

```
while(a>b) x=1
```

- 1. if a>b goto(3)
- 2. goto(4)
- 3. x=1
- 4. exit



$S \rightarrow$ while E do S_1

```
S.begin : = newlabel;

E.true : = newlabel;

E.false : = S.next;

S_1.next : = S.begin;

S.code : = gen(S.begin ':')|| E.code ||

gen(E.true ':') || S_1.code ||

gen('goto' S.begin)
```