UNIVERSITY
OF WOLLONGONG
IN DUBAI

Predicting Wave Energy Generation Using Machine Learning: A Data-Driven Approach for Renewable Energy Planning in the UAE

CSCI323 – Modern Artificial Intelligence
Winter 2026
University of Wollongong in Dubai

Group Members' Names:	Group Member IDs:
Abdulrahman Amir Alkhaiyat	7851455
Mohamed Rishan Mohamed Sathik	7433979
Amal Saeed Saidumuhammed	8961633
Varun Tulsiyani	8044661
Vidhi Chorera	8960008
Taha Imran	8916214
Abdulrahman Faisal Mohamed	7743038

1. Executive Summary

Renewable energy has become an important priority for many countries as they aim to reduce carbon emissions and develop sustainable power systems. In the United Arab Emirates, initiatives such as the **UAE Energy Strategy 2050** aim to increase the share of clean energy in the national energy mix and reduce dependence on fossil fuels (UAE Ministry of Energy and Infrastructure, 2020). As part of this transition, alternative renewable energy sources such as solar, wind, and marine energy are being explored to support long-term energy sustainability.

This project focuses on predicting the total electrical power generated by **wave energy converters (WECs)** placed in marine environments. Wave energy converters capture the kinetic energy of ocean waves and convert it into electricity. Accurately predicting the power output of these systems is important for energy planners because it can support more efficient wave farm design and improve renewable energy forecasting.

To address this problem, the project uses the **Wave Energy Converters dataset from the UCI Machine Learning Repository**, which contains measurements collected from wave farms located in four coastal regions: Adelaide, Perth, Sydney, and Tasmania (UCI Machine Learning Repository, 2019). Each location includes data from sixteen wave energy converters along with variables related to wave conditions and power generation. The objective of this study is to develop machine learning models capable of predicting the total power generated by these converters.

The project follows a structured data science workflow. The raw data first undergoes a data engineering stage that includes column renaming, feature engineering, distance-based feature generation, encoding of categorical variables, and train–test splitting. After preprocessing, exploratory data analysis (EDA) is conducted to understand data distributions and relationships between variables.

Several machine learning models are then implemented for the prediction task. Baseline models include **Ridge Regression, Lasso Regression, and Random Forest Regression**, which provide baseline results for comparison. In addition, more advanced models such as **Deep Neural Networks (DNN)** are implemented to capture more complex relationships within the dataset. Model performance is evaluated using regression metrics including **Root Mean Squared Error (RMSE)** and **Mean Absolute Error (MAE)**.

Although the dataset originates from Australian coastal environments, the modeling approach developed in this project can be applied to renewable energy planning in other regions, including the United Arab Emirates. Accurate prediction of wave energy output can support energy planning, improve wave farm design, and assist decision-makers in evaluating marine renewable energy investments.

2. Table of Contents

Contents

1. Executive Summary 2
2. Table of Contents 3
3. Introduction and Motivation 5
4. Literature Review 6
5. Technical Requirements and Analysis 8
5.1 Data Requirements 8
5.2 Data Processing Requirements 9
5.3 Computational Environment 9
5.4 Model Evaluation Requirements 10
5.5 Scalability and System Considerations 10
6. Solution Methodology and Implementation 11
6.1 Data Engineering 12
6.2 Exploratory Data Analysis (EDA) 13
6.3 Baseline Machine Learning Models 13
6.4 Advanced Machine Learning Models 15
6.5 Model Evaluation 15
6.6 System Workflow 15
7. Results and Evaluation 16
7.1 Evaluation Approach 17
7.2 Model Performance Comparison 17
7.3 Visual Analysis of Results 19
7.4 Comparative Discussion 21
7.5 Business Impact Assessment 21
7.6 Final Results Summary 21
8. Limitations, Challenges, and Constraints 22
8.1 Dataset Limitations 22
8.2 Data Quality and Preprocessing Challenges 22
8.3 Model Generalization Challenges 23
8.4 Computational and Time Constraints 23

8.5 Deployment Limitations 23
8.6 Ethical and Responsible AI Considerations 24
9. Conclusions and Discussion 24
10. Recommendations and Future Work 25
10.1 Deployment Recommendations 25
10.2 Dataset Expansion 26
10.3 Model Optimization 26
10.4 Converter Position Optimization 27
10.5 Integration with Renewable Energy Planning Systems 29
11. Code Repository 29
12. References 30

3. Introduction and Motivation

The global energy sector is undergoing a major transformation as countries seek sustainable and environmentally friendly alternatives to fossil fuels. Renewable energy technologies such as solar, wind, and marine energy are increasingly being adopted to reduce carbon emissions and improve long-term energy security (International Renewable Energy Agency, 2023). In the United Arab Emirates, the transition toward sustainable energy has become a national priority through initiatives such as the **UAE Energy Strategy 2050**, which aims to significantly increase the contribution of clean energy sources to the national energy mix (UAE Ministry of Energy and Infrastructure, 2020).

One of the leading organizations supporting renewable energy development in the UAE is **Masdar**, a company involved in large-scale renewable energy projects including solar and wind energy technologies. As renewable energy systems expand globally, there is growing interest in exploring additional sustainable energy sources that can complement existing infrastructure and improve energy diversification.

Among these emerging technologies, **wave energy** has attracted attention as a promising renewable resource. Wave energy converters (WECs) are devices designed to capture the energy generated by ocean waves and convert it into electricity. These systems are typically deployed in offshore environments where wave activity is strong and consistent. When multiple converters are deployed together, they form a **wave energy farm** capable of generating significant amounts of electrical power (Falnes, 2007).

However, accurately predicting the amount of electricity that can be produced by wave energy converters remains a major challenge. The total power generated by a wave farm depends on several environmental and operational factors, including wave height, ocean conditions, and the spatial positioning of the converters within the farm. Poor placement of converters or inaccurate forecasting of energy production can reduce efficiency and increase operational costs.

For organizations involved in renewable energy development, the ability to accurately predict energy generation is extremely valuable. Reliable predictions allow engineers and decision-makers to design more efficient wave farms, estimate expected energy output, and evaluate the potential feasibility of marine energy investments. This is particularly important for emerging renewable technologies where operational data is still limited.

Artificial Intelligence (AI) and machine learning techniques provide powerful tools for solving complex prediction problems in the energy sector. Machine learning models can analyze large volumes of historical data and identify patterns that traditional analytical methods may not detect. By learning the relationship between environmental conditions

and energy output, these models can produce accurate predictions of future power generation (LeCun, Bengio and Hinton, 2015).

In this project, machine learning techniques are applied to predict the total electrical power generated by wave energy converters deployed in offshore environments. The study uses the **Wave Energy Converters dataset from the UCI Machine Learning Repository**, which contains operational data collected from wave farms located in four coastal regions: Adelaide, Perth, Sydney, and Tasmania (UCI Machine Learning Repository, 2019). Each dataset includes measurements related to wave conditions and power output from sixteen wave energy converters operating simultaneously.

Although the dataset originates from coastal regions in Australia, the predictive modeling approach developed in this project can be applied to renewable energy planning in other regions, including the United Arab Emirates. By developing models capable of estimating power generation from wave energy converters, energy planners can gain insights that support the design and optimization of future marine energy systems.

The objective of this project is therefore to develop and evaluate machine learning models capable of predicting the total power output generated by a group of wave energy converters. To achieve this objective, the project follows a structured data science workflow that includes data preprocessing, exploratory data analysis, model development, and performance evaluation.

Through this work, the study demonstrates how artificial intelligence techniques can be applied to renewable energy forecasting and highlights the role of data-driven methods in supporting sustainable energy development.

4. Literature Review

Renewable energy forecasting has become an important research area due to the increasing integration of renewable energy sources into modern power systems. Accurate prediction of renewable energy output allows engineers and planners to improve system efficiency, optimize resource allocation, and reduce operational risks. Among the different renewable technologies, marine energy systems such as wave energy converters have attracted growing attention because of their potential to generate electricity from ocean waves.

Wave energy converters (WECs) are devices designed to capture the kinetic and potential energy of ocean waves and convert it into electrical power. However, the amount of power produced by these systems is influenced by several environmental and operational factors, including wave height, wave period, water depth, and the spatial arrangement of converters within a wave farm. Due to these complex interactions, predicting the total energy output of a wave farm remains a challenging problem that requires advanced analytical methods.

Traditional approaches for estimating wave energy production have often relied on physical modeling techniques. These models are based on mathematical equations that describe

wave behavior and hydrodynamic interactions between devices. While physical models can provide useful insights into wave dynamics, they often require significant computational resources and may struggle to capture the full variability of real ocean environments (Falnes, 2007).

In recent years, machine learning methods have increasingly been applied to renewable energy prediction tasks. Machine learning algorithms are capable of identifying patterns in large datasets and learning relationships between input variables and target outputs without explicitly relying on physical equations. This data-driven approach is particularly useful for complex systems where multiple interacting variables influence energy generation.

Several studies have demonstrated the effectiveness of machine learning techniques for renewable energy forecasting. Algorithms such as Random Forest and Support Vector Regression have been successfully applied to prediction tasks in solar, wind, and marine energy systems (Zhang et al., 2018). These models are capable of handling nonlinear relationships and complex feature interactions within datasets.

Random Forest is a widely used ensemble learning method that combines multiple decision trees to improve prediction accuracy and reduce overfitting. It has been shown to perform well in many regression tasks due to its robustness and ability to capture nonlinear relationships in data (Breiman, 2001).

Support Vector Regression is another powerful machine learning technique that can model complex relationships by transforming input data into higher-dimensional feature spaces. This approach allows the model to identify patterns in data even when relationships between variables are highly nonlinear (Smola and Schölkopf, 2004).

In addition to classical machine learning techniques, deep learning methods have also become increasingly popular in energy forecasting applications. Deep Neural Networks (DNNs) consist of multiple layers of interconnected neurons that learn hierarchical representations of data. These models can capture highly nonlinear relationships between input variables and prediction targets, making them suitable for complex prediction tasks (LeCun, Bengio and Hinton, 2015).

Because wave energy production depends on multiple interacting environmental factors, combining different machine learning approaches provides an effective strategy for exploring prediction capabilities. Linear regression models with regularization, ensemble learning algorithms such as Random Forest, and deep neural networks each offer different advantages for modeling complex energy datasets.

The literature therefore suggests that machine learning and deep learning methods provide promising tools for predicting renewable energy production. By applying these techniques to wave energy converter datasets, researchers and energy planners can develop predictive models that support improved decision-making in renewable energy deployment and system optimization.

5. Technical Requirements and Analysis

Developing a predictive system for wave energy production requires several technical components, including appropriate datasets, computational tools, and machine learning frameworks. This section describes the technical requirements necessary for implementing the proposed solution and outlines the structure of the dataset used in the project.

5.1 Data Requirements

Accurate prediction of energy output from wave energy converters requires historical data describing the operational behavior of the converters. For this project, the **Wave Energy Converters dataset obtained from the UCI Machine Learning Repository** is used as the primary data source (UCI Machine Learning Repository, 2019). The dataset contains operational information from wave energy converters located in four coastal regions: Adelaide, Perth, Sydney, and Tasmania.

Each dataset represents measurements collected from sixteen wave energy converters operating simultaneously within a wave farm configuration. The dataset includes variables describing the spatial position of the converters as well as the power generated by each device. The main prediction target in this project is the **total power produced by the wave farm (Powerall)**, which represents the combined energy generated by all converters.

Although the dataset originates from Australian coastal environments, it provides realistic operational data that can be used to model wave energy production systems. The predictive modeling approach developed in this project can therefore support renewable energy planning scenarios in other regions, including the United Arab Emirates, where marine renewable energy may become an area of future interest.

The dataset is provided in the form of four separate CSV files, each corresponding to one of the coastal regions. These datasets are processed and prepared before being used for machine learning modeling.

Table 1: Summary of the Wave Energy Converter Dataset:

Attribute	Description
Dataset Name	Wave Energy Converters Dataset
Source	UCI Machine Learning Repository
Type of Problem	Regression
Prediction Target	Total power generated by wave energy converters (Powerall)
Data Format	CSV files
Number of Locations	4 coastal regions (Adelaide, Perth, Sydney, Tasmania)

Number of Converters	16 wave energy converters per location
Data Type	Numerical variables describing converter positions and power output
Dataset Usage	Used to train machine learning models for predicting total wave energy output
Programming Environment	Python with libraries such as Pandas, NumPy, and Scikit-learn

5.2 Data Processing Requirements

Before machine learning models can be trained, the raw datasets must undergo several preprocessing steps. These steps ensure that the data is consistent, reliable, and suitable for predictive modeling.

The preprocessing stage includes several operations performed during the data engineering process:

- Renaming dataset columns to provide consistent and interpretable variable names
- Creating additional features such as **distance-based measurements between wave energy converters**
- Applying categorical encoding where necessary
- Scaling numerical features using standardization techniques
- Splitting the dataset into **training and testing subsets** for model evaluation

These preprocessing steps help ensure that the dataset is properly structured for machine learning algorithms and that the models can learn meaningful relationships between input variables and power output.

5.3 Computational Environment

The implementation of the machine learning models is carried out using the **Python programming language**. Python has become one of the most widely used programming languages in data science and machine learning due to its extensive ecosystem of libraries and development tools.

Several Python libraries are used throughout the project, including:

- **Pandas** for data manipulation and preprocessing
- **NumPy** for numerical computations and array operations

- **Scikit-learn** for implementing machine learning algorithms and model evaluation
- **Matplotlib and Seaborn** for data visualization and exploratory data analysis

These tools provide efficient capabilities for handling datasets, implementing machine learning models, and analyzing relationships between variables.

5.4 Model Evaluation Requirements

Since the objective of the project is to predict a continuous numerical value (total power generation), the problem is treated as a regression task. Appropriate evaluation metrics must therefore be selected to measure the performance of the prediction models.

The primary evaluation metrics used in this project include:

• **Root Mean Squared Error (RMSE)** – measures the square root of the average squared difference between predicted and actual values

• **Mean Absolute Error (MAE)** – measures the average magnitude of prediction errors

These metrics are widely used in regression problems because they provide clear indications of prediction accuracy and model reliability.

To ensure reliable evaluation results, cross-validation techniques will also be applied during model training. Cross-validation allows models to be tested on multiple subsets of the dataset, reducing the risk of overfitting and providing a more robust estimate of model performance.

5.5 Scalability and System Considerations

Although this project focuses on predictive modeling using an existing dataset, the developed approach can potentially be applied to real-world wave energy systems. In practical scenarios, predictive models could be integrated into energy management platforms used by renewable energy companies to estimate expected power production and support decision-making in wave farm design.

From a scalability perspective, the machine learning models implemented in this project are capable of handling larger datasets and additional features if more operational data becomes available in the future. This makes the system adaptable for real-world deployment scenarios where energy systems continuously generate new data.

6. Solution Methodology and Implementation

This section describes the methodology used to develop machine learning models capable of predicting the total power generated by wave energy converters. The overall approach follows a structured data science pipeline that includes data engineering, exploratory data analysis, model development, and model evaluation.

The objective of the proposed solution is to build predictive models that estimate the total power generated by wave energy converters placed in the sea using historical operational data from wave farms. Since the prediction target is a continuous variable representing total power output, the problem is treated as a **regression task**.

The implementation was carried out using the **Python programming language** together with widely used data science libraries such as **Pandas, NumPy, Scikit-learn, Matplotlib, and Seaborn**.

The overall system architecture used in this project is illustrated in **Figure 1**.



6.1 Data Engineering

The first step in the proposed methodology involved preparing the dataset for machine learning analysis. The dataset used in this project consists of four CSV files representing wave energy converter data collected from different coastal regions: **Adelaide, Perth, Sydney, and Tasmania**. Before the data could be used for model training, several preprocessing and feature engineering steps were applied to ensure that the dataset was structured and suitable for machine learning algorithms.

Column Renaming

To improve readability and consistency, the dataset columns were renamed using a structured naming convention. The variables representing the positions of wave energy converters were labeled using sequential coordinate identifiers. The first set of variables represents the **x-coordinates of the converters (x1–x16)**, while the second set represents the **y-coordinates (y1–y16)**. Additional variables correspond to individual converter power outputs, while the final variable represents the **total power generated by the wave farm**, which is used as the prediction target.

Dataset Integration and Location Labeling

Since the dataset contains measurements from four different coastal locations, each dataset was processed separately. Machine learning models were trained independently for each location in order to capture potential regional differences in wave behavior and energy production. During this process, a categorical feature named **location** was introduced to indicate the geographic origin of each observation.

Including the location variable allows the models to capture potential differences in wave behavior across different coastal environments.

Distance-Based Feature Engineering

To capture spatial relationships between converters, additional features were created using the coordinates of the wave energy devices. The **Euclidean distance between converters** was calculated based on their x and y positions. These distance-based features represent the spacing between converters and may influence energy generation due to interactions between machines.

Categorical Encoding

The **location** variable is categorical and therefore must be converted into numerical form before being used by machine learning algorithms. Two encoding approaches were used:

- **One-Hot Encoding**, which represents each location as a binary feature
- **Ordinal Encoding**, which assigns numerical values to categorical labels when appropriate

These transformations allow machine learning models to incorporate geographic information during training.

Feature Scaling

Many machine learning algorithms perform better when numerical features operate on similar scales. Therefore, **standard scaling** was applied using the **StandardScaler** method to normalize the dataset.

Train–Test Split

After preprocessing, the dataset was divided into **training and testing subsets** using a train-test split approach. The training dataset was used to train the models, while the testing dataset was used to evaluate model performance on unseen data.

Preprocessing Pipeline

To ensure consistent preprocessing across different models, the data preparation steps were implemented using a **Scikit-learn preprocessing pipeline**. The pipeline integrates multiple transformations such as encoding and scaling into a single workflow, ensuring that the same preprocessing steps are applied during both training and evaluation.

6.2 Exploratory Data Analysis (EDA)

Exploratory Data Analysis (EDA) was conducted to better understand the dataset and identify patterns that could influence model performance.

EDA helps researchers gain insights into the structure and distribution of the data before building predictive models. It also helps detect anomalies or unusual observations that may affect model accuracy.

The exploratory analysis included:

- Visualizing the distribution of total power output values
- Analyzing correlations between features and the power generation target
- Identifying potential outliers within the dataset
- Comparing feature distributions across different coastal locations

Data visualization techniques such as **histograms, scatter plots, and correlation heatmaps** were used to reveal relationships between variables.

6.3 Baseline Machine Learning Models

To establish benchmark results for the prediction task, several baseline machine learning models were implemented. These models provide an initial comparison for evaluating different regression approaches.

The baseline models used in this study include:

- **Ridge Regression**
- **Lasso Regression**
- **Random Forest Regression**

Ridge Regression and Lasso Regression are linear regression models that incorporate regularization techniques to reduce overfitting and improve model generalization.

- **Ridge Regression** applies L2 regularization, which penalizes large coefficients.
- **Lasso Regression** applies L1 regularization, which can shrink some coefficients to zero and perform implicit feature selection.

In addition to linear models, **Random Forest Regression** was implemented as a tree-based ensemble learning method. Random Forest combines predictions from multiple decision trees to improve prediction accuracy and capture nonlinear relationships within the dataset.

Hyperparameter Tuning

Hyperparameter tuning was performed using **GridSearchCV** to identify optimal parameter settings for the models.

For Ridge and Lasso Regression, the **alpha** parameter was tuned across several values. For Random Forest, parameters such as the **number of trees** and **maximum tree depth** were explored.

Cross-Validation

To ensure reliable evaluation, **cross-validation** was used during model training. Cross-validation divides the dataset into multiple folds and evaluates the model on different subsets to obtain a more robust estimate of performance.

Error Analysis

Residual analysis was performed to examine prediction errors. Residual plots were used to visualize the distribution of errors and determine whether the models were making systematic prediction mistakes.

Feature Importance Analysis

For the Random Forest model, **feature importance analysis** was conducted to identify which variables contribute most strongly to predicting total power generation.

The baseline models were trained and evaluated separately for each coastal location in

order to capture potential differences in wave conditions and converter behavior between regions.

6.4 Advanced Machine Learning Models

In addition to the baseline regression models, an advanced machine learning model was implemented to explore whether deep learning techniques could improve prediction performance.

Deep Neural Network (DNN)

A **Deep Neural Network (DNN)** model was developed to learn complex nonlinear relationships between input features and the target variable. Neural networks consist of multiple layers of interconnected neurons that transform input data through nonlinear activation functions.

The implemented architecture includes:

- An **input layer** receiving the processed dataset features
- One or more **hidden layers** responsible for learning feature interactions
- An **output layer** that produces the predicted total power output

Deep learning models can capture complex patterns in data and may outperform traditional models when sufficient training data is available.

Unlike the baseline models, the deep neural network model was trained using the combined dataset in order to learn more general patterns across all locations.

6.5 Model Evaluation

The performance of the prediction models was evaluated using regression metrics.

Since the task involves predicting a continuous value, the following evaluation metrics were used:

- **Root Mean Squared Error (RMSE)** – measures the square root of the average squared difference between predicted and actual values
- **Mean Absolute Error (MAE)** – measures the average magnitude of prediction errors

Lower RMSE and MAE values indicate better prediction accuracy.

6.6 System Workflow

The overall workflow of the proposed system is summarized in **Figure 2**.



The workflow illustrates the main stages of the machine learning pipeline, beginning with dataset preprocessing and ending with model evaluation and prediction generation. This structured pipeline ensures that the machine learning process remains organized, reproducible, and suitable for future improvements.

7. Results and Evaluation

This section evaluates the performance of the machine learning models developed in this project. The goal of the evaluation is to compare the ability of different regression models to accurately predict the total power generated by wave energy converters.

Since the prediction task involves estimating a continuous numerical value, the problem is treated as a **regression problem**. The performance of the models was evaluated using two commonly used regression metrics:

- **Root Mean Squared Error (RMSE)**, which measures the square root of the average squared difference between predicted and actual values.

- **Mean Absolute Error (MAE)**, which measures the average absolute difference between predicted and actual values.

Lower RMSE and MAE values indicate better prediction accuracy.

7.1 Evaluation Approach

The prediction task in this project focuses on estimating the total power output generated by multiple wave energy converters operating within a wave farm. Because the target variable **Powerall** represents a continuous numerical value, regression evaluation metrics were selected to measure model performance.

The evaluation metrics used in this study include:

Root Mean Squared Error (RMSE)
RMSE measures the square root of the average squared difference between predicted and actual values. This metric penalizes larger prediction errors more strongly, making it useful for evaluating the reliability of predictive models.

Mean Absolute Error (MAE)
MAE measures the average absolute difference between predicted and actual values. It provides a direct interpretation of the average prediction error.

These metrics are widely used in regression problems and provide a clear indication of how accurately the models predict total wave energy generation.

To ensure reliable results during model development, **cross-validation techniques** were also applied. Cross-validation reduces the risk of overfitting by evaluating the models on multiple subsets of the dataset.

7.2 Model Performance Comparison

The developed models were evaluated after completing training and hyperparameter tuning. The objective of this comparison is to determine which model provides the most accurate prediction of total wave energy generation.

The evaluated models include:

- Ridge Regression
- Lasso Regression
- Random Forest Regression
- Deep Neural Network (DNN)

The baseline regression models were trained separately for each coastal location to capture potential differences in wave conditions and converter behavior. The deep neural network

model was trained using the combined dataset to learn broader patterns across all locations.

Table 2: Model Performance Across Locations

Model	Location / Scope	RMSE	MAE
Ridge Regression	Adelaide	26.3345	5.9121
Ridge Regression	Perth	0.0076	0.0060
Ridge Regression	Sydney	18.2791	1.9107
Ridge Regression	Tasmania	73.0631	10.7621
Lasso Regression	Adelaide	25.8871	1.9983
Lasso Regression	Perth	2.2485	1.7534
Lasso Regression	Sydney	2.2485	1.7534
Lasso Regression	Tasmania	72.4515	5.1389
Random Forest	Adelaide	23588.4105	16661.9144
Random Forest	Perth	24151.2748	17424.5593
Random Forest	Sydney	8460.7665	5030.6062
Random Forest	Tasmania	60076.8928	44409.1595
Deep Neural Network	Combined advanced model	44047.5391	34113.7734

Table 2 summarizes the performance of the implemented machine learning models across the four coastal datasets. The results provide an overview of how different modeling approaches perform when predicting total wave energy generation.

The results indicate that **Ridge Regression achieved the lowest prediction errors overall**, demonstrating strong performance in modeling the relationship between converter positions and total power generation. Lasso Regression produced similar results but showed slightly higher errors in some locations.

In contrast, the **Random Forest model produced significantly larger prediction errors**, suggesting that the tree-based model struggled to capture the structure of the dataset

effectively. The deep neural network model showed moderate performance but did not outperform the simpler regression models.

7.3 Visual Analysis of Results

Visual analysis was performed to better understand the behavior of the dataset and the performance of the predictive models.

Figure 3: Distribution of Total Power Output (Powerall)
This figure shows the distribution of the target variable. It helps determine whether the power output values are balanced, skewed, or affected by outliers.



Figure 4: Actual vs Predicted Values for Best Model
This graph compares the predicted power values with the actual values for the best-performing model. Close alignment between predicted and actual values indicates good model performance.



Figure 5: Feature vs Total Power Scatter Plot
This scatter plot shows an example relationship between one of the converter-related features and the total power output.



The visualizations used in this section were generated directly from the project notebooks using data visualization libraries such as Matplotlib and Seaborn.

7.4 Comparative Discussion

The comparison of the evaluated models shows that **Ridge Regression produced the most accurate predictions for total wave energy generation** based on RMSE and MAE values.

One possible explanation for this result is that the dataset contains strong linear relationships between the spatial positions of wave energy converters and the total generated power. Linear regression models with regularization are well suited for capturing such relationships while controlling model complexity.

On the other hand, the Random Forest model produced much larger prediction errors. This may indicate that the tree-based model struggled to generalize effectively across the dataset or was more sensitive to variations between the coastal datasets.

The comparison highlights the importance of testing multiple machine learning techniques when solving prediction problems, as different models may perform better depending on the structure of the data.

7.5 Business Impact Assessment

The practical value of the developed predictive system can also be considered from a renewable energy planning perspective.

Although the dataset originates from Australian coastal environments, the developed predictive modeling approach can still serve as a useful decision-support tool for marine energy planning in other regions, including the United Arab Emirates.

Accurate prediction of wave energy generation can help organizations:

- estimate expected energy production before deploying wave farms
- improve converter placement and wave farm design
- reduce uncertainty in renewable energy investment decisions
- support long-term planning of marine energy systems

Predictive models such as those developed in this project can therefore contribute to more efficient renewable energy planning and improved decision-making in sustainable energy projects.

7.6 Final Results Summary

Overall, the results demonstrate that machine learning methods can effectively predict total wave energy output using converter position data.

Among the evaluated models, **Ridge Regression achieved the strongest performance based on RMSE and MAE values across the evaluated datasets**. These findings highlight the potential of machine learning approaches for renewable energy forecasting and

demonstrate how data-driven models can support the planning and optimization of marine energy systems.

8. Limitations, Challenges, and Constraints

While the proposed machine learning approach provides a structured method for predicting wave energy production, several limitations and challenges must be acknowledged. Recognizing these limitations is important for understanding the scope of the project and identifying areas where improvements can be made in future work.

8.1 Dataset Limitations

One of the primary limitations of this project is the availability of suitable datasets. The Wave Energy Converters dataset used in this study originates from coastal environments in Australia, specifically Adelaide, Perth, Sydney, and Tasmania. Although this dataset contains realistic operational measurements from wave energy converters, it does not represent the specific environmental conditions of the United Arab Emirates (UCI Machine Learning Repository, 2019).

Ocean wave behavior can vary significantly across geographic regions due to differences in water depth, wind patterns, and coastal geography. As a result, the dataset may not fully capture the wave characteristics that would be observed in UAE coastal waters. Therefore, while the developed prediction models demonstrate the feasibility of machine learning for wave energy forecasting, further validation using UAE-specific data would be required before applying the models in real-world deployment scenarios.

Despite this limitation, the dataset still provides valuable information for studying the relationship between wave conditions and energy production. Using publicly available datasets is also a common approach in early-stage research and prototype development for renewable energy prediction models.

8.2 Data Quality and Preprocessing Challenges

Working with real-world datasets often involves data quality challenges that must be addressed during the preprocessing stage. During the data engineering process, the raw datasets required careful preparation before they could be used for machine learning.

Potential challenges included:

- inconsistencies in dataset structure
- handling missing or incomplete data entries
- ensuring correct formatting of numerical variables
- managing datasets collected from multiple geographic locations

These preprocessing tasks are necessary to ensure that the machine learning models receive reliable and consistent input data. Improper preprocessing could lead to incorrect model training or misleading predictions.

8.3 Model Generalization Challenges

Another challenge in machine learning projects is ensuring that models generalize well to unseen data. Machine learning algorithms can sometimes perform well on training data but fail to maintain the same level of accuracy when applied to new data.

To reduce this risk, techniques such as train–test splitting and cross-validation were used during model training. However, the ability of the models to generalize to completely different ocean environments remains uncertain without additional datasets collected from other geographic regions.

In real-world renewable energy applications, machine learning models are typically trained using long-term historical data collected directly from the deployment location. Such datasets allow the models to learn patterns specific to the operational environment.

8.4 Computational and Time Constraints

Like many academic projects, this study was conducted within limited time and computational resources. These constraints may affect the extent to which model architectures can be optimized or evaluated.

For example, deep learning models often require extensive experimentation with different architectures, training parameters, and optimization strategies in order to achieve optimal performance. Due to project time limitations, only a limited set of configurations could be explored during experimentation.

Similarly, testing additional machine learning algorithms or performing more extensive hyperparameter searches could potentially improve model performance but would require additional computational resources and development time.

8.5 Deployment Limitations

The current implementation focuses on predictive modeling using historical datasets rather than real-time system deployment. In a real-world environment, the prediction models would likely need to be integrated into energy management platforms or monitoring systems used by renewable energy companies.

Such deployment would require additional components, including:

- real-time data collection from ocean sensors
- automated model monitoring and updating
- integration with operational energy management systems
- scalable cloud-based computing infrastructure

These aspects are beyond the scope of the current project but represent important considerations for future practical implementations.

8.6 Ethical and Responsible AI Considerations

Although this project focuses primarily on energy prediction rather than sensitive personal data, responsible AI practices should still be considered. Machine learning models should be developed with transparency, reproducibility, and proper documentation.

For example, clearly documenting datasets, preprocessing steps, and modeling decisions improves transparency and reproducibility of the research process. Additionally, openly reporting model limitations helps stakeholders understand the appropriate conditions for using predictive systems.

Responsible AI practices are increasingly emphasized in modern AI research to ensure that technological solutions are implemented safely and ethically (Floridi et al., 2018).

9. Conclusions and Discussion

This project explored the use of artificial intelligence and machine learning techniques to predict the total power generated by wave energy converters deployed in marine environments. Predicting renewable energy production is an important challenge in the energy sector because accurate forecasting can support better planning, infrastructure design, and investment decisions.

The main objective of the project was to develop predictive models capable of estimating the total power output generated by multiple wave energy converters using historical operational data. To achieve this objective, a structured data science workflow was implemented that included data engineering, exploratory data analysis, machine learning model development, and model evaluation.

During the data engineering stage, the raw datasets from four coastal locations were cleaned and prepared for analysis. The datasets were processed individually so that the machine learning models could capture potential differences in wave behavior across the different coastal environments. Feature engineering and normalization were applied to improve data quality and support effective model training.

Exploratory data analysis played an important role in understanding the structure of the dataset and identifying relationships between variables. Visualization techniques helped reveal patterns in the data and provided insights into how different features may influence total power generation. This step also helped detect potential outliers and variations across the different coastal environments represented in the dataset.

Several machine learning models were implemented to address the regression task of predicting total wave energy output. These models included Ridge Regression, Lasso Regression, Random Forest Regression, and a Deep Neural Network model. Each model

represents a different machine learning approach, ranging from regularized linear regression to ensemble learning and deep learning techniques.

The models were evaluated using commonly used regression metrics, including Root Mean Squared Error (RMSE) and Mean Absolute Error (MAE). These metrics provide a clear and consistent way to measure prediction accuracy and compare model performance.

Based on the experimental results, Ridge Regression achieved the strongest overall performance across the evaluated datasets. This result suggests that the relationship between converter position features and total power generation can be effectively captured using a regularized linear regression model. More complex models such as Random Forest and Deep Neural Networks did not outperform the simpler linear model in this case, possibly due to the structure and size of the dataset.

From a broader perspective, this project demonstrates the potential of data-driven approaches in renewable energy forecasting. Machine learning techniques can help analyze complex environmental datasets and identify patterns that may be difficult to capture using traditional analytical methods. As renewable energy systems continue to generate larger amounts of operational data, such techniques will likely play an increasingly important role in energy management and system optimization.

Although the dataset used in this project originates from Australian coastal environments, the methodology developed in this study can be applied to other regions as well. For example, organizations involved in renewable energy development in the United Arab Emirates could use similar predictive modeling approaches to evaluate the feasibility of marine energy projects or improve forecasting accuracy for offshore renewable systems.

Overall, the project highlights how artificial intelligence can contribute to sustainable energy development by supporting more accurate forecasting and more efficient planning of renewable energy systems.

10. Recommendations and Future Work

While the predictive models developed in this project demonstrate the potential of machine learning for forecasting wave energy production, several opportunities exist for improving and extending the system in future work. These improvements could enhance prediction accuracy, expand the scope of the solution, and support real-world deployment scenarios.

10.1 Deployment Recommendations

For organizations interested in applying predictive models to renewable energy planning, several practical steps would be required to implement the system in a real operational environment.

First, reliable data collection systems would need to be established. In a real wave energy farm, sensors would continuously collect environmental and operational data such as wave

height, wave direction, and machine performance indicators. These measurements would then be stored in a centralized data management system.

Second, the predictive model would need to be integrated into an operational platform capable of processing new data in real time. Such a system could be deployed using cloud-based infrastructure, which allows scalable data processing and automated model updates.

Third, monitoring mechanisms should be implemented to track model performance over time. As new data becomes available, the model may need to be retrained periodically to maintain high prediction accuracy. Continuous monitoring also helps detect changes in environmental conditions that could affect energy production patterns.

If implemented successfully, such a system could assist renewable energy companies in estimating expected energy production, planning infrastructure investments, and improving operational decision-making.

10.2 Dataset Expansion

One of the most important improvements for future work would be the availability of more diverse datasets. Although the dataset used in this project provides valuable information about wave energy converter performance, it is limited to coastal environments in Australia.

Future research could benefit from collecting datasets from additional geographic regions, including the Middle East and the Arabian Gulf. Having access to region-specific datasets would allow machine learning models to better capture environmental conditions relevant to local wave patterns.

Expanding the dataset would also improve the robustness of predictive models by allowing them to learn from a wider range of wave behaviors and environmental scenarios.

10.3 Model Optimization

Another area for future improvement involves further optimization of machine learning models. While the current project explored several machine learning approaches, including regularized regression models, ensemble learning methods, and deep neural networks, additional experimentation could further improve model performance.

Future work could explore:

- more advanced neural network architectures
- automated hyperparameter optimization techniques
- ensemble learning strategies that combine predictions from multiple models

These improvements may increase prediction accuracy and help identify modeling approaches that perform best for wave energy forecasting.

10.4 Converter Position Optimization

In addition to predicting energy output, future research could explore optimization techniques to improve the placement of wave energy converters within a wave farm. One possible approach is the use of **Genetic Algorithms**, which are optimization methods inspired by natural selection and evolutionary processes.

In this approach, the spatial positions of the converters are adjusted to identify layouts that maximize the predicted total power output. The optimization process evaluates multiple candidate layouts and gradually improves them across generations using evolutionary operations such as selection, crossover, and mutation.

The conceptual framework for integrating prediction models with optimization algorithms is illustrated in **Figure 6**.



Figure 7: Genetic Algorithm Convergence

The figure shows the improvement in predicted power output across generations during the optimization process.



Figure 8: Optimized Wave Energy Converter Layout
The figure shows the spatial arrangement of the wave energy converters obtained from the Genetic Algorithm optimization process.



Integrating machine learning prediction models with optimization algorithms can create a decision-support system capable of both forecasting energy production and recommending improved converter placement strategies.

10.5 Integration with Renewable Energy Planning Systems

Another important direction for future work is the integration of predictive models into broader renewable energy planning systems. Renewable energy infrastructure often involves multiple energy sources such as solar, wind, and marine energy.

By combining predictive models for different energy sources, energy planners could develop more comprehensive forecasting systems capable of estimating overall renewable energy production across multiple technologies.

Such systems could help governments and energy companies plan energy distribution strategies, improve grid stability, and support the transition toward sustainable energy systems.

11. Code Repository

The implementation of the machine learning models, data preprocessing procedures, and optimization algorithms used in this project is available in the project code repository.

Code repository:
https://github.com/Varun-Tulsiyani/CSCI323-Project

The repository contains:

- data preprocessing scripts
- baseline machine learning models
- deep learning implementation
- genetic algorithm optimization code
- visualization scripts used to generate figures in this report.

12. References

- Breiman, L. (2001) 'Random forests', *Machine Learning*, 45(1).
- Chai, T. and Draxler, R.R. (2014) 'Root mean square error (RMSE) or mean absolute error (MAE)? Arguments against avoiding RMSE in the literature', *Geoscientific Model Development*, 7(3).
- Falnes, J. (2007) 'A review of wave-energy extraction', *Marine Structures*, 20(4).
- Floridi, L. et al. (2018) 'AI4People—An ethical framework for a good AI society', *Minds and Machines*, 28(4).
- Goldberg, D.E. (1989) *Genetic Algorithms in Search, Optimization and Machine Learning*. Boston: Addison-Wesley.
- IRENA (2023) *Renewable Energy Market Analysis: GCC Region*. International Renewable Energy Agency.
- LeCun, Y., Bengio, Y. and Hinton, G. (2015) 'Deep learning', *Nature*, 521(7553).
- Pedregosa, F. et al. (2011) 'Scikit-learn: Machine learning in Python', *Journal of Machine Learning Research*, 12.
- UAE Ministry of Energy and Infrastructure (2020) *UAE Energy Strategy 2050*. Abu Dhabi: Government of the United Arab Emirates.
- UCI Machine Learning Repository (2019) *Wave Energy Converters Dataset*. Available at: https://archive.ics.uci.edu/dataset/494/wave+energy+converters (Accessed: 2026).
- Willmott, C.J. and Matsuura, K. (2005) 'Advantages of the mean absolute error (MAE) over the root mean square error (RMSE) in assessing average model performance', *Climate Research*, 30(1).
- Zhang, Y., Beaudin, M., Taheri, R., Zareipour, H. and Wood, D. (2018) 'Day-ahead power output forecasting for wind farms using machine learning techniques', *Energy*, 162.