

# Unit 2

SVM,Types, Problems,Kernel functions

# Support Vector Machine – Introduction




- Support Vector Machine or SVM is one of the most popular Supervised Learning algorithms, which is used for Classification as well as Regression problems.
- However, primarily, it is used for Classification problems in Machine Learning.
- The goal of the SVM algorithm is to create the best line or decision boundary that can segregate n-dimensional space into classes so that we can easily put the new data point in the correct category in the future.
- This best decision boundary is called a hyperplane.

# Support Vector Machine – Hyperplane



- There can be multiple lines/decision boundaries to segregate the classes in n-dimensional space, but we need to find out the best decision boundary that helps to classify the data points.
- This best boundary is known as the hyperplane of SVM.



## Support Vector Machine – Hyperplane

- The dimensions of the hyperplane depend on the features present in the dataset, which means if there are 2 features (as shown in image), then hyperplane will be a straight line.
- And if there are 3 features, then hyperplane will be a 2-dimension plane.
- We always create a hyperplane that has a maximum margin, which means the maximum distance between the data points.

# Support Vector Machine – Types of SVM





**SVM can be of two types:**

- 1. Linear SVM:** Linear SVM is used for linearly separable data, which means if a dataset can be classified into two classes by using a single straight line, then such data is termed as linearly separable data, and classifier is used called as Linear SVM classifier.
- 2. Non-linear SVM:** Non-Linear SVM is used for non-linearly separated data, which means if a dataset cannot be classified by using a straight line, then such data is termed as non-linear data and classifier used is called as Non-linear SVM classifier.

# Support Vector Machine – Types of SVM



- Linear SVM:




# Support Vector Machine – Types of SVM



- Linear SVM:



## Support Vector Machine – Types of SVM



$$\max \frac{2}{\|\vec{w}\|}$$

s.t.

$$(w \cdot x + b) \geq 1, \forall x \text{ of class 1}$$


$$(w \cdot x + b) \leq -1, \forall x \text{ of class 2}$$




# Support Vector Machine – Types of SVM



- Non-Linear SVM:
- If data is linearly arranged, then we can separate it by using a straight line, but for non-linear data, we cannot draw a single straight line.
- So to separate these data points, we need to add one more dimension.
- For linear data, we have used two dimensions x and y, so for non-linear data, we will add a third dimension z.
- It can be calculated as:  $z = x^2 + y^2$  ✓



## Support Vector Machine – Types of SVM




# Example on Linear SVM


Suppose we are given the following positively labeled data points,

$$\left\{ \begin{pmatrix} 3 \\ 1 \end{pmatrix}, \begin{pmatrix} 3 \\ -1 \end{pmatrix}, \begin{pmatrix} 6 \\ 1 \end{pmatrix}, \begin{pmatrix} 6 \\ -1 \end{pmatrix} \right\}$$

and the following negatively labeled data points,

$$\left\{ \begin{pmatrix} 1 \\ 0 \end{pmatrix}, \begin{pmatrix} 0 \\ 1 \end{pmatrix}, \begin{pmatrix} 0 \\ -1 \end{pmatrix}, \begin{pmatrix} -1 \\ 0 \end{pmatrix} \right\}$$





# Support Vector Machine - Linear Example Solved

- Each vector is augmented with a 1 as a bias input

- So,  $s_1 = \begin{pmatrix} 1 \\ 0 \end{pmatrix}$ , then  $\tilde{s}_1 = \begin{pmatrix} 1 \\ 0 \\ 1 \end{pmatrix}$

- Similarly,

- $s_2 = \begin{pmatrix} 3 \\ 1 \end{pmatrix}$ , then  $\tilde{s}_2 = \begin{pmatrix} 3 \\ 1 \\ 1 \end{pmatrix}$  and  $s_3 = \begin{pmatrix} 3 \\ -1 \end{pmatrix}$ , then  $\tilde{s}_3 = \begin{pmatrix} 3 \\ -1 \\ 1 \end{pmatrix}$

## Support Vector Machine - Linear Example Solved

$$\alpha_1 \tilde{s}_1 \cdot \tilde{s}_1 + \alpha_2 \tilde{s}_2 \cdot \tilde{s}_1 + \alpha_3 \tilde{s}_3 \cdot \tilde{s}_1 = -1$$

$$\alpha_1 \tilde{s}_1 \cdot \tilde{s}_2 + \alpha_2 \tilde{s}_2 \cdot \tilde{s}_2 + \alpha_3 \tilde{s}_3 \cdot \tilde{s}_2 = +1$$

$$\alpha_1 \tilde{s}_1 \cdot \tilde{s}_3 + \alpha_2 \tilde{s}_2 \cdot \tilde{s}_3 + \alpha_3 \tilde{s}_3 \cdot \tilde{s}_3 = +1$$

$$\alpha_1 \begin{pmatrix} 1 \\ 0 \\ 1 \end{pmatrix} \begin{pmatrix} 1 \\ 0 \\ 1 \end{pmatrix} + \alpha_2 \begin{pmatrix} 3 \\ 1 \\ 1 \end{pmatrix} \begin{pmatrix} 1 \\ 0 \\ 1 \end{pmatrix} + \alpha_3 \begin{pmatrix} 3 \\ -1 \\ 1 \end{pmatrix} \begin{pmatrix} 1 \\ 0 \\ 1 \end{pmatrix} = -1$$

$$\alpha_1 \begin{pmatrix} 1 \\ 0 \\ 1 \end{pmatrix} \begin{pmatrix} 3 \\ 1 \\ 1 \end{pmatrix} + \alpha_2 \begin{pmatrix} 3 \\ 1 \\ 1 \end{pmatrix} \begin{pmatrix} 3 \\ 1 \\ 1 \end{pmatrix} + \alpha_3 \begin{pmatrix} 3 \\ -1 \\ 1 \end{pmatrix} \begin{pmatrix} 3 \\ 1 \\ 1 \end{pmatrix} = 1$$

$$\alpha_1 \begin{pmatrix} 1 \\ 0 \\ 1 \end{pmatrix} \begin{pmatrix} 3 \\ -1 \\ 1 \end{pmatrix} + \alpha_2 \begin{pmatrix} 3 \\ 1 \\ 1 \end{pmatrix} \begin{pmatrix} 3 \\ -1 \\ 1 \end{pmatrix} + \alpha_3 \begin{pmatrix} 3 \\ -1 \\ 1 \end{pmatrix} \begin{pmatrix} 3 \\ -1 \\ 1 \end{pmatrix} = 1$$

## Support Vector Machine - Linear Example Solved

$$\begin{aligned}
 \alpha_1 \tilde{s}_1 \cdot \tilde{s}_1 + \alpha_2 \tilde{s}_2 \cdot \tilde{s}_1 + \alpha_3 \tilde{s}_3 \cdot \tilde{s}_1 &= -1 & \alpha_1(1+0+1) + \alpha_2(3+0+1) + \alpha_3(3+0+1) &= -1 \\
 \alpha_1 \tilde{s}_1 \cdot \tilde{s}_2 + \alpha_2 \tilde{s}_2 \cdot \tilde{s}_2 + \alpha_3 \tilde{s}_3 \cdot \tilde{s}_2 &= +1 & \alpha_1(3+0+1) + \alpha_2(9+1+1) + \alpha_3(9-1+1) &= 1 \\
 \alpha_1 \tilde{s}_1 \cdot \tilde{s}_3 + \alpha_2 \tilde{s}_2 \cdot \tilde{s}_3 + \alpha_3 \tilde{s}_3 \cdot \tilde{s}_3 &= +1 & \alpha_1(3+0+1) + \alpha_2(9-1+1) + \alpha_3(9+1+1) &= 1
 \end{aligned}$$

$$\alpha_1 \begin{pmatrix} 1 \\ 0 \\ 1 \end{pmatrix} \begin{pmatrix} 1 \\ 0 \\ 1 \end{pmatrix} + \alpha_2 \begin{pmatrix} 3 \\ 1 \\ 1 \end{pmatrix} \begin{pmatrix} 1 \\ 0 \\ 1 \end{pmatrix} + \alpha_3 \begin{pmatrix} 3 \\ -1 \\ 1 \end{pmatrix} \begin{pmatrix} 1 \\ 0 \\ 1 \end{pmatrix} = -1$$

$$2\alpha_1 + 4\alpha_2 + 4\alpha_3 = -1$$

$$4\alpha_1 + 11\alpha_2 + 9\alpha_3 = 1$$

$$4\alpha_1 + 9\alpha_2 + 11\alpha_3 = 1$$

$$\alpha_1 \begin{pmatrix} 1 \\ 0 \\ 1 \end{pmatrix} \begin{pmatrix} 3 \\ 1 \\ 1 \end{pmatrix} + \alpha_2 \begin{pmatrix} 3 \\ 1 \\ 1 \end{pmatrix} \begin{pmatrix} 3 \\ 1 \\ 1 \end{pmatrix} + \alpha_3 \begin{pmatrix} 3 \\ -1 \\ 1 \end{pmatrix} \begin{pmatrix} 3 \\ 1 \\ 1 \end{pmatrix} = 1$$

$$\alpha_1 = -3.5$$

$$\alpha_2 = 0.75$$

$$\alpha_3 = 0.75$$


$$\alpha_1 \begin{pmatrix} 1 \\ 0 \\ 1 \end{pmatrix} \begin{pmatrix} 3 \\ -1 \\ 1 \end{pmatrix} + \alpha_2 \begin{pmatrix} 3 \\ 1 \\ 1 \end{pmatrix} \begin{pmatrix} 3 \\ -1 \\ 1 \end{pmatrix} + \alpha_3 \begin{pmatrix} 3 \\ -1 \\ 1 \end{pmatrix} \begin{pmatrix} 3 \\ -1 \\ 1 \end{pmatrix} = 1$$



# Support Vector Machine - Linear Example Solved

$$\begin{aligned}\tilde{w} &= \sum_i \alpha_i \tilde{s}_i \\ &= -3.5 \begin{pmatrix} 1 \\ 0 \\ 1 \end{pmatrix} + 0.75 \begin{pmatrix} 3 \\ 1 \\ 1 \end{pmatrix} + 0.75 \begin{pmatrix} 3 \\ -1 \\ 1 \end{pmatrix} \\ &= \begin{pmatrix} 1 \\ 0 \\ -2 \end{pmatrix}\end{aligned}$$

- Finally, remembering that our vectors are augmented with a bias.
- We can equate the last entry in  $\tilde{w}$  as the hyperplane offset  $b$  and write the separating
- Hyperplane equation  $\mathbf{y} = \mathbf{w}\mathbf{x} + \mathbf{b}$
- with  $\mathbf{w} = \begin{pmatrix} 1 \\ 0 \end{pmatrix}$  and  $\mathbf{b} = -2$ .




# Support Vector Machine – Non Linear Example Solved

Suppose we are given the following positively labeled data points,

$$\left\{ \begin{pmatrix} 2 \\ 2 \end{pmatrix}, \begin{pmatrix} 2 \\ -2 \end{pmatrix}, \begin{pmatrix} -2 \\ -2 \end{pmatrix}, \begin{pmatrix} -2 \\ 2 \end{pmatrix} \right\}$$

and the following negatively labeled data points,

$$\left\{ \begin{pmatrix} 1 \\ 1 \end{pmatrix}, \begin{pmatrix} 1 \\ -1 \end{pmatrix}, \begin{pmatrix} -1 \\ -1 \end{pmatrix}, \begin{pmatrix} -1 \\ 1 \end{pmatrix} \right\}$$



## Support Vector Machine – Non Linear Example Solved

- Our goal, again, is to discover a separating hyperplane that accurately discriminates the two classes.
- Of course, it is obvious that no such hyperplane exists in the input space
- Therefore, we must use a nonlinear SVM (that is, we need to convert data from one feature space to another.

$$\Phi_1 \begin{pmatrix} x_1 \\ x_2 \end{pmatrix} = \begin{cases} \begin{pmatrix} 4 - x_2 + |x_1 - x_2| \\ 4 - x_1 + |x_1 - x_2| \\ x_1 \\ x_2 \end{pmatrix} & \text{if } \sqrt{x_1^2 + x_2^2} > 2 \\ \begin{pmatrix} x_1 \\ x_2 \end{pmatrix} & \text{otherwise} \end{cases}$$

## Support Vector Machine – Non Linear Example Solved

$$\Phi_1 \begin{pmatrix} x_1 \\ x_2 \end{pmatrix} = \begin{cases} \begin{pmatrix} 4 - x_2 + |x_1 - x_2| \\ 4 - x_1 + |x_1 - x_2| \end{pmatrix} & \text{if } \sqrt{x_1^2 + x_2^2} > 2 \\ \begin{pmatrix} x_1 \\ x_2 \end{pmatrix} & \text{otherwise} \end{cases}$$

Positive Examples

$$\left\{ \begin{pmatrix} 2 \\ 2 \end{pmatrix}, \begin{pmatrix} 2 \\ -2 \end{pmatrix}, \begin{pmatrix} -2 \\ -2 \end{pmatrix}, \begin{pmatrix} -2 \\ 2 \end{pmatrix} \right\}$$

## Support Vector Machine – Non Linear Example Solved


$$\Phi_1 \begin{pmatrix} x_1 \\ x_2 \end{pmatrix} = \begin{cases} \begin{pmatrix} 4 - x_2 + |x_1 - x_2| \\ 4 - x_1 + |x_1 - x_2| \end{pmatrix} & \text{if } \sqrt{x_1^2 + x_2^2} > 2 \\ \begin{pmatrix} x_1 \\ x_2 \end{pmatrix} & \text{otherwise} \end{cases}$$

Positive Examples

$$\left\{ \begin{pmatrix} 2 \\ 2 \end{pmatrix}, \begin{pmatrix} 2 \\ -2 \end{pmatrix}, \begin{pmatrix} -2 \\ -2 \end{pmatrix}, \begin{pmatrix} -2 \\ 2 \end{pmatrix} \right\} \rightarrow \left\{ \begin{pmatrix} 2 \\ 2 \end{pmatrix}, \begin{pmatrix} 10 \\ 6 \end{pmatrix}, \begin{pmatrix} 6 \\ 6 \end{pmatrix}, \begin{pmatrix} 6 \\ 10 \end{pmatrix} \right\}$$

Negative Examples

$$\left\{ \begin{pmatrix} 1 \\ 1 \end{pmatrix}, \begin{pmatrix} 1 \\ -1 \end{pmatrix}, \begin{pmatrix} -1 \\ -1 \end{pmatrix}, \begin{pmatrix} -1 \\ 1 \end{pmatrix} \right\} \rightarrow \left\{ \begin{pmatrix} 1 \\ 1 \end{pmatrix}, \begin{pmatrix} 1 \\ -1 \end{pmatrix}, \begin{pmatrix} -1 \\ -1 \end{pmatrix}, \begin{pmatrix} -1 \\ 1 \end{pmatrix} \right\}$$





## Support Vector Machine – Non Linear Example Solved

- Now we can easily identify the support vectors,

$$\left\{ s_1 = \begin{pmatrix} 1 \\ 1 \end{pmatrix}, s_2 = \begin{pmatrix} 2 \\ 2 \end{pmatrix} \right\}$$

- Each vector is augmented with a 1 as a bias input

$$\tilde{s}_1 = \begin{pmatrix} 1 \\ 1 \\ 1 \end{pmatrix} \quad \tilde{s}_2 = \begin{pmatrix} 2 \\ 2 \\ 1 \end{pmatrix}$$

## Support Vector Machine – Non Linear Example Solved

$$\alpha_1 \tilde{s}_1 \cdot \tilde{s}_1 + \alpha_2 \tilde{s}_2 \cdot \tilde{s}_1 = -1 \quad \alpha_1(1+1+1) + \alpha_2(2+2+1) = -1$$

$$\alpha_1 \tilde{s}_1 \cdot \tilde{s}_2 + \alpha_2 \tilde{s}_2 \cdot \tilde{s}_2 = +1 \quad \alpha_1(2+2+1) + \alpha_2(4+4+1) = 1$$

$$\alpha_1 \begin{pmatrix} 1 \\ 1 \\ 1 \end{pmatrix} \begin{pmatrix} 1 \\ 1 \\ 1 \end{pmatrix} + \alpha_2 \begin{pmatrix} 2 \\ 2 \\ 1 \end{pmatrix} \begin{pmatrix} 1 \\ 1 \\ 1 \end{pmatrix} = -1$$

$$3\alpha_1 + 5\alpha_2 = -1$$

$$5\alpha_1 + 9\alpha_2 = 1$$

$$\alpha_1 \begin{pmatrix} 1 \\ 1 \\ 1 \end{pmatrix} \begin{pmatrix} 2 \\ 2 \\ 1 \end{pmatrix} + \alpha_2 \begin{pmatrix} 2 \\ 2 \\ 1 \end{pmatrix} \begin{pmatrix} 2 \\ 2 \\ 1 \end{pmatrix} = 1$$

## Support Vector Machine – Non Linear Example Solved

$$\begin{aligned}\tilde{w} &= \sum_i \alpha_i \tilde{s}_i = -7 \begin{pmatrix} 1 \\ 1 \\ 1 \end{pmatrix} + 4 \begin{pmatrix} 2 \\ 2 \\ 1 \end{pmatrix} \\ &= \begin{pmatrix} 1 \\ 1 \\ -3 \end{pmatrix}\end{aligned}$$

- Finally, remembering that our vectors are augmented with a bias.
- We can equate the last entry in  $\tilde{w}$  as the hyperplane offset  $b$  and write the separating
- Hyperplane equation  $\mathbf{y} = \mathbf{w}\mathbf{x} + \mathbf{b}$
- with  $\mathbf{w} = \begin{pmatrix} 1 \\ 1 \end{pmatrix}$  and  $\mathbf{b} = -3$ .

