Ex No: 6

Date:

RECOGNIZE A VALID VARIABLE WITH LETTERS AND DIGITS USING LEX AND YACC

AIM:

To recognize a valid variable which starts with a letter followed by any number of letters or digits.

ALGORITHM:

- Define lexical rules in variable.l with regex to match valid variables: start with a letter, followed by letters or digits. Tokenize input, distinguishing letters and digits.
- Use lexer (variable.l) to tokenize input into meaningful units like letters and digits.
- Implement grammar rules in parser (variable.y) for recognizing valid variable names using context-free grammar. Incorporate lexer tokens into parsing.
- In parser, implement error handling to detect invalid variable names. Set a flag (e.g., valid) to mark invalid identifiers.
- Check validity post-parsing; if flag remains true, indicate valid identifier. Otherwise, display message for invalid input.

PROGRAM: identifier 303.1:

```
% {
  #include "y.tab.h"
% }
%%
[a-zA-Z_][a-zA-Z_0-9]* return letter;
[0-9]
                  return digit;
             return yytext[0];
              return 0;
\n
%%
int yywrap()
return 1;
}
identifier.y:
% {
  #include<stdio.h>
  int valid=1;
% }
```

```
%token digit letter
%%
start: letter s
s: letter s
   | digit s |;
%%
int yyerror()
  printf("\nIts not a identifier!\n");
  valid=0;
  return 0;
int main() {
  printf("\nEnter a name to test for an identifier: ");
  yyparse();
  if(valid) {
     printf("\nIt is a identifier!\n");
  } }
```

OUTPUT:

```
[VaruneshB210701303@localhost ~]$ vi identifier303.1
[VaruneshB210701303@localhost ~]$ vi identifier303.y
[VaruneshB210701303@localhost ~]$ lex identifier303.1
[VaruneshB210701303@localhost ~]$ yacc -d identifier303.y
[VaruneshB210701303@localhost ~]$ cc lex.yy.c y.tab.c
[VaruneshB210701303@localhost ~]$ ./a.out
Enter a name to test for an identifier: a

It is a identifier!
[VaruneshB210701303@localhost ~]$ ./a.out
Enter a name to test for an identifier: int

Its not a identifier!
[VaruneshB210701303@localhost ~]$
```

RESULT: