



- Question
 - Consider the following IP address: 172.17.8.10/22. Which subnet mask is assigned to this address?
- Answers
- ✓ A: 255.255.252.0
 - B: 255.255.0.0
 - **C**: 255.255.255.0
 - D: 255.255.255.252



- Question
 - You need to find out which directories in the Linux file system are included in the system path. What command can you use?
- Answers
 - A: show \$PATH
- ✓ B: echo \$PATH
 - C: print PATH
 - D: man path



- Question
 - You need to add the user james to the secondary group developers.
 Which command can be used to do this?
- Answers
 - A: useradd -g developers james
 - B: usermod -g developers james
 - C: groupadd -U james developers
- ✓ D: usermod -aG developers james



- Question
 - Which file contains a list of your most recently entered shell commands?
- Answers
 - A: ~/.history
- ✓ B: ~/.bash_history
 - C: /etc/bash_history
 - D: ~/.bash_commands



- Question
 - Which of the following manual sections contain man pages for utilities and commands that can be used by any user?
- Answers
 - A: 9
- ✓ B: 1
 - **C**: 3
 - D: 7



- Question
 - You are using man to view the manual page for the chmod utility.
 Which keystroke will exit man?
- Answers
 - A: X
 - B: Ctrl+X
- ✓ C: Q
 - D: Ctr+Q



- Question
 - You need to search for man pages that relate to the Samba daemon.
 Which command will do this?
- Answers
- ✓ A: man -k samba
 - B: man -s samba
 - C: which samba
 - D: search samba



- Question
 - You want to view a list of the aliases currently defined on your Linux system. Which command will do this?
- Answers
 - A: alias -a
- ✓ B: alias
 - C: alias -l
 - D: env alias



- Question
 - Where are most of the configuration files stored in a Linux file system?
- Answers
 - A: /boot
- ✓ B: /etc
 - C: /usr
 - D: /var



Question

You are logged on the terminal and your current directory is /etc. You want to create a file named readme.txt in your home directory. Which command will do this?

- A: vi readme.txt
- B: vi readme.txt -new
- C: vi ~/readme.txt
 - D: vi /home/readme.txt



- Question
 - Which keystroke will switch vi from command mode to insert mode?
- Answers
 - A: DELETE
- **✓ •** B: L
 - C: ESC
 - D: F2



Question

You have made several changes to a configuration file using vi. You realize that you have made many mistakes and want to quit without saving the changes. Which command will do this?

Answers

■ A: :q

B: :exit

C: :exit!

✓ ■ D: :q!



- Question
 - You have created a new file using vi and need to save the file to disk and exit the program. Which command will do this?
- Answers
 - **A**::w
- ✓ B: :wq
 - **C**::q
 - D::e!



- Question
 - Which directory is the <u>home directory</u> of the <u>root</u> user?
- Answers
 - A: /home/root
 - B: /
 - C: /users/root
- ✓ D: /root



- Question
 - You need to delete the Temp directory within your <u>user's home</u> <u>directory</u>. Given that Temp has files in it, which is the best command to do this?
- Answers
 - A: rmdir Temp
 - B: rmdir ~/Temp
- ✓ C: rm -r ~/Temp
 - D: rm ~/Temp



Question

You need to find all files named readme.txt in your Linux file system.
Which is the correct command to do this?

- A: find readme.txt
- B: find / readme.txt
- C: find / -name readme.txt
 - D: find -name readme.txt



Question

You need to examine the contents of your /var/messages.log file, but you would like to scroll it forward and backward, and to search in it. Which is the best command to do this?

- A: head /var/messages.log
- B: cat /var/messages.log
- C: tail /var/messages.log
- ✓ D: less /var/messages.log



- Question
 - Your Linux system has two SATA disks. Which of the following refers to the second SATA drive in the system?
- Answers
- ✓ A: /dev/sdb
 - B: /dev/sdd
 - C: /dev/sda
 - D: /dev/sdc



- Question
 - Where does the Linux kernel reside?
- Answers
 - A: MBR
- ✓ B: /boot
 - C: /kernel
 - D:/proc



- Question
 - Your Linux system has three SATA disks. Which of the following refers to the second partition on the first drive?
- Answers
 - A: /dev/sda1
 - B: /dev/sdb2
- ✓ C: /dev/sda2
 - D: /dev/sdc2



- Question
 - Which configuration parameter in /etc/default/grub specifies how long the system will wait before the default operating system is booted?
- Answers
 - A: GRUB DEFAULT
- ✓ B: GRUB_TIMEOUT
 - C: GRUB_SAVED_TIMEOUT
 - D: BOOT_TIMEOUT



- Question
 - You need to switch your system to runlevel 3. Which command should you use?
- Answers
 - A: systemctl isolate graphical.target
 - B: systemctl isolate runlevel5.target
- C: systemctl isolate multi-user.target
 - D: systemctl isolate nongraphical.target



Question

You currently have an RPM package file named newsoft-3.0.0-15.x86_64.rpm installed on your Linux system. You have recently downloaded the newsoft-3.2.0-45.x86_64.rpm package. What command would you use to install the newer version of this package?

- ✓ A: rpm -U newsoft-3.2.0-45.x86_64.rpm
 - B: rpm -i newsoft-3.2.0-45.x86_64.rpm
 - C: rpm -i --upgrade newsoft-3.2.0-45.x86_64.rpm
 - D: rpm -e newsoft-3.2.0-45.x86 64.rpm



Question

You created an ext4 file system on the <u>first partition on the second hard</u> <u>disk</u> in your system and now need to mount it in /mnt/extraspace in <u>read-write mode</u>. Which commands will do this?

- ✓ A: mount -t ext4 /dev/sdb1 /mnt/extraspace
 - B: mount -t ext4 -o ro /dev/sdb1 /mnt/extraspace
 - C: mount -t ext /dev/sdb1 /mnt/extraspace
 - D: mount -t ext4 /dev/sda1 /mnt/extraspace



Question

• Which of the following files is used to store user accounts related information on a Linux system that has been configured to use local authentication?

- A: /etc/users
- B: /etc/local_users
- C: /etc/shadow
 - D: /etc/passwords



- Question
 - Which two folders store systemd units of type service?
- Answers
 - A: /bin/systemd/system/
- ✓ B: /usr/lib/systemd/system/
 - C: /lib64/systemd/system/
 - D: /usr/systemd/system/



Question

You have just downloaded an RPM package file named newsoft-3.2.0-45.x86_64.rpm to your home directory. Assuming the current directory is your home directory, what command could you use to install the package on your system?

- A: rpm -install newsoft-3.2.0-45.x86_64.rpm
- ✓ B: rpm -ivh newsoft-3.2.0-45.x86_64.rpm
 - C: rpm -add newsoft-3.2.0-45.x86 64.rpm
 - D: rpm newsoft-3.2.0-45.x86_64.rpm



- Question
 - You need to format the <u>second partition</u> on the <u>third SATA disk</u> using the <u>ext4</u> file system. Which is the correct command to do this?
- Answers
 - A: mkfs -t ext4 /dev/sdb3
 - B: mk.xfs /dev/sdc2
- C: mkfs.ext4 /dev/sdc2
 - D: mkext4 /dev/sdc2



- Question
 - You need to change the ownership of the readme.txt file to <u>user</u> and <u>users</u>. Which command will do this?
- Answers
 - A: change user:users readme.txt
 - B: owner user:users readme.txt
 - C: chmod user:users readme.txt
- ✓ D: chown user.users readme.txt



- Question
 - You need to create a compressed archive of /etc to a removable disk drive mounted at /mnt/backup. Which command will do this?
- Answers
 - A: tar -xzvf /mnt/backup/backup.tar.gz /etc
- ✓ B: tar -czvf /mnt/backup/backup.tar.gz /etc
 - C: tar -czvf /mnt/backup/backup.tar.gz ~/etc
 - D: tar -czvf /etc /mnt/backup/backup.tar.gz

