


DevOps and Containerization

The Big Picture. Basic Toolkit. Containerization



SoftUni Team
Technical Trainers



Software University

<https://softuni.bg>

You Have Questions?

sli.do

#DevOps-CI

**facebook.com/groups/
containerizationandinfrastructurejune2025**



This Module (M1)
Topics and Infrastructure


1. The Big Picture

- Main Pain Points and Causes
- Goals and Benefits
- Adoption and Tools

2. Basic Toolkit

3. Containerization








The Big Picture


(Why) Do we need a change?

Typical Company Organization*



* Many departments and all depend on IT in one way or another

Typical IT Organization*



* IT has its own units

- Complex pipeline
- Mixed environment
 - Externally customized software
 - Custom internal software
- Staff is leaving or being moved elsewhere
 - Absent know-how, outdated or missing documentation
- Operations have to maintain black-boxes



Main Pain Points
At least some of them

Common Pain Points



The diagram features a light gray background with a network of thin lines and circles. Four dark blue squares are arranged in a 2x2 grid in the center. Each square contains white text. The squares are interconnected by a network of lines and circles, with some circles being larger than others, creating a complex web-like structure.

Outages

Low value

Slow IT

Fighting

- Happen at the most inappropriate time
 - Typically, in high priority systems
 - Usually with long recovery time
- Lead to
 - Panic mode
 - Lost trust
- May be caused by
 - Repeated errors/issues
 - Lack of expertise

- Slow delivery
 - Long time to wait before the actual consumption
- Long implementation periods
 - Often the delivery is outdated and doesn't match the current requirements


- In fact, is more a perception than a reality
- It leads to
 - Software-as-a-Service solutions
 - Departmental solutions
- It is caused by
 - Long waiting
 - Too many restrictions
 - Poor performance

- Involved parties
 - IT vs. Business
 - Internally in IT
- Typically caused by
 - Lost trust
 - Absence of transparency
 - Different motivators or bonus schemes



Causes

Common Causes



**Lack of
Knowledge**

**Slow
Processes**

**Over-
something**

Logistics

- **Poor communication**
 - Between the departments
 - Internally in IT, between roles
- **Missing documentation**
- **Hard to distinguish between important and unimportant**
 - Too many meetings
 - Too many and too complex reports

- **Sources**

- Slow provisioning of environments
- Approval takes time
- (Too many) too specialized people
- Next role is waiting for the previous one to finish

- **Affected parties**

- Internal
- External

- **Over-provision**
 - Request more resources than actually needed
- **Over-production**
 - Ask for features just to keep everyone busy
- **Over-processing**
 - For example, apply unnecessary transformations over and over
- **Over-delivery**
 - Deliver more than requested

- **Slow delivery of features**
 - Long (time expensive) updates
 - Repetitive manual testing procedures
- **Unnecessary iterations**
 - From environment to environment
- **Delivery in a rush**
 - Do it on time no matter the quality
- **Postpone a delivery**
 - A ready feature is waiting something else to be shipped first



Goals and Benefits



**Increase
the
Value**

**Respect
the
People**

How can DevOps help?

- Can add value and flow improvement
- Mind the prerequisites
 - Identify a **shared pain**
 - **Address the causes**
- Embrace the result
 - **Added value => financial impact**

- We should not cut costs, but free up resources
- This can be achieved by
 - Focus on customer value
 - Optimize the process
 - Reduce delivery time
 - Shared knowledge
 - Avoid batching
 - Address bottlenecks

Core Values* of DevOps Movement

- **Culture**
 - Break down barriers between teams, safe environment
- **Automation**
 - Save time, prevent defects, create consistency, self-service
- **Measurement**
 - If you can not measure it, you can not improve it
- **Sharing**
 - Sharing the tools, discoveries, and lessons

* Damon Edwards and John Willis



Adoption
Making the Transition

Three Main Tasks

**Change
the
Culture**

**Change
the
Organization**

**Handle
the
Objections**

- **Question** to identify the **Shared Objective**
- **Data-driven** decisions
- **Authorization** for action
- **Responsibility** for actions
- (Cross-) **Teamwork** and **Respect**
- **Learning** and **Sharing** even from *Mistakes*
- **Trust** (between parties)
- **Values** and **Rewards** (who, why, how)
- **Continuous improvement** mindset

- **Understand** the processes
 - All components - systems, people, value, etc.
 - Achieve **clear vision**
- **Assess and acknowledge bottlenecks**
 - Inconsistent environments
 - Manual and custom builds
 - Poor quality
 - No communication

- **Change (or adjust) team structure** (if needed)
 - Concentrated knowledge or many tasks assigned to one person
 - Generalists vs Specialists
 - Complete (or consistent) team
 - Prepare handoff (think about the next step)
- **Assessment** of people and processes
 - Including the rewards and punishment system
 - Including the budgeting
- **Clean-up** (remove extra steps, components, ...)

Typical Objections to Handle

- **Security** (developers on production, security issues)
 - Communication, Upfront quality, Proper testing, Ship quickly
- **Compliance** (restricted access, all-or-nothing)
 - Better control - who, what, where
- **Remote teams** (internal teams or external parties)
 - Shared objectives, Technology solutions, Renegotiation
- **Impact** on employees
- Presence of **legacy systems**
- Lack of appropriate **skills** (technical and soft skills)



Mentality and Tools

~~If it isn't broke, don't fix it~~



Continuous Improvement

- Planning (transparency)
- Issue tracking (feedback)
- Source control (control code & configuration)
- Building and testing
- Security assessment (vulnerabilities, secrets, privileges, etc.)
- Continuous integration and deployment
- Configuration and infrastructure management (consistency)
- Monitoring and logging (measurement)
- Collaboration and knowledge sharing (connect & share)

Cloud Platforms could provide the whole environment or serve one or more of the listed categories



It's Time For a Break
Back in a few minutes 😊




Virtualization


Fundamental Principles and Use Cases

What is Virtualization?


- Virtualization is the **act** of creating a **software-based** or virtual (rather than physical) version of something
- Main definitions
 - Host OS (machine)
 - Virtual machine
 - Guest OS (machine)
 - Guest additions



- A **hypervisor** or **virtual machine monitor (VMM)** is computer software, firmware, or hardware, that creates and runs virtual machines



Type 1 (bare metal)




Type 2 (hosted)

- Infrastructure **consolidation**
 - Better usage and utilization of the available hardware
- Maintain **separate environments**
 - For example – development, test, production
- **Testing and evaluation**
 - Test a newer software version or evaluate a product
- **High availability** and **disaster recovery**

- We would like to
 - Install **multiple** machines on **limited** hardware resources
 - Manage their **isolation**
 - Manage their **state** – our own time-machine
 - **Move, export, and import** them
 - **Clone** them – create **multiple copies** out of one master
- The answer is **Virtualization**

- Cross-platform
- Broad guest OS support
- Easy to install
- Simple GUI
- Automation options
- Free



The image features a central dark blue circle containing a grey gear. Overlaid on the gear is the text 'DevOps', with 'Dev' in white and 'Ops' in yellow. Below this central circle, the word 'Linux' is written in a dark blue, sans-serif font. The entire composition is set against a light grey background with a network-like pattern of thin lines and circles of varying sizes.

DevOps

Linux

- It is a **phenomenon**
 - Went all the way from a **student's hobby** to **world domination**
- Internet **runs** on Linux
 - Operating system for **over 95%** of the top one million domains *
- It runs on **100%** of the **top 500** supercomputers **
- There is **huge demand** for Linux skills
- It is both **challenging** and **fun**

* <https://www.linuxfoundation.org/about>

** <https://www.top500.org/statistics/details/osfam/1>

What we need to know?

- General knowledge about Linux
- Working with users, groups, and permissions
- Working with files and folders
- Handling some basic network related tasks
- Software and services management
- Basic bash scripting skills



Bash Scripting

Structure. Flow Control. Sourcing. Execution

Script Signature

```
#!/bin/bash
```

Comments

```
#  
# hello.sh  
#
```

Local Variable

```
attn="dear"
```

Command

```
echo "Hello $attn $USER"
```

Execution: **bash hello.sh** or **./hello.sh** or just **hello.sh**

- Description
 - Display line of text
- Example

```
[user@host ~]$ echo 'Hello world!'  
'Hello world!'
```

```
[user@host ~]$ echo -e 'Line 1\nLine2'  
Line1  
Line2
```


- Description
 - Read a line from the standard input and split it into fields
- Example

```
[user@host ~]$ read -p "Enter name:" NM_ENT  
Enter name: James
```

```
[user@host ~]$ echo $NM_ENT  
James
```

- Description
 - Execute commands based on conditional
- Example

```
count=1
if [ $count -eq 0 ]; then
    echo 'Equal to 0'
else
    echo 'Not equal to 0'
fi
```

- Description
 - Evaluate conditional expression
- Example

```
# Compare numbers: OP1 -eq | -ne | -lt | -le | -gt | -ge OP2
```

```
# Compare strings: ST1 = | != | < | > ST2
```

```
# Compare files: FL1 -nt | -ot FL2
```

```
# File tests: -d | -e | -f | -x FILE
```

- Description
 - Execute command for each member in a list
- Example

```
# List all files with prefix "item:"  
  
for i in $( ls ); do  
    echo item: $i  
done
```

- Description
 - Execute commands as long as a test succeeds
- Example

```
# Print numbers from 1 to 5
count=1
while [ $count -le 5 ]; do
    echo $count
    count=$((count+1))
done
```

- Description
 - Execute commands as long as a test does not succeed
- Example

```
# Print numbers from 1 to 5
count=1
until [ $count -gt 5 ]; do
    echo $count
    count=$((count+1))
done
```

- Sourcing
 - No subshell is created
 - Any variables set become part of the environment
 - Methods: **. script.sh** or **source script.sh**
- Execution
 - Subshell is always created
 - No subshell if using **exec ./script.sh**




Source Control

Git. Files Lifecycle. Basic Commands

- Distributed Version Control
- Created by the Linux development community in 2005
- Can be used on-premise and in the cloud
- Snapshot based
- Three states - Committed, Modified, and Staged

Files Lifecycle



- Create an empty Git repository

```
git init
```

- Clone an existing repository

```
git clone https://github.com/user/repo
```

- Show repository objects

```
git show
```

- Show different states of files in working directory and staging

```
git status
```

- Add files from working directory to staging

```
git add file.txt
```

- Remove a file from staging and working directory

```
git rm old_file.txt
```

- Move or rename file

```
git mv old_file.txt new_file.txt
```

- Commit the staged changes

```
git commit
```

- Get all not existing objects from remote repository

```
git fetch https://github.com/user/repo
```

- Get and merge changed objects from remote repository

```
git pull
```

- Push the changes to a remote repository

```
git push
```



Vagrant

Introduction. Basic Commands

- Building and managing virtual machine environments
- Supports providers like VirtualBox, VMware, AWS, etc.
- Provisioning tools such as shell scripts, Chef, or Puppet
- Multiplatform
- Integration with source control systems
- Public boxes catalog: <https://app.vagrantup.com/boxes/search>
- Local storage for boxes: `~/.vagrant.d/boxes`

- Boxes are the package format for the Vagrant environment
- They can be used by anyone on any supported platform
- Used to bring up an identical working environment
- Box files have three different components
 - **Box File** - Compressed (tar, tar.gz, zip) file that is specific to a single provider and can contain anything
 - **Box Catalog Metadata** - JSON document that specifies the name of the box, a description, available versions, etc.
 - **Box Information** - JSON document that can provide additional information

- Create a tiny VM
- Install the OS with minimalistic profile (SSH included)
- Install any additional required tools and services
- Install hypervisor addons (for example, VirtualBox Add-ons)
- Make the **vagrant** user a member of the ***sudoers*** list
- Install the insecure vagrant key
- Cleanup packages cache and align the hard drive
- Package and publish the box

- Ruby syntax
- One file per environment
- General file structure

```
# -*- mode: ruby -*-  
# vi: set ft=ruby :  
...  
Vagrant.configure("2") do |config|  
  config.vm.box = "shekeriev/debian-11"  
...  
end
```

```
Vagrant.configure("2") do |config|
  config.vm.box = "shekeriev/centos-8-minimal"
  # Provider settings
  config.vm.provider "virtualbox" do |vb|
    # Display the VirtualBox GUI when booting the machine
    vb.gui = true
    # Customize the amount of memory on the VM:
    vb.memory = "1024"
  end
  # Provisioning section
  config.vm.provision "shell", inline: <<SHELL
    dnf -y upgrade
    dnf install -y httpd
  SHELL
end
```

Basic Vagrant Commands

- Initialize the environment

```
vagrant init [options] [box]
```

- Login to HashiCorp's Vagrant Cloud

```
vagrant login
```

- Connect to machine via SSH

```
vagrant ssh [options] [name|id]
```

- Check status of a vagrant machine

```
vagrant status [name|id]
```

Basic Vagrant Commands

- Start and provision grant environment

```
vagrant up [options] [name|id]
```

- Stop a vagrant machine

```
vagrant halt [options] [name|id]
```

- Stop and delete vagrant machine

```
vagrant destroy [options] [name|id]
```

- Manage boxes

```
vagrant box <subcommand> [<arguments>]
```



Practice: Vagrant in Action

Live Demonstration in Class




Containers and Docker

Past. Present. Future

“ OS-level virtualization refers to an operating system paradigm in which the kernel allows the existence of **multiple isolated user space instances** known as **containers, zones, jails, ...** ”

Road to Containers

Companies and Solutions



Enablement Technologies

- **System Containers (BSD Jails, Solaris Zones, ...)**

- **LXC + LXD + LXCF by Canonical**
- Container hypervisor (system containers)
- <https://linuxcontainers.org/>

OS-centric
Multiple processes

- **Application Containers (containerd, CRI-O, ...)**

- **Docker by Docker Inc**
- Tools and application container engine
- <https://www.docker.com/>


App-centric
Single process *

VMs vs Containers

- VMs virtualize the hardware
- Complete isolation
- Complete OS installation. Requires more resources
- Runs almost any OS
- Containers virtualize the OS
- Lightweight isolation
- Shared kernel. Requires fewer resources
- Runs on the same OS



Together: VMs and Containers





Docker
Whole New World

Containers Concepts (Docker View)

- **Container host** is a physical or virtual computer system configured with a **container engine**
- **Container image** shows the state of a container, including registry or file system changes
- **Container OS image** is the first layer of potentially many image layers that make up a container
- **Container repository** stores container images and their dependencies

- **Container**

- A runnable instance of an image. Containers are processes with much more isolation

- **Image**

- A read-only template of a container built from layers. Images provide a way for simpler software distribution

- **Repository**

- A collection of different versions of an image identified by tags

- **Registry**

- A collection of repositories







Image Layers





** Not required, but we could install it there as well*

*** TCP or UNIX socket*



■ Docker Desktop

- Linux
- macOS
- Windows

Specific requirements: OS version, Hypervisor, etc.

■ Docker Engine

- Various Linux distributions →
- Various hardware architectures

Deployment via **package system** (two channels – **stable**, and **test**), **script**, or **archive**

x86_64/amd64

arm64 (aarch64)

arm (armhf)

s390x

- Provided by Docker
 - Cloud
 - Docker Hub (<https://hub.docker.com/explore/>)
 - On-premise
 - Standalone
 - Containerized
- Provided by 3rd parties
 - Quay.io, Artifactory, Google Container Registry, etc.

Registries can be
private or **public**

Repositories can
also be **private**
or **public**



Working with Docker

Commands

- Syntax varies amongst versions
 - Old (short) style – still available
 - New style – preferred
- Grouped by target
 - Management Commands
 - General Commands

- Purpose
 - Search the Docker Hub for images

- Old (short) syntax

```
docker search [OPTIONS] TERM
```

- New syntax

```
# same
```

- Example (*search for image that have ubuntu in their name*)

```
docker search ubuntu
```

- Purpose
 - Pull an image or a repository from a registry

- Old (short) syntax

```
docker pull [OPTIONS] NAME[:TAG|@DIGEST]
```

- New syntax

```
docker image pull [OPTIONS] NAME[:TAG|@DIGEST]
```

- Example (*download the ubuntu:latest image locally*)

```
docker image pull ubuntu:latest
```


- Purpose
 - Run a command in a new container

- Old (short) syntax

```
docker run [OPTIONS] IMAGE [COMMAND] [ARG]
```

- New syntax

```
docker container run [OPTIONS] IMAGE [COMMAND] [ARG]
```

- Example (*run bash in ubuntu based container interactively*)

```
docker container run -it ubuntu bash
```

- Purpose
 - List locally available images

- Old (short) syntax

```
docker images [OPTIONS] [REPOSITORY[:TAG]]
```

- New syntax

```
docker image ls [OPTIONS] [REPOSITORY[:TAG]]
```

- Example (*list all tags for the fedora image*)

```
docker image ls fedora
```

- Purpose
 - List containers
- Old (short) syntax

```
docker ps [OPTIONS]
```

- New syntax

```
docker container ls [OPTIONS]
```

- Example (*return running and stopped container IDs*)

```
docker container ls -a -q
```

- Purpose
 - Remove one or more containers

- Old (short) syntax

```
docker rm [OPTIONS] CONTAINER [CONTAINER]
```

- New syntax

```
docker container rm [OPTIONS] CONTAINER [CONTAINER]
```

- Example (*remove container by its name*)

```
docker container rm weezy_snake
```

- Purpose
 - Remove one or more images

- Old (short) syntax

```
docker rmi [OPTIONS] IMAGE [IMAGE]
```

- New syntax

```
docker image rm [OPTIONS] IMAGE [IMAGE]
```

- Example (*remove the ubuntu and fedora images*)

```
docker image rm ubuntu fedora
```

- Purpose
 - Create a new container

- Old (short) syntax

```
docker create [OPTIONS] IMAGE [COMMAND] [ARG]
```

- New syntax

```
docker container create [OPTIONS] IMAGE [COMMAND] [ARG]
```

- Example (*create a container without starting it*)

```
docker container create -t -i fedora bash
```

- Purpose
 - Rename a container

- Old (short) syntax

```
docker rename CONTAINER NEW_NAME
```

- New syntax

```
docker container rename CONTAINER NEW_NAME
```

- Example (*change container name from cont1 to newcont1*)

```
docker container rename cont1 newcont1
```

- Purpose
 - Kill one or more running containers

- Old (short) syntax

```
docker kill [OPTIONS] CONTAINER [CONTAINER]
```

- New syntax

```
docker container kill [OPTIONS] CONTAINER [CONTAINER]
```

- Example (*stop a container by its ID*)

```
docker container kill 0cbf27183
```


- Purpose
 - Start one or more stopped containers

- Old (short) syntax

```
docker start [OPTIONS] CONTAINER [CONTAINER]
```

- New syntax

```
docker container start [OPTIONS] CONTAINER [CONTAINER]
```

- Example (*start a container by its ID and attach to it*)

```
docker container start -a -i 0cbf27183
```

- Purpose
 - Restart a one or more containers

- Old (short) syntax

```
docker restart [OPTIONS] CONTAINER [CONTAINER]
```

- New syntax

```
docker container restart [OPTIONS] CONTAINER [CONTAINER]
```

- Example (*restart a container by its ID*)

```
docker container restart 0cbf27183
```

- Purpose
 - Stop one or more running containers

- Old (short) syntax

```
docker stop [OPTIONS] CONTAINER [CONTAINER]
```

- New syntax

```
docker container stop [OPTIONS] CONTAINER [CONTAINER]
```

- Example (*stop a container by its ID*)

```
docker container stop 0cbf27183
```

- Purpose
 - Pause all processes within one or more containers

- Old (short) syntax

```
docker pause CONTAINER [CONTAINER]
```

- New syntax

```
docker container pause CONTAINER [CONTAINER]
```

- Example (*pause a container by its ID*)

```
docker container pause 0cbf27183
```

- Purpose
 - Resume all processes within one or more containers

- Old (short) syntax

```
docker unpause CONTAINER [CONTAINER]
```

- New syntax

```
docker container unpause CONTAINER [CONTAINER]
```

- Example (*resume a container by its ID*)

```
docker container unpause 0cbf27183
```

- Purpose
 - Attach to a running container

- Old (short) syntax

```
docker attach [OPTIONS] CONTAINER
```

- New syntax

```
docker container attach [OPTIONS] CONTAINER
```

- Example (*attach to the process in a container by its ID*)

```
docker container attach 0cbf27183
```



Practice: Working with Containers

Live Demonstration in Class

- DevOps
 - Is for companies of any size
 - Adds value and flow improvement
- DevOps is a combination of
 - Cultural changes
 - Organizational changes
 - Tools
- We are not alone – there is a toolkit to help us
- Vagrant allows us to automate infrastructure life-cycle



Vagrant download

<https://developer.hashicorp.com/vagrant/downloads>

Vagrant documentation

<https://developer.hashicorp.com/vagrant/docs>

Vagrant boxes repository (Vagrant Cloud)

<https://app.vagrantup.com/boxes/search>

VirtualBox download

<https://www.virtualbox.org/wiki/Downloads>

VirtualBox documentation

<https://www.virtualbox.org/manual/UserManual.html>

CentOS download

<https://www.centos.org/download/>

CentOS (Red Hat) documentation

https://access.redhat.com/documentation/en-us/red_hat_enterprise_linux/9

Debian download

<https://www.debian.org/download>

Debian documentation

<https://www.debian.org/doc/>



SoftUni Diamond Partners



**SUPER
HOSTING
.BG**




THE CROWN IS YOURS



encorp.io

VIVACOM

Questions?



- Software University – High-Quality Education, Profession and Job for Software Developers
 - softuni.bg, softuni.org
- Software University Foundation
 - softuni.foundation
- Software University @ Facebook
 - facebook.com/SoftwareUniversity



- This course (slides, examples, demos, exercises, homework, documents, videos and other assets) is **copyrighted content**
- Unauthorized copy, reproduction or use is illegal
- © SoftUni – <https://softuni.org>
- © Software University – <https://softuni.bg>

