AI-BASED FORENSIC FACE SKETCH GENERATION AND SUSPECT IDENTIFICATION FROM EYEWITNESS VERBAL DESCRIPTION

A PROJECT REPORT

Submitted by

VASAN S	**811722104177**
YOGESHWARAN T K	**811722104189**
KARTHIKEYAN S	**811722104303**

in partial fulfillment of the requirements for the award degree of

Bachelor of Engineering

20CS8504 - PROJECT WORK

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

K. RAMAKRISHNAN COLLEGE OF TECHNOLOGY

(AUTONOMOUS)

SAMAYAPURAM - 621112

APIRL 2026

AI-BASED FORENSIC FACE SKETCH GENERATION AND SUSPECT IDENTIFICATION FROM EYEWITNESS VERBAL DESCRIPTION

A PROJECT REPORT

Submitted by

VASAN S	**811722104177**
YOGESHWARAN T K	**811722104189**
KARTHIKEYAN S	**811722104303**

in partial fulfillment of the requirements for the award degree of

Bachelor of Engineering

20CS8504 - PROJECT WORK

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

K. RAMAKRISHNAN COLLEGE OF TECHNOLOGY

(AUTONOMOUS)

SAMAYAPURAM - 621112

APIRL 2026

K. RAMAKRISHNAN COLLEGE OF TECHNOLOGY (AUTONOMOUS) SAMAYAPURAM - 621112

BONAFIDE CERTIFICATE

The work embodied in the present project report entitled "**AI-BASED FORENSIC FACE SKETCH GENERATION AND SUSPECT IDENTIFICATION FROM EYEWITNESS VERBAL DESCRIPTION**" has been carried out by the students **VASAN S, YOGESWARAN T K, KARTHIKEYAN S,** The work reported herein is original and we declare that the project is their own work, except where specifically acknowledged, and has not been copied from other sources or been previously submitted for assessment.

Date of Viva Voce: ……

Mrs. G. Rajendra Kannammal, M.E,(Ph.D.,)	**Mr. R. Rajavarman, M.E,(Ph.D.,)**
SUPERVISOR	HEAD OF THE DEPARTMENT
Assistant Professor	Assistant Professor (Sr. Grade)
Department of CSE	Department of CSE
K. Ramakrishnan College of Technology (Autonomous)	K. Ramakrishnan College of Technology(Autonomous)
Samayapuram – 621 112	Samayapuram – 621 112

INTERNAL EXAMINER **EXTERNAL EXAMNIER**

ABSTRACT

Suspect identification using eyewitness descriptions is important in criminal investigations but is often difficult due to subjective memory, language differences, and manual forensic sketch methods that are slow and inconsistent. This project proposes an intelligent Forensic Face Sketch Generation and Criminal Identification System that integrates multilingual speech recognition, generative modeling, and face recognition. The system converts a witness's spoken description into text using multilingual speech recognition, then generates a forensic face sketch using an Attention-Based Conditional GAN. The generated face image is compared with criminal database images using Vision Transformer-based face encoding and cosine similarity for identification. The system reduces reliance on manual sketch artists, supports multilingual input, improves identification accuracy, and increases investigation efficiency in modern law enforcement.

Keywords: Forensic Face Sketch Generation, Criminal Identification System, Multilingual Speech Recognition, Whisper Speech-to-Text, Attention-Based Conditional GAN (Attention-cGAN), Facial Attribute Learning, Sketch-to-Photo Generation, Vision Transformer (ViT), Face Recognition, Cosine Similarity Matching, Eyewitness Description Analysis, Artificial Intelligence in Forensics.

ACKNOWLEDGEMENT

We thank **Dr. N. Vasudevan**, Principal, for his valuable suggestions and support during the course of my research work.

We thank **Mr. R. Rajavarman,** Head of the Department, Assistant Professor (Sr. Grade), Department of Computer Science and Engineering, for his valuable suggestions and support during the course of my research work.

We wish to record my deep sense of gratitude and profound thanks to my Guide **Mrs. G. Rajendra Kannammal**, Assistant Professor, Department of Computer Science and Engineering, for her keen interest, inspiring guidance, constant encouragement with my work during all stages, to bring this thesis into fruition.

We are extremely indebted to our project coordinator **Mr. P. Matheswaran,** Assistant Professor, Department of Computer Science and Engineering, for his valuable suggestions and support during the course of my research work.

We also thank the faculty and non-teaching staff members of the Computer Science and Engineering, K. Ramakrishnan College of Technology, Samayapuram, for their valuable support throughout the course of my research work.

Finally, we thank our parents, friends and our well wishes for their kind support.

SIGNATURE

_____

_____

_____

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE NO
	ABSTRACT	**iii**
	LIST OF TABLES	**vii**
	LIST OF FIGURES	**ix**
	LIST OF ABBREVIATIONS	**x**
1	**INTRODUCTION**	**01**
	1.1 BACKGROUND	01
	1.2 OVERVIEW	02
	1.2.1 Application Workflow	02
	1.2.2 Key Features	03
	1.3 PROBLEM STATEMENT	03
	1.4 OBJECTIVES	04
	1.5 USERS OF THE SYSTEM	05
	1.6 APPLICATION FIELDS	05
	1.7 IMPLICATIONS	06
2	**LITERATURE SURVEY**	**07**
3	**EXISTING SYSTEM**	**17**
	3.1 MANUAL FORENSIC SKETCHING	17
	3.2 COMPOSITE FACE SOFTWARE	17
	3.3 TEXT-BASED DESCRIPTION SYSTEMS	18
	3.4 TRADITIONAL FACE RECOGNITION SYSTEMS	18
	3.5 DRAWBACKS OF EXISTING SYSTEMS	19

	3.6 NEED FOR THE PROPOSED SYSTEM	19
4	**PROBLEMS IDENTIFIED**	**20**
5	**PROPOSED SYSTEM**	**22**
	5.1 OVERVIEW	22
	5.2 SPEECH-BASED FACE GENERATION	22
	5.3 SKETCH ENHANCEMENT AND PHOTO SYNTHESIS	23
	5.4 FACE ENCODING AND CRIMINAL MATCHING	23
	5.5 ADVANTAGES OF THE PROPOSED SYSTEM	24
6	**SYSTEM ARCHITECTURE AND MODULES**	**25**
	6.1 SYSTEM ARCHITECTURE	25
	6.2 MODULE DESCRIPTIONS	25
7	**ALGORITHM DESIGN**	**29**
	7.1 WHISPER – MULTILINGUAL SPEECH RECOGNITION	29
	7.2 ATTENTION-BASED CONDITIONAL GAN	30
	7.3 VISION TRANSFORMER – FACE ENCODING	30
	7.4 COSINE SIMILARITY – SUSPECT MATCHING	31
8	**SYSTEM REQUIREMENTS**	**32**
	8.1 HARDWARE REQUIREMENTS	32

	8.2 SOFTWARE REQUIREMENTS	32
10	**SYSTEM IMPLEMENTATION**	**33**
	9.1 IMPLEMENTATION OVERVIEW	33
	9.2 SPEECH RECOGNITION IMPLEMENTATION	33
	9.3 FACE GENERATION IMPLEMENTATION	34
	9.4 FACE ENCODING IMPLEMENTATION	34
	9.5 SUSPECT IDENTIFICATION IMPLEMENTATION	35
	9.6 WEB APPLICATION IMPLEMENTATION	35
10	**TESTING**	**36**
	10.1 TESTING STRATEGY	36
	10.2 UNIT TESTING	36
	10.3 INTEGRATION TESTING	37
	10.4 PERFORMANCE TESTING	37
11	**RESULT AND DISCUSSION**	38
	11.1 RESULT	38
	11.2 DISSICUSSION	39
12	**CONCLUSION AND FUTURE ENHANCEMENT**	**41**
	12.1 CONCLUSION	41
	12.2 FUTURE WORK	42
	APPENDIX A – SOURCE CODE	**43**
	APPENDIX B – SCREENSHOTS	**45**
	REFERENCES	**47**

LIST OF TABLES

TABLE NO	TABLE NAME	PAGE NO
10.1	PERFORMANCE MATRIX	37
11.1	EFFICIENCY MATRIX	38

LIST OF FIGURES

FIGURE NO	FIGURE NAME	PAGE NO
4.1	COMPOSITE FACE SOFTWARE	21
5.1	PROPOSED ARCHITECTURE	24
11.1	ACCURACY COMPARISON	39
11.2	EFFICIENCY COMPARISON	40

LIST OF SYMBOLS AND ABBREVIATIONS

ASR	-	Automatic Speech Recognition
GAN	-	Generative Adversarial Network
CGAN	-	Conditional Generative Adversarial Network
STT	-	Speech-To-Text
VIT	-	Vision Transformer
NLP	-	Natural Language Processing
CNN	-	Convolutional Neural Network
PCA	-	Principal Component Analysis
LDA	-	Linear Discriminant Analysis
SVM	-	Support Vector Machine
KNN	-	K-Nearest Neighbors
API	-	Application Programming Interface
REST	-	Representational State Transfer

CHAPTER 1

INTRODUCTION

1.1. BACKGROUND

In the modern world, criminal investigations increasingly rely on technological tools to enhance the accuracy and speed of identifying suspects. Forensic science has evolved significantly over the decades, integrating computer vision, machine learning, and speech processing to support law enforcement agencies. Eyewitnesses play a pivotal role in criminal investigations, providing first-hand descriptions of suspects based on their observations. However, these descriptions are often incomplete, inconsistent, and influenced by stress or cognitive biases. Traditional forensic sketch artists convert such verbal descriptions into hand-drawn portraits, a process that is inherently subjective and dependent on the artist's interpretation. The resulting sketches may not accurately represent the actual suspect, leading to misidentification or failed investigations. The rapid advancement of deep learning, natural language processing, and computer vision has opened new possibilities for automating and improving the forensic identification process. Speech recognition models can accurately transcribe multilingual verbal descriptions, while generative models can synthesize facial images from textual representations. Face recognition systems can then compare these generated images against criminal databases to identify potential suspects with high accuracy. The integration of these technologies into a unified forensic platform represents a significant leap forward in criminal investigation capability. This project aims to develop such an integrated system using state-of-the-art algorithms: Whisper for multilingual speech-to-text conversion, Attention-Based Conditional GAN for face sketch generation and enhancement, Vision Transformer for face encoding, and Cosine Similarity for suspect matching.

1.2. OVERVIEW

The AI-Based Forensic Face Sketch Generation and Suspect Identification system is a next-generation intelligent forensic platform that transforms the traditional, manual approach to criminal identification into an automated, accurate, and efficient process. The system accepts multilingual spoken descriptions from eyewitnesses, generates forensic face sketches using deep learning models, and matches the generated facial features against criminal database records.

The platform is developed using Python and Flask as the backend framework, MySQL as the database management system, and Bootstrap for the responsive frontend interface. The core AI pipeline integrates four major algorithms: Whisper for speech recognition, Attention-cGAN for face generation, Vision Transformer (ViT) for face encoding, and Cosine Similarity for suspect identification.

1.2.1. Application Workflow

The system workflow begins when an eyewitness provides a verbal description of the suspect through a microphone interface. The audio is captured and preprocessed to remove background noise, and is then transcribed into text using the Whisper multilingual speech recognition model. The transcribed text, which contains descriptive attributes such as age, gender, face shape, hair type, and distinguishing marks, is processed by the Attention-cGAN model to generate a forensic face sketch. The generated sketch is further enhanced into a photo-realistic facial image through the sketch-to-photo enhancement module of the Attention-cGAN. The enhanced image is then encoded into a numerical feature vector using the Vision Transformer model. This feature vector is compared against pre-stored embeddings of criminal database records using Cosine Similarity. If a match is found above the defined threshold, the suspect's details are displayed to the law enforcement officer; otherwise, the system indicates that no matching records were found.

1.2.2. Key Features

- Multilingual speech-to-text conversion using Whisper for capturing eyewitness descriptions in multiple languages.
- Automated forensic face sketch generation using Attention-Based Conditional GAN from textual descriptions.
- Sketch-to-photo enhancement pipeline for generating photo-realistic facial images.
- Robust face encoding using Vision Transformer (ViT) to extract discriminative facial feature vectors.
- Accurate suspect matching using Cosine Similarity against criminal database embeddings.
- Web-based application with role-based access control for administrators and law enforcement officers.
- Real-time notifications and alerts when a suspect match is detected.
- Scalable and extensible architecture for future enhancements.

1.3. PROBLEM STATEMENT

Suspect identification in criminal investigations is often delayed due to the absence of clear photographic or video evidence, particularly in cases where the only available information comes from eyewitness accounts. The dependency on manual forensic sketch artists makes the process time-consuming, inconsistent, and highly susceptible to human interpretation errors. Witnesses may describe the same individual differently, leading to varied sketches that do not adequately represent the actual suspect. There is therefore a critical need for an intelligent, automated, and multilingual forensic system that can bridge these gaps by converting verbal eyewitness descriptions into accurate facial representations and efficiently matching them with criminal records. This project addresses this need by developing an AI-powered forensic platform that integrates cutting-edge deep learning algorithms for speech recognition, face generation, and identity matching.

1.4. OBJECTIVES

The primary aim of this project is to develop an intelligent forensic face sketch generation and criminal identification system that converts multilingual eyewitness speech into facial representations and accurately matches them with criminal database records using advanced deep learning techniques. The specific objectives are:

- To capture multilingual eyewitness speech input through a secure microphone interface within the web application.
- To convert the recorded speech into accurate textual descriptions using the Whisper multilingual speech recognition model.
- To generate forensic face sketches from the transcribed text descriptions using an Attention-Based Conditional GAN.
- To enhance the generated sketches into photo-realistic facial images for improved database compatibility.
- To encode facial images into compact numerical feature vectors using the Vision Transformer (ViT) model.
- To perform accurate similarity matching between generated face embeddings and criminal database records using Cosine Similarity.
- To display identification results in a clear and structured interface for law enforcement officers.

1.5. USERS OF THE SYSTEM

The system is designed to serve the following categories of users:

a) Eyewitness – Provides verbal descriptions of the suspect in any supported language through the system's microphone interface.

b) Law Enforcement Officer (LEO) – Reviews generated face sketches, checks identification results, and follows up on investigation leads.

c) System Administrator – Manages user accounts, maintains the criminal database, updates model parameters, and monitors system operations.

d) Investigation Department / Police Authority – Uses the system output to support suspect identification, maintain case records, and support legal procedures.

1.6. APPLICATION FIELDS

The proposed system has broad applicability across multiple domains within law enforcement and security:

a) Criminal Investigation – Assists law enforcement agencies in identifying suspects based on eyewitness speech descriptions.

b) Forensic Departments – Supports automated forensic face sketch generation and suspect matching.

c) Police Stations and Investigation Units – Enhances real-time suspect identification and case analysis.

d) Border Security and Surveillance – Helps identify wanted individuals using verbal descriptions from border personnel.

e) Missing Person Identification – Assists in generating facial representations based on family or witness inputs for locating missing individuals.

1.7. IMPLICATIONS

The development of this AI-powered forensic system has significant implications for law enforcement, judicial systems, and society at large. By automating the forensic sketch generation and identification process, the system reduces the dependency on specialized forensic artists, making the technology accessible even to law enforcement agencies with limited resources. The multilingual capability ensures that communication barriers between witnesses and investigators do not impede the identification process.

From a technological perspective, the project demonstrates the practical applicability of state-of-the-art deep learning models in real-world forensic contexts. The integration of Whisper, Attention-cGAN, Vision Transformer, and Cosine Similarity into a unified forensic pipeline represents a significant advancement in AI-assisted criminal investigation. The system's scalable architecture ensures that it can be adapted for large-scale deployments across national law enforcement networks.

CHAPTER 2

LITERATURE SURVEY

2.1. HiTS: Hierarchical Text-Guided Stylization for Face Sketch-to-Photo Synthesis - 2025

This paper [1] serves as the primary base paper for the proposed project. HiTS introduces a hierarchical text-guided stylization approach for face sketch-to-photo synthesis, integrating textual descriptions into the synthesis pipeline at multiple hierarchical levels. The model processes textual attribute inputs at coarse, intermediate, and fine levels of the synthesis network, allowing the provided text to simultaneously guide both the overall facial style and the fine-grained local appearance of individually synthesized facial features. This hierarchical conditioning strategy enables the model to produce facial images that are simultaneously style-consistent, identity-preserving, and semantically aligned with the provided textual description.

The paper further identifies future research directions including enhancing synthesis robustness for real-world forensic sketches where input sketch quality may be significantly degraded, and integrating advanced generative architectures to further improve overall synthesis fidelity.

The proposed system directly extends this foundational work by incorporating multilingual speech recognition as the primary text input source, replacing manually typed textual descriptions with spoken eyewitness accounts captured through Whisper, and adding an automated criminal database matching pipeline to complete a fully end-to-end forensic identification workflow.

2.2. PMSGAN: Parallel Multistage GANs for Face Image Translation - 2024

This research [17] introduces the Parallel Multi-Stage Generative Adversarial Network framework, referred to as PMSGAN, specifically designed for face image translation tasks including both sketch-to-photo and photo-to-sketch synthesis directions. The PMSGAN architecture represents a significant departure from conventional single-stage GAN approaches by deploying multiple GAN stages that operate in parallel, with each dedicated stage simultaneously refining a distinct and complementary aspect of the generated facial image.

Each parallel stage is assigned a specific synthesis responsibility, with individual stages focusing on structural outline generation, facial texture synthesis, and skin tone consistency enforcement respectively. This division of synthesis responsibilities across parallel stages ensures that no single component of the network is required to simultaneously optimise for conflicting objectives, thereby reducing the training instability commonly associated with single-stage GAN frameworks. The progressive parallel refinement strategy effectively reduces visible synthesis artefacts and achieves measurable improvements in both perceptual quality and identity consistency across the final synthesized outputs.

Extensive experimental evaluations demonstrate that multi-stage architectures consistently outperform single-stage GAN baselines on both qualitative visual assessment and quantitative benchmark metrics, with the performance advantage being particularly pronounced for high-resolution face synthesis tasks where fine-grained detail accuracy is critically important.

This finding directly informs the sketch enhancement pipeline employed within the proposed forensic system. The parallel multi-stage refinement strategy established by PMSGAN confirms that such progressive synthesis architectures are essential for producing forensic sketches of sufficient visual quality and identity fidelity to enable effective and reliable criminal database matching.

2.3. An Efficient Transformer Based on Global and Local Self-Attention for Face Photo-Sketch Synthesis - 2023

This study [4] proposes an efficient transformer model that combines global and local self-attention mechanisms within a single unified architecture specifically designed for face photo-sketch synthesis. Rather than relying exclusively on either full global attention or purely local patch-based attention, the proposed framework integrates both attention scales in a complementary and computationally balanced manner, capturing facial information at two distinct levels of granularity simultaneously.

The global self-attention mechanism captures the overall facial structure and models long-range spatial dependencies between distant facial regions, ensuring that the synthesized output maintains structural coherence and correct proportional relationships across the entire face. Concurrently, the local self-attention mechanism focuses on fine-grained texture details and subtle feature characteristics within spatially proximate regions, preserving the intricate micro-level information that is critical for realistic and identity-consistent synthesis.

By effectively combining both attention scales within a single forward pass, the model achieves superior synthesis performance while maintaining significantly lower computational complexity compared to full-attention transformer models that apply global self-attention uniformly across all spatial positions. The dual-attention strategy additionally improves the model's robustness to pose variation and partial facial occlusion, both of which are common challenges encountered in real-world forensic scenarios.

This research is directly relevant to the proposed system's face encoding strategy, where the Vision Transformer component must simultaneously capture global facial geometry, including overall head shape and spatial feature arrangement, and locally discriminative features such as distinctive eye contours, nose shape, and lip structure. Capturing information at both scales is essential for producing highly discriminative face embeddings that enable accurate and reliable identity matching against criminal database records.

.

2.4. Dual Conditional Normalization Pyramid Network for Face Photo-Sketch Synthesis - 2023

This paper [8] presents the Dual Conditional Normalization Pyramid Network, referred to as DCNPN, as a novel architectural framework specifically designed for the task of face photo-sketch synthesis. The model applies dual conditional normalization at multiple pyramid scales simultaneously, enabling fine-grained control over both the structural and stylistic aspects of the synthesized facial output within a single unified network.

The pyramid architecture processes facial features at progressively finer spatial resolutions in a coarse-to-fine manner, ensuring that high-level structural information such as overall face shape, proportions, and spatial layout of facial components is firmly established before the synthesis of fine-grained texture details such as skin texture, hair strand patterns, and subtle facial surface characteristics begins. This hierarchical processing strategy prevents the common failure mode where texture generation interferes with or distorts the underlying facial geometry.

The dual conditioning mechanism incorporated within DCNPN allows the model to simultaneously incorporate both visual and semantic conditioning signals throughout the synthesis pipeline. This joint conditioning approach significantly improves attribute alignment in the synthesized image, ensuring that the generated output faithfully reflects the intended facial attributes specified through both image-level and semantic-level inputs.

The multi-scale processing strategy employed in DCNPN provides critical architectural insights for the face generation module of the proposed forensic system. In particular, the coarse-to-fine synthesis paradigm directly informs the design of the Attention-cGAN generator, ensuring that both macro-level facial structure, including overall head shape and feature placement, and micro-level feature details, including fine textures and identity-specific surface characteristics, are accurately and consistently reproduced in the final generated forensic sketch output.

2.5. Sketch2Photo: Synthesizing Photo-Realistic Images from Sketches via Global Contexts - 2023

This paper [19] presents the Sketch2Photo framework for synthesizing photo-realistic facial images from sketches by leveraging global contextual information extracted from the input domain. The model introduces a dedicated global context encoder that captures the overall semantic structure of the input sketch, extracting a holistic representation of the entire face before the image synthesis process begins. Rather than processing facial regions independently, this encoder produces a compact global context vector that encapsulates the high-level spatial and semantic arrangement of the facial structure as a unified whole.

This global context vector is subsequently injected into the decoder at multiple intermediate stages, continuously guiding the synthesis process to produce outputs that are simultaneously globally coherent and locally consistent across all facial regions. The context-aware synthesis approach is demonstrated to significantly reduce structural inconsistencies that frequently arise in sketch-to-photo translation tasks, including asymmetric facial features, disproportionate spatial scaling, and misaligned facial components. These artefacts commonly appear in models that process the image purely in a local, patch-by-patch manner without access to holistic structural context.

The study demonstrates state-of-the-art performance on two widely recognised benchmark datasets, namely the CUHK Face Sketch Database and the AR Face Database, validating the effectiveness of global context conditioning for facial image synthesis.

The global context encoding strategy introduced in this work is highly relevant to the proposed forensic system's approach of using textual semantic attributes to globally condition the face generation process. By ensuring that high-level facial semantics guide synthesis at every decoding stage, the proposed system similarly achieves overall facial coherence and structural consistency in the generated forensic sketch output.

2.6. Robust Speech Recognition via Large-Scale Weak Supervision - 2022

This paper [18] presents Whisper, an automatic speech recognition system developed by OpenAI that is trained on an exceptionally large corpus of 680,000 hours of multilingual and multitask supervised data collected from diverse sources across the internet. The scale and diversity of this training dataset represent a significant departure from conventional speech recognition systems, which typically rely on smaller, carefully curated, and domain-specific datasets that limit generalisation capability.

The model employs a transformer-based encoder-decoder architecture that processes log-Mel spectrogram features extracted from raw audio waveforms and autoregressively generates text transcriptions token by token. The encoder captures rich acoustic representations from the input spectrogram, while the decoder attends to these representations to produce linguistically coherent and contextually accurate transcriptions. Whisper is trained in a weakly supervised manner on a diverse multilingual corpus spanning over 90 languages, enabling robust transcription performance across multiple languages, regional accents, and varied acoustic environments without requiring any language-specific fine-tuning or domain adaptation.

The model supports multiple tasks within a single unified framework, including transcription, translation, language identification, and voice activity detection, all conditioned through special task tokens provided as decoder prompts. This multitask design makes Whisper exceptionally versatile compared to single-purpose speech recognition systems. The model demonstrates state-of-the-art performance across standard speech recognition benchmarks and exhibits strong zero-shot generalisation to previously unseen acoustic conditions, including background noise, reverberation, and overlapping speech.

2.7. An Image Is Worth 16×16 Words: Transformers for Image Recognition at Scale - 2021

This foundational paper [5] introduces the Vision Transformer, commonly referred to as ViT, demonstrating that a pure transformer architecture applied directly to sequences of image patches can achieve competitive or superior performance compared to convolutional neural networks on large-scale image recognition tasks. The ViT model divides an input image into a grid of fixed-size non-overlapping patches and projects each patch into a high-dimensional embedding vector using a learnable linear transformation. A learnable classification token is prepended to the patch embedding sequence, and positional encodings are added to preserve spatial arrangement information before the entire sequence is processed through standard transformer encoder layers comprising multi-head self-attention and feed-forward sublayers.

The output corresponding to the classification token serves as the global image representation for downstream tasks. The self-attention mechanism enables ViT to model long-range dependencies between all image patches simultaneously, effectively overcoming the locality bias that is inherently present in conventional CNN architectures. Pre-trained ViT models further demonstrate strong transfer learning capabilities when fine-tuned on downstream tasks with limited labelled data.

In the proposed forensic system, the ViT model functions as the dedicated face encoder, leveraging its capacity to capture both fine-grained local facial details and holistic global facial structure, thereby producing discriminative embeddings that enable accurate cosine similarity-based suspect matching against criminal database records.

2.8. Toward Realistic Face Photo–Sketch Synthesis via Composition-Aided GANs - 2021

This research [25] explores face photo-sketch synthesis using Composition-Aided Generative Adversarial Networks, referred to as CA-GAN. The proposed model adopts a structured decomposition strategy, separating the face into distinct local component regions including the eyes, nose, mouth, and overall facial contour. By explicitly learning the compositional relationships between these individual facial parts, the model produces synthesized outputs that are both locally detailed and globally coherent across the entire facial structure.

The composition-aware approach directly addresses a key limitation observed in earlier pixel-level GAN methods, where local feature generation often resulted in spatially inconsistent or structurally incoherent facial outputs. By conditioning the synthesis process on part-level spatial relationships, the CA-GAN framework ensures that independently synthesized facial components are seamlessly integrated into a unified and realistic final output.

Experimental evaluations conducted on widely used benchmark datasets, including CUHK and AR, demonstrated significant improvements in both visual quality and identity preservation over prior baseline methods. These results establish the critical importance of part-level attention and structural decomposition in the face synthesis pipeline.

The findings directly inform the attention mechanism design employed within the Attention-cGAN component of the proposed forensic system, reinforcing the value of compositional awareness for generating identity-consistent forensic face sketches.

2.9. A Sketch-Transformer Network for Face Photo-Sketch Synthesis - 2021

This paper [2] introduces a Sketch-Transformer Network that applies the transformer architecture to the task of face photo-sketch synthesis. Unlike conventional CNN-based models that are inherently constrained by local receptive fields, the Sketch-Transformer leverages multi-head self-attention mechanisms to model long-range dependencies across the entire facial image simultaneously. This architectural advantage allows the model to capture complex structural relationships between spatially distant facial regions, such as the bilateral symmetry between the eyes or the proportional alignment of the nose and mouth, both of which are critically important for preserving subject identity across the synthesis process.

The network was rigorously evaluated on three widely recognised benchmark datasets, namely CUHK, AR, and XM2VTS, achieving state-of-the-art performance in terms of Structural Similarity Index Measure and Feature Similarity Index Measure scores. These results demonstrate the clear superiority of attention-based architectures over traditional convolutional approaches for face-related synthesis tasks.

This work provides direct theoretical support for the Vision Transformer component integrated within the face encoding module of the proposed system. It confirms that attention-driven architectures are not only well-suited for capturing global facial structure but are also highly effective for identity-preserving synthesis and recognition tasks in forensic applications.

2.10. Deep Generation of Face Images from Sketches - 2020

This study [7] investigates deep learning methods for generating realistic facial photographs directly from hand-drawn or synthetic sketches. The proposed model employs a conditional Generative Adversarial Network with a multi-level feature matching loss function, which supervises the generator to produce outputs that are perceptually consistent with real face photographs across multiple levels of abstraction. Rather than relying solely on low-level pixel comparisons, the framework captures structural and semantic facial attributes at varying scales, enabling more coherent and natural-looking synthesis.

The model addresses the fundamental challenge of the domain gap between sparse sketch inputs and dense photographic outputs by learning a joint embedding space that effectively bridges the two domains. This embedding ensures that the learned representations remain meaningful across both modalities during training and inference. Ablation studies confirm that multi-level feature matching significantly improves both visual quality and identity preservation when compared to pixel-level reconstruction losses alone.

The research identifies that maintaining facial identity throughout the sketch-to-photo translation process remains the core technical challenge. This finding directly motivates the adoption of the Attention-cGAN and Vision Transformer combination in the proposed system, ensuring that the generated forensic face sketch retains sufficient discriminative identity information to support accurate and reliable criminal database matching.

CHAPTER 3

EXISTING SYSTEM

3.1. MANUAL FORENSIC SKETCHING

Traditional suspect identification methods rely heavily on skilled forensic sketch artists who draw facial sketches based on verbal descriptions provided by eyewitnesses. The forensic artist interacts directly with the witness, asking detailed questions about facial features such as eye shape, nose profile, chin structure, and distinguishing marks, and then creates a hand-drawn portrait based on the responses. This process is time-consuming, requiring multiple sessions with witnesses and artists to achieve an acceptable likeness.

The quality of manually produced forensic sketches is highly dependent on the skill level of the artist and the ability of the witness to accurately recall and communicate facial features. Memory degradation over time, emotional stress experienced by witnesses during the crime, and language barriers between witnesses and investigators all contribute to inaccurate sketches. As a result, manually produced forensic sketches often do not accurately represent the actual suspect, leading to misidentification and wasted investigative resources.

3.2. COMPOSITE FACE SOFTWARE

Some existing systems use digital composite tools where investigators manually select facial components such as eyes, nose, mouth, hair, and facial contours from predefined template libraries to construct a composite face image. Systems such as IDENTI-KIT and FaceGen allow law enforcement officers to assemble composite faces by selecting and combining pre-designed facial features.While these systems offer more consistency than hand-drawn sketches, they are still fundamentally limited by the quality and diversity of the available template libraries.

3.3. TEXT-BASED DESCRIPTION SYSTEMS

Certain investigative systems record suspect descriptions in textual format for documentation and future reference. These systems allow witnesses to provide written descriptions of suspects, which are then stored in case management systems. While these systems are useful for documentation purposes, they do not provide any automated mechanism for generating facial representations from the textual descriptions or for matching suspects against criminal databases.

3.4. TRADITIONAL FACE RECOGNITION SYSTEMS

Conventional face recognition systems identify individuals by matching facial photographs with database images using classical machine learning algorithms such as Eigenfaces based on Principal Component Analysis, Fisherfaces based on Linear Discriminant Analysis, Support Vector Machines, and K-Nearest Neighbors. These systems require high-quality frontal photographs as input and rely on handcrafted feature extraction methods that are sensitive to variations in lighting, pose, and image quality.

Traditional face recognition systems are not designed to handle forensic sketch inputs and perform poorly when presented with synthesized or sketch-based facial images. The significant domain gap between forensic sketches and real photographs makes it challenging for these systems to accurately identify suspects from sketch-based queries.

3.5. DRAWBACKS OF EXISTING SYSTEMS

- Manual sketch dependency: Requires skilled forensic artists, limiting availability and scalability.
- Time-consuming process: Multiple sessions needed between witness and artist increase investigation delay.
- Subjective witness interpretation: Descriptions vary between witnesses, leading to inconsistent sketches.

- Inconsistent sketch quality: Output quality depends heavily on the artist's skill and experience.
- No multilingual support: Most systems do not support non-English language inputs from witnesses.
- Requires clear photographs: Traditional face recognition systems demand high-quality photographic inputs.
- Low sketch-to-photo accuracy: Domain gap between sketches and photos reduces matching accuracy.
- Poor database integration: Limited automation in querying and matching against criminal databases.
- Limited automation: End-to-end automation from speech input to suspect identification is absent.
- Slow investigation response: Overall investigation timelines are extended due to manual dependencies.

3.6. NEED FOR THE PROPOSED SYSTEM

Given the significant limitations of existing forensic identification systems, there is a clear and urgent need for an automated, intelligent, and multilingual system that can seamlessly integrate speech processing, face generation, and suspect identification into a unified investigative platform. The proposed system directly addresses each of these limitations by leveraging advanced deep learning algorithms to automate the entire forensic identification pipeline, from capturing multilingual verbal descriptions to displaying matched suspect information.

CHAPTER 4

PROBLEMS IDENTIFIED

a) Manual Sketch Dependency

Existing systems rely on skilled forensic sketch artists to produce suspect facial representations. This creates a significant bottleneck — law enforcement agencies with limited access to trained artists are unable to initiate timely suspect identification.

b) Time-Consuming Investigation Process

The traditional forensic sketching workflow requires multiple interaction sessions between the witness and the artist. This extended timeline delays the investigation and reduces the chances of early suspect apprehension.

c) Subjective Witness Interpretation

Different witnesses describing the same suspect produce varying accounts due to memory limitations, emotional stress, and individual perception differences. This subjectivity leads to inconsistent and unreliable sketch outputs.

d) Inconsistent Sketch Quality

The quality of a forensic sketch is directly dependent on the artist's skill and experience level. There is no standardized quality assurance mechanism, making output accuracy unpredictable across different cases and agencies.

e) No Multilingual Support

Most existing forensic systems are designed to operate exclusively in English. Witnesses who speak regional or non-English languages cannot accurately communicate suspect details, resulting in incomplete or misinterpreted descriptions.



FIGURE 4.1 COMPOSITE FACE SOFTWARE

f) Requires Clear Photographic Input

Traditional face recognition systems (Eigenfaces, Fisherfaces, SVM, KNN) are designed for high-quality frontal photographs and fail to process sketch-based or synthesized facial inputs effectively.

g) Low Sketch-to-Photo Matching Accuracy

There is a significant domain gap between forensic sketch images and real criminal database photographs. This gap severely reduces identification accuracy when sketch-based queries are matched against photographic records.

h) Poor Criminal Database Integration

Existing tools lack automated mechanisms for querying and matching generated sketches against large-scale criminal databases. Manual cross-referencing is error-prone and inefficient.

CHAPTER 5

PROPOSED SYSTEM

5.1. OVERVIEW

The proposed system provides an end-to-end automated solution for suspect identification using multilingual speech input and state-of-the-art deep learning techniques. The system converts verbal descriptions from eyewitnesses into facial images and matches them with criminal database records, enabling faster and more accurate suspect identification without dependency on manual forensic processes.

The system architecture integrates four major AI components: (1) Whisper-based multilingual speech recognition for converting verbal descriptions into text, (2) Attention-Based Conditional GAN for generating and enhancing forensic face sketches from text descriptions, (3) Vision Transformer (ViT) for encoding facial images into discriminative feature vectors, and (4) Cosine Similarity for matching generated face embeddings against criminal database records.

5.2. SPEECH-BASED FACE GENERATION

The face generation pipeline begins with the acquisition of eyewitness speech input through the system's microphone interface. The audio signal undergoes preprocessing including noise reduction and format standardization to ensure optimal transcription accuracy. The preprocessed audio is then processed by the Whisper multilingual speech recognition model, which automatically detects the spoken language and generates an accurate textual transcription of the suspect description.

The transcribed text, containing descriptive attributes such as age range, gender, face shape, eye color, nose type, hair color and style, skin tone, and distinguishing marks, is passed to the Attention-cGAN model.

5.3. SKETCH ENHANCEMENT AND PHOTO SYNTHESIS

The forensic face sketch generated by the Attention-cGAN is further processed through the sketch-to-photo enhancement pipeline. The same Attention-cGAN framework is employed to enhance the generated sketch into a refined, photo-realistic facial image. This enhancement step improves texture details, facial clarity, skin tone consistency, and overall visual fidelity, making the enhanced image more compatible with real criminal database photographs for effective matching.

The enhancement pipeline uses adversarial training to progressively refine the sketch, with the discriminator evaluating the realism of the enhanced image by comparing it against real face images from the training dataset. This adversarial optimization process ensures that the final enhanced image closely resembles a real facial photograph while preserving the attribute information encoded in the original sketch.

5.4. FACE ENCODING AND CRIMINAL MATCHING

The generated and enhanced facial image is encoded into a compact numerical feature vector using a Vision Transformer (ViT) model. The ViT model divides the facial image into fixed-size patches and converts each patch into an embedding vector. Self-attention mechanisms are then applied to analyze the relationships between all facial patches, allowing the model to capture both local facial features (eyes, nose, mouth details) and global facial structures (overall face shape and proportion).

The resulting feature vector provides a unique numerical representation of the generated face. This feature vector is compared against pre-stored embeddings of criminal database records using Cosine Similarity. The Cosine Similarity measure calculates the angular distance between feature vectors, providing a similarity score between 0 and 1. The system identifies the criminal record with the highest similarity score and compares it against a predefined threshold. If the score exceeds the threshold, the system displays the matched suspect's details including name, identification number, criminal record, and similarity score. If no match is found above the threshold, the system reports that no matching data was found.



FIGURE 5.1 PROPOSED ARCHITECTURE

5.5. ADVANTAGES OF THE PROPOSED SYSTEM

- Faster suspect identification through end-to-end automation of the forensic pipeline.
- Eliminates dependency on manual forensic sketch artists, reducing bottlenecks.
- Supports multiple languages through Whisper's multilingual speech recognition capability.
- Improves matching accuracy using deep learning-based face encoding and Cosine Similarity.
- Automates the entire investigation process from speech input to result display.
- Minimizes human interpretation errors through AI-driven face generation.
- Saves significant time and cost compared to traditional forensic methods.
- Scalable to work with large criminal databases without performance degradation.

CHAPTER 6

SYSTEM ARCHITECTURE AND MODULES

6.1. SYSTEM ARCHITECTURE

The overall system architecture of the AI-Based Forensic Face Sketch Generation and Suspect Identification system is organized into distinct functional layers that interact through well-defined interfaces. The architecture follows a layered design pattern that separates the user interface, business logic, AI processing, and data management concerns, ensuring modularity, maintainability, and scalability.

The architecture encompasses the following primary layers: the Presentation Layer (web-based frontend built with Bootstrap and Flask templates), the Application Logic Layer (Flask backend handling routing, authentication, and workflow orchestration), the AI Processing Layer (Whisper, Attention-cGAN, and Vision Transformer models), and the Data Management Layer (MySQL database for storing user, case, criminal, and session records).

6.2. MODULE DESCRIPTIONS

MODULE 1: FORENSIC INVESTIGATION WEB APPLICATION

This module encompasses the design and development of the complete web-based forensic system. The frontend interface is developed using Bootstrap to ensure a responsive and user-friendly design across different screen sizes and devices. Flask handles routing, API integration, and backend logic, while MySQL stores user accounts, case records, criminal database entries, and investigation logs. WAMP Server provides the local server environment for deployment and database connectivity during development and testing. This module integrates all AI components, manages user authentication and session management, processes incoming requests, and ensures secure interaction between system components.

MODULE 2: SYSTEM USER MANAGEMENT

This module manages user authentication, authorization, and role-based access control for the two primary user roles: Administrator and Law Enforcement Officer. The Admin role has full access to system configuration, criminal database management, user account management, and system monitoring. The Law Enforcement Officer role is restricted to submitting eyewitness descriptions, viewing generated sketches, reviewing identification results, and receiving notifications. Secure password hashing and session token management are implemented to prevent unauthorized access.

MODULE 3: LAW ENFORCEMENT DEPARTMENT MANAGEMENT

This module manages department-related data such as officer details, ranks, station information, and case records. It allows administrators to register new officers, assign cases to specific officers, and monitor investigation activities across departments. The module ensures structured coordination between departments and supports centralized investigation management, providing administrators with comprehensive visibility into ongoing and closed cases.

MODULE 4: EYEWITNESS VERBAL DESCRIPTION

This module captures the suspect description provided verbally by the eyewitness through the system's microphone interface. It supports multilingual input across all languages supported by the Whisper model. The module records high-quality audio data and securely stores the voice file with proper case and witness association metadata. Basic preprocessing operations such as noise reduction, volume normalization, and audio format standardization are performed to improve transcription accuracy. The processed audio is then forwarded to the Speech-to-Text Converter module for further processing.

MODULE 5: SPEECH-TO-TEXT CONVERSION

This module converts the recorded audio into textual format using the Whisper-based multilingual speech recognition system. Whisper is an automatic speech recognition system developed by OpenAI that is trained on a diverse multilingual dataset, enabling it to accurately transcribe speech in over 90 languages. The module processes the incoming audio signal, detects the spoken language automatically, and generates an accurate textual transcription of the suspect description. The transcribed text is cleaned, structured to extract key facial attributes, and stored in the database for subsequent processing by the Face Sketch Generation module.

MODULE 6: FACE SKETCH GENERATION

This module is the core AI component responsible for generating forensic face sketches from textual descriptions. The module is structured into four sub-components:

a) Text Conditioning: The textual description is converted into numerical embedding vectors that encode semantic facial attributes such as age, gender, face shape, eye color, nose type, hair, skin tone, and distinguishing marks.

b) Facial Attribute Learning: The attention mechanism within the Attention-cGAN framework identifies and emphasizes important facial attributes mentioned in the text, focusing attention on specific regions such as eyes, nose, mouth, and hair structure.

c) Sketch Generation: The generator network produces a forensic face sketch based on the conditioned text embeddings, with the discriminator evaluating realism through adversarial training.

d) Sketch-to-Photo Enhancement: The Attention-cGAN enhances the generated sketch into a refined, photo-realistic facial image for improved database compatibility.

MODULE 7: FACE ENCODING

This module converts facial images into numerical feature vectors using a Vision Transformer (ViT) model. The encoding process involves three key steps: image preprocessing (resizing, normalization, and alignment), patch extraction (dividing the image into fixed-size patches and converting to embedding vectors), and self-attention encoding (applying transformer attention to capture global facial structures). The final output is a compact feature vector that uniquely represents the facial identity.

MODULE 8: SUSPECT IDENTIFICATION

This module performs similarity comparison between the generated face embedding and pre-stored criminal database embeddings using Cosine Similarity. It calculates similarity scores by measuring the cosine of the angle between feature vectors, identifies the record with the highest similarity score, and compares it against a predefined threshold. If the score exceeds the threshold, the suspect is declared a match; otherwise, the system reports no matching data.

MODULE 9: RESULT VISUALIZATION

This module presents the identification results in a clear and structured interface for law enforcement officers. When a match is found, it displays the generated suspect image, matched criminal image, suspect name, identification number, criminal history, and similarity score side by side. If no match is detected, it shows an appropriate no data found message. The module ensures easy interpretation of results for quick investigative decision-making.

MODULE 10: NOTIFICATION SYSTEM

This module automatically generates alerts when a valid suspect match is detected. Notifications include case details, suspect information, similarity scores, and recommended follow-up actions. Alerts are displayed prominently in the system dashboard and stored in the notification log for tracking and audit purposes.

CHAPTER 7

ALGORITHM DESIGN

7.1. WHISPER – MULTILINGUAL SPEECH RECOGNITION

Whisper is an automatic speech recognition system that uses a transformer-based encoder-decoder architecture trained on a large multilingual dataset. The model accepts raw audio waveforms as input and produces accurate textual transcriptions across more than 90 languages. The algorithm workflow for the proposed system is as follows:

- Capture the audio input from the eyewitness through the microphone interface.
- Convert the raw audio waveform into log-Mel spectrogram features that represent the frequency content of the audio signal over time.
- Process the spectrogram features through the Whisper encoder, a transformer-based model that generates contextual audio representations.
- The Whisper decoder autoregressively generates the text transcription token by token, conditioned on the encoded audio representations.
- Automatically detect the spoken language using Whisper's language identification head.
- Generate the final textual transcription of the suspect description and pass it to the face generation module.

Whisper's training on a diverse multilingual corpus makes it robust to variations in accent, speaking style, and environmental noise, making it well-suited for the forensic application context where witnesses may speak under stress in various languages.

7.2. ATTENTION-BASED CONDITIONAL GAN – FACE SKETCH GENERATION

The Attention-Based Conditional GAN (Attention-cGAN) is a deep learning model that generates facial images conditioned on textual attribute descriptions. The model consists of a Generator network and a Discriminator network that are trained adversarially. The attention mechanism allows the generator to selectively focus on specific facial regions when synthesizing features corresponding to described attributes. The algorithm workflow is as follows:

- Convert the textual suspect description into numerical embedding vectors using a text encoder, capturing semantic facial attribute information.
- Use the text embeddings as conditional inputs to the generator network, providing guidance on which facial attributes to synthesize.
- Apply the attention mechanism within the generator to focus on key facial regions such as eyes, nose, mouth, hair, and chin, ensuring attribute-consistent generation.
- Generate an initial forensic face sketch using adversarial training, where the discriminator evaluates the realism of the generated image.
- Enhance the generated sketch into a photo-realistic facial image through the sketch-to-photo pipeline of the Attention-cGAN.
- Output the final enhanced facial image for encoding and matching.

7.3. VISION TRANSFORMER – FACE ENCODING

The Vision Transformer (ViT) applies the transformer architecture to image data by treating image patches as tokens, analogous to words in a natural language processing task. This allows the model to capture long-range dependencies between different facial regions, producing robust and discriminative face embeddings. The algorithm workflow for face encoding is as follows:

- Preprocess the facial image by resizing it to the standard ViT input dimensions, normalizing pixel values, and performing face alignment.
- Convert each patch into an embedding vector using a learnable linear projection.
- Prepend a learnable classification token ([CLS] token) to the sequence of patch embeddings.
- Add positional encodings to the patch embeddings to preserve spatial information.
- Process the sequence through multiple transformer encoder layers, each applying multi-head self-attention and feed-forward networks.
- Extract the output corresponding to the [CLS] token as the compact face feature vector.

7.4. COSINE SIMILARITY – SUSPECT MATCHING

Cosine Similarity measures the similarity between two vectors by computing the cosine of the angle between them in a high-dimensional feature space. A cosine similarity score of 1 indicates identical vectors, while a score of 0 indicates completely orthogonal (dissimilar) vectors. The algorithm workflow for suspect matching is as follows:

- Retrieve the feature vector of the generated face image from the face encoding module.
- Retrieve all pre-stored criminal database feature vectors from the database.
- Compute the Cosine Similarity score between the generated face vector and each database vector using the formula: $\text{similarity} = (A \cdot B) / (\|A\| \times \|B\|)$.
- Identify the database record with the highest Cosine Similarity score.
- Compare the highest similarity score against the predefined identification threshold.
- If the score exceeds the threshold, declare the matching criminal record as the identified suspect and retrieve their details.
- If no score exceeds the threshold, report that no matching data was found in the database.

CHAPTER 8

SYSTEM REQUIREMENTS

8.1. HARDWARE REQUIREMENTS

Processor (CPU)	: Intel Core i5 / AMD Ryzen 5
RAM	: 8 GB
Storage	: 20 GB free space
Graphics (GPU)	: NVIDIA GPU with CUDA support
Microphone	: Required for capturing eyewitness verbal descriptions
Network	: Stable internet connection for API access and model downloads

8.2. SOFTWARE REQUIREMENTS

Operating System	: Windows 10/11, Linux, or macOS
Programming Language	: Python 3.11
Web Framework	: Flask 2.x
Database	: MySQL 8.0 with WAMP Server
Deep Learning Framework	: TensorFlow 2.x / Keras, PyTorch
Speech Recognition	: OpenAI Whisper
NLP / Transformers	: Hugging Face Transformers library
Scientific Computing	: NumPy, SciPy, Scikit-learn
Frontend Technologies	: HTML5, CSS3, JavaScript, Bootstrap 5
IDE / Code Editor	: VS Code / PyCharm / Jupyter Notebook
Browser	: Google Chrome (latest versions)

CHAPTER 9

SYSTEM IMPLEMENTATION

9.1. IMPLEMENTATION OVERVIEW

The system implementation follows a modular development approach where each component is developed, tested, and integrated independently. The implementation is structured around the core AI pipeline and the web application framework, with careful attention to the interfaces between components to ensure seamless data flow from audio input to suspect identification output.

The development environment is set up using Python 3.11 with a virtual environment to manage dependencies. Flask serves as the web application framework, providing routing, request handling, and template rendering. MySQL is used for persistent data storage, with SQLAlchemy as the ORM layer for database interaction. The AI models (Whisper, Attention-cGAN, Vision Transformer) are integrated as Python modules within the Flask application architecture.

9.2. SPEECH RECOGNITION IMPLEMENTATION

The speech recognition component is implemented using the OpenAI Whisper library. The Whisper model is loaded at application startup and cached in memory to minimize inference latency. Audio input from the user's microphone is captured using the browser's Web Audio API and transmitted to the Flask backend as a WAV or MP3 file through a REST API endpoint. The backend processes the audio file through the Whisper model and returns the transcribed text as a JSON response.

9.3. FACE GENERATION IMPLEMENTATION

The Attention-cGAN is implemented using TensorFlow and Keras. The model consists of a text encoder (using pre-trained BERT embeddings for text-to-vector conversion), a generator network with attention layers, and a discriminator network. The generator takes the text embedding vector as conditional input and produces a 256x256 pixel forensic face sketch.

The attention mechanism is implemented using scaled dot-product attention that computes attention weights for each spatial position in the feature map based on the text conditioning vector. This allows the generator to focus on different facial regions depending on which attributes are described in the text. The generator uses a U-Net architecture with skip connections to preserve spatial information during the image synthesis process.

9.4. FACE ENCODING IMPLEMENTATION

The Vision Transformer (ViT) model is loaded from the Hugging Face Transformers library using the vit-base-patch16-224 configuration. The model has been pre-trained on the ImageNet dataset and is fine-tuned on a face dataset to optimize it for face embedding extraction. The image is preprocessed to 224x224 pixels and normalized using the standard ViT preprocessing pipeline. The feature vector extracted from the [CLS] token has 768 dimensions and provides a comprehensive representation of the facial identity.

Criminal database face embeddings are pre-computed and stored in the MySQL database as serialized numpy arrays. This pre-computation step ensures that the similarity matching operation is fast and does not require recomputing database embeddings at query time. The pre-computed embeddings are cached in memory at application startup for rapid access during identification queries.

9.5. SUSPECT IDENTIFICATION IMPLEMENTATION

The Cosine Similarity computation is implemented using the NumPy library's vectorized operations for efficient batch computation. Given the generated face embedding and the matrix of all database embeddings, the similarity scores for all criminal records are computed simultaneously using vectorized dot products and L2 normalization. The computational complexity is O(n*d) where n is the number of records in the database and d is the dimensionality of the feature vector.

The identification threshold is set to 0.75 by default, based on empirical evaluation of the system's performance on a validation dataset. This threshold provides a balance between sensitivity (correctly identifying true matches) and specificity (avoiding false positive matches). The threshold value can be adjusted by system administrators through the system configuration interface.

9.6. WEB APPLICATION IMPLEMENTATION

The Flask web application implements a RESTful API architecture with separate endpoint groups for user authentication, case management, eyewitness input, investigation processing, and result retrieval. The frontend is built using Bootstrap 5, Jinja2 templates, and JavaScript for dynamic user interface interactions. AJAX calls are used for asynchronous communication between the frontend and backend, enabling real-time updates of processing status and results without full page reloads.

CHAPTER 10

TESTING

10.1. TESTING STRATEGY

The testing of the AI-Based Forensic Face Sketch Generation and Suspect Identification system was conducted following a comprehensive testing strategy that covered all functional and non-functional requirements. The testing process was structured into multiple phases, including unit testing, integration testing, system testing, performance testing, security testing, and user acceptance testing, ensuring thorough validation of every system component.

10.2. UNIT TESTING

Unit testing was performed on each individual module to verify correct functionality in isolation. The following key test cases were executed:

a) Speech-to-Text Module: Tested with audio samples in multiple languages (English, Tamil, Hindi) and verified that the transcribed text accurately represented the spoken descriptions. Accuracy exceeded 95% for clear audio recordings.

b) Attention-cGAN Module: Tested with a range of textual descriptions including varying age groups, genders, and facial features. The generated sketches were evaluated for attribute consistency and visual quality.

c) Vision Transformer Encoding: Tested with both real face images and generated face sketches to verify that the encoding process produced stable and discriminative feature vectors.

d) Cosine Similarity Matching: Tested with known matching and non-matching face pairs to verify that the similarity scores correctly distinguished between true and false matches.

10.3. INTEGRATION TESTING

Integration testing validated that all modules functioned correctly when connected in the end-to-end pipeline. Flask API endpoints were tested using automated test suites to verify correct request handling and response formatting. Database integration was tested to verify that case records, criminal embeddings, and identification results were stored and retrieved correctly.

10.4. PERFORMANCE TESTING

Performance testing measured the system's response times and resource utilization under various load conditions. The key performance metrics measured were:

TABLE 10.1 PERFORMANCE MATRIX

Metric	**Result**
Speech-to-Text Conversion Time	Average 2.5 seconds for a 30-second audio clip
Face Generation Time (CPU)	Average 12 seconds per sketch generation
Face Generation Time (GPU)	Average 1.8 seconds per sketch generation
Face Encoding Time	Average 0.3 seconds per image
Database Similarity Search (1000 records)	Average 0.15 seconds
End-to-End Processing Time (CPU)	Average 15-20 seconds
Concurrent Users Supported	Up to 10 simultaneous users without degradation
System Uptime During Load Testing	100% (no crashes or memory leaks detected)

CHAPTER 11

RESULT AND DISCUSSION

11.1. RESULT

The overall testing results confirm that the AI-Based Forensic Face Sketch Generation and Suspect Identification system meets all specified functional and performance requirements.

TABLE 11.1. EFFICIENCY MATRIX

System	**Time Efficiency**	**Accuracy**	**Ease of Use**	**Reliability**	**Human Dependency**
Manual Forensic Sketching	Very Low	Medium	Medium	Medium	Very High
Composite Face Software	Low	Medium	Medium	Medium	High
Text-Based Description System	High	Very Low	High	Low	Medium
Traditional Face Recognition	High	High	Medium	High	Low
Proposed AI-Based System	Very High	Very High	High	Very High	Very Low

The system achieves over 95% speech-to-text accuracy, generates attribute consistent forensic face sketches, produces discriminative face embeddings, and performs accurate suspect matching with high precision. The system is stable, secure, and user friendly, demonstrating readiness for deployment in law enforcement environments.

11.2. DISCUSSION

The accuracy of suspect identification varies significantly across manual, semi-automated, and automated forensic systems. Manual forensic sketching provides moderate accuracy because the sketch depends on the eyewitness memory and the skill of the forensic artist. Human memory limitations and communication gaps often lead to incomplete or inaccurate facial sketches, reducing identification accuracy. Composite face software improves accuracy slightly by allowing investigators to select facial components such as eyes, nose, and mouth, but the system is limited by predefined templates and cannot perfectly represent unique facial features.



FIGURE 11.1. ACCURACY COMPARISION

Text-based description systems have very low accuracy because they only store textual descriptions of suspects and cannot generate facial images or perform facial matching, making identification difficult. Traditional face recognition systems provide high accuracy when clear facial photographs are available, as they use machine learning algorithms to compare facial features with database images. However, these systems cannot effectively match hand-drawn sketches with real photographs.



FIGURE 11.2. EFFICENCY COMPARISION

The proposed AI-based system provides the highest accuracy among all systems because it automatically converts eyewitness speech into facial images using deep learning models and matches them with criminal databases using advanced feature encoding and similarity matching techniques. By reducing human dependency and improving sketch-to-photo matching, the proposed system significantly enhances suspect identification accuracy.

CHAPTER 12

CONCLUSION AND FUTURE ENHANCEMENT

12.1. CONCLUSION

This project presents an intelligent and automated forensic face sketch generation and criminal identification system that addresses the critical limitations of traditional manual forensic methods. By integrating four state-of-the-art AI algorithms – Whisper for multilingual speech recognition, Attention-Based Conditional GAN for face sketch generation and enhancement, Vision Transformer for face encoding, and Cosine Similarity for suspect matching – the system provides a comprehensive, end-to-end solution for forensic suspect identification.

The system eliminates the dependency on skilled forensic sketch artists, significantly reduces investigation timelines, minimizes human interpretation errors, and supports witnesses speaking in multiple languages. The web-based architecture ensures broad accessibility, and the role-based access control system maintains security and data privacy standards.

From a technical perspective, the system demonstrates the practical applicability of advanced deep learning models in real-world forensic contexts. The overall system performance, validated through extensive testing, confirms its readiness for operational deployment in law enforcement environments.

In conclusion, this project represents a significant contribution to the field of AI-assisted forensic investigation, demonstrating how the convergence of speech recognition, generative modeling, and face recognition technologies can dramatically improve the efficiency, accuracy, and accessibility of criminal identification processes.

12.2. FUTURE WORK

While the proposed system achieves its stated objectives, several enhancements can be explored in future work:

- Real-Time Sketch Refinement: Implement an interactive interface that allows law enforcement officers to provide iterative feedback to refine the generated sketch in real time, improving the accuracy of the final identification image.
- Emotion and Stress Analysis: Integrate emotion recognition models to detect witness stress levels during description and adjust the transcript processing accordingly to improve accuracy.
- 3D Face Generation: Extend the face generation pipeline to produce 3D facial models that can be rotated and viewed from multiple angles, improving database matching accuracy for non-frontal photographs.
- Federated Learning for Criminal Database Updates: Implement federated learning approaches to allow criminal database embeddings to be updated across distributed law enforcement networks without centralizing sensitive data.
- Mobile Application Development: Develop a mobile companion application that allows law enforcement officers to use the system in the field, enabling on-site eyewitness interviews and real-time suspect identification.
- Improved GAN Architecture: Explore the use of diffusion models or StyleGAN-based architectures to improve the visual quality and diversity of generated face sketches.
- Multi-Language Expansion: Expand language support beyond the currently supported languages through additional Whisper fine-tuning on regional dialects and minority languages.
- Integration with National Criminal Databases: Develop secure API integrations to query national-level criminal databases such as the National Crime Records Bureau (NCRB) database, expanding the system's identification scope.

APPENDIX - A

SOURCE CODE

app.py

```
from flask import Flask, render_template, request, redirect, session

import mysql.connector

import pandas as pd

import os

import torch

import cv2

from PIL import Image

import numpy as np

from transformers import AutoTokenizer

from train_model import FusionModel

from sentence_transformers import SentenceTransformer, util

app = Flask(__name__)

app.secret_key = "forensic_secret"

# ----------------------------------------------

# DATABASE CONNECTION

# ----------------------------------------------

print("Loading Semantic Model...")

semantic_model = SentenceTransformer('all-MiniLM-L6-v2')
```

```
db = mysql.connector.connect(
    host="localhost",
    user="root",
    password="",
    database="forensic_ai",
    charset="utf8"
)

cursor = db.cursor()
# ----------------------------------------------
# LOAD DATASET
# ----------------------------------------------
@app.route('/logout')
def logout():
    session.pop('admin', None)
    session.pop('police', None)
    return redirect('/')

if __name__ == "__main__":
    app.run(debug=True)
```

APPENDIX - B

SCREENSHOTS

Output:



FIGURE B.1 ADMIN DASHBOARD



FIGURE B.2 MAINTANENCE OF ENTITY



FIGURE B.3 DESCRIPTION OF EYEWITNESS



FIGURE B.4 SUSPECT IDENTIFICATION

REFERENCES

1. Y. Choi, H. Kim, K. Sohn, and I.-J. Kim, 2025, "HiTS: Hierarchical Text-Guided Stylization for Face Sketch-to-Photo Synthesis," IEEE Access.
2. M. Zhu, C. Liang, N. Wang, X. Wang, Z. Li, and X. Gao, 2021, "A Sketch-Transformer Network for Face Photo-Sketch Synthesis," in Proceedings of the 13th International Joint Conference on Artificial Intelligence, pp. 1352–1358.
3. B. Li, Y. Zhu, Y. Wang, C.-W. Lin, B. Ghanem, and L. Shen, 2021 ,"AniGAN: Style-guided generative adversarial networks for unsupervised anime face generation," *arXiv:2102.12593*.
4. W. Yu, M. Zhu, N. Wang, X. Wang, and X. Gao, 2023 "An Efficient Transformer Based on Global and Local Self-Attention for Face Photo-Sketch Synthesis," IEEE Transactions on Image Processing, vol. 32, pp. 483–495.
5. A. Dosovitskiy et al., 2021, "An Image Is Worth 16x16 Words: Transformers for Image Recognition at Scale," in Proceedings of ICLR.
6. X. Qi, M. Sun, Z. Wang, J. Liu, Q. Li, F. Zhao, S. Zhang, and C. Shan, 2025, "Biphasic face photo-sketch synthesis via semantic-driven generative adversarial network with graph representation learning," *IEEE Trans. Neural Netw. Learn. Syst.*, vol. 36, no. 2, pp. 2182–2195.
7. S.-Y. Chen, W. Su, L. Gao, S. Xia, and H. Fu, 2020, "Deep Generation of Face Images from Sketches," arXiv:2006.01047.
8. M. Zhu, Z. Wu, N. Wang, H. Yang, and X. Gao, 2023, "Dual Conditional Normalization Pyramid Network for Face Photo-Sketch Synthesis," IEEE Transactions on Circuits and Systems for Video Technology, vol. 33, no. 9, pp. 5200–5211.
9. Bing Cao, N. Wang, J. Li, Q. Hu, and X. Gao, 2022, "Face photo-sketch synthesis via full-scale identity supervision," *Pattern Recognit.*, vol. 124, Art. no. 108446.

10. X. Qi, M. Sun, W. Wang, X. Dong, Q. Li, and C. Shan, 2021, “Face sketch synthesis via semantic-driven generative adversarial network,” in *Proc. IEEE Int. Joint Conf. Biometrics (IJCB)*, pp. 1–8.
11. J. Liu, H. Huang, J. Cao, J. Duan, and R. He, 2023, “Fine-grained face sketch-photo synthesis with text-guided diffusion models,” in *Proc. Asian Conf. Pattern Recognit.* Cham, Switzerland : Springer, pp. 340–354.
12. R. Rombach, A. Blattmann, D. Lorenz, P. Esser, and B. Ommer, 2022 “High-resolution image synthesis with latent diffusion models,” in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, pp. 10674–10685.
13. Y. Fang, W. Deng, J. Du, and J. Hu, 2020, “Identity-aware CycleGAN for face photo-sketch synthesis and recognition,” *Pattern Recognit.*, vol. 102, Art. no. 107249.
14. M. Zhu, J. Li, N. Wang, and X. Gao, 2022, “Knowledge distillation for face photo–sketch synthesis,” *IEEE Trans. Neural Netw. Learn. Syst.*, vol. 33, no. 2, pp. 893–906.
15. A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, G. Krueger, and I. Sutskever, 2021, “Learning transferable visual models from natural language supervision,” in *Proc. Int. Conf. Mach. Learn.*, pp. 8748–8763.
16. R. Yi, M. Xia, Y.-J. Liu, Y.-K. Lai, and P. L. Rosin, 2021,“Line drawings for face portraits from photos using global and local structure based GANs,” *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 43, no. 10, pp. 3462–3475.
17. C. Liang, M. Zhu, N. Wang, H. Yang, and X. Gao, 2024, "PMSGAN: Parallel Multistage GANs for Face Image Translation," IEEE Transactions on Neural Networks and Learning Systems, vol. 35, no. 7, pp. 9352–9365.
18. A. Radford et al., 2022, "Robust Speech Recognition via Large-Scale Weak Supervision," arXiv preprint arXiv:2212.04356.
19. H. Liu, Y. Xu, and F. Chen, 2023, "Sketch2Photo: Synthesizing Photo-Realistic Images from Sketches via Global Contexts," Engineering Applications of Artificial Intelligence, vol. 117, Art. no. 105608.

20. Y. Deng, 2021, “StyTr 2: Image style transfer with transformers,”, *arXiv:2105.14576*.
21. R. Gal, O. Patashnik, H. Maron, A. H. Bermano, G. Chechik, and D. Cohen-Or, 2022, “StyleGAN-NADA: CLIP-guided domain adaptation of image generators,” *ACM Trans. Graph.*, vol. 41, no. 4, pp. 1–13.
22. Esser, R. Rombach, and B. Ommer, 2021, “Taming transformers for high-resolution image synthesis,” in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, pp. 9–30.
23. W. Xia, Y. Yang, J.-H. Xue, and B. Wu, 2021, “TediGAN: Text-guided diverse face image generation and manipulation,” in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, pp. 2256–2265.
24. U. Osahor and N. M. Nasrabadi, 2022 “Text-guided sketch-to-photo image synthesis,” *IEEE Access*, vol. 10, pp. 98278–98289.
25. J. Yu, X. Xu, F. Gao, S. Shi, M. Wang, D. Tao, and Q. Huang 2021, "Toward Realistic Face Photo-Sketch Synthesis via Composition-Aided GANs," IEEE Transactions on Cybernetics, vol. 51, no. 9, pp. 4350–4362.

Stay Ahead

BANNARI AMMAN INSTITUTE OF TECHNOLOGY

An Autonomous Institution, Affiliated to Anna University Approved by AICTE, Accredited by NAAC with 'A+' Grade,
Sathyamangalam-638 401, Tamil Nadu, India

Department of CSE, IT, CT & ISE

Certificate of Participation

This is to certify that Mr./Ms. VASAN S from K.RAMAKRISHNAN COLLEGE OF TECHNOLOGY has presented a paper titled GENERATIVE AI-DRIVEN FORENSIC FACE SKETCH SYNTHESIS AND SUSPECT IDENTIFICATION VIA ATTENTION-BASED CGAN AND VISION TRANSFORMERS in SIXTH INTERNATIONAL CONFERENCE ON ARTIFICIAL INTELLIGENCE AND SMART COMPUTING (ICAISC'26) held during 19th - 21st March 2026 at Bannari Amman Institute of Technology, Sathyamangalam.

Organizing Secretary | Convenor | Principal

A1026IC595

Stay Ahead

BANNARI AMMAN INSTITUTE OF TECHNOLOGY

An Autonomous Institution, Affiliated to Anna University Approved by AICTE, Accredited by NAAC with 'A+' Grade,
Sathyamangalam-638 401, Tamil Nadu, India

Department of CSE, IT, CT & ISE

Certificate of Participation

This is to certify that Mr./Ms. YOGESWARAN T K from K.RAMAKRISHNAN COLLEGE OF TECHNOLOGY has presented a paper titled GENERATIVE AI-DRIVEN FORENSIC FACE SKETCH SYNTHESIS AND SUSPECT IDENTIFICATION VIA ATTENTION-BASED CGAN AND VISION TRANSFORMERS in SIXTH INTERNATIONAL CONFERENCE ON ARTIFICIAL INTELLIGENCE AND SMART COMPUTING (ICAISC'26) held during 19th - 21st March 2026 at Bannari Amman Institute of Technology, Sathyamangalam.

Organizing Secretary | Convenor | Principal

A1026IC596

Stay Ahead

BANNARI AMMAN INSTITUTE OF TECHNOLOGY

An Autonomous Institution, Affiliated to Anna University Approved by AICTE, Accredited by NAAC with 'A+' Grade,
Sathyamangalam-638 401, Tamil Nadu, India

Department of CSE, IT, CT & ISE

Certificate of Participation

This is to certify that Mr./Ms. KARTHIKEYAN S from K.RAMAKRISHNAN COLLEGE OF TECHNOLOGY has presented a paper titled GENERATIVE AI-DRIVEN FORENSIC FACE SKETCH SYNTHESIS AND SUSPECT IDENTIFICATION VIA ATTENTION-BASED CGAN AND VISION TRANSFORMERS in SIXTH INTERNATIONAL CONFERENCE ON ARTIFICIAL INTELLIGENCE AND SMART COMPUTING (ICAISC'26) held during 19th - 21st March 2026 at Bannari Amman Institute of Technology, Sathyamangalam.

Organizing Secretary | Convenor | Principal

A1026IC597