

# Sample Output

## POST

**POST** /api/Marks ^

Parameters Cancel Reset

No parameters

Request body application/json

```
{
  "studentId": 0,
  "studentName": "Ragavi",
  "className": "8B",
  "subjectName": "Science",
  "mark": 67
}
```

Execute Clear

	StudentId	StudentName	ClassName	SubjectName	Mark
1	1	John	8A	Maths	89
2	2	Sam	8B	Science	78
3	3	Arun	8B	English	88
4	4	Ravi	8A	Social	89
5	5	Ragavi	8B	Science	67

## GET

**GET** /api/Marks

Parameters

No parameters

ExecuteClear

Responses

Curl

```
curl -X 'GET' \
  'http://localhost:5025/api/Marks' \
  -H 'accept: text/plain'
```

Request URL

http://localhost:5025/api/Marks

Server response

Code

Details

200

Response body

```
{
  {
    "studentId": 1,
    "studentName": "John",
    "className": "8A",
    "subjectName": "Maths",
    "mark": 85
  },
  {
    "studentId": 2,
    "studentName": "Sam",
    "className": "8B",
    "subjectName": "Science",
    "mark": 78
  },
  {
    "studentId": 3,
    "studentName": "Varun",
    "className": "8A",
    "subjectName": "Biology",
    "mark": 74
  },
  {
    "studentId": 5,
    "studentName": "Ragavi",
    "className": "8B",
    "subjectName": "Science",
    "mark": 78
  }
}
```

Download

## GET by ID

**GET** /api/Marks/{id}

Parameters

Cancel

Name	Description
<b>id</b> * required	
integer(\$int32)	2
(path)	

ExecuteClear

Responses

Curl

```
curl -X 'GET' \
  'http://localhost:5025/api/Marks/2' \
  -H 'accept: text/plain'
```

Request URL

http://localhost:5025/api/Marks/2

Server response

Code

Details

200

Response body

```
{
  "studentId": 2,
  "studentName": "Sam",
  "className": "8B",
  "subjectName": "Science",
  "mark": 78
}
```

Download

## PUT by ID

**PUT** /api/Marks/{id}

Parameters

Cancel

Reset

Name	Description
<b>id</b> * required integer(\$int32) (path)	<input type="text" value="3"/>

Request body

application/json

```
{  "studentId": 3,  "studentName": "Varun",  "className": "8A",  "subjectName": "Biology",  "mark": 74}
```

Execute

Clear

	StudentId	StudentName	ClassName	Subject Name	Mark
1	1	John	8A	Maths	89
2	2	Sam	8B	Science	78
3	3	Varun	8A	Biology	74
4	4	Ravi	8A	Social	89
5	5	Ragavi	8B	Science	67

## DELETE By ID

**DELETE** /api/Marks/{id} ^

Parameters Cancel

Name	Description
<b>id</b> * required integer(\$int32) (path)	<input type="text" value="4"/>

Execute Clear

	StudentId	StudentName	ClassName	SubjectName	Mark
1	1	John	8A	Maths	89
2	2	Sam	8B	Science	78
3	3	Varun	8A	Biology	74
4	5	Ragavi	8B	Science	67