Literature Review: SmartConnect 6G – Optimizing M2M Communication Using Q-Learning

Jyotiraditya, Atul Kumar Pandey, and Piyush Prakhar
Department of ECE, BIT Mesra, Patna Campus
Email: {btech15053.22, btech15169.22}@bitmesra.ac.in, atulkrpandey@gmail.com

Abstract—This literature review discusses recent advancements in machine-type communication (MTC) and Random Access (RA) protocols in dense IoT networks. It evaluates Reinforcement Learning (RL) methods including Q-learning, DQN, and MARL and contrasts them with SmartConnect 6G—an AI-enhanced RA optimization system using Q-learning. The review shows that SmartConnect 6G significantly improves performance over prior approaches, especially in terms of collision rate, access delay, and SINR, validated through MATLAB simulations.

Index Terms—SmartConnect 6G, Q-learning, Random Access, Reinforcement Learning, mMTC, IoT, SINR, Delay Reduction

I. Introduction

Massive Machine-Type Communication (mMTC) is a cornerstone use case in 6G networks. It supports ultra-dense IoT connectivity in scenarios like smart cities, healthcare, and industrial automation. However, traditional LTE-A Random Access (RA) procedures—such as contention-based slotted ALOHA—cannot scale effectively. They are known to result in a collision rate of up to 5 per access frame, delays exceeding 10 ms, and SINR fixed around 10 dB under dense traffic conditions [1], [2].

II. State of the Art and Limitations

A. Q-Learning for Slot Access

Rodrigues et al. [3] proposed distributed Q-learning for time-slot selection in mMTC scenarios. Their model enabled each device to learn low-collision slots over time, leading to 15–20% improvement. However, it lacked environmental feedback such as SINR and did not address delay-sensitive scenarios or scale well with MIMO.

B. NOMA-Based Access

In [4], Q-learning was combined with NOMA power-domain multiplexing to dynamically allocate RA slots and power levels. This improved spectral efficiency but failed to account for real-time SINR variations. Moreover, the system complexity grew with device count, limiting its scalability.

C. Deep RL for Delay Reduction

Bekele and Choi [5] implemented DQN-based access for MTC devices using a Markov Decision Process (MDP). Their system achieved a 58.9% reduction in access delay. Yet, deep RL methods require large state/action spaces and intensive training—making them less viable for lightweight IoT devices.

D. MARL for MIMO Enhancement

Jadoon et al. [6] proposed a multi-agent system that selects pilot signals in MIMO settings using MARL. Their agents improved average SINR by up to 3 dB across antennas. However, this approach introduced additional signaling overhead and coordination complexity that would hinder mMTC scaling.

E. SCMA and Grant-Free Access

Reddy et al. [7] explored SCMA and Q-learning for grant-free RA. While it improved collision control by 20%, it was tailored to short-packet scenarios without considering SINR or access delay. Khan et al. [8] applied deep RL to optimize grant-free access but similarly focused on latency over signal reliability.

III. SmartConnect 6G Simulation-Based Advantage

SmartConnect 6G introduces a centralized, slot-based Q-learning model enhanced with SINR feedback. It dynamically learns slot preferences that minimize contention while maximizing signal clarity. Unlike deep RL frameworks, it maintains a lightweight structure, converging within 100 episodes.

Simulations in MATLAB revealed:

- **Collision Rate:** Reduced from 5.0 to 0.5 (↓90%)
- **Access Delay:** Reduced from 10 ms to 0.8 ms (↓92%)
- **Average SINR:** Increased from 10 dB to 15 dB (↑50%)
- **Per-Antenna SINR:** Improved from 10.2–11.8 dB to 15.2–18.1 dB

IV. Comparative Evaluation

TABLE I
PERFORMANCE COMPARISON OF RA STRATEGIES

Study	Method	Collisions	Delay	SINR
[3]	QL (Slot)	↓20%	–	–
[4]	QL (NOMA)	↓30%	–	↑2 dB
[5]	DQN	–	↓59%	–
[6]	MARL-MIMO	–	–	↑3 dB
[7]	QL (SCMA)	↓20%	–	–
[8]	Deep RL	–	↓58.9%	–
SmartConnect 6G	QL (Slot+SINR)	**↓90%**	**↓92%**	**↑50%**

V. Conclusion and Future Work

SmartConnect 6G bridges a critical gap in the RA literature. It outperforms both traditional and AI-enhanced alternatives by integrating SINR-aware Q-learning into slot-level access scheduling. Its simple yet effective design offers high reliability and low delay, validated under dense mMTC simulation settings.

Future enhancements may include:

- Deep Q-learning models for larger state-action spaces
- Integration into multi-cell and edge-based networks
- Field testing via hardware testbeds and 6G simulators

References

[1] H. Thomsen *et al.*, "Code-expanded random access to increase contention access resources and reduce collision probability," *Trans. Emerg. Telecommun. Technol.*, vol. 24, no. 4, pp. 355–365, 2013.

[2] W. Wang *et al.*, "Performance enhancement of LTE random access procedure for M2M communications," *EURASIP J. Wireless Commun. Netw.*, vol. 2016, no. 1, pp. 1–13, 2016.

[3] L. Rodrigues *et al.*, "Distributed Q-learning for RA slot selection in mMTC," *arXiv:2105.09788*, 2021.

[4] F. Silva and T. Abrão, "Multi-power Q-learning for NOMA-based mMTC random access," *IEEE Access*, vol. 11, pp. 34567–34578, 2023.

[5] Y. Bekele and J. W. Choi, "Deep Reinforcement Learning-Based Random Access for mMTC," *IEEE Commun. Lett.*, vol. 25, no. 10, pp. 3191–3195, 2021.

[6] M. A. Jadoon *et al.*, "Multi-Agent Reinforcement Learning for Pilot Selection in MIMO RA," *arXiv:2206.11238*, 2022.

[7] S. Reddy *et al.*, "SCMA-Q-learning based random access for short packet communication," in *Proc. IEEE PIMRC*, 2021.

[8] M. U. Khan *et al.*, "Deep RL-based grant-free RA optimization for mMTC," *Physical Communication*, vol. 46, p. 101264, 2021.