

**Scripting and Computer Environments - CSE 505**  
**IIIT Hyderabad - Monsoon 2016**  
**LAB WORK**

Lab No. 7  
Lab Date: 1/11/2016

---

**Guidelines :**

1. Read all questions carefully.
2. Please use man and apropos before calling a TA for help.

**Submission Format :**

1. Create a folder <rollno>\_lab<lab\_no>. All your work should be in this folder ONLY
  2. You have to generate a script file with the name <rollno>\_lab<lab no>.script
  3. Create <Question\_no>.py for all questions in section
  4. Directory Structure :  
    |d- <rollno>\_lab<lab\_no>  
    |f- <Question\_no>.py  
    |d/f- All files/directories created in this session
  5. Zip the folder to <rollno>\_lab<lab\_no>.tar and upload it
- 

**Lab Questions**

1. You are given *Marks.csv* file which contains marks assigned to each student on a scale of 10. Now your task is to generate *Grades-final.csv* file which will hold the <student-name, Total marks obtained by the student in all the labs & assignments, Average of the total, Grade>. The grade for each student is computed based on the conditions given in the below table.

Condition	Normalized Grade
Total marks $\geq$ Average(All students marks)	B
Total marks $<$ Average(All students marks)	C

After performing the above operations, the intermediate output(NOT the final output)

would be( Here the average(All students marks) is 50.5 )

```
prabhakar@prabhakar-Vostro-3550:~/temp
$ cat Grades-PreFinal.csv
Name, Total for all Labs and Assignments, Average of all labs & assignments, Grade
Amar, 49, 8.167, C
Akbar, 49, 8.167, C
Anthony, 51, 8.5, B
Gonzalviz, 50, 8.333, C
Bajji rao, 52, 8.667, B
Mastani, 52, 8.667, B
```

Now in the intermediate output, based on the *total-marks* the top 2 students should be given a A grade while the bottom 2 students should be given D grade. The final output should be similar to the one given in below image.

```
prabhakar@prabhakar-Vostro-3550:~/temp
$ cat Grades-Final.csv
Name, Total for all Labs and Assignments, Average of all labs & assignments, Grade
Amar, 49, 8.167, D
Akbar, 49, 8.167, D
Anthony, 51, 8.5, B
Gonzalviz, 50, 8.333, C
Bajji rao, 52, 8.667, A
Mastani, 52, 8.667, A
```

Store your Final output in *Grades-Final.csv*.

**Note:** You are **NOT** supposed to store intermediate results in any temporary files

**How to take input?**

\$ python Q1.py Marks.csv #### Output should get saved in *Grades-Final.csv*

2. Its an extension of Q1. You are expected to pass the list of lines read from Marks.txt to the function `getReportFromMarks()` defined in the Q1.py and the function `q1.getReportFromMarks()` returns you the list containing the graded marks.

```
In [18]: gradedLines = q1.getReportFromMarks(lines)

In [19]: print gradedLines
[['Amar', '49', '8.167', 'D'], ['Akbar', '49', '8.167', 'D'], ['Anthony', '51', '8.5', 'B'], ['Gonzalviz', '50', '8.333', 'C'], ['Bajji rao', '52', '8.667', 'A'], ['Mastani', '52', '8.667', 'A']]
```

3. Write program
  - a. Source1.py -> having DivideByZero Exception
  - b. Source2.py -> having TypeError Exception
  - c. Source3.py -> having Assertion error
  - d. Source4.py -> having ImportError
  - e. Source5.py ->having KeyError

And handle these exceptions : print the type of exception occurred



2.html=>1

3.html=>1

Name of the outputFile is pageFreq

All in all, you have to read 4 html files present in the folder HTMLPages

The names of the files are given above (page1.html , page2.html etc upto page4)

Let your output be sorted in lexicographic order alphabetically as above (as in the format followed in a dictionary).

Thanks to Madhudeep for discussing this idea with me :)

7: Question(S):

This Question is on the similar lines of the previous question.

If you've successfully done the previous question. This shouldn't come off as a big problem.

You must've observed that there were references from one page to another sequentially. We want you to find out if there are any cyclic references in the html pages.

Ie: if page1 => page2 => page3 => page4 => page1

Write a html file saying cycle is present.

As in generate an html output file.

You can use this simple format

```
<!DOCTYPE html>
```

```
<html>
```

```
<body>
```

```
<h1>Output</h1>
```

```
<p>Cycle Present</p>
```

```
</body>
```

```
</html>
```

So your input files are present in 2 folders, read both the folders and

open the folder HTMLPages1

read everything in them and find out if a cyclic refernce is present in them

open the folder HTMLPages2

read everything in them and find out if a cyclic reference is present in them

output shall be a html file.

in both cases you will be generating a html output file.

The name of the output file will be output1.html if the folder containing html pages have cycle references

The name of the output file will be output2.html if the folder containing html pages do not have cycle references.

Thanks to shweta for discussing the problem with me :)