

Name: _____

Class: _____

Mr. Rawson • GCSE Computer Science



Year 11 2026

Programming 8 — Sub Programs

Why we need them

VOCAB Sub program (OCR 2.2.3) — a named block of code that does one job. It runs when the program calls it by name. Procedures and functions are both sub programs

You have been using sub programs since your first lesson. `print()`, `len()`, `int()` and `input()` are all sub programs that someone else wrote. You call each one by its name, give it what it needs in the brackets, and it does its job.

You write a sub program once, then run it from anywhere in your program just by writing its name. Today you write your own.

OCR's GCSE requires you to know the two main types of sub program: procedures and functions. Today we go through both: a procedure does a job (Section 2), and a function does a job **and hands a value back** (Section 3).

What it gives you	How
Write it once, use it many times	The code lives in one place; every call reuses it.
Easier to read	<code>show_menu()</code> says what happens in two words.
Easier to test	Each sub program can be run and checked on its own.
Easier to change	Fix or improve it in one place and every call gets the change.
Work in a team	Different programmers can write different sub programs.

These are the answers the exam wants when it asks for an advantage of sub programs. Breaking a big problem into sub programs is **decomposition**, from 2.1.

1 Parameters: giving a sub program what it needs

VOCAB Parameter (OCR 2.2.3) — a name in the brackets of a sub program that receives a value when the sub program is called

You already hand values to sub programs every lesson. `len("Computer")` works on any word because you put the word in the brackets. The value in the brackets is what the sub program works on.

The rule. Put the values a sub program needs inside its brackets. When there is more than one, separate them with commas; the order matters. When it needs nothing, the brackets stay empty, but they are still written.

You type	Prints	The parameters
<code>print(len("Computer"))</code>	8	One: the word to measure.
<code>print(round(3.14159, 2))</code>	3.14	Two: the number, then how many decimal places.
<code>print(max(4, 9, 2))</code>	9	Three: the numbers to compare.
<code>print()</code>	a blank line	None, so the brackets are empty.

Now try • Predict first, then run: `print(len("St Leonards"))`, `print(round(7.456, 1))`, `print(max(15, 3, 21, 8))`.

Check • 11 (the space counts), 7.5, 21.

In the next two sections you write your own sub programs, and give them parameters in the same way.

2 A procedure

VOCAB Procedure (OCR 2.2.3) — a sub program that does its job when it is called, such as printing a menu, and does not hand a value back

The rule. Start with `def`, then the name, then empty brackets and a colon. Indent every line that belongs to the procedure. Then **call** it by writing its name and brackets, with no indent. Put the `def` above the call, so Python has read the procedure before it is asked to run it.

In Python, `def` starts **every** sub program, procedures and functions alike. What makes one a function is a return that hands a value back (Section 3). In the exam's ERL, a procedure starts with the word procedure instead.

```
def show_menu():
    print("1 - New game")
    print("2 - Load game")
    print("3 - Quit")

show_menu()
```

Line	What it does
<code>def show_menu():</code>	Defines a procedure called <code>show_menu</code> . Nothing prints yet: Python only remembers the code.
The three print lines	Indented once, so they belong to the procedure.
<code>show_menu()</code>	The call . Python jumps into the procedure, runs its three lines, then carries on from the line after the call.

It prints the three menu lines. Write `show_menu()` twice and the menu prints twice, from code written once.

Now try • Write a procedure called `welcome` that asks the user for their name, then prints a welcome message using it. Call it **twice**.

Check • Enter Ana, then Ben. It prints Hello Ana, welcome to Computer Science. and then the same for Ben.

A procedure with parameters. Name the values the procedure needs inside the brackets of the `def` line. When you call it, put the actual values in the brackets, in the same order.

```
def siblings(brothers, sisters):
    total = brothers + sisters
    print("You have " + str(total) + " siblings.")

siblings(2, 1)
```

The call `siblings(2, 1)` puts 2 into `brothers` and 1 into `sisters`, first to first and second to second. It prints You have 3 siblings. Call `siblings(0, 4)` and the same code prints You have 4 siblings.

Now try • Write a procedure called `person` with two parameters, name and age. It prints the name and age in one sentence. Then, if the age is under 18, it prints Too young to vote.; otherwise it prints Old enough to vote.

Call it with `person("Ana", 15)` and `person("Ben", 40)`.

Check • Four lines: Ana is 15. Too young to vote. Ben is 40. Old enough to vote.

3 A function hands a value back

VOCAB Function (OCR 2.2.3) — a sub program that returns a value to the line that called it. A procedure does its job and returns nothing

`len("hello")` does not print anything. It works out 5 and hands it back to your program, which can store it or print it. A sub program that hands a value back is a **function**.

The rule. End the function with `return` and the value to hand back. Where you call it, catch the value: store it in a variable, or put the call straight inside `print()`.

```
def perimeter(length, width):  
    perim = 2 * (length + width)  
    return perim  
  
p = perimeter(5, 7)  
print(p)  
print(perimeter(3, 4))
```

`perimeter(5, 7)` works out 24 and `return` hands it back to the line that called it, so `p` becomes 24. The last line calls it again and prints the result straight away: 14.

Procedure or function? One question decides it.

	Procedure	Function
Hands a value back?	No: it just does its job	Yes, with <code>return</code>
Called like this	<code>show_menu()</code> on its own line	<code>p = perimeter(5, 7)</code> or inside <code>print()</code>
Use it to	show a menu, print a report	work something out: a total, an area

Now try • Write a function `circle_area(radius)` that returns the area of a circle. Use $\pi = 3.14$, so the area is `3.14 * radius ** 2`. Print the result for a radius of 10, then store the result for a radius of 2 in a variable called `small` and print `small`.

Check • 314.0, then 12.56.

4 A full example: a cash machine menu

A cash machine shows a menu and runs a different job for each choice. Each job is a procedure, so the main program at the bottom stays short: show the menu, ask, then call one procedure.

```
def withdrawal():
    print("You have selected cash withdrawal")

def balance():
    print("You have selected balance")

def pin_services():
    print("You have selected PIN services")

def pay_bills():
    print("You have selected pay bills")

def cancel():
    print("Card returned. Goodbye")

print("Menu")
print("1 - Cash withdrawal")
print("2 - Balance")
print("3 - PIN services")
print("4 - Pay bills")
print("5 - Cancel")
option = int(input("Please select an option 1-5: "))

if option == 1:
    withdrawal()
elif option == 2:
    balance()
elif option == 3:
    pin_services()
elif option == 4:
    pay_bills()
elif option == 5:
    cancel()
else:
    print("Please only enter an option 1, 2, 3, 4 or 5")
```

Part	What it does
The five def blocks	Define one procedure for each menu choice. Nothing runs yet.
The six print lines	The main program starts here: it shows the menu.
int(input(...))	Asks for a choice. int() turns the typed text into a whole number, so it can be compared with 1, 2 and so on.
if ... elif ... else	Calls exactly one procedure, chosen by the number. Any other number reaches else.

Each procedure here is one line, to keep the example short. In a real cash machine, withdrawal() would be many lines long, and the main program would still call it with one word. That is what makes the main program easy to read.

Now try • Type the program in and run it three times, entering 1, then 5, then 9.

Check • You have selected cash withdrawal, then Card returned. Goodbye, then Please only enter an option 1, 2, 3, 4 or 5.

Now add option 6 - Mini statement: a new procedure, a new menu line, and a new `elif`. Update the last message so it lists 6 as well.

Check • Entering 6 prints your mini statement message.

5 Local and global variables

The rule. A variable made **inside** a sub program is **local**: it exists only while that sub program runs, and only the sub program can use it. A variable made in the **main program**, with no indent, is **global**: every part of the program can read it. To get a value **out** of a sub program, return it.

```
VAT = 0.2

def with_vat(price):
    extra = price * VAT
    return price + extra

print(with_vat(50))
```

Name	Scope	Why
VAT	global	Made in the main program. The function can read it. It is a constant : set once, never changed, so it is written in capitals.
price	local	A parameter belongs to its sub program.
extra	local	Made inside the function. When the function ends, it is gone.

It prints 60.0. Only the returned value leaves the function; `extra` stays inside it. Typing `print(extra)` in the main program gives a `NameError`, because the main program has no variable called `extra`.

Why local is the default. Each sub program keeps its own variables, so two sub programs can both use a name like `total` without changing each other's. That makes a program easier to test and to fix, and it is the advantage the exam asks about.

Now try • **Predict first.** The sub program has parameters with the **same names** as two global variables. Write down what the last two lines print, then run it.

```
var1 = 2
var2 = 3

def my_sub(var1, var2):
    var1 = var1 * 30
    var2 = var2 * 30
    return var2

var3 = my_sub(4, 5)
var4 = var1 + var2 + var3
print(var4)
print(var1)
```

Check • 155, then 2. Inside `my_sub`, `var1` and `var2` are local copies starting at 4 and 5, so the global 2 and 3 are untouched. `var3` is the returned 150, and $2 + 3 + 150 = 155$.

Changing a global from inside a sub program. Write `global` and the name as the first line of the sub program. Then the sub program uses the main program's variable instead of making a local one.

```
score = 0

def add_point():
    global score
    score = score + 1

add_point()
add_point()
print(score)
```

It prints 2. Returning a value is usually the cleaner choice; `global` is there for a value the whole program shares, such as a game's score.

6 Pass an array in

The rule. An array can be a parameter, like any other value. Inside the function, loop over it exactly as in Programming 6, using the parameter's name.

```
def array_total(numbers):
    total = 0
    for i in range(len(numbers)):
        total = total + numbers[i]
    return total

scores = [5, 8, 2, 1, 9, 10, 7, 6]
print(array_total(scores))
```

The call hands `scores` to the function, where it is called `numbers`. The loop adds every box and `return` hands back 48. The same function totals **any** array: `array_total([3, 4])` returns 7.

Now try • (a) Write a function `average(numbers)` that returns the average of an array. A function can call another function: use `array_total(numbers)` for the total and divide by `len(numbers)`.

Check • `print(average(scores))` prints 6.0.

(b) Write a function `biggest(numbers)` that returns the largest value. Start `big` at `numbers[0]`, then loop through the rest, and whenever a box is larger than `big`, store it in `big`.

Check • `biggest(scores)` returns 10, and `biggest([-4, -9, -2])` returns -2.

(c) Print both results in one sentence.

Check • Average 6.0, highest 10.

Stretch A shop till

A shop till is decomposed into four sub programs: scan barcodes, look up prices, calculate the total, calculate change. Write the two that do the arithmetic.

1. `till_total(prices)` takes an array of prices **in pence** and returns the total.
2. `change(total, paid)` returns the change in pence.
3. The main program stores `[120, 85, 250]`, asks how much the customer paid in pence, and prints the total and the change using your two functions.

Check • Total 455. Pay 500 and the change is 45.

The exam writes it differently

OCR's exam language, ERL, uses a different word for each kind of sub program, and closes each one with its own end line instead of using the indent.

ERL (what you read)	Python (what you type)	Meaning
procedure show_menu() ... endprocedure	def show_menu():	A procedure
function perimeter(length, width) ... endfunction	def perimeter(length, width):	A function
return perim	return perim	Hand the value back
global score = 0	score = 0 in the main program	A global variable
p = perimeter(5, 7)	p = perimeter(5, 7)	Calling a function

The perimeter function in ERL.

```
function perimeter(length, width)
    perim = 2 * (length + width)
    return perim
endfunction

p = perimeter(5, 7)
print(p)
```

Python uses `def` for both kinds. In ERL, the word tells you which it is: if it says function, look for the return.