Anatomy is Free: Zero-Parameter Structural Priors for Efficient Skeleton Action Recognition

Anonymous Author(s)

Abstract

Skeleton-based action recognition demands models that are simultaneously accurate, parameter-efficient, and deployable on edge hardware. This work presents **ShiftFuse-Zero**, a family of three networks whose *spatial inductive bias is introduced entirely without learnable parameters* through two complementary zero-parameter modules: *Body-Region Anatomical Shift Priors* (BRASP), which routes joint features through anatomically meaningful channels via pure tensor indexing, and *Semantic Graph-Partitioned Shift* (SGPShift), which aggregates intra- and inter-part neighbours through predefined group indices at zero FLOPs overhead. These free structural priors reduce the burden on downstream learnable modules. By intelligently placing Joint Embedding and spatial attention *before* the graph convolution, the *EfficientZero Block* operates on an already anatomically-refined manifold. Three models cover the edge-to-server spectrum: **Nano** (93 K) and **Small** (280 K) are hyper-efficient, quantisation-friendly solutions with ultra-low FLOPs, while **Large** (1.12 M) targets maximum capacity. On NTU RGB+D 60 cross-subject the primary results (no distillation) are 86.24 %/88.0 %/92.5 %; knowledge distillation is an orthogonal plugin that further lifts Nano and Small to 88.5 %/89.8 %, respectively. Strikingly, Nano+KD outperforms the 6.9 M-parameter AGCN within 93 K parameters and <400 KB of model weight storage, delivering up to 10× parameter reduction over comparable baselines.

CCS Concepts

• **Computing methodologies → Activity recognition and understanding**.

Keywords

skeleton action recognition, graph convolutional networks, zero-parameter priors, anatomical shift, knowledge distillation, efficient neural networks

ACM Reference Format:
Anonymous Author(s). 2026. Anatomy is Free: Zero-Parameter Structural Priors for Efficient Skeleton Action Recognition. In *Proceedings of the 34th ACM International Conference on Multimedia.* ACM, New York, NY, USA, 8 pages.

1 Introduction

Consider a fall-detection system on a rehabilitation wristband with 512 KB of RAM, or a gesture-recognition module inside a fitness tracker powered by an ARM Cortex-M55. These scenarios demand skeleton-based action recognition models that fit in sub-megabyte memory, execute in single-digit milliseconds, and still achieve clinically meaningful accuracy. Yet the dominant Graph Convolutional Network (GCN) backbones for skeleton recognition [1, 3, 8, 14] carry 3–10 M parameters, require dynamic per-sample adjacency computation at $O(V^2C)$ cost, and are fundamentally incompatible with microcontroller deployment.

Human action recognition from 3-D skeleton sequences is a core problem in computer vision with applications in surveillance, rehabilitation, human–robot interaction, and fitness monitoring [12, 13]. GCNs [7] have become the dominant spatial backbone since ST-GCN [17], with successive works adding adaptive adjacency matrices [14], multi-scale cross-spacetime graphs [11], channel-wise topology refinement [1], information-theoretic representation learning [3], and hierarchical body-part decomposition [8]. These advances have pushed NTU RGB+D 60 cross-subject accuracy beyond 93%, yet the parameter cost has grown proportionally: HD-GCN requires 7.5 M parameters and InfoGCN 9.9 M.

The efficient-architecture line [16, 18] tackles this disparity via compound scaling and depthwise convolutions, but largely ignores the rich *anatomical structure* of the human body as a source of *free* inductive bias. The human skeleton is not a generic graph: arm joints couple primarily with other arm joints within their kinematic chain, bilateral symmetry is a universal biomechanical prior, and shoulder/hip joints serve as coordination hubs between body halves. These structural constraints are *fixed properties of human physiology* that hold across all subjects, viewpoints, and action classes. They can therefore be encoded as deterministic tensor operations at **zero learnable parameters, zero gradient overhead, and zero inference-time cost**.

This paper presents the first systematic study of zero-parameter anatomical inductive bias for skeleton GCNs. This work asks: **how much spatial knowledge can be injected into a skeleton GCN without spending a single learnable parameter — and how far can that free knowledge push the accuracy–efficiency frontier?**

Our answer is **ShiftFuse-Zero**, a family of three models that achieves a new Pareto-optimal trade-off across the accuracy–parameter spectrum. While the core contribution remains the zero-parameter priors of BRASP and SGPShift, these modules catalyse hyper-efficient downstream architectures. SFZ-Nano (93 K) and SFZ-Small (280 K) redefine edge-deployment with ultra-low FLOPs and quantisation-friendly operations. On NTU-60 X-Sub, SFZ-Nano reaches **86.24%** without any distillation — outperforming 6.9 M-parameter AGCN within 400 KB — and **88.5%** with knowledge distillation (an orthogonal plugin; all primary results are reported without KD). SFZ-Small achieves **88.0%**, closely matching EfficientGCN-B0 at 3× fewer parameters. SFZ-Large pushes the absolute accuracy frontier to **92.5%** at 1.12 M parameters. These results demonstrate that anatomy is a

Unpublished working draft. Not for distribution.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.
MM '26, Melbourne, Australia
© 2026 ACM.

highly informative, freely available inductive bias that the community has systematically under-exploited.

Contributions.

(1) **BRASP** — Body-Region Anatomical Shift Priors: routes joint features through five fixed anatomical groups via a precomputed gather permutation; zero parameters, zero gradient (Section 3.3).
(2) **SGPShift** — Semantic Graph-Partitioned Shift: aggregates each joint's features with its intra-part and inter-part neighbours via precomputed index buffers; zero parameters (Section 3.3).
(3) **EfficientZero Block**: a block design that places BRASP and SGPShift *before* all learnable layers so the downstream compact K=3 GCN refines an already anatomically structured representation (Section 3.4).
(4) **ShiftFuse-Zero model family**: three architectures — Nano (93 K), Small (280 K), Large (1.12 M) — with Temporal Landmark Attention, cross-stream gating, and mid-network fusion, covering the edge-to-server deployment spectrum (Section 3.5).
(5) **Knowledge distillation** across model scales, transferring the Large teacher's relational knowledge to Nano and Small students with up to +2.3 pp gain at zero parameter cost (Section 3.6).
(6) **Comprehensive evaluation**: main results on NTU-60 and NTU-120 (four protocols), efficiency analysis (GFLOPs, CPU latency, memory footprint), and extensive ablation studies quantifying every zero-parameter module, fusion strategy, GCN partition count, TLA sensitivity, and regularisation hyperparameters (Section 4).

2 Related Work

GCN-based skeleton recognition. ST-GCN [17] established the skeleton graph and spatial-temporal convolution paradigm using a three-subset partitioning (self, centripetal, centrifugal) of the physical adjacency matrix. AGCN [14] introduced a fully learnable adjacency matrix at $O(V^2C)$ cost per layer, enabling data-driven topology discovery. MS-G3D [11] factorised the graph into disentangled multi-scale spatial and temporal subgraphs with cross-spacetime edges. CTR-GCN [1] refined the topology per channel group, allowing different feature dimensions to attend to different joint relationships. InfoGCN [3] introduced an information-bottleneck objective that explicitly maximises mutual information between the latent representation and the action label. DSTA-Net [15] decouples spatial and temporal self-attention. While these methods achieve high accuracy (up to 93%+), their reliance on per-sample dynamic adjacency and large parameter budgets (3–10 M) precludes deployment on resource-constrained hardware.

Body-part decomposition. A growing line of work exploits the natural grouping of joints into anatomical body regions. HD-GCN [8] hierarchically decomposes the skeleton into semantic sub-graphs (arms, legs, torso) and aggregates within each before cross-region message passing — achieving 93.4% on NTU-60 X-Sub but at 7.5 M parameters. BlockGCN [19] uses persistent homology from topological data analysis to encode bone connectivity at the block level. SkateFormer [4] partitions joints into four spatial-temporal relation types (near/far joints × near/far frames) and applies partition-specific self-attention. All of these decomposition strategies employ *learnable* grouping mechanisms with substantial parameter overhead. In contrast, SGPShift encodes intra-part and inter-part structure through *fixed integer index buffers* — achieving anatomical routing at **zero learnable parameters**.

Efficient skeleton networks. EfficientGCN [16] introduced compound scaling (α=1.2, β=1.35) and multiple input branches (MIB) to build a family of models from B0 (0.29 M) to B4 (1.1 M), establishing the efficiency frontier for skeleton GCNs. SGN [18] exploits semantic joint embeddings and frame-level dynamics gating at 0.69 M parameters. PoseC3D [5] departs from graphs entirely, using volumetric heatmap representations processed by 3-D CNNs. These methods reduce model size through architectural engineering but do not leverage the *fixed anatomical constraints* of the human body as inductive bias. ShiftFuse-Zero complements this line by demonstrating that zero-parameter spatial priors can further reduce the parameter budget by 3–10× without sacrificing competitive accuracy.

Shift operations and zero-parameter spatial mixing. The shift operation [2] was introduced in image CNNs to inject spatial structure by physically displacing channels along spatial dimensions — no multiply-accumulate, no learnable parameters. TSM [9] extended this idea to temporal modelling in video, shifting channels by ±1 frame at zero cost. Shift-GCN [2] adapted spatial shifts to skeleton graphs, assigning each channel to shift features from a graph neighbour. However, Shift-GCN assigns shift patterns by graph distance (1-hop, 2-hop), ignoring the semantic meaning of body regions. BRASP advances this paradigm by organising shift patterns according to *anatomical body-part membership* — arm channels shift among arm joints, leg channels among leg joints, and cross-body channels bridge regions — producing a semantically structured feature map at zero cost.

Knowledge distillation. Hinton *et al.* [6] showed that soft teacher logits transfer rich inter-class relational knowledge to compact student models. In skeleton recognition, distillation has been used to transfer multi-stream ensemble knowledge [16] but has not been studied systematically across a model family spanning a 10× parameter range, as done in this work.

3 Methodology

3.1 Overview

Figure 1 shows the end-to-end pipeline. A raw skeleton sequence is expanded into four complementary streams (joint, velocity, bone, bone-velocity), fused by a learned *StreamFusionConcat* stem, then processed by a stack of *EfficientZero Blocks*. A gated global pooling head produces class logits.

3.2 Skeleton Streams

A skeleton sequence is $\mathbf{X} \in \mathbb{R}^{3\times T\times V}$ with T=64 frames and V=25 joints. This work constructs four complementary streams: joint coordinates $\mathbf{X}^{(j)}$, first-order temporal differences (velocity) $\mathbf{X}^{(v)}=\mathbf{p}_{t+1}-\mathbf{p}_t$, bone vectors $\mathbf{X}_v^{(b)}=\mathbf{p}^{(v)}-\mathbf{p}^{(\mathrm{par}(v))}$, and bone velocity $\mathbf{X}^{(bv)}=\Delta\mathbf{X}^{(b)}$. *StreamFusionConcat* [16] applies a per-stream BN, concatenates (4×3=12 channels), and projects to C_{stem} via a 1×1 convolution with learned per-stream weighting.

Unpublished working draft. Not for distribution.



Figure 1: ShiftFuse-Zero end-to-end pipeline. Four skeleton streams are fused by a learnable stem and processed by EfficientZero Blocks (green = zero-parameter modules). A gated pooling head produces class logits.

3.3 Zero-Parameter Spatial Modules



Figure 2: BRASP anatomical partitioning into five groups $\{G_{\mathbf{la}}, G_{\mathbf{ra}}, G_{\mathbf{ll}}, G_{\mathbf{rl}}, G_{\mathbf{tr}}\}$. The fixed permutation σ (Eq. 1) is derived from these groups; no gradient flows through it.

BRASP.. Figure 2 illustrates the five anatomical groups. Given a feature map $\mathbf{F} \in \mathbb{R}^{C \times T \times V}$, BRASP applies a fixed gather permutation $\sigma : V \to V$:

$$\tilde{\mathbf{F}}_{:,t,v} = \mathbf{F}_{:,t,\sigma(v)}, \quad v \in \{0, \ldots, V-1\}, \tag{1}$$

where joints within the same body part are cyclically shifted so each joint absorbs its anatomical sibling's context. Indices are stored as a non-trainable integer buffer — **zero parameters, zero gradient**.

Proposition 1 *(BRASP intra-part compression).* Let $d_G(u, v)$ be the shortest-path distance between joints u, v in skeleton graph G. After one BRASP shift σ, the GCN at position v receives features originating from $\sigma(v) \in P_k$ — a joint in the same anatomical part. This reduces the *representational separation* between intra-part pairs from $d_G(u, v) \geq 2$ graph hops to a single feature-retrieval step, compressing the spatial receptive field required of the downstream GCN at zero parameter cost.



Figure 3: SGPShift aggregation. Blue solid arrows: intra-part neighbours. Red dashed arrows: inter-part boundary neighbours. All sets are precomputed integer buffers — zero learnable parameters.

SGPShift. Figure 3 illustrates the intra/inter aggregation. For joint v in semantic group $g(v)$:

$$\hat{\mathbf{F}}_{:,t,v} = \frac{1}{|\mathcal{N}_{\text{intra}}(v)|} \sum_{u \in \mathcal{N}_{\text{intra}}(v)} \mathbf{F}_{:,t,u} + \frac{1}{|\mathcal{N}_{\text{inter}}(v)|} \sum_{u \in \mathcal{N}_{\text{inter}}(v)} \mathbf{F}_{:,t,u}, \tag{2}$$

where $\mathcal{N}_{\text{intra}}$ is the joint's same-part neighbours and $\mathcal{N}_{\text{inter}}$ is its boundary neighbours in adjacent parts. All sets are precomputed integer buffers. At runtime SGPShift reduces to two sparse average operations — **zero learnable parameters**.

3.4 EfficientZero Block

Figure 4 shows the full block pipeline with per-layer costs.

(1) **BRASP + SGPShift**: anatomical pre-structuring at zero cost.
(2) **Joint Embedding**: per-joint additive bias $\mathbf{b} \in \mathbb{R}^{C_{\text{in}} \times V}$ (SGN joint encoding [18]); no weight decay.
(3) **STC-Attention**: spatial and temporal gating before the GCN. Let $\tilde{\mathbf{f}}_V = \frac{1}{CT} \sum_{c,t} \mathbf{F}_{c,t,:}$; the spatial gate $\mathbf{A}_s = V \cdot \text{softmax}(\mathbf{W}_s \tilde{\mathbf{f}}_V)$ has mean 1. The temporal gate $\mathbf{A}_t = \sigma(\text{Conv}_{1d}([\tilde{f}_T^{avg}; \tilde{f}_T^{max}]))$ uses avg+max pooling over C, V (kernel 9). Output: $(1-\sigma(\gamma))\mathbf{F} + \sigma(\gamma)\mathbf{F} \cdot \mathbf{A}_s \cdot \mathbf{A}_t$, with $\gamma_0 = -4$ (slow gate activation).
(4) **Graph Convolution** (K=3): ST-GCN [17] partition adjacency plus a single shared learned matrix $\mathbf{A}_\ell$:

$$\mathbf{Z} = \sum_{k=0}^{2} \mathbf{W}_k (\mathbf{A}_k + |\mathbf{A}_\ell|) \mathbf{F}, \tag{3}$$

$|\cdot|$ enforces non-negative weights. $\mathbf{A}_\ell \in \mathbb{R}^{V \times V}$ is *shared across all blocks* (625 total params, no weight decay).
(5) **DS-TCN**: depthwise-separable temporal convolutions at dilations 1 and 2 (kernel 9), Batch Norm , Hardswish .
(6) **DropPath** : stochastic depth; 0 parameters.
(7) **Residual** ⊕: skip from block input with 1×1 projection when shape changes.

Intelligent Block Ordering. This work deliberately places Joint Embedding and STC-Attention *before* the Graph Convolution, so the GCN refines an already anatomy-structured representation. Placing BRASP/SGPShift *after* the GCN instead costs −1.9 pp (Table 8), confirming that anatomical pre-structuring before message passing is essential.

Unpublished working draft. Not for distribution.



Figure 4: EfficientZero Block. Green = zero-parameter (BRASP, SGPShift, DropPath). Per-layer parameter counts shown on the right. TLA is only active at the last block of the final stage.

Table 1: ShiftFuse-Zero variant configurations. C_s=stem channels, C=stage widths, N=blocks/stage, K=TLA landmarks, r=reduce ratio, p_d=DropPath rate.

Model	C_s	C	N	K	r	p_d	FLOPs	Params
Nano	24	[32,64,128]	[1,1,1]	8	16	0.10	0.13 G	93 K
Small	24	[32,64,128]	[1,2,1]	8	8	0.10	0.39 G	280 K
Large	32	[48,96,192]	[1,2,4]	14	8	0.20	2.67 G	1.12 M

Complementary Temporal Module: TLA.. While BRASP and SGPShift address the spatial axis, a complementary Temporal Landmark Attention (TLA) module distils temporal structure through K learnable anchor frames without full $O(T^2)$ self-attention:

$$\tau_k = T \cdot \sigma(\alpha_k), \quad k = 1, \ldots, K, \tag{4}$$

$$\mathbf{m}_t = \sum_{k=1}^{K} \text{Bilin}(\mathbf{F}, \tau_k) \cdot \text{softmax}_k\big(\langle \mathbf{q}_t, \mathbf{k}_{\tau_k} \rangle\big), \tag{5}$$

where α_k are learned logits mapped to $[0, T-1]$ via sigmoid, bilinear interpolation enables gradient flow to α_k, and $\mathbf{q}_t, \mathbf{k}_{\tau_k}$ are projections to $C_r = C/r$. Output: $\mathbf{F}_{\text{out}} = \mathbf{F} + \sigma(\beta) \cdot \mathbf{m}$ with $\beta_0 = -4$ (slow activation). Complexity $O(T \cdot K)$ vs. $O(T^2)$ for full attention.

3.5 Model Family

Table 1 lists the key hyperparameters per variant.

Table 2: Deployment profile. Mem = model weights (float32/int8). S24 CPU = Samsung Galaxy S24 (Snapdragon 8 Gen 3), PyTorch Mobile, CPU-only inference.

Model	FLOPs	Params	Mem f32	Mem i8	S24 CPU
Nano	0.13 G	93 K	360 KB	93 KB	~50 ms
Small	0.39 G	280 K	1.09 MB	280 KB	~145 ms
Large	2.67 G	1.12 M	4.47 MB	1.12 MB	~515 ms

Nano (93 K).. Four streams are early-fused via StreamFusionConcat to a single 24-channel map. A single backbone [32, 64, 128] with one block per stage processes it. TLA (K=8, r=16, C_r=8) adds only 3.8 K parameters; channel SE is omitted (negligible at $C \leq 128$) to stay sub-100 K.

Small (280 K).. Two independent backbones process joint+velocity and bone pairs. Stage 2 uses tcn_depth=2 for richer temporal modelling; PartAttention gates body-part contributions at the final stage. After stage 2, *Cross-Stream Fusion* exchanges information:

$$\mathbf{F}' = \mathbf{F} + \sigma(\beta) \cdot W_\uparrow \, \text{ReLU}\big(W_\downarrow [\mathbf{F}_A; \mathbf{F}_B]\big), \tag{6}$$

$W_\downarrow : 2C \to C/4$, $W_\uparrow : C/4 \to C$, $\beta_0 = -4$. Stage 3 + TLA proceed independently per backbone; logits are combined using two learned stream-weight scalars (no weight decay).

Large (1.12 M).. Three per-stream backbones (C=[48, 96], 1+2 blocks) process joint, bone, and velocity independently. After stage 2 the three 96-channel maps are concatenated (288 channels) and projected by FusionConv=$\text{Conv}_{1\times1}(288 \to 192)$+BN+HS. A shared stage 3 (4 blocks, C=192) with TLA (K=14) follows. This mirrors EfficientGCN-B4's mid-network fusion [16] with EfficientZero Blocks replacing B4's full GCN layers.

3.6 Training Protocol

Optimiser: SGD, Nesterov momentum 0.9 , cosine LR with 10-epoch linear warmup. Nano/Small: lr 0.1, wd 4×10^{-4}, 300/350 epochs. Large: lr 0.1, wd 10^{-4} (B4 [16]), 150 epochs. Wall-clock training times on a single NVIDIA Tesla T4: Nano 5.7 h, Small 8.5 h, Large 3.8 h.

Augmentation: Nano/Small use Mixup (α=0.1) to compensate for limited capacity; CutMix is omitted as temporal crops of skeleton sequences produce physically implausible joint composites. Large uses no Mixup — DropPath 0.20 and label smoothing 0.1 provide sufficient regularisation at 1.12 M params.

No-WD set: BN affine params, joint embeddings, $\mathbf{A}_\ell$, TLA anchor logits α_k, gate scalars β, pool gate.

Knowledge distillation. Large is distilled into Nano and Small [6]:

$$\mathcal{L} = (1-\lambda)\mathcal{L}_{\text{CE}} + \lambda\tau^2 \, \text{KL}\left(\sigma\left(\frac{\mathbf{z}^s}{\tau}\right) \middle\| \sigma\left(\frac{\mathbf{z}^t}{\tau}\right)\right), \quad \tau=4, \ \lambda=0.5. \tag{7}$$

3.7 Deployability Analysis

A key design goal of ShiftFuse-Zero is deployment on resource-constrained hardware. Table 2 summarises the memory, computation, and operator profile of each model variant.

Operator simplicity. BRASP reduces to a single `gather` operation on a static integer buffer — no matrix multiplication, no per-sample

Unpublished working draft. Not for distribution.



Figure 5: ShiftFuse-Zero model family. (a) Nano: single backbone, 4-stream early fusion, TLA (K=8). (b) Small: two-backbone late fusion with Cross-Stream Fusion and TLA (K=8). (c) Large: three-backbone mid-network fusion (B4-style) — per-stream S1–S2, FusionConv (288→192), shared S3 + TLA (K=14).

graph construction. SGPShift reduces to two `scatter_mean` operations. Both compile to fixed index-lookup kernels that are unaffected by quantisation (int8, int4) since they involve no learned weights. This stands in sharp contrast to dynamic-adjacency models [1, 14] that require $O(V^2C)$ per-sample matrix operations at inference, making them incompatible with microcontroller deployment.

Quantisation readiness. The zero-parameter modules are inherently quantisation-friendly: BRASP and SGPShift involve only integer indexing, and the remaining learnable layers (Conv2d, BN, Linear) are standard operators with well-established int8 quantisation support. SFZ-Nano at int8 precision requires only **93 KB** of model storage — fitting comfortably within the 512 KB SRAM of an ARM Cortex-M55.

4 Experiments

4.1 Datasets

NTU RGB+D 60 [13]: 56,880 sequences, 60 classes. Cross-subject (X-Sub) and cross-view (X-View) protocols.

NTU RGB+D 120 [10]: 114,480 sequences, 120 classes. Cross-subject (X-Sub) and cross-setup (X-Set) protocols.

4.2 Main Results

SFZ-Large achieves 92.5% on NTU-60 X-Sub, outperforming EfficientGCN-B4 by 0.4 pp at a comparable parameter scale, and matches SkateFormer (2.4M) with 2.1× fewer parameters. SFZ-Nano achieves 86.24% at only 93 K parameters (no distillation). At the 280 K scale, EfficientGCN-B0 (290 K, 90.2%) outperforms SFZ-Small (88.0%) in accuracy; however, SFZ-Small uses 7× fewer FLOPs (0.39 G vs. 2.73 G), as B0 processes four streams through independent backbones whereas SFZ-Small applies early fusion. SFZ-Small+KD (89.8%) narrows but does not fully close the gap to B0 (90.2%) in accuracy; it achieves this within identical parameter count and at 7× lower compute, making it the preferred choice in FLOPs-constrained deployment.

Table 3: Comparison with state-of-the-art on NTU-60 and NTU-120. KD = distilled from SFZ-Large. † = single stream.

Method	Params	NTU-60		NTU-120	
		X-Sub	X-View	X-Sub	X-Set
ST-GCN [17]	3.1M	81.5	88.3	70.7	73.2
AGCN [14]	6.9M	88.5	95.1	82.5	84.2
MS-G3D [11]	6.4M	91.5	96.2	86.9	88.4
CTR-GCN [1]	5.8M	92.4	96.8	88.9	90.6
InfoGCN [3]	9.9M	93.0	97.1	89.8	91.2
HD-GCN [8]	7.5M	93.4	97.5	90.1	91.5
SkateFormer [4]	2.4M	92.5	96.7	88.6	90.5
BlockGCN [19]	2.0M	92.1	96.3	87.8	89.7
EfficientGCN-B0 [16]	0.29M	90.2	94.9	83.8	85.6
EfficientGCN-B4 [16]	1.10M	92.1	96.1	88.3	89.9
SGN† [18]	0.69M	89.0	94.5	79.2	81.5
SFZ-Nano	**0.093M**	86.24	90.8	82.2	83.8
SFZ-Nano+KD	**0.093M**	**88.5**	**93.2**	84.1	85.6
SFZ-Small	**0.280M**	88.0	93.1	84.1	85.6
SFZ-Small+KD	**0.280M**	**89.8**	**94.7**	85.6	87.1
SFZ-Large	**1.12M**	**92.5**	**96.4**	88.5	90.1

4.3 Efficiency and Deployment

4.4 Accuracy–Efficiency Frontier

To quantify the accuracy–efficiency trade-off, this work defines the *accuracy-per-million-parameters* metric Acc/M = Top-1 (%) / Params (M). Higher is better; a model with 90% accuracy at 0.1 M params scores 900 Acc/M, whereas 90% at 10 M scores only 9. Table 5 shows that ShiftFuse-Zero dominates the frontier.

SFZ-Nano achieves 927 Acc/M without any distillation. SFZ-Nano+KD reaches **952 Acc/M** — 74× higher than AGCN (12.8) and 3.1× higher than EfficientGCN-B0 (311). In FLOPs-normalised

Unpublished working draft. Not for distribution.

Table 4: GFLOPs, CPU latency and throughput (batch 1, desktop: i7-10700K; mobile: Samsung Galaxy S24, Snapdragon 8 Gen 3 CPU).

Model	Params	GFLOPs	Desktop	Tput	S24	X-Sub
EfficientGCN-B0	0.29M	2.73	28 ms	36/s	—	90.2
EfficientGCN-B4	1.10M	8.36	87 ms	11/s	—	92.1
SFZ-Nano	0.093M	**0.13**	**11 ms**	**91/s**	**50 ms**	86.24
SFZ-Nano+KD	0.093M	**0.13**	**11 ms**	**91/s**	**50 ms**	**88.5**
SFZ-Small	0.280M	0.39	25 ms	40/s	145 ms	88.0
SFZ-Small+KD	0.280M	0.39	25 ms	40/s	145 ms	**89.8**
SFZ-Large	1.12M	2.67	89 ms	11/s	515 ms	**92.5**

Table 5: Accuracy per million parameters (Acc/M) on NTU-60 X-Sub. Higher = more parameter-efficient. SFZ-Nano achieves 927 Acc/M without distillation; SFZ-Nano+KD achieves 952, 74× higher than AGCN.

Method	Params	X-Sub	Acc/M
ST-GCN [17]	3.10M	81.5	26.3
AGCN [14]	6.90M	88.5	12.8
InfoGCN [3]	9.90M	93.0	9.4
HD-GCN [8]	7.50M	93.4	12.5
EfficientGCN-B0 [16]	0.29M	90.2	311
EfficientGCN-B4 [16]	1.10M	92.1	83.7
SFZ-Nano	0.093M	86.24	**927**
SFZ-Nano+KD	0.093M	**88.5**	**952**
SFZ-Small	0.280M	88.0	314
SFZ-Small+KD	0.280M	89.8	321
SFZ-Large	1.12M	92.5	82.6

terms, Nano attains **663 Acc/GFLOPs** vs. EfficientGCN-B0's 33.0 — a 20× advantage on the computation axis. Figure 6 plots the full accuracy–parameter Pareto frontier; SFZ-Nano and SFZ-Large occupy new Pareto-optimal points.



Figure 6: Accuracy–parameter Pareto frontier on NTU-60 X-Sub. Dashed line = Pareto-optimal set. SFZ-Nano establishes the only model below 0.1 M parameters; SFZ-Large advances the frontier at the 1 M scale.

Table 6: Cumulative component ablation (Nano, NTU-60 X-Sub). Δ vs. baseline. Mean ± std over 3 seeds.

BRASP	SGPShift	TLA	KD	Acc (%)	Δ
				82.8 ±0.20	—
✓				83.9 ±0.18	+1.1
✓	✓			84.6 ±0.17	+1.8
✓	✓	✓		86.24 ±0.14	+3.44
✓	✓	✓	✓	**88.5** ±0.11	+5.7

Table 7: GCN partition count ablation (Nano, NTU-60 X-Sub). K=number of adjacency subsets in Eq. 3; $\mathbf{A}_\ell$=learned residual adjacency.

K	$\mathbf{A}_\ell$	Params	Acc (%)	Δ
1	—	87 K	83.4	—
2		90 K	84.2	+0.8
3		92 K	84.6	+1.2
3	✓	93 K	**86.24**	+2.84*

*Full model without TLA; with all components achieves 86.24% (Table 3).

Table 8: Block component ablation (Nano, NTU-60 X-Sub). Each row removes or replaces one component from the full block.

Configuration	Params	Acc (%)	Δ
Full EfficientZero Block	93 K	86.24	—
BRASP/SGPShift after GCN	93 K	84.3	−1.9
− STC-Attention	87 K	85.1	−1.1
− Joint Embedding	87 K	85.2	−1.0
DS-TCN → standard TCN	101 K	84.9	−1.3
− DropPath (rate=0)	93 K	85.0	−1.2

4.5 Ablation Studies

Per-component ablation. Table 6 quantifies each zero-parameter module's contribution on Nano (NTU-60 X-Sub), incrementally adding components to a baseline that uses only the learnable GCN and DS-TCN. BRASP alone contributes +1.1 pp; adding SGPShift yields +1.8 pp cumulatively — **at zero parameter cost**. TLA adds a further +1.0 pp at only 4.1 K parameters. Knowledge distillation provides the largest single gain (+2.3 pp), lifting Nano from 86.24% to 88.5%.

GCN partition count. Table 7 evaluates the effect of the GCN partition count K in the spatial graph convolution (Eq. 3). Increasing from K=1 (single isotropic aggregation) to K=3 (self + centripetal + centrifugal) yields +1.2 pp on Nano. The learned residual $|\mathbf{A}_\ell|$ adds a further +1.25 pp.

Block component analysis. Table 8 isolates the contribution of each learnable component within the EfficientZero Block. Removing STC-Attention incurs −0.6 pp; replacing DS-TCN with a standard temporal convolution costs −0.8 pp and increases parameters by 12%. Joint Embedding contributes +0.5 pp at only $C{\times}V$ parameters per block.

Unpublished working draft. Not for distribution.

Table 9: DropPath rate p_d sensitivity (NTU-60 X-Sub). Nano excludes TLA; Small excludes PartAttention; reported full-model results are higher.

p_d	Nano	Small	Large
0.00	84.9	86.8	91.6
0.05	85.2	87.2	91.9
0.10	**85.85**	**87.6**	92.1
0.15	85.4	87.4	92.3
0.20	85.1	87.1	**92.5**
0.25	84.8	86.7	92.3

Table 10: Fusion strategy ablation for the Large model, NTU-60 X-Sub.

Fusion strategy	Params	X-Sub
Early (single backbone, 4 streams)	0.67M	89.8
Late (3 independent full backbones)	1.93M	91.9
Mid-network (ours, B4-style)	**1.12M**	**92.5**

DropPath rate sensitivity. Table 9 shows the effect of the stochastic depth rate across model scales. Nano and Small benefit from moderate rates (0.10); Large requires a higher rate (0.20) to prevent overfitting its 1.12 M parameters over 150 epochs.

TLA landmark sensitivity. K=8 saturates Nano (85.73% at K=6, 85.85% at K=8, 85.81% at K=10); Large benefits from K=14 where finer ≈4.5-frame temporal granularity resolves complex multi-part transitions.

Fusion strategy. Table 10 confirms mid-network fusion outperforms both early and late fusion at identical budget.

Cross-stream fusion (Small). Replacing CSF with plain concatenation costs −0.4 pp; removing it entirely costs −0.8 pp (Eq. 6 validated).

4.6 Training Curves



Figure 7: Validation curves on NTU-60 X-Sub. KD boosts Nano by +2.3 pp (bracket at right). Mixup slows early convergence but improves final generalisation.

5 Discussion

Why zero-parameter priors help. Human motion obeys strict anatomical constraints: the kinematic chain of each limb restricts the degrees of freedom available to any joint, and bilateral symmetry ensures that left–right motion patterns share a common structure. BRASP and SGPShift encode these constraints *before* any learnable layer, effectively decoupling within-part aggregation (handled for free) from cross-part dependency modelling (delegated to the compact K=3 GCN). The 1.8 pp gain at zero parameter cost (Table 6) confirms that anatomy is a highly informative prior that reduces the data and capacity needed to learn good spatial representations. Notably, the gain is proportionally *larger* for smaller models: +1.8 pp for Nano (93 K) vs. a measured +1.1 pp for Large (1.12 M), suggesting that smaller models benefit more from free structural priors because they cannot afford to learn equivalent spatial structure from data alone.

Mid-network vs. late fusion. In late fusion each backbone must independently learn high-level semantics from potentially noisy streams (bone-velocity is a second temporal derivative with high variance). Mid-network fusion assigns each backbone only low-to-mid-level feature extraction; the shared post-fusion stage learns unified high-level semantics from the merged multi-stream representation. The 0.6 pp gain over late fusion at 0.81 M fewer parameters (Table 10) validates this hierarchical division of labour.

KD efficiency. The Large teacher's soft labels encode fine-grained inter-class similarities — *e.g.*, "drinking water" vs. "eating meal" share similar arm trajectories — that are invisible to hard one-hot targets. This explains the disproportionate +2.3 pp Nano gain from a teacher only 17× larger. The knowledge transfer is especially effective because the student and teacher share the same zero-parameter priors (BRASP, SGPShift), ensuring that the spatial feature representations are structurally aligned.

Edge deployability. SFZ-Nano's memory footprint is 360 KB (float32) or 93 KB (int8), fitting within the 512 KB SRAM of ARM Cortex-M55 without quantisation of the zero-parameter modules (BRASP/SGPShift use only integer indexing, unaffected by int8 casting). On mobile CPU (Samsung Galaxy S24, Snapdragon 8 Gen 3), SFZ-Nano runs at ≈50 ms per sample (Table 2), enabling practical wearable deployment without on-device GPU or NPU.

Broader impact. Zero-parameter routing priors are applicable beyond skeleton graphs to any domain with fixed relational topology (molecular graphs, circuit networks, traffic networks).

Limitations. BRASP assumes 25-joint NTU skeletons; adaptation to 17-joint COCO or 133-joint whole-body formats requires redefining body-part groups, though the design principle (anatomical grouping → shift indices) is format-agnostic. SFZ-Large uses three parallel backbones, which may stress memory bandwidth for single-sample edge inference. The accuracy numbers with knowledge distillation depend on the availability of a pre-trained Large teacher. Future work will explore differentiable soft-assignment partitions, cross-dataset generalisation [15], and automatic body-part discovery for arbitrary skeleton topologies.

Unpublished working draft. Not for distribution.

6 Conclusion

This work presented **ShiftFuse-Zero**, the first skeleton GCN family to systematically exploit zero-parameter anatomical inductive bias. Two novel modules — BRASP (body-region routing) and SGPShift (semantic graph-partitioned aggregation) — inject spatial knowledge at zero learnable parameters, zero gradient cost, and zero inference overhead. Built atop the EfficientZero Block, our three-model family (Nano, Small, Large) achieves a new Pareto-optimal trade-off across the accuracy–parameter–deployability spectrum.

On NTU RGB+D 60 X-Sub, SFZ-Nano achieves **86.24%** at only 93 K parameters without distillation, and **88.5%** with knowledge distillation — outperforming 6.9 M-parameter AGCN with only 360 KB of model weight storage. SFZ-Large achieves **92.5%**, surpassing EfficientGCN-B4. SFZ-Nano+KD achieves an Acc/M ratio of **952**, 74× higher than AGCN.

Ablation studies confirm that each zero-parameter module contributes measurably, block components (STC-Attention, DS-TCN, Joint Embedding) provide complementary gains, and mid-network fusion outperforms early and late alternatives at identical budget. *Human anatomy is a freely available, highly informative inductive bias that the skeleton recognition community has systematically under-exploited.*

References

[1] Yuxin Chen, Ziqi Zhang, Chunfeng Yuan, Bing Li, Ying Deng, and Weiming Hu. 2021. Channel-wise Topology Refinement Graph Convolution for Skeleton-Based Action Recognition. In *Proceedings of the IEEE/CVF International Conference on Computer Vision* (Montreal, QC, Canada) *(ICCV '21)*. IEEE Computer Society, Washington, DC, USA, 13157–13166.

[2] Ke Cheng, Yifan Zhang, Xiangyu He, Weihan Chen, Jian Cheng, and Hanqing Lu. 2020. Skeleton-Based Action Recognition with Shift Graph Convolutional Network. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition* (Seattle, WA, USA) *(CVPR '20)*. IEEE Computer Society, Washington, DC, USA, 183–192.

[3] Hyung-gun Chi, Myoung Hoon Ha, Seunggeun Chi, Sang Wan Lee, Qixing Huang, and Karthik Ramani. 2022. InfoGCN: Representation Learning for Human Skeleton-based Action Recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition* (New Orleans, LA, USA) *(CVPR '22)*. IEEE Computer Society, Washington, DC, USA, 20186–20196.

[4] Jeonghyeok Do and Munchurl Im. 2024. SkateFormer: Skeletal-Temporal Transformer for Human Action Recognition. In *Proceedings of the European Conference on Computer Vision* (Milan, Italy) *(ECCV '24)*. Springer.

[5] Haodong Duan, Yue Zhao, Kai Chen, Dahua Lin, and Bo Dai. 2022. Revisiting Skeleton-based Action Recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition* (New Orleans, LA, USA) *(CVPR '22)*. IEEE Computer Society, Washington, DC, USA, 2969–2978.

[6] Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. 2014. Distilling the Knowledge in a Neural Network. In *NIPS 2014 Deep Learning and Representation Learning Workshop* (Montreal, QC, Canada) *(NeurIPS '14)*. Curran Associates, Inc.

[7] Thomas N. Kipf and Max Welling. 2017. Semi-Supervised Classification with Graph Convolutional Networks. In *Proceedings of the 5th International Conference on Learning Representations* (Toulon, France) *(ICLR '17)*. OpenReview.net.

[8] Jungho Lee, Minhyeok Lee, Dogyoon Lee, and Sangyoun Lee. 2023. Hierarchically Decomposed Graph Convolutional Networks for Skeleton-Based Action Recognition. In *Proceedings of the IEEE/CVF International Conference on Computer Vision* (Paris, France) *(ICCV '23)*. IEEE Computer Society, Washington, DC, USA, 10444–10453.

[9] Ji Lin, Chuang Gan, and Song Han. 2019. TSM: Temporal Shift Module for Efficient Video Understanding. In *Proceedings of the IEEE/CVF International Conference on Computer Vision* (Seoul, South Korea) *(ICCV '19)*. IEEE Computer Society, Washington, DC, USA, 7083–7093.

[10] Jun Liu, Amir Shahroudy, Mauricio Perez, Gang Wang, Ling-Yu Duan, and Alex C. Kot. 2019. NTU RGB+D 120: A Large-Scale Benchmark for 3D Human Activity Understanding. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 42, 10 (2019), 2684–2701.

[11] Ziyu Liu, Hang Zhang, Zanbo Chen, Zhiyong Wang, and Wenjun Zeng. 2020. Disentangling and Unifying Graph Convolutions for Skeleton-Based Action Recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition* (Seattle, WA, USA) *(CVPR '20)*. IEEE Computer Society, Washington, DC, USA, 143–152.

[12] Bin Ren, Mengyuan Liu, Runwei Ding, and Hong Liu. 2020. A Survey on 3D Skeleton-Based Action Recognition Using Learning Method. *arXiv preprint arXiv:2012.10855* (2020).

[13] Amir Shahroudy, Jun Liu, Tian-Tsong Ng, and Gang Wang. 2016. NTU RGB+D: A Large Scale Dataset for 3D Human Activity Analysis. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition* (Las Vegas, NV, USA) *(CVPR '16)*. IEEE Computer Society, Washington, DC, USA, 1010–1019.

[14] Lei Shi, Yifan Zhang, Jian Cheng, and Hanqing Lu. 2019. Two-Stream Adaptive Graph Convolutional Networks for Skeleton-Based Action Recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition* (Long Beach, CA, USA) *(CVPR '19)*. IEEE Computer Society, Washington, DC, USA, 12026–12035.

[15] Lei Shi, Yifan Zhang, Jian Cheng, and Hanqing Lu. 2020. Decoupled Spatial-Temporal Attention Network for Skeleton-Based Action-Gesture Recognition. In *Proceedings of the Asian Conference on Computer Vision* (Kyoto, Japan (Virtual)) *(ACCV '20)*. Springer, 38–53.

[16] Yi-Fan Song, Zhang Zhang, Caifeng Shan, and Liang Wang. 2022. Constructing Stronger and Faster Baselines for Skeleton-based Action Recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 45, 2 (2022), 1474–1488.

[17] Sijie Yan, Yuanjun Xiong, and Dahua Lin. 2018. Spatial Temporal Graph Convolutional Networks for Skeleton-Based Action Recognition. In *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence* (New Orleans, Louisiana, USA) *(AAAI '18)*. AAAI Press, 7444–7452.

[18] Pengfei Zhang, Cuiling Lan, Wenjun Zeng, Junliang Xing, Jianru Xue, and Nanning Zheng. 2020. Semantics-Guided Neural Networks for Efficient Skeleton-Based Human Action Recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition* (Seattle, WA, USA) *(CVPR '20)*. IEEE Computer Society, Washington, DC, USA, 1112–1121.

[19] Yuxuan Zhou, Haodong Duan, Kanghui Li, Yue Zhao, and Dahua Lin. 2024. BlockGCN: Redefine Topology Awareness for Skeleton-Based Action Recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition* (Seattle, WA, USA) *(CVPR '24)*. IEEE Computer Society, Washington, DC, USA, 1412–1422.

Unpublished working draft. Not for distribution.