FULL DEMO SAFETY DATA SHEET

SYNTHETIC TEST FIXTURE ONLY — NOT AN AUTHENTIC SDS — DO NOT USE FOR REAL CHEMICAL HANDLING, OPERATIONS, COMPLIANCE, OR SAFETY DECISIONS

Product identifier: AquaClean-7 Demo Process Fluid (fictional mixture)

Supplier: SafeFlow Test Laboratory (fictional) **Document ID:** SF-SDS-DEMO-007 **Revision:** 2.0

Issue date: 27 October 2026 **CAS:** Not applicable; fictional mixture

This is a deliberately synthetic 16-section SDS-shaped document for software testing. Every chemical identity, hazard statement, limit, measurement, compatibility statement, and toxicology value below is invented. It is designed to test whether SafeFlow can extract the seven PSI fields, preserve section/page provenance, and keep extraction confidence separate from human verification.

PSI FIELD INDEX — EXPECTED LOCATIONS

PSI parameter	Expected source	Demo content to detect
1. Toxicity information	Section 11	Fictional inhalation LC50 estimate and respiratory effects
2. PEL / TLV / REL	Section 8	Fictional TWA, STEL, and IDLH values
3. Physical data	Section 9	pH, boiling/freezing point, vapor pressure, density, solubility
4. Reactivity data	Section 10 — Reactivity	Fictional incompatible materials
5. Corrosivity data	Section 10 — Corrosivity note; also Section 2	Fictional corrosivity to selected metals and pH
6. Thermal/chemical stability	Section 10 — Stability	Fictional stability and decomposition threshold
7. Hazardous effects of inadvertent mixing	Section 10 — Hazardous reactions	Fictional heat/vapor/gas evolution on mixing

Section 1 — Identification

Product: AquaClean-7 Demo Process Fluid. **Intended use:** software parsing test only. **Restrictions:** fictional product; do not manufacture, handle, or use it.

Section 2 — Hazard Identification

Fictional classification for parser testing: Corrosive to metals, Category 1; acute inhalation toxicity, Category 4; serious eye damage, Category 1. **Signal word:** Danger. This invented classification is not a real hazard assessment.

Section 3 — Composition / Information on Ingredients

Fictional mixture: Component A, 12% by mass; Component B, 8% by mass; water, 80% by mass. Components A and B are placeholders, not real chemical identities, and have no assigned CAS numbers.

Section 4 — First-Aid Measures

Synthetic example text: inhalation may cause respiratory irritation; eye contact may cause severe irritation. This is not first-aid guidance and must not be used for an actual exposure.

Section 5 — Fire-Fighting Measures

Fictional example: designated non-flammable for parser testing. Do not use this statement to plan real firefighting or emergency response.

Section 6 — Accidental Release Measures

No operational spill response is supplied because the product is fictional. Do not use this document for incident response.

Section 7 — Handling and Storage

No real handling or storage instructions are supplied. This synthetic fixture is not a basis for process operation.

Section 8 — Exposure Controls / Personal Protection

PERMISSIBLE EXPOSURE LIMITS — ALL VALUES BELOW ARE INVENTED: Demo Authority PEL: 10 ppm, 8-hour TWA; Demo Hygiene TLV: 5 ppm, 8-hour TWA and 10 ppm STEL; Demo Institute REL: 5 ppm TWA and 10 ppm STEL; fictional IDLH: 50 ppm. These are parser-test placeholders, not valid occupational exposure limits.

Section 9 — Physical and Chemical Properties

PHYSICAL DATA — ALL VALUES BELOW ARE INVENTED: Appearance: pale blue liquid; odor: mild citrus-like; pH: 11.2 at 20°C; initial boiling point: 104°C; freezing point: –2°C; vapor pressure: 2.1 kPa at 20°C; relative density: 1.08 at 20°C; vapor density: 1.2 (air = 1); flash point: not applicable in this fictional example; water solubility: miscible.

Section 10 — Stability and Reactivity

10.1 Reactivity data (fictional): The demo fluid is stated to react with strong acids and strong oxidizing agents. Avoid mixing with concentrated acids. This compatibility statement is invented for parser testing.

10.2 Corrosivity data (fictional): The demo fluid is stated to be corrosive to carbon steel, zinc, and aluminum under the fictional test conditions. The fictional pH is 11.2 at 20°C. No real corrosion-rate measurements are available. This is a synthetic corrosivity field, not a materials-selection recommendation.

10.3 Thermal and chemical stability (fictional): Stable under the fictional recommended storage conditions. Decomposition is stated to begin above 180°C, producing irritating vapors. Temperature and decomposition products are invented, not measured or validated.

10.4 Hazardous effects of inadvertent mixing (fictional): Mixing with concentrated acid is stated to release heat and irritating vapor. Mixing with a concentrated placeholder Component B is stated to cause rapid gas evolution. These are invented parser-test statements and must not be treated as real incompatibility data.

Section 11 — Toxicological Information

TOXICITY INFORMATION — FICTIONAL: Acute inhalation toxicity estimate: LC50 (4-hour, rat) = 1,500 ppm. Respiratory irritation is listed as a possible effect in this synthetic example. The value is invented and is not a measured toxicological result.

Section 12 — Ecological Information

No real ecological data available. Intentionally incomplete.

Section 13 — Disposal Considerations

No real disposal recommendation is provided for this fictional product.

Section 14 — Transport Information

No real transport classification is assigned.

Section 15 — Regulatory Information

This synthetic fixture is not a regulatory SDS and does not establish compliance with OSHA or any other jurisdiction.

Section 16 — Other Information

Prepared solely to test SafeFlow document ingestion. All data are fictional. SafeFlow should treat extracted values as **unverified** until checked against authoritative sources and approved by a qualified reviewer. Do not infer that a field is safe or hazard-free merely because information is absent.