SHUBHAM EXTRUSION
AN ADVANCE BLOWN FILM TECHNOLOGY

Date: 23/06/2025

QUOTE#JPQ0DOM-SE3HR-1350-55/55/55-LL+ (A-B-C) THREE LAYERS

To,
VINAYAK POLYMERS
Shed No. 22, ARCOGUL,
Chikhodara Chowkdi,
Vaghasi, Anand – 388320
Mob:80004 02410
Email id: admin@vinayakpolymers.com

Kind Attn: Mr. Haryush Patel
Dear sir,

Subject: Techno-Commercial Price Offer **(Premium Model: SE3HR-1350-55/55/55-LL+ (A-B-C) Three Layer)**

Annexure – 1: General Specifications, Machine Output & Gauge Variation **(Page No. 3)**
Annexure – 2: Shubham Extrusion Standard Scope of Supply **(Page No. 4)**
Annexure – 3: Price **(Page No. 5)**
Annexure – 4: Technical Specifications **(Page No. 6 to 12)**
Annexure – 5: Terms & Conditions **(Page No. 13 to 15)**

SHUBHAM EXTRUSION Make SE3HR-1350-55/55/55-LL+ Blown Film Plant

Above image is for reference only. Actual supply will be as per contract agreed upon.

Annexure – 1 (General Specifications, Machine Output & Gauge Variation):

General Specifications:

Subject	Description
Film:	Three Layer Flattened Tubular
End Product Description:	Mulch film, (**Note:** Application depends on die selected. Different application may have Different die and die lip gap.)
Film Layflat Range:	750 – 1250mm
Film Thickness Range:	20 – 150µm
Die & Die Lip Gap:	300mm Die with 2.2mm Lip Gap For LL-LDPE
Raw Material:	**LLDPE, LDPE, Metallocenes**
Maximum Melt Capacity:	330kg/Hr
Maximum Film Output:	200kg/Hr
Connected Load:	155Kw
Plant Dimensions (L x W x H):	10m x 5m x 8.8m

Output at Specific Job Sizes:

Polymer	Die Dia. (mm)	Film Size (mm x µm)	Output (kg/Hr)
Mulch film Application	**300mm (2.2mm Lip Gap)**	**1220 x 25micron**	**200kgs/hr.(@ line Speed of 60mpm)**
Mulch film Application	**300mm (2.2mm Lip Gap)**	**1220 x 15micron**	**160kgs/hr. (@ line Speed of 80mpm)**

Gauge Variation:

Film Thickness Range (µm)	Variations Without Auto Thickness Control (90% Circumference)
51µm to 150µm	**± 5% to 6% (2 Sigma)**
35µm to 50µm	**± 6% to 7% (2 Sigma)**
20µm to 34µm	**± 3 to 4µm (2 Sigma)**

Important Notes:

Terms & Condition to Obtain the Above Mentioned Output:
• **Above mentioned output can be achieved with 25% blending of LDPE (0.2 MFT-1 MFI). Depends upon thickness & application.**
• Use virgin polymers only.
• We have considered **LDPE:** 0.2 – 2 MFI polymers of Reliance/ EXXON MOBIL/ SABIC, **LLDPE:** polymers 19010 Reliance/ 18010 Reliance/ FB2230 Borouge/ 118W SABIC.
• **Average ambient temperature should be within $33C^0$ – $35C^0$.**
• **Air ring air temperature must be within $16C^0$ – $20C^0$.**
• **Air cooled air chiller of 10TR is must to obtain the above mentioned output.**
• **In case of temperature is above 45°C, output of the machine may get reduced by 10% to 15%.**

Annexure – 2 (Shubham Extrusion Standard Scope of Supply):

Subject	Description	Qty.
Extruder – A (Outer Layer):	• 55mm diameter extruder with grooved feed barrier screw • **L/D ratio:** 30:1 • 30kW/ 40HP/ 1440RPM main motor **(ABB/WEG make)** • with AC frequency drive **(ABB/YASKAWA make)**	**1 Unit**
Extruder – B (Middle Layer):	• 55mm diameter extruder with grooved feed barrier screw • **L/D ratio:** 30:1 • 30kW/ 40HP/ 1440RPM main motor **(ABB/WEG make)** • with AC frequency drive **(ABB/YASKAWA make)**	**1 Unit**
Extruder – C (Inner Layer):	• 55mm diameter extruder with grooved feed barrier screw • **L/D ratio:** 30:1 • 30kW/ 40HP/ 1440RPM main motor **(ABB/WEG make)** • with AC frequency drive **(ABB/YASKAWA make)**	**1 Unit**
Screen Changer:	Candle type manual screen changer for all three extruders	**3 Nos.**
Gearbox:	Fully imported **(Sun-Lung Make, Made in Taiwan)** helical gearbox with force lubrication through mechanical pump and plate type heat exchanger for oil cooling with oil filter & magnet plug along with thrust bearing **(SKF make)**	**3 Nos.**
Die Head:	• **300mm fix Die for 3-layer film for LL-LDPE with 2.2mm Die lip gap** • **Fully imported Die head with North American design** • **Assembly with hard chrome plating in full surface of the Die, and made from Japanese forged steel, toughened 28 to 30 HRC & stress relieved** • **Die made on 5 axes CNC machine with tapper lock assembly for best gap uniformity for individual layer and over all gap uniformity**	**1 Unit**
Die Lifting:	Hoist arrangement for Die lifting provided	**1 Unit**
Air Ring:	Three lip air cooling ring with aerodynamic design for fast and uniform cooling of film bubble, Air ring has a circular casing with many air entries and circular insert as an air guide for air impinging on the film bubble, Air entry (4”x 6 Nos.)	**1 Unit**
Blower:	10HP main blower with **(ABB/WEG Make)** Motor with AC frequency drive **(ABB/YASKAWA MAKE)**	**1 Unit**
Calibration Basket:	Scissor type calibrating basket with PBT rollers with motorized close-open mechanism	**1 Unit**
Flattening Board:	Flattening board with with PBT rollers, Narrow wide with motorized mechanism. Side support with motorized close-open movement.	**1 Unit**
Take Off Unit:	Take off unit with Vertical reversing haul-off rotation with AC frequency drive **(ABB/YASKAWA MAKE)**	**1 Unit**
Load Cell:	Three zone load cell for auto tension control **(E+L make)**	**1 Unit**
Trim Suction Blower:	Trim suction blower with 1HP ABB make motor **(ABB/WEG Make)**	**1 Unit**
Winder:	Two station Duplex Type pneumatic surface winder with HMI Screen, with Flying Knife with Auto splicing & Auto changeover mechanism on pre-Selected length	**1 Unit**
Expander Rolls:	Provided on film guide path and both winding stations	**4 Nos.**
Air Shafts:	3” air shafts provided on both winding stations **(Resource make)**	**4 Nos.**
Machine Operating Panel:	• Electrical control cabinet incorporating AC frequency drives **(ABB/YASKAWA make)** • Electrical control cabinet incorporating auto-tune PID temperature controllers **(Omron make)** • Energy meter • Melt pressure transducer with indicator for all three extruders **(Gefran make)** • Master synchronization between take off, winder nip and both winding stations	**1 Unit**

Winder Operating Panel:	Remote box type separate panel with 7" touch screen HMI for winder	**1 Unit**

Annexure – 3 (Price):

Price of the Machine:

Machine Model:	SE3HR-1350-55/55/55-LL+
Basic Ex-Works Ahmedabad Price (INR.):	**1,27,90,000.00 (One Crore Twenty-Seven Lakh Ninety Thousand Only)**
Payment Terms:	45% advance along with PO, balance payment before dispatch after satisfactory trial run at our factory.
Bank Details:	• Beneficiary Name: Shubham Extrusion Machines Pvt. Ltd. • Beneficiary A/C No.: 8745316776 • Bank Name: Kotak Mahindra Bank • Branch: Ramol, Ahmedabad, India • IFSC Code: KKBK0000837
Taxes:	GST & TCS will be charged extra at prevailing rates at the time of dispatch.
Freight & Insurance	Freight, insurance and all onward charges will be at customer's account.
Delivery Time:	Within 90 – 120 days after receipt of the 45% advance payment.
Packing:	Packing charges will be 1.5% extra applicable on basic price before discounts for essential packing.

Optional Attachments:

SR NO	OPTIONAL ATTACHMENTS	PRICE IN INR
1	Opto Electric Digital Edge guiding system (Alteem/E+L make)	INR 2,40,000.00
2	Extra Bubble stabilizer over airing (This is require for Higher ourput in lower Thickness for Better Bubble Stability)	INR 6,00,000.00

SR NO	OPTIONAL ATTACHMENTS CUSTOMER SCOPE OF SUPPLY
1	Trio hoper loader with dryer **(Nu – Vu Conair make)**
2	10TR air cooled air chiller **(Nu – Vu Conair make)**
3	5TR air cooled water chiller for feedbush & gearbox cooling **(Nu – Vu Conair make)**
4	Logo printer with 2nos of idler rollers and stand 2nos With Extended Platfrom

Notes:

- If customer wishes to purchase optional equipment directly from suppliers suggested by us and wish to install the same at our factory, then Shubham Extrusion will charge 10% of purchase amount as handling charge.
- Shubham Extrusion Technik Pvt. Ltd. is not responsible for any services for such handling charges.
- The output indications are based on the conditions that average ambient temperature should be within 35°C, outgoing water temperature form the grooved feed section of the Barrel should be controlled within 25°C, air outlet temperature from the air ring at the Die should be 20°C and Relative humidity is 60%.
- The gauge variation shall be within ± 5 – 7% of film thickness or ± 3 – 4µm, whichever is higher at 90% of film periphery.
- Output and gauge variation depends upon polymer grade, film lay flat, film thickness, nip height, die lip size, other processing and operating parameters, etc.
- In case of thyristor drives used on extruders and post extrusion equipments, ensure that the incoming supply is having 415V ± 5%, 3 Phase, 50Hz. If this is beyond the limit given, it is essential to install a voltage stabilizer.
- The performance figures and specifications given in our quotation, acknowledgment of order, catalogues etc. are indicative only and cannot be guaranteed nor shall we be liable for any damages, direct or indirect for non-performance on these Counts. Our warranty is only for manufacturing defects.

Annexure – 4 (Technical Specifications):

Extruder – A (Outer Layer) & Extruder – C (Inner Layer):

Subject	Description
Screw Dia. (mm) with L/D Ratio:	55mm Dia. with 30:1 L/D ratio
Screw Type:	Single screw extruder 55mm Dia. mounted on wheels
Drive (kW/HP):	30kW/40HP AC motor **(ABB/WEG make)**
Control:	Through AC frequency drive **(ABB/YASKAWA make)**
Gearbox:	Fully imported **(Sun-Lung make, Made in Taiwan)** helical gearbox with force lubrication through mechanical pump and plate type heat exchanger for oil cooling with oil filter & magnet plug along with thrust bearing **(SKF make)**
Gearbox Torque:	6630Nm
Thrust Bearing:	**SKF make**
Thrust Capacity (KN):	918kN
Feed Section:	With grooved sleeve in barrel
Power Transmission:	Directly coupled
Lubrication:	Force
Material of Construction & Surface Treatment:	**Nitro Alloy Steel (EN41B) Plasma Nitrided Screw & Barrel**
Heating Load (kW):	9kW ceramic heaters **(EXCEL make)**
Number of Heating Zones:	3 Zones for barrel + 1 Zone for screen changer
Barrel Cooling:	Blower fan cooling system for all four zones
Hopper (Ltr.):	47Ltr. capacity with magnetic grill
Screen Pack:	Candle type screen changer for inner & outer Layer
Screw Removal:	From front side

Extruder – B (Middle Layer):

Subject	Description
Screw Dia. (mm) with L/D Ratio:	55mm Dia. with 30:1 L/D ratio
Screw Type:	Single screw extruder 55mm Dia. mounted on wheels
Drive (kW/HP):	30kW/40HP AC motor **(ABB/WEG make)**
Control:	Through AC frequency drive **(ABB/YASKAWA make)**
Gearbox:	Fully imported **(Sun-Lung make, Made in Taiwan)** helical gearbox with force lubrication through mechanical pump and plate type heat exchanger for oil cooling with oil filter & magnet plug along with thrust bearing **(SKF make)**
Gearbox Torque:	6630Nm
Thrust Bearing:	**SKF make**
Thrust Capacity (KN):	918kN
Feed Section:	With grooved sleeve in barrel
Power Transmission:	Directly coupled
Lubrication:	Force
Material of Construction & Surface Treatment:	**Nitro Alloy Steel (EN41B) Plasma Nitrided Screw & Barrel**
Heating Load (kW):	9kW ceramic heaters **(EXCEL make)**
Number of Heating Zones:	3 Zones for barrel + 1 Zone for screen changer
Barrel Cooling:	Blower fan cooling system for all four zones
Hopper (Ltr.):	47Ltr. capacity with magnetic grill
Screen Pack:	Candle type screen changer for middle layer
Screw Removal:	From front side

Three Layer Die & Air Ring:

Subject	Description
Type:	Three layer fix type die
Die & Die Lip Gap (mm):	300mm Dia. for LL-LDPE with 2.2mm lip gap
Die Design:	Spiral type
Mounting:	Center trolley with adjustment screws
Working Direction:	Upwards
Material of Construction (Die):	**Made from Japanese forged steel, toughened 28 to 30 HRC & stress relieved**
Surface Treatment:	Hard chrome plating in full surface of the Die
Die Gap Adjustment:	By moving die ring with the adjusting bolts
Connection to Extruders:	By threaded flanges
Heating Load (kW):	18kW ceramic heaters **(EXCEL make)**
Number of Heating Zones:	7 zones
Bubble Cooling System Type:	OBC type
Air Cooling Ring Type:	Three lips air ring
Material of Construction (Air Cooling Ring):	Aluminum body with MS/Al lips
Air Cooling Ring Design:	3 lip air ring specially aerodynamically designed for LL-LDPE/LDPE **(Air inlets: 4" x 6 Nos.)**
Air Flow Adjustment:	10HP AC frequency drive **(ABB/YASKAWA Make)** for blower motor **(ABB/WEG make)**
Pressure Gauge:	Air pressure and temperature indicator on air cooling ring

Calibration Basket:

Subject	Description
Bubble Guide:	• Scissor type one fixed calibrating basket with PBT rollers with safety limit switch, motorized close-open for suitable Layflat of 750mm – 1250mm

Vertical Reversing Haul Haul-Off Rotation:

Subject	Description
Design:	Vertical oscillating haul-off
Degree of Nip Oscillation:	358° sensed by limit switches
Control:	0.375kW/ 0.5HP AC frequency drive to control the speed of oscillating haul-off with planetary gearbox
Time for One Oscillation:	4 – 12 minutes
Air Control to Turner Bars:	By regenerative blowers (0.56kW/ 0.75HP x 2 nos.)
Idler Rollers:	90mm Dia. (12 Nos.)

Flattening Board:

Subject	Description
Flattening Board Type:	Pneumatic open-close mechanism
Flattening Board Material of Construction:	Free moving PBT Rollers
Flattening Board Narrow – Wide Operation:	Motorized narrow – wide operation
Bubble Support:	Side support with motorized open – close movement

Take-Off Nip Roller Assembly:

Subject	Description
Take-Off Nip Roller Type:	Reversing type
Take-Off Nip Roller Width (mm):	1350mm
Take-Off Nip Roller Material of Construction & Surface Treatment:	**One hard chrome plated chilling type steel roller** and one neoprene coated rubber roller
Take-Off Nip Roller Actuation:	Electro pneumatic type **(Janatics make)**
Take-Off Nip Roller Motor (kW/HP):	0.75kW/1HP AC motor open loop control with gearbox **(Rotomotive make)**
Take-Off Nip Roller Drive:	Through **1.1kw/1.5HP** AC frequency drive **(ABB/YASKAWA make)**
Take-Off Nip Roller Power Transmission:	Through timing belt
Take-Off Nip Roller Line Speed Range (m/Minutes):	7 – 90m/minutes

Winder Nip:

Subject	Description
Winder Nip Type:	Fixed type
Winder Nip Roller Diameter (mm) & Width (mm):	125mm diameter & 1350mm width
Winder Nip Material of Construction & Surface Treatment:	**One hard chrome plated steel roller** and one neoprene coated rubber roller
Winder Nip Actuation:	Pneumatic operated **(Janatics make)**
Winder Nip Drive & Drive Load (kW/HP):	0.75kW/ 1HP AC motor with gearbox **(Roto motive make)**
Winder Nip Control:	Through AC frequency drive 1.1kw/1.5hp **(YASKAWA/ABB make)**
Winder Nip Power Transmission:	Through chain and sprockets

Standard Features:

- Digital Type Meter Counter
- Auto Tension Control Mechanism Through Load Cell **(E+L make)**
- Touch Screen HMI on Winder Panel

Fully Automatic Two Station Pneumatic Surface Winder:

Above image is for reference only. Actual supply will be as per contract agreed upon

Above image is for reference only. Actual supply will be as per contract agreed upon

Subject	Description
Winder Type:	Fully automatic two station pneumatic surface winder
Winder Drum Roller Diameter (mm) & Width (mm):	355mm diameter & 1350mm width
Winder Application:	Winding of flattened film
Number of Winding Stations:	Two stations
Winder Design:	Surface winding
Winder Motor (kW/HP):	0.75W/1HP AC motor with gearbox for each station **(Rotomotive make)**
Winder Control:	Through variable AC frequency drive 1.1kw/1.5hp **(ABB/WEG make)** & on-off switch on winder
Winder Drum Power Transmission:	Through direct drive
Winder Expander Roller:	Expander rollers for wrinkle free operation provided on each winding station
Winder Core Tube Diameter (mm) & Width (mm):	76mm diameter & 1350mm width
Maximum Winding Diameter (mm) & Weight (kg):	800mm/ 800kg (whichever occurs first)
Length Counter:	Digital length cum line speed indicator
Trim Suction Blower (kW/HP):	3.7kW/ 3HP blower with motor **(ABB make)**
Winding Arm:	Close – open with electro pneumatic mechanism
Tubular Film Separation:	Supported by air jet lossa cutter along with blades loaded with dead weight
Slitting Assembly:	By blade holders (4 Nos.) with 2 blades per holder (Adjustable along the width) provided on each winding station
Winder Auto Tension Control:	Through load cell, encoder feedback & plc control system for both winding stations
Winder Auto Splicing:	Auto splicing through rod less cylinder over preselected length **(Festo make)**

Reel Changing Mechanism:

Subject	Description
Actuation of Reel Change:	By reading sensor & PLC
Meter Counter Mechanism:	Electronic meter counter through proximity sensor
Winder Shaft:	3" (4 Nos.) Air shafts
Winder Core Tube Dimensions (mm):	76mm x 185mm x 1350mm

Standard Features of Winder:

Winder & Pneumatic Circuit:
• Bubble layer separation for side slitting of tube
• Auto splicing over preselected length
• Slitting and trim suction assembly
• Auto reel change over mechanism
• Digital meter counter
• 9’’ true color touch screen HMI
• Pneumatic circuit system with pressure of 5 kg/cm²
• Pneumatic circuit provided for diaphragm cylinder
• Pneumatic circuit provided for nip actuation
• Pneumatic circuit provided for swiveling
• Pneumatic circuit provided for winder shaft locking
• Pneumatic circuit provided for web cutting
• Pneumatic circuit provided for pressure cylinder
• Antistatic eliminators provided on both winding station to eliminate static electricity in web

Electrical Control Panel for Heaters:

Sr. No.	Description
1	Digital temperature controller with SSR microprocessor based auto tuning type with dual display for set temperature value and actual temperature value **(Omron make)**
2	All the MCBs are **SIEMENS make**
3	SSR System for better energy efficiency, precise temperature control for durability of heaters
4	14Nos. of heating zones
5	Provision for low & high temperature protection

Electrical Control Panel for Drives:

Sr. No.	Description	Qty.
1	Extruder – A: Outer layer (55mm Extruder) with 30kW/ 40HP AC Motor **(ABB/WEG make) & AC** frequency drive **(ABB/YASKAWA make)**	**1 No.**
2	Extruder – B: Middle layer (55mm Extruder) with 30kW/ 40HP AC Motor **(ABB/WEG make) & AC** frequency drive **(ABB/YASKAWA make)**	**1 No.**
3	Extruder – C: Inner layer (55mm Extruder) with 30kW/ 40HP AC Motor **(ABB/WEG make) & AC** frequency drive **(ABB/YASKAWA make)**	**1 No.**
4	Main blower (Air cooling ring blower) with 7.5kW/ 10HP AC Motor **(ABB/WEG make) & AC** frequency drive **(ABB/YASKAWA make)**	**1 No.**
5	Take-off nip with 1.1kW/ 1.5HP AC frequency drive **(ABB/YASKAWA make)**	**1 No.**
6	Vertical haul-off rotation with 0.375kW/ 0.5HP AC frequency drive **(ABB/YASKAWA make)**	**1 No.**
7	Winder nip with load cell control with 1.1kW/ 1.5HP AC frequency drive **(ABB/YASKAWA make)**	**1 No.**

Control Panel for Winder:

Sr. No.	Description	Qty.
1	7” touch screen HMI for winder	**1 No.**
2	Winding station 1 with 1.1kW/1.5HP AC frequency drive **(ABB/YASKAWA make)**	**1 No.**
3	Winding station 2 with 1.1kW/ 1.5HP AC frequency drive **(ABB/YASKAWA make)**	**1 No.**
4	Digital length cum line speed indicator with buzzer	**1 No.**

Control Panel Color: RAL (7034) Gray & Off-White

Annexure – 5 (Terms & Conditions):

Terms and Conditions (Part – 1):

Terms	Conditions
Payment Terms:	45% advance along with PO, balance payment before dispatch after satisfactory trial run at our factory.
Bank Details:	• Beneficiary Name: Shubham Extrusion Machines Pvt. Ltd. • Beneficiary A/C No.: 8745316776 • Bank Name: Kotak Mahindra Bank • Branch: Ramol, Ahmedabad, India • IFSC Code: KKBK0000837
Taxes:	GST & TCS will be charged extra at prevailing rates at the time of dispatch.
Freight & Insurance	Freight, insurance and all onward charges will be at customer's account.
Delivery Time:	Within 90 – 120 days after receipt of the 45% advance payment.
Packing:	Packing charges will be 1.5% extra applicable on basic price before discounts for essential packing.
Trial:	Raw material will be managed by the customer as per our suggested recipe for the trial at our factory.
Erection & Commissioning:	• Shubham Extrusion will depute an Engineer/Technician for supervision of machine erection and commissioning. • Charges to be paid for the machine Erection & installation agency will be managed by the customer. • All the utilities like electricity, earthing, air & water supply connection, distribution panel and others should be ready before the installation process commence. • Engineer's airfare, to & fro, pick up & drop and accommodation will be managed by the customer. • Engineer's local travel expense from airport/ railway station/ bus station by auto/ cab will be managed by the customer. • **As per the government's guideline for Covid-19 situation, customer should take care of the below mentioned conditions:** **a)** Provide hygienic food and packaged drinking water bottle to our service person. **b)** Provide mask and sanitizer to our person daily. **c)** Provide hotel accommodation where hygiene and cleanliness is well maintained. **d)** Provide safe travel from hotel to your factory. **e)** Provide a man power who doesn't have any symptoms like fever and cough. • **The quotation does not include the following, which will be extra to cost on the buyer / customer:** **a)** Actual to & fro fare for two persons to be borrow by the customer. **b)** All raw materials, skilled & unskilled labor required during erection should be provided by customer as well as all other infrastructure necessities including water supply, air conditioning as the case may be at his expense. **c)** Designs, specifications indicated in the offer are subject to constant modifications and changes from time to time and therefore, specifications designs indicated in the offer are not final or binding on the supplier.

Note:

- Under no circumstance Shubham Extrusion Technik Pvt. Ltd. shall be liable for lost products, production, time, and/or waste of raw material.

Terms & Conditions (Part – 2):

Subject	Description
Offer Validity:	• This offer is valid subject to our final confirmation. • This sales contract will come into effect and considered valid only when buyer / customer place a firm order with respect to price quantity etc. and this order when confirmed in writing by the seller.
Inspection:	• We shall offer pre-dispatch inspection at our works by you or your authorized representative. • Trial will be done for one size & one gauge.
Scope of Delivery:	• The delivery period given in the order confirmation begins upon the date of the order confirmation by the supplier. The delivery period shall be reasonably extended if the buyer requests in the case of labor disputes, force majeure or other unforeseen circumstances as laid down in clause and also this can apply in sub-contractor case. • The company shall not be held liable for any loss or damage of whatsoever nature, if any, caused as a result of delay in or failure of delivery.
Forfeiting of Advance:	Once the buyer / customer places the order along with advance amount and supplier confirms it the entire amount of advance will be forfeited in the case of buyer / customer wishes to cancel the order, and fails to lift the machine within 15 days from the date of intimation by the supplier to lift the machine.
Property Rights:	The supplier reserves absolute proprietary rights over the goods ordered until such time the full payment is received as agreed in time under this contract.
Repairs and/or Alteration:	• Any alternation and / or repair carried out by buyer / customer or by a third party without the prior written concerned by the supplier does not fall within the scope of the warrantee offered by the supplier. Any resultant consequences arising out of such alteration and / or repairs that does not fall. With twin scope of suppliers guarantee will not be to the supplier's risk. • In case the buyer / customers fail to fulfill this commitment under this contract the supplier will not be responsible for any obligations including repairs and / or alternation.
Loss/ Damage/ Pilferage Etc. During the Transit:	It is in the interest of buyer / customer to obtain insurance cover against the respective order, since the suppliers responsibilities cease as soon as the goods are delivered to the transport carrier. The supplier ceases to own any conscious liabilities against any damages, loss, pilferage etc. while the goods are in transit or thereafter.
Bought-Out Items:	• The supplier offers its warrantee over bought out items supplied along with its manufactured goods. Any warrantee as the case may be offered by the supplier of the bought-out items will however be effective, without recourse to the supplier of this contract. • Attachment & Accessories provided with the main plant are covered by warrantee whatsoever.

Terms & Conditions (Part – 3):

Subject	Description
Warranty:	The supplier undertakes warrantee for period of six months for all electrical & electronic parts & all other mechanical component in one-year warranty from the date of dispatch for the goods manufactured by him against any manufacturing defects or supply by him. The warrantee does not cover any defect or damage caused by accident, transit misuse of the machine. The guarantee presumes that use the equipment with necessary care as per the standard industrial practice and does not include components which are subject to tear and wear. • This warrantee will come into effect from the date that the goods is ready for the dispatch governed by following guidelines. • That each article of part is properly installed used & operated in normal manner under standard working condition. • That the buyer / customer should notify the supplier at this Ahmedabad office by a Regd. Post within 15 days in first discovery of any defect and no claims will be entertained thereafter. • That the buyer / customer should obtained return authorization from the supplier before returning any defective article and / or part through a transport carrier on a freight pre-paid basis to the supplier's Ahmedabad office. • That the supplier reserves sole discretion in carrying out these obligations. • That the supplier will determine after the buyer / customer returns such defective article and / or part and shall replace such article and/ or party only in case it is found that the defect is the result of poor material and / or unsound workmanship. The supplier's decision will be final. • **Manufacturing Warranty:** 1 year from the date of dispatch, against manufacturing defect. • **Extruder Gearbox Warranty:** 1 year from the date of dispatch, against manufacturing defect. • **Electrical Components (VFDs, HMI & Motors) Warranty:** 6 Month from the date of dispatch, against manufacturing defect. • **Heaters Warranty:** 3 Months from the date of dispatch, against manufacturing defect. • Shubham Extrusion Technik Pvt. Ltd. will provide the toolkit with the machine at the time of dispatch. • **Spares:** Heaters kit will be chargeable (Extra at actual). • Customer will have to pay only for repairing/ purchasing of the parts/ components if the parts/ components cannot be claimed under warranty in the case of replacement/repairing required.
Limitation of Liabilities:	The supplier's liabilities are limited only to such effect as explicitly specified here in above governed by this contract and under no circumstances will this contract be valid if terms of payment & are not fully and punctually complied by the buyer / customer.
Jurisdiction:	This offer is subject to the Jurisdiction of Ahmedabad (Gujarat) Courts only.

Thanking you,
Sincerely yours,
For, SHUBHAM EXTRUSION TECHNIK PVT. LTD.

MR JANAK PATEL
GM SALES
+91 8488843586