

Ex No: 7**Date: 11/09/24****Autoencoder using the Fashion MNIST Dataset
(With Denoising the dataset)****Objective:**

To build an autoencoder that denoises Fashion MNIST images by compressing them into a lower-dimensional representation and reconstructing the original images from the compressed format.

Descriptions:

In this exercise, we broke the implementation down into three steps:

Data Preparation:

- Fashion MNIST images are loaded and normalized using TensorFlow Datasets (TFDS).
- Noise is added to the images, and the noisy images are used as inputs to the model, while the clean images are used as targets.

Model Architecture:

- **Encoder:** Consists of two Conv2D layers followed by MaxPooling layers, reducing the image size while extracting features.
- **Bottleneck:** A dense representation compresses the information further.
- **Decoder:** Upsamples the compressed representation back to the original image size using Conv2D and UpSampling2D layers.

Training:

- The model is compiled with the Adam optimizer and binary cross-entropy loss.
- The training is performed for 40 epochs with a batch size 128.

Model:**Encoder:**

- Two convolutional layers with 64 and 128 filters respectively, each followed by a MaxPooling layer.
- Compresses the image down to a smaller representation.

Bottleneck:

- A convolutional layer with 256 filters that acts as the compressed representation layer.

Decoder:

- Two convolutional layers that upsample the encoded representation back to the original image size.

USN NUMBER: 1RVU22CSE187

NAME: Vedansh Maheshwari


Model: "functional"

Layer (type)	Output Shape	Param #
input_layer (InputLayer)	(None, 28, 28, 1)	0
conv2d (Conv2D)	(None, 28, 28, 64)	640
max_pooling2d (MaxPooling2D)	(None, 14, 14, 64)	0
conv2d_1 (Conv2D)	(None, 14, 14, 128)	73,856
max_pooling2d_1 (MaxPooling2D)	(None, 7, 7, 128)	0
conv2d_2 (Conv2D)	(None, 7, 7, 256)	295,168
conv2d_4 (Conv2D)	(None, 7, 7, 128)	295,040
up_sampling2d (UpSampling2D)	(None, 14, 14, 128)	0
conv2d_5 (Conv2D)	(None, 14, 14, 64)	73,792
up_sampling2d_1 (UpSampling2D)	(None, 28, 28, 64)	0
conv2d_6 (Conv2D)	(None, 28, 28, 1)	577

Total params: 739,073 (2.82 MB)
Trainable params: 739,073 (2.82 MB)
Non-trainable params: 0 (0.00 B)

Result and Analysis:

The autoencoder learned to denoise the images by reconstructing them from noisy inputs. The clean outputs show that the model effectively removed noise, retaining key details of the original images.



GitHub Link:

[https://github.com/VedanshMaheshwari/Deep-](https://github.com/VedanshMaheshwari/Deep-Learning/blob/main/Labs/Lab%206/Lab06_4_Encoder_Denoising_DISTRI_VedanshM.ipynb)

[Learning/blob/main/Labs/Lab%206/Lab06_4_Encoder_Denoising_DISTRI_VedanshM.ipynb](https://github.com/VedanshMaheshwari/Deep-Learning/blob/main/Labs/Lab%206/Lab06_4_Encoder_Denoising_DISTRI_VedanshM.ipynb)