1 Input Parameters

Module	Tension Member Design - Bolted to End Gusset
Axial (kN)*	76.0
Length (mm) *	1250.0
Section Profile*	Angles
Section Size*	Ref List of Input Section
Section Material	E 250 (Fe 410 W)A
Ultimate Strength, F_u (MPa)	410
Yield Strength, F_y (MPa)	250
Bolt Details - Input and Design Preference	
Diameter (mm)	[8]
Property Class	[4.6]
Type	Bearing Bolt
Hole Type	Standard
Detailing - Design Preference	
Edge Preparation Method	Sheared or hand flame cut
Are the Members Exposed to Corrosive Influences?	False
Plate Details - Input and Design Preference	
Thickness (mm)	[8, 10, 12, 14, 16, 18, 20, 22, 25, 28, 32, 36, 40, 45, 50, 56, 63, 75, 80, 90, 100, 110, 120]
Material	E 250 (Fe 410 W)A

1.1 List of Input Section

Section Size*	'40 x 40 x 5'

1.2 List of Input Section

Section Size*	'40 x 40 x 5'

2 Design Checks

Design Status	Fail

2.1 Selected Member Data

C:/Users/parth/Downloads/Osdag/ResourceFiles/images/equaldp.png

Section Size*		('40 x 40 x 5', 'Angles')		
Material		E 250 (Fe 410 W)A		
Mass, m (kg/m)		2.99		
Area, A (cm^2)		381.0		
A (mm)	40.0	I_v(cm^4)	2.33	
B (mm)	40.0	r_z (cm)	1.21	
t (mm)	5.0	r_y (cm)	1.21	
R_1 (mm)	5.5	r_u (cm)	1.52	
R_2 (mm)	0.0	r_v (cm)	0.78	
C_y (mm)	11.7	Z_z (cm^3)	1.97	
C_z (mm)	11.7	Z_y (cm^3)	1.97	
I_z (cm^4)	5.58	Z_{pz} (cm^3)	3.55	
I_y(cm^4)	5.58	Z_{py} (cm^3)	3.57	
I_u (cm^4)	8.83	Radius of gyration, r (cm)	7.8	

2.2 Spacing Check

Check	Required	Provided	Remarks
Min. Diameter (mm)		$d = 8$	
Hole Diameter (mm)		$d_0 = 8$	
Minimum Bolts (nos)		$r_l = 1$	

Check	Required	Provided	Remarks
Min. Gauge Distance (mm)	$p/g_{\min} = 2.5d$ $= 2.5 \times 8.0$ $= 20.0$ [Ref. IS 800:2007, Cl.10.2.2]	0.0	
Min. Edge Distance (mm)	$e_{\min} = 1.5d_0$ $= 1.5 \times 8$ $= 12.0$ [Ref. IS 800:2007, Cl.10.2.4.2]	15	
Spacing Check	depth $= 2\ e + (r_l - 1)\ g$ $= 2 \times 15 + (1 - 1) \times 20$ $= 30$	29.5	**Fail**

2.3 Member Check

Check	Required	Provided	Remarks
Tension Yielding Capacity (kN)		$T_{\text{dg}} = \frac{A_g f_y}{\gamma_{m0}}$ $= \frac{381.0 \times 250}{1.1 \times 10^3}$ $= 86.59$ [Ref. IS 800:2007, Cl.6.2]	
Slenderness	$\frac{KL}{r} \leq 400$	$\frac{KL}{r} = \frac{1 \times 1250.0}{7.8}$ $= 160.26$ [Ref. IS 800:2007, Cl.7.1.2]	**Pass**