# Word Representation

• Represent every word as an  $\mathbb{R}^{|V| \times 1}$  vector with all 0s and one 1 at the index of that word.(|V| is the size of our vocabulary )

ullet Represent every word as an  $\mathbb{R}^{|V| imes 1}$  vector with all 0s and one 1 at the index of that word.(|V| is the size of our vocabulary )

### Example:

High, Low, Hotel, Resort

$$w^{High} = \begin{bmatrix} 1\\0\\0\\0 \end{bmatrix}, w^{Low} = \begin{bmatrix} 0\\1\\0\\0 \end{bmatrix}, W^{Hotel} = \begin{bmatrix} 0\\0\\1\\0 \end{bmatrix}, w^{Resort} = \begin{bmatrix} 0\\0\\0\\1 \end{bmatrix}$$

#### Problem with One Hot Vector

Vector size very big.(Consider vocab size of 13M words)

- Vector size very big.(Consider vocab size of 13M words)
- Sparse Vector

- Vector size very big.(Consider vocab size of 13M words)
- Sparse Vector
- Cannot capture semantic similarity.

- Vector size very big.(Consider vocab size of 13M words)
- Sparse Vector
- Cannot capture semantic similarity.
   Example:

- Vector size very big.(Consider vocab size of 13M words)
- Sparse Vector
- Cannot capture semantic similarity.
   Example:
   Hotel and Resort are synonyms but vector are not similar

#### **Problem with One Hot Vector**

- Vector size very big.(Consider vocab size of 13M words)
- Sparse Vector
- Cannot capture semantic similarity.

Example:

Hotel and Resort are synonyms but vector are not similar

 $\mathsf{Hotel} = [0 \ 0 \ 1 \ 0]$ 

Resort =  $[0 \ 0 \ 0 \ 1]$ 

### Learn encode similarity in the vectors themselves

• How we learn to encode similarity in the vectors themselves?

- How we learn to encode similarity in the vectors themselves?
  - Represent words by their context.

- How we learn to encode similarity in the vectors themselves?
  - Represent words by their context.
- Distributional semantics:

- How we learn to encode similarity in the vectors themselves?
  - Represent words by their context.

#### • Distributional semantics:

A word's meaning is given by the words that frequently appear close-by

- How we learn to encode similarity in the vectors themselves?
  - Represent words by their context.

#### Distributional semantics:

A word's meaning is given by the words that frequently appear close-by

"You shall know a word by the company it keeps"
 (J. R. Firth 1957: 11)

- How we learn to encode similarity in the vectors themselves?
  - Represent words by their context.

#### Distributional semantics:

A word's meaning is given by the words that frequently appear close-by

- "You shall know a word by the company it keeps"
   (J. R. Firth 1957: 11)
- Context of word w in text is a set of words (within a fixed-size window) that appear nearby.

- How we learn to encode similarity in the vectors themselves?
  - Represent words by their context.

#### Distributional semantics:

A word's meaning is given by the words that frequently appear close-by

- "You shall know a word by the company it keeps" (J. R. Firth 1957: 11)
- Context of word w in text is a set of words (within a fixed-size window) that appear nearby.
- Contexts are used to construct a representation of w

### Word Representation - Word2Vec - Context

... government debt problems turning into banking crises as happened in 2009...
... saying that Europe needs unified banking regulation to replace the hodgepodge...
... India has just given its banking system a shot in the arm...

Those context words will represent

These context words will represent banking

### Word Representation - Word2Vec - Context

... government debt problems turning into banking crises as happened in 2009...
... saying that Europe needs unified banking regulation to replace the hodgepodge...
... India has just given its banking system a shot in the arm...

These context words will represent banking

 Construct a dense vector for each word to be similar to word vectors that appear in similar contexts.

### Word Representation - Word2Vec - Context

... government debt problems turning into banking crises as happened in 2009...
... saying that Europe needs unified banking regulation to replace the hodgepodge...
... India has just given its banking system a shot in the arm...

These context words will represent banking

 Construct a dense vector for each word to be similar to word vectors that appear in similar contexts.

 $\mathsf{Window}\;\mathsf{size}=2$ 

Window size = 2

Center

India has just given its banking system a shot in the arm

Window size = 2

Center
India has just given its banking system a shot in the arm
Context

Window size = 2

Center
India has just given its banking system a shot in the arm
Context

India has just given its banking system a shot in the arm

Window size = 2

Center
India has just given its banking system a shot in the arm
Context
India has just given its banking system a shot in the arm
India has just given its banking system a shot in the arm

Window size = 2

Center
India has just given its banking system a shot in the arm
Context
India has just given its banking system a shot in the arm
India has just given its banking system a shot in the arm

Word2vec (Mikolov et al. 2013)  $^{1}$  is a framework for learning word vectors.

<sup>&</sup>lt;sup>1</sup>Tomas Mikolov et al.,Distributed Representations of Words and Phrases and Their Compositionality, NIPS, Volume 2, 2013, 3111–3119

Word2vec (Mikolov et al. 2013) <sup>1</sup> is a framework for learning word vectors.

<sup>&</sup>lt;sup>1</sup>Tomas Mikolov et al., Distributed Representations of Words and Phrases and Their Compositionality, NIPS, Volume 2, 2013, 3111–3119

Word2vec (Mikolov et al. 2013) <sup>1</sup> is a framework for learning word vectors.

#### Idea:

We have a large corpus of text

<sup>&</sup>lt;sup>1</sup>Tomas Mikolov et al., Distributed Representations of Words and Phrases and Their Compositionality, NIPS, Volume 2, 2013, 3111–3119

Word2vec (Mikolov et al. 2013) <sup>1</sup> is a framework for learning word vectors.

- We have a large corpus of text
- Every word in a fixed vocabulary is represented by a vector.

<sup>&</sup>lt;sup>1</sup>Tomas Mikolov et al., Distributed Representations of Words and Phrases and Their Compositionality, NIPS, Volume 2, 2013, 3111–3119

Word2vec (Mikolov et al. 2013) <sup>1</sup> is a framework for learning word vectors.

- We have a large corpus of text
- Every word in a fixed vocabulary is represented by a vector.
- Go through each position t in the text, which has a center word c and context ("outside") words o.

<sup>&</sup>lt;sup>1</sup>Tomas Mikolov et al.,Distributed Representations of Words and Phrases and Their Compositionality, NIPS, Volume 2, 2013, 3111–3119

Word2vec (Mikolov et al. 2013)  $^{1}$  is a framework for learning word vectors.

- We have a large corpus of text
- Every word in a fixed vocabulary is represented by a vector.
- Go through each position t in the text, which has a center word c and context ("outside") words o.
- Use the similarity of the word vectors for c and o to calculate the probability of o given c (or vice versa).


<sup>&</sup>lt;sup>1</sup>Tomas Mikolov et al., Distributed Representations of Words and Phrases and Their Compositionality, NIPS, Volume 2, 2013, 3111–3119

Word2vec (Mikolov et al. 2013) <sup>1</sup> is a framework for learning word vectors.

- We have a large corpus of text
- Every word in a fixed vocabulary is represented by a vector.
- Go through each position t in the text, which has a center word c and context ("outside") words o.
- Use the similarity of the word vectors for c and o to calculate the probability of o given c (or vice versa).
- Keep adjusting the word vectors to maximize this probability.


<sup>&</sup>lt;sup>1</sup>Tomas Mikolov et al.,Distributed Representations of Words and Phrases and Their Compositionality, NIPS, Volume 2, 2013, 3111–3119

Example windows and process for computing  $P(w_{t+1}|w_t)$ 



http://web.stanford.edu/class/cs224n/slides/cs224n-2019-lecture01-wordvecs1.pdf

Example windows and process for computing  $P(w_{t+1}|w_t)$ 



http://web.stanford.edu/class/cs224n/slides/cs224n-2019-lecture01-wordvecs1.pdf

Two Algorithm


- Two Algorithm
  - Continuous bag-of-words (CBOW)

- Two Algorithm
  - ① Continuous bag-of-words (CBOW)
    - Predict a center word from the surrounding context in terms of word vectors.


- Two Algorithm
  - ① Continuous bag-of-words (CBOW)
    - Predict a center word from the surrounding context in terms of word vectors.
  - ② Skip-gram

- Two Algorithm
  - ① Continuous bag-of-words (CBOW)
    - Predict a center word from the surrounding context in terms of word vectors.
  - ② Skip-gram
    - Predicts the probability of context words from a center word.


- Two Algorithm
  - ① Continuous bag-of-words (CBOW)
    - Predict a center word from the surrounding context in terms of word vectors.
  - ② Skip-gram
    - Predicts the probability of context words from a center word.




A simple CBOW model with only one word in the context




A simple CBOW model with only one word in the context




A simple CBOW model with only one word in the context




A simple CBOW model with only one word in the context V = Vocabulary size N = Word embedding vector size




A simple CBOW model with only one word in the context



A simple CBOW model with only one word in the context



A simple CBOW model with only one word in the context





A simple CBOW model with only one word in the context


Example: How we take word embedding/ word vector from Weight  $W_{N\!\times\!V}^{'}$ 


$$\begin{bmatrix} 0 & 0 & 0 & 1 & 0 \end{bmatrix} \times \begin{bmatrix} 17 & 24 & 1 \\ 23 & 5 & 7 \\ 4 & 6 & 13 \\ 10 & 12 & 19 \\ 11 & 18 & 25 \end{bmatrix} = \begin{bmatrix} 10 & 12 & 19 \end{bmatrix}$$


https://israelg99.github.io/2017-03-23-Word2Vec-Explained/

















- Input layer takes the one hot encoded vectors of the context words as input.
- Two sets of weights
  - ① between input layer and hidden layer (size  $V \times N$ )
  - ② between input layer and hidden layer (size NxV)
- Input is multiplied with input-hidden weights and hidden input is multiplied with hidden-output weights to produce a output vector.
- Output vector is then passed through a softmax function which gives the probability of target word w.r.t each context word.
- Target word is the one hot encoding representation of the word
- Error between output and target is calculated and then update weights.

### Word Representation - Word2Vec - CBOW - Softmax

- Simply calculates probability of occurrence of the target word w.r.t.
   the context word
- Consider that target word is denoted by vector  $u_c$  and context words are denoted by vectors  $\hat{v}$ .
- The probability sums to 1

$$P(u_c|\hat{v}) = \frac{\exp(u_c^T \hat{v})}{\sum_{j=1}^{|V|} \exp(u_j^T \hat{v})}$$


Input Layer

0 • 0

V-dim


I like playing football with friend

Skip-gram Architecture




I like playing football with friend


Skip-gram Architecture





Skip-gram Architecture

CxV - dim









- One hot encoded vector of target word is taken as input and multiplied with VxN input hidden matrix.
- Hidden layer is multiplied with hidden output matrix to give the output vectors.
- Take softmax function over the output vectors and then calculate the error between the actual vector and the predicted vectors and backpropagate to update the weights.

## Word Representation - Word2Vec - Objective Function

For each position t = 1, ..., T, predict context words within a window of fixed size m, given center word  $w_j$ .

Likelihood = 
$$L(\theta) = \prod_{t=1}^{T} \prod_{-m < j < m, j \neq 0} P(w_{t+j}|w_t; \theta)$$

## Word Representation - Word2Vec - Objective Function

• For each position t = 1, ..., T, predict context words within a window of fixed size m, given center word  $w_j$ .

Likelihood = 
$$L(\theta) = \prod_{t=1}^{T} \prod_{-m \le j \le m, j \ne 0} P(w_{t+j}|w_t; \theta)$$

• The cost function  $J(\theta)$  is the (average) negative log likelihood:

$$J(\theta) = -\frac{1}{T} \log L(\theta) = -\frac{1}{T} \sum_{t=1}^{T} \sum_{-m \le j \le m, j \ne 0} P(w_{t+j}|w_t; \theta)$$

## Word Representation - Word2Vec - Objective Function

• For each position t = 1, ..., T, predict context words within a window of fixed size m, given center word  $w_j$ .

Likelihood = 
$$L(\theta) = \prod_{t=1}^{T} \prod_{-m \le j \le m, j \ne 0} P(w_{t+j}|w_t; \theta)$$

• The cost function  $J(\theta)$  is the (average) negative log likelihood:

$$J(\theta) = -\frac{1}{T} \log L(\theta) = -\frac{1}{T} \sum_{t=1}^{T} \sum_{-m \le j \le m, j \ne 0} P(w_{t+j}|w_t; \theta)$$

Relies only on local information of a corpus.

- Relies only on local information of a corpus.
- The semantics learnt for a given word, is only affected by the surrounding words.

- Relies only on local information of a corpus.
- The semantics learnt for a given word, is only affected by the surrounding words.
- Require to look local information and global information of a corpus.