ResearchPaper Lens — Forensic & Analytical Report

Generated at: 2026-10-25T05:11:41.264341+00:00 (UTC) | Schema Version: 1.0.0 | File: sample_02_metadata_rich.txt

1. Document Integrity & Cryptographic Evidence

Metric / Digest	Value
Filename:	sample_02_metadata_rich.txt
File Size:	1,686 bytes
Pages / Words / Sentences:	1 pages | 164 words | 14 sentences
References Section:	Detected & Isolated
SHA-256 Digest:	`03c37331af3e710a6751d80842a47cc9aa72ecd8307c9112a62bca0b2ce09396`
SHA-1 Digest:	`1f46c8466dd0a0d2500409311c6b6f05f7f0c14f`
MD5 Digest:	`36800a85252836d5ad4fb7d8358f4abf`

2. Explainable Review Cues & Limitations

- Extractive Faithfulness: TextRank extracts verbatim sentences directly from source text (0% hallucination risk).
- Graph Centrality: Vertex importance is determined via PageRank (d=0.85, max_iter=100) over TF-IDF cosine similarities.
- Chronological Ordering: Extracted sentences are strictly restored to their original document sequence.
- Scanned PDF Limitation: Low-text heuristic (< 100 chars/page) flags image-only PDFs where embedded text is minimal.
- Lexical Search Boundary: Passage retrieval uses lexical TF-IDF matching and does not perform neural semantic re-ranking.
- Privacy by Default: Sensitive personal identifiers, emails, and credentials are automatically masked.

3. TextRank Extractive Summary (49 words, 29.9% compression)

Extracted 3 sentences out of 14 using TF-IDF PageRank graph centrality.

Graph Neural Networks for Academic Document Analysis Abstract Information retrieval and natural language processing techniques increasingly utilize graph-based representations for document modeling. In this paper, we evaluate TextRank algorithms applied to technical document segmentation. Graph-Based Centrality Formulation We represent documents as sentence graphs where vertices correspond to individual sentences.

4. Academic Baseline Summaries

Method	Output
Lead-k: *(First k sentences)*	Graph Neural Networks for Academic Document Analysis Abstract Information retrieval and natural language processing techniques increasingly utilize graph-based representations for document modeling. In this paper, we evaluate TextRank algorithms applied to technical document segmentation. Introduction Academic literature has grown exponentially over the past decade.

Word-Frequency: *(Term count weighting)*	Graph Neural Networks for Academic Document Analysis Abstract Information retrieval and natural language processing techniques increasingly utilize graph-based representations for document modeling. In this paper, we evaluate TextRank algorithms applied to technical document segmentation. Graph-Based Centrality Formulation We represent documents as sentence graphs where vertices correspond to individual sentences.

5. Salient Keywords (TF-IDF Aggregation)

document: 1.00	**centrality**: 0.80	**technical**: 0.75
academic: 0.71	**graph**: 0.66	**frequency**: 0.65
based: 0.61	**sentences**: 0.58	**textrank**: 0.56
calculated: 0.53		

Confidentiality & Privacy: Redactions applied (0 sensitive patterns masked). Document evaluated locally with ResearchPaper Lens.