LastOne

Social Architecture

Design Spec — All Three Layers

Version 1.0 — March 2026

About this document

This document is the full design and system logic record for the LastOne Social Architecture. It covers all three layers: Quit Groups, Nearby Quitters, and Community Feed. It is a working reference for the design and development team, not a concept document. Every decision here was made deliberately.

This document covers:

- Why the social layer exists and what it is designed to do
- Layer 1: Quit Groups — full design, flows, shared moments, privacy model
- Layer 2: Nearby Quitters — foundations spec and privacy tiers
- Layer 3: Community Feed — full design, moderation, and nudge system
- System logic reference for all three layers
- Full decisions log

Why the Social Layer Exists

Smoking is a social behaviour. Lighting up at the tapri, the chai break between lectures, the cigarette shared after a stressful exam — for Indian college students, smoking is woven into the fabric of how people connect. Quitting in isolation while your friends keep smoking is one of the primary reasons quit attempts fail.

The social layer exists to keep quitting from being lonely. It does not try to replace the social ritual of smoking. It tries to build a new one around quitting — people doing it together, supporting each other, and making the journey feel shared rather than solitary.

Core principle: the social layer is about togetherness, not surveillance. It surfaces the right information at the right time, with the user's consent, to make others feel less alone.

Three layers, all in-app

Layer 1	Quit Groups — small groups of 2–6 people the user already knows. The most intimate layer. Active accountability and shared journey.
Layer 2	Nearby Quitters — opt-in discovery of other LastOne users in the same area. Loose connection with strangers who are quitting nearby.
Layer 3	Community Feed — a shared space for the entire LastOne community. Posts, questions, encouragement. Most relevant from Stage 3 onwards.

Layer 1: Quit Groups

Quit Groups are the heart of the social layer. They are small groups of friends — people who already know each other — who choose to quit together. The design philosophy is collaborative quitting: shared motivation, shared wins, shared hard moments. Not parallel quitting where everyone does their own thing and happens to be in the same app.

1.1 What makes this different from solo quitting

Solo quitting in LastOne is a fully supported experience. But Quit Groups add a second layer on top of it: the knowledge that people who know you are going through the same thing, at roughly the same time, and are paying attention.

This matters because the primary failure mode for our target user is social. The chai break happens with friends. The tapri is a shared ritual. Quit Groups make it possible to change that ritual together, rather than one person opting out while everyone else stays in.

1.2 Group structure

- 2–6 members per group
- Created by any member at any stage
- Invite via shareable link (WhatsApp, SMS, or copy)
- Each member keeps their individual stage, streak, and progress
- The group has a founding date — set by the creator, cannot be backdated

> *The founding date is symbolic, not mechanical. It is the anchor of 'we started this together' and never resets, even if individual members relapse and restart. The group is still X days old. The individual is on day 3 of a new attempt. Both are true simultaneously.*

1.3 Group dashboard

The group dashboard is the shared view all members see. It shows:

- Founding date and 'fighting together for X days' counter — always counting up, never resets
- Combined smoke-free days this week — additive, gain-framed, never punishes one person's slip
- Each member's individual streak and current stage
- Recent shared moments — milestones, rough day flags, SOS pings, weekly reflections
- Optional group chat layer

1.4 Joining a group

There are two ways to form a group: the creator invites friends who are already on LastOne, or invites friends who are new to the app. Both paths are supported.

New user joining via invite link
Full LastOne onboarding is shown, with group context visible throughout. The friend knows they are joining a group from the start.

Existing user joining via invite link
Onboarding is skipped. The user goes straight to sharing preferences and joins the group directly.

After joining, every member sets their sharing preferences before the group dashboard opens. This is a one-time setup that can be changed anytime from settings.

1.5 Sharing preferences

Every shared moment in a Quit Group requires the member's consent. Sharing preferences are set at group join, recommended defaults lean toward sharing, and every toggle is individually switchable at any time.

Sharing feature	What gets shared	Default
Milestone sharing	Health milestones and streak milestones. Prompted after the win — user chooses to share or keep private.	On (recommended)
Rough day flag	A signal that the user is having a hard day. App suggests it after a slip or multiple cravings. Always user-initiated.	On (recommended)
SOS group ping	An SOS alert to the group, with optional context. User chooses whether to ping the group during an SOS flow.	On (recommended)
Coping activity signal	Tool name only when a coping tool is completed. No craving detail shared.	On (recommended)

Privacy principle: nothing is shared automatically without the user's knowledge. Recommended defaults lean toward sharing because sharing genuinely helps, but every default can be turned off.

1.6 Shared moments in detail

Milestone sharing

When a user hits a milestone — a health recovery moment or a streak milestone — the app shows the celebration and then asks 'share with your group?'. If yes, the milestone appears in the group dashboard and all members receive a notification. If no, the milestone is still logged privately and the streak updates as normal.

Rough day flag

The rough day flag is the support mechanism. When the app detects a slip has been logged or multiple cravings in a short window, it suggests the user flag their day to the group. The suggestion is a gentle prompt — never automatic, never behind the user's back.

When a flag is sent, group members receive a notification: "[Name] is having a rough day — could you check in on them?" Members can react or send a direct message. This is the highest-impact shared moment in the system because the support is direct and personal.

SOS to group

During an SOS flow, after the user has selected their coping tools, they are offered the option to ping their Quit Group. The ping includes an optional context field — "I'm at the tapri and everyone's smoking" — so the friend who responds knows the situation and can actually help.

Members who receive an SOS ping get a push notification. The notification is warm and action-oriented, not alarming.

Coping activity signal

When a user completes a coping tool — breathing exercise, game, reframing prompt — a lightweight signal is sent to the group: "[Name] just used the breathing tool." The craving detail is never shared. The signal tells the group someone is actively managing a hard moment, which can prompt a supportive reaction or message.

Weekly group reflection

Every Sunday, a single question is sent to the group: "What was the hardest moment this week?" Each member answers privately in their own time. Once answered, their response becomes visible to the group. This is the intimacy-builder — it creates shared vulnerability without requiring anyone to be vulnerable first.

Members who do not answer are not pressured. The prompt disappears after 48 hours.

1.7 Reactions

Group members can react to any shared moment using the same four reactions used in the Community Feed:

- I hear you
- I feel this
- You've got this
- This helped me

No public counts. No negative reactions. Reactions are supportive by design.

1.8 Relapse handling in groups

When a member relapses and restarts, their individual streak resets. Their stage clock restarts. But the group founding date does not change, and their membership is not affected. The group's 'combined smoke-free days' stat may dip for a week, but the group itself continues.

The rough day flag and SOS system are specifically designed for this moment. A member who has slipped can flag their day or ping the group without having to explain themselves in detail. The group responds to the signal, not the story.

Layer 2: Nearby Quitters

Nearby Quitters is the discovery layer. It allows users to find other LastOne users quitting in the same area — college, city, or national — and connect with them. It is looser and more anonymous than Quit Groups, and entirely opt-in.

> *This layer is documented here from the product foundations. Full design and flows are parked for a future session.*

2.1 How it works

Users opt in to discovery from their settings. Once opted in, they choose a visibility tier and a discovery radius. They can browse other users who have opted in within their chosen radius. Connecting requires mutual acceptance.

2.2 Privacy tiers

Tier	What others see	What you see
Fully visible	Name, photo, stage, broad location radius	All other users in radius at all tiers
Semi-visible	Pseudonym, avatar, broad area only	All other users in radius at all tiers
Hidden	Nothing — you do not appear in discovery	All other users in radius at all tiers

2.3 Key constraints

- Opt-in only. Default is off.
- The app never shows exact location — broad area label only (e.g. ‘South Delhi’, ‘Koramangala’)
- Connection requires mutual acceptance. No one-sided following.
- Messaging enabled only after mutual connection.
- Meeting up is decided between two people privately, never facilitated by the app.
- Discovery radius options: college area, city, national.

2.4 Stage connection

Nearby Quitters becomes most relevant at Stage 3, when the acute withdrawal phase is over and the user has bandwidth to consider connecting with new people. A gentle nudge surfaces at Stage 3 if the user has not yet opted in.

Layer 3: Community Feed

The Community Feed is the outermost layer. It is a shared space open to the entire LastOne community — a place for journey posts, questions, and encouragement between strangers who are going through the same thing at different points in the same timeline.

> *The emotional logic: Quit Groups = accountability with people you know. Community Feed = validation from strangers who get it.*

3.1 Who it is for

Early-stage users (Stage 0–2) are primarily readers. The feed tells them they are not alone before they have anything to share themselves. Later-stage users (Stage 3+) become both readers and posters. Their lived experience — cravings, slips, small wins — is genuinely useful to people just starting out.

3.2 Stage access rules

Stage	Access	Notes
Stage 0–2	Read-only	Posting locked. Soft nudge explains it unlocks at Stage 3. No hard gate.
Stage 3+ (first attempt)	Full access	Guidelines gate shown before first post. One-time only.
Stage 3+ (returning user)	Full access	Guidelines gate skipped. Welcome-back message shown instead.

3.3 Core constraints

- No public metrics. No like counts, no view counts, no follower numbers.
- No social competition. The feed is about togetherness, not performance.
- Anonymous posts stay anonymous — even during moderation.
- Slips are never surfaced as drama. The no-shame rule applies throughout.
- Two-level structure only — posts and replies. No reply-to-a-reply.

3.4 Post types

Type	Purpose
Milestone	Share a win — a day count, a health recovery moment, a personal breakthrough

Type	Purpose
Reflection	Freeform story — what happened, how it felt, what helped
Question	Ask the community for help, advice, or perspective
Encouragement	General shoutout to the community, not attached to a specific person

3.5 Reactions

Four fixed supportive-only reactions. No counts shown publicly.

- I hear you — empathy
- I feel this — solidarity
- You’ve got this — encouragement
- This helped me — practical value

3.6 Moderation system

Auto-filter

Every post passes through an automated filter before going live. Hard-blocked terms are rejected. Masked profanity (f***) is allowed through. The filter is intentionally lenient — our users are 18–25-year-old college students who talk casually and vent hard.

Community reporting

Any user can report any post. The flow: tap report → one confirmation tap → optional context box → reporter acknowledgement. The post disappears from the reporter’s feed immediately. A warm message confirms the report is being reviewed.

Auto-hide threshold

When a post receives 3 unique reports, it is automatically hidden from the feed for all users and enters the moderation queue. This protects vulnerable users during the gap between flagging and human review. The threshold of 3 is a starting point to be revisited at scale.

Moderator review

The LastOne team reviews flagged posts. Decision options: restore (post goes live again) or remove permanently. In both cases, the poster is notified with the decision, which guideline was violated (if removed), and the full guideline text to re-read.

Repeat violations

Violations are logged per account. A second violation within the violation window triggers a formal warning. Continued violations lead to posting suspension and team escalation. Violation window is TBD with team.

3.7 Nudge system

Triggers

Nudges fire at three contextual moments: health milestone reached, craving successfully overcome, streak milestone hit. Never during SOS or an active craving. Never stacked.

User type split

User type	Nudge copy register
First attempt, first time at Stage 3	“Share your story — someone starting out needs to hear it.”
Returning user (quit_attempt_number > 1)	“Your perspective matters right now. People here remember what week one feels like.”

Decay system

If a user consistently ignores nudges, volume reduces progressively across three levels: full (pop-up + push) → Level 1 (pop-up only) → Level 2 (home screen card only) → Level 3 (stopped). One post at any level resets the counter to full volume.

PART B: SYSTEM LOGIC REFERENCE

This section documents implementable logic for all three layers. Intended for Claude Code or a developer.

B1. Quit Groups Logic

Group creation

- creator_id: uuid of user who creates the group
- group_name: string, set by creator
- founding_date: date, set by creator. Must be today or future. Cannot be backdated.
- max_members: 6. min_members: 2 (must have at least 2 to be active).
- invite_link: generated on creation, shareable. Single-use per member.

Member join flow

- New user: full onboarding with group_context_shown = true. On completion, route to sharing preferences.
- Existing user: skip onboarding. Route directly to sharing preferences.
- On sharing preferences completion: set member_active = true, add to group dashboard.

Sharing preferences data structure

- share_milestones: boolean, default true
- share_rough_day: boolean, default true
- share_sos_ping: boolean, default true
- share_coping_signal: boolean, default true

All toggleable anytime from settings. Checked before any shared moment is sent.

Group stats

- fighting_together_days: (today − founding_date) in days. Never resets.
- combined_smokefree_days_this_week: sum of each active member's smoke-free days in current 7-day window. Recalculated daily.

Shared moments logic

> **Milestone sharing**
> On milestone_unlocked = true: show celebration, then prompt 'share with group?'. If yes and share_milestones = true: post to group feed, push to all members.

Rough day flag
Trigger suggestion when: slip_logged = true OR craving_count_24h >= 3. Show prompt. If user accepts and share_rough_day = true: send flag to group, push to all members with check-in prompt.

SOS to group
During SOS flow, after tool selection: show group ping option with optional context_field. If user taps ping and share_sos_ping = true: push to all members with context if provided.

Coping activity signal
On coping_tool_completed = true: if share_coping_signal = true, send tool_name only to group feed. No craving detail.

Weekly reflection
Fire every Sunday at 10:00am local time. Prompt expires after 48 hours. Answers stored per member. Visible to group on submission.

B2. Nearby Quitters Logic

- opt_in: boolean, default false
- visibility_tier: full | semi | hidden
- discovery_radius: college | city | national
- connection: requires mutual acceptance. request → accept flow.
- messaging: enabled only after mutual connection.
- location_precision: broad area label only. Never coordinates.

B3. Community Feed Logic

Feed access

- Grant full access if: current_stage >= 3 OR quit_attempt_number > 1
- Grant read-only if neither condition is true
- Show guidelines gate if: has_seen_guidelines = false AND quit_attempt_number = 1
- Show welcome-back message if: quit_attempt_number > 1 AND is_first_post_this_attempt = true

Post submission

- Run auto-filter. If blocked: reject, notify, allow edit and resubmit.
- If passes: publish, set post_status = live, report_count = 0.
- Each unique report increments report_count. Duplicate reports from same user ignored.
- report_count >= 3: set post_status = hidden, add to moderation_queue.

Moderation outcome

- Restore: set post_status = live, notify poster (decision = restored).
- Remove: set post_status = removed, notify poster (decision = removed, guideline_violated, guideline_text).
- Log violation: violation_count++, last_violation_timestamp = now.
- Repeat within violation_window: issue warning. Continued: suspend posting, escalate.

Nudge system

- Nudge fires if: current_stage >= 3 OR quit_attempt_number > 1
- Safety check: never fire if sos_active = true OR craving_active = true OR nudge_pending = true
- Decay: nudge_ignore_count >= 3 → Level 1. >= 6 → Level 2. >= 9 → stopped.
- Reset: any post resets nudge_ignore_count = 0, restores full volume.

Decisions Log

A record of every major design decision made across all three layers, and the reasoning behind each one.

Decision	What we decided	Why
Group founding date	Set by creator, cannot be backdated, never resets on relapse.	The founding date is the symbolic anchor of the group's shared identity. Resetting it on a member's relapse would punish the group for one person's slip.
Individual vs group timelines	Individual stage and streak stay personal. Group stat is additive and separate.	Two friends who start together will diverge. Tying the group's health to any one member's timeline creates unfair pressure.
Sharing as opt-out, not opt-in	Defaults lean toward sharing, with clear explanation at setup. All toggleable.	Sharing genuinely helps, but forcing it violates trust. Informed recommended defaults give the feature its best chance without removing agency.
Rough day flag is always self-triggered	The app suggests flagging but never sends it automatically.	Nothing is shared behind the user's back. The suggestion respects the user's hard moment; the decision to reach out is always theirs.
Founding date cannot be backdated	Future or today only.	Prevents gaming of the 'fighting together for X days' stat.
Community Feed reactions	Four supportive-only reactions. No counts shown publicly.	Removes performance incentive. Keeps focus on connection.
Report threshold	3 unique reports triggers auto-hide.	User comfort takes priority over post visibility during the gap before human review.
Relapse and feed access	Returning users keep posting access regardless of current stage.	Locking a returning contributor out contradicts the core principle that restarts reset the timeline, not the relationship.
Nudge decay	3 ignores drops volume by one tier. One post resets to full.	Respects the user's implicit signal without going silent or repeating the same nudge endlessly.
Two-level reply structure	Posts and replies only. No reply-to-a-reply.	Prevents the feed from becoming a social platform with pile-on dynamics.

Decision	What we decided	Why
Layer 2 is opt-in, default off	Nearby Quitters discovery is off until the user turns it on.	Privacy is the default. Discovery is a power feature for users who actively want it.

Confidential. For internal team use only.