A MINI PROJECT REPORT ON

GrievanceIQ: Autonomous Banking Grievance Redressal and Predictive Operational Intelligence Platform

submitted in partial fulfillment of the requirement
for the award of the Degree of

Bachelor of Technology
in
Computer Engineering

by

VEDANT PATIL (UID: 2024300170)
ASHMIT PATIL (UID: 2024300168)
MAYURI TARDE (UID: 2024300258)

Class: T.E. Computer Engineering Division: C & D

under the guidance of

DR. RUPALI SAWANT



Department of Computer Engineering
Bharatiya Vidya Bhavan's
Sardar Patel Institute of Technology
(Autonomous Institute Affiliated to University of Mumbai)
Munshi Nagar, Andheri-West, Mumbai-400058
University of Mumbai
Academic Year: 2026-2027

DEPARTMENT OF COMPUTER ENGINEERING
BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Autonomous Institute Affiliated to University of Mumbai)
Munshi Nagar, Andheri (West), Mumbai - 400 058

Approval Certificate

This is to certify that the Project entitled "GrievanceIQ: Autonomous Banking Grievance Redressal and Predictive Operational Intelligence Platform" submitted by Vedant Patil (UID: 2024300170), Ashmit Patil (UID: 2024300168), and Mayuri Tarde (UID: 2024300258) is approved for the partial fulfillment of Mini Project / Bachelor of Technology in Computer Engineering (T.E. Computer Engineering, Divisions C & D) towards obtaining the Degree of Bachelor of Technology in Computer Engineering from University of Mumbai during the academic year 2026-2027.

_____	_____
(signature)	(signature)
Dr. Rupali Sawant	**External Examiner**
Project Guide	**Name: _____**
Department of Computer Engineering	**Date: _____**
_____	_____
(signature)	(signature)
Dr. Sudhir Dhage	**Dr. B. N. Chaudhari**
Head of Department	**Principal**
Department of Computer Engineering	**Sardar Patel Institute of Technology**

Seal of the Institute

Declaration

We wish to state that the work embodied in this project titled "GrievanceIQ: Autonomous Banking Grievance Redressal and Predictive Operational Intelligence Platform" forms our own contribution to the work carried out under the guidance of Dr. Rupali Sawant at the Sardar Patel Institute of Technology, Department of Computer Engineering, during the academic year 2026-2027. We declare that this written submission represents our ideas in our own words and where others' ideas or words have been included, we have adequately cited and referenced the original sources. We also declare that we have adhered to all principles of academic honesty and integrity and have not misrepresented or fabricated or falsified any idea/data/fact/source in our submission. We further confirm that the implementation, mathematical models, experimental validations, and benchmark results reported here are authentic and truthful.

_____	_____	_____
Vedant Patil	**Ashmit Patil**	**Mayuri Tarde**
UID: 2024300170	**UID: 2024300168**	**UID: 2024300258**

Date: 04 November 2026
Place: Mumbai

Acknowledgement

We wish to express our profound gratitude and deep sense of appreciation to our esteemed project guide, Dr. Rupali Sawant, Department of Computer Engineering, Sardar Patel Institute of Technology, for her invaluable guidance, technical mentorship, constructive critique, and continuous encouragement throughout the conceptualization, algorithmic formulation, full-stack software development, and validation of GrievanceIQ. Her rigorous standards in software engineering, privacy verification, and mathematical modelling were pivotal to the success of this endeavor.

We extend our sincere thanks to Dr. Sudhir Dhage, Professor and Head of the Department of Computer Engineering, for providing state-of-the-art computational infrastructure, academic support, and fostering a vibrant departmental research ecosystem that inspired our focus on national BFSI challenges.

We express our sincere indebtedness to our respected Principal, Dr. B. N. Chaudhari, for his visionary institutional leadership and for establishing the APNI Leap initiative at Sardar Patel Institute of Technology, which bridges undergraduate classroom theories in Operating Systems, Networks, and Algorithms with impactful real-world societal systems.

We also convey our appreciation to all faculty members, laboratory instructors, and administrative staff of the Department of Computer Engineering for their continuous assistance. Finally, we thank our parents, family members, and peers for their steadfast moral support, understanding, and encouragement throughout the course of this project.

Vedant Patil (2024300170)
Ashmit Patil (2024300168)
Mayuri Tarde (2024300258)
Department of Computer Engineering
S.P.I.T., Mumbai

Abstract

The rapid digitization of the Indian banking, financial services, and insurance (BFSI) landscape---spearheaded by the Unified Payments Interface (UPI), immediate payment services, and mobile banking applications---has broadened credit and retail payment supply to millions of citizens. However, this massive transactional throughput is accompanied by a severe escalation in payment failures, unauthorized electronic debits, ATM cash dispensing anomalies, and turnaround delays. Aggrieved depositors face immense friction navigating manual customer service queues, obscure escalation matrices, and English-centric static portals. Furthermore, citizens frequently paste unredacted 16-digit payment card numbers, 12-digit Aadhaar identifiers, and Permanent Account Numbers (PAN) into complaint descriptions, causing widespread compliance infractions under India's Digital Personal Data Protection (DPDP) Act of 2023. Concurrently, bank operational executives lack forward-looking analytical tools to forecast queue congestion, predict Service Level Agreement (SLA) breaches, or dynamically balance frontline officer workloads.

GrievanceIQ (Autonomous Banking Grievance Redressal and Predictive Operational Intelligence Platform) addresses these challenges through an end-to-end, privacy-hardened, and mathematically grounded architecture. The system introduces an ingestion-level regex sanitization pipeline that enforces case-insensitive, zero-loss masking of payment cards, Aadhaar, and PAN identifiers prior to database persistence or logging. To dismantle linguistic barriers, GrievanceIQ embeds a browser-native streaming voice dictation interface atop the W3C Web Speech API, featuring buffer-isolated state updates that eliminate transcript duplication loops across English, Hindi (hi-IN), and Marathi (mr-IN).

Incoming disputes are autonomously triaged by an NLP categorization pipeline combining Term Frequency-Inverse Document Frequency (TF-IDF) unigram/bigram tokenization with a Multinomial Naive Bayes classifier, validated against Sentence-BERT (all-MiniLM-L6-v2) embeddings for fine-grained subcategory prediction and historical dispute clustering. For documentary evidence verification, GrievanceIQ incorporates an optical character recognition (OCR) engine that extracts structured financial entities from transaction slips, passbooks, and ATM failure logs, executing a deterministic 4-point cross-validation (transaction reference, bank identity, account digits, and disputed amount) to score claim credibility.

At the operational intelligence tier, GrievanceIQ operationalizes Kleinrock's M/M/c multi-server queueing theory via the Erlang-C analytical formulation. The engine computes real-time queue dwell times, traffic intensities, and statutory SLA breach probabilities, powering an interactive 'What-If' staffing sandbox that enables branch managers to simulate surge conditions and determine optimal officer allocations. For each registered grievance, the platform compiles a tamper-evident statutory PDF receipt embedding an ISO/IEC 18004 dynamic 2D QR code pointing to live, unauthenticated case status endpoints.

The software architecture couples an asynchronous Python FastAPI backend utilizing SQLAlchemy ORM and SQLite/PostgreSQL with a reactive single-page frontend built on React 18, Vite, and Tailwind CSS. The system has been validated across a master suite of 48 automated tests covering end-to-end complaint lifecycles, PII zero-leakage security, OCR precision, and SLA countdowns. On empirical benchmarks, the ML triage engine achieved 83.49% multi-class accuracy across 2,998 test records with a macro F1-score of 0.835, and sub-150ms endpoint latencies. GrievanceIQ is designed as an operational assistive triage prototype; final financial

reversals and binding legal settlements remain under the formal jurisdiction of scheduled commercial banks and the Reserve Bank of India (RBI) Ombudsman.

Contents

Section / Chapter Topic	Page
Abstract	iv
List of Figures	x
List of Tables	xii
List of Abbreviations and Symbols	xiii
1 Introduction and Problem Definition	1
1.1 Project Background	1
1.2 Problem Statement	1
1.3 Motivation	2
1.4 Objectives	2
1.5 Scope of the Project	3
1.5.1 Features Included	3
1.5.2 Features Outside the Scope	4
1.5.3 Intended Users	4
1.5.4 Operating Environment	4
1.5.5 Expected Scale of Operation	5
1.6 Proposed Solution	5
1.7 Novelty and Originality	6
1.8 Feasibility Analysis	6
1.8.1 Technical Feasibility	6
1.8.2 Economic Feasibility	7
1.8.3 Operational Feasibility	7
1.8.4 Time and Resource Feasibility	7
1.9 Social Relevance and Practical Applications	7
1.10 Success Criteria and Key Performance Indicators (KPIs)	8

2 Literature Review and Study of Existing Systems	10
2.1 Study of Existing Systems	10
2.2 Review of Research Papers and Technical Resources	11
2.3 Comparative Analysis	14
2.4 Limitations of Existing Systems	15
2.5 Identified Research or Engineering Gap	16
2.6 Proposed Improvements	16
3 Software Requirements Specification (SRS)	18
3.1 Purpose and Scope of the SRS	18
3.2 Intended Users and Stakeholders	19
3.3 Overall Product Description	19
3.4 Functional Requirements (FR-01 to FR-20)	21
3.5 Non-Functional Requirements	30
3.6 Hardware and Software Requirements	33
3.7 Constraints and Assumptions	35
3.8 Use Cases and User Stories	36
4 System Architecture and Detailed Design	40
4.1 Overall System Architecture	40
4.2 Component and Module Description	41
4.3 Architecture Selection and Justification	45
4.4 Data Flow Diagrams (DFD Level 0, Level 1, Level 2)	47
4.5 UML Diagrams (Use Case, Class, Sequence, Activity, State, Flow)	60
4.6 Database Design (Schema, Normalization, Indexing, Records)	73
4.7 Security and Error Handling Design	95
5 Algorithm Design and Data Structures	97
5.1 Identification of Critical Operations	97

5.2 Algorithm Design (Algorithms 1 to 16)	99
5.3 Flowcharts and State Transitions	107
5.4 Data Structure Selection	107
5.5 Algorithm Selection and Justification	108
5.6 Time Complexity Analysis	111
5.7 Space Complexity Analysis	117
5.8 Optimization Opportunities	122
6 Subject-Wise Engineering Concepts and APNI Leap Alignment	126
6.1 Software Engineering	126
6.2 Computer Networks	127
6.3 Database Management Systems	127
6.4 Operating Systems	128
6.5 Data Structures	129
6.6 Design and Analysis of Algorithms	130
6.7 Cloud Computing	131
6.8 Master Mapping of Subjects to Project Implementation	131
7 Implementation and Module-Wise Coding	134
7.1 Development Environment and Tools	134
7.2 Overall Implementation Strategy	134
7.3 Module-Wise Implementation (M0 to M7)	135
7.4 Front-End Implementation	141
7.5 Back-End Implementation	142
7.6 Database Implementation	142
7.7 Communication and Concurrency Implementation	143
7.8 Git Repository Setup and Member Contributions	143
7.9 Integration of Modules	144

7.10 Implementation Challenges and Resolutions	145
8 Scalability, Performance and Resource Management	147
8.1 Scalability Requirements	147
8.2 Workload and Load Model	147
8.3 Resource Utilization	148
8.4 Concurrent Processing	148
8.5 Scheduling and Synchronization Analysis	149
8.6 Performance Measurement	149
8.7 Performance Results	149
8.8 Bottleneck Identification	150
8.9 Optimization and Improvement	150
8.10 Cloud Deployment and Resource Utilization	151
8.11 Scalability Limitations	152
9 Testing and Validation	153
9.1 Testing Strategy	153
9.2 Unit Testing	153
9.3 Integration Testing	154
9.4 Functional Testing	154
9.5 Non-Functional Testing	154
9.6 Boundary and Invalid-Input Testing	155
9.7 Concurrency and Stress Testing	156
9.8 Test Case Specification (TC-01 to TC-23)	156
9.9 Defect Identification and Resolution	158
9.10 Validation Against KPIs	158
9.11 Limitations and Untested Scenarios	159
10 Results, Demonstration and Discussion	160

10.1 Implemented Features	160
10.2 Screenshots and Demonstration Evidence	161
10.3 Functional Results	165
10.4 Performance Results	167
10.5 Comparison with Existing Systems	167
10.6 Achievement of Objectives	168
10.7 Discussion of Findings	169
10.8 Practical Applicability	170
11 Conclusion and Future Scope	171
11.1 Conclusion	171
11.2 Achievement of Objectives	171
11.3 Major Engineering Contributions	172
11.4 Current Limitations	172
11.5 Future Enhancements	173
11.6 Lessons Learned	173
References	175

List of Figures

Figure #	Figure Title / Caption Description	Page
1	Overall System Architecture of GrievanceIQ	41
2	Level 0 DFD: Context Diagram	48
3	Level 1 DFD, Diagram 1A: Intake, PII Redaction & NLP Triage	49
4	Level 1 DFD, Diagram 1B: Evidence OCR & Bot Resolution	50
5	Level 1 DFD, Diagram 1C: Officer Assignment & SLA Monitoring	51
6	Level 1 DFD, Diagram 1D: Predictive Queueing, Audit & Receipt	51
7	Level 2 DFD: Process 1.0, Intake and DPDP PII Sanitization	53
8	Level 2 DFD: Process 2.0, OCR Extraction & 4-Point Entity Cross-Match	54
9	Level 2 DFD: Process 3.0, TF-IDF and SBERT Classification Engine	55
10	Level 2 DFD: Process 4.0, Kleinrock M/M/c Predictive Queue Simulator	56
11	Level 2 DFD: Process 5.0, Officer Adjudication & Resolution Memo	57
12	Level 2 DFD: Process 6.0, ReportLab PDF Receipt & Dynamic QR Encoding	58
13	Relational Entity-Relationship Diagram (Master ERD across 18 Tables)	59
14	Functional Dependency Graph & 3NF/BCNF Normalization Decomposition	60
15	Use Case Diagram of GrievanceIQ	61
16	Class Diagram, Part 1: Service & Orchestration Layer	62
17	Class Diagram, Part 2: Relational Domain Entity Model	63
18	Sequence Diagram, Part 1: Ingestion, Voice Dictation & Triage	64
19	Sequence Diagram, Part 2: Tier-1 Bot Adjudication & Escalation	65
20	Activity Diagram, Part 1: Multi-Attribute Intake & Redaction	67
21	Activity Diagram, Part 2: Document Verification & Resolution	68
22	State Machine Diagram, Part 1: Grievance Lifecycle Pipeline	69
23	State Machine Diagram, Part 2: Officer Assignment Lifecycle	70
24	User Flow Diagram, Part 1: Complainant Mobile & Web Flow	71

25	User Flow Diagram, Part 2: Bank Officer Adjudication Flow	72
26	Entity-Relationship Diagram of GrievanceIQ	73
26-B	Database Indexing & B-Tree Query Execution Plan	74
27	Citizen Landing Portal and Trilingual Language Selector	161
28	Interactive Complaint Filing Form with Real-Time Voice Dictation	161
29	DPDP Act 2023 Ingestion-Level PII Masking Live Preview	162
30	Autonomous ML Categorization and Confidence Rating	162
31	Tier-1 AI GrievanceBot Adjudication and Immediate Settlement	162
32	Documentary Evidence Uploader with OCR 4-Point Entity Validation	163
33	Statutory PDF Receipt with Dynamic ISO/IEC 18004 QR Tracking Code	163
34	Public Grievance Status Tracker with Visual SLA Breach Countdown	163
35	Grievance Redressal Officer Workspace and Priority Queue	164
36	AI Copilot Memo Drafter and Formal Adjudication Console	164
37	Executive Bank Health Scorecard and Systemic Risk Radar	164
38	Predictive Operational Sandbox (M/M/c Erlang-C Staffing Modeler)	165
39	Scheduled Commercial Banks Operational Leaderboard	165
40	Immutable Append-Only Forensic Audit Trail Viewer	165
10-A	Machine Learning Classification Performance by Category	166
10-B	Multi-Class Classification Confusion Matrix across 2,998 Test Cases	167
10-C	Statutory SLA Turnaround Time Reduction: Traditional vs GrievanceIQ	168
41	Turnitin Plagiarism Report: 9% Overall Similarity Index	169

List of Tables

Table #	Table Title / Context Description	Page
3	Key Performance Indicators and Target Benchmarks	8
4	Comparative Analysis of Grievance Redressal Frameworks	14
5	Intended Users and Primary Stakeholder Roles	19
6	Six-Stage Autonomous Grievance Processing Pipeline	20
33	Non-Functional Performance and Latency Requirements	30
34	Security and Statutory DPDP Act Privacy Requirements	31
35	System Business Rules and Operational Invariants	32
36	Full-Stack Development and Production Runtime Stack	33
37	Algorithmic Libraries and AI/ML Components	34
38	Principal RESTful API Endpoints Directory	34
39	Architecture Open Items and Production Roadmap (TBD)	36
49	Comprehensive User Stories Specification	39
51	Data Flow Diagram Relational Data Stores	47
52	ER-to-Relational Mapping and Cardinality Rules	75
53	Relational Foreign Key and Cardinality Summary	76
54	Primary Key Specifications Across 18 Tables	77
55	Foreign Key Referential Action Specifications (CASCADE vs SET NULL)	78
56	Relational Database CHECK Constraints	80
57	Nullable Relational Attributes and Justifications	80
58	Relational Column DEFAULT Constraints	81
59	Relational Data-Type Precision and Boundary Constraints	81
60	Role-Based Access Control (RBAC) and Security Policies	82
61	Application-Level Data Integrity Rules	83
62	Summary of System Integrity Mechanisms	83

63	Functional Dependencies and Normal Form Analysis (3NF/BCNF)	85
64	Relational Database Anomalies Prevented by Schema Design	86
65	Currently Implemented Database Indexes	87
66	Primary Application Access Patterns and Query Shapes	88
67	Proposed Secondary Performance Indexes	89
68	Comprehensive Indexing Strategy Summary	91
69	Operational Data Volume in Demonstration Database	91
70	Sample Records: complaints and users	92
71	Sample Records: evidence_docs and ocr_extractions	92
72	Sample Records: predictions and similar_complaints	93
73	Sample Records: audit_logs and resolutions	94
80	Mathematical Notation for Time Complexity Analysis	112
81	Comprehensive Time Complexity Summary for Algorithms 1-16	112
82	Mathematical Notation for Space Complexity Analysis	117
83	Comprehensive Space Complexity Summary for Algorithms 1-16	118
84	Master Mapping of APNI Leap Subjects to Implementation	131
85	Full Development Environment and Version Directory	134
95	Frontend Application Views and Routing Table	141
96	Backend RESTful Endpoints and HTTP Verbs	142
97	Group Member Responsibilities and Module Contributions	144
98	Processing Pipeline Execution Stages and Integration	144
99	Technical Implementation Challenges and Mitigations	145
100	System Scalability and Concurrency Limits	147
101	Demonstration Workload and Experimental Data Volume	147
102	Empirically Measured Latencies vs Target Benchmarks	149
104	Architectural Optimizations and Empirical Speedups	151

106	Test Suite Categories and Verification Scope	153
107	Functional Requirement Test Coverage Matrix (FR-01 to FR-20)	154
108	Boundary Condition and Invalid Input Scenarios	155
109	Representative Master Test Cases Specification (TC-01 to TC-23)	156
110	Final Validation of System Metrics Against Target KPIs	158
111	Master Inventory of Implemented System Features	160
115	Comparative Matrix: GrievanceIQ vs Existing Industry Portals	168
116	Project Objective to Empirical Code Evidence Mapping	168
117	Final Status of Project Engineering Objectives	171

List of Abbreviations and Symbols

Abbreviations

Abbreviation	Full Form / Technical Meaning
AI	Artificial Intelligence
API	Application Programming Interface
ASGI	Asynchronous Server Gateway Interface (Python Uvicorn)
BFSI	Banking, Financial Services, and Insurance
CBS	Core Banking Solution (e.g., Infosys Finacle, TCS BaNCS)
CPGRAMS	Centralized Public Grievance Redress and Monitoring System
CSRF	Cross-Site Request Forgery
DFD	Data Flow Diagram
DPDP	Digital Personal Data Protection Act of 2023 (India)
FIFO	First In, First Out
IMPS	Immediate Payment Service
ISO	International Organization for Standardization
JWT	JSON Web Token
KYC	Know Your Customer
ML	Machine Learning
MNB	Multinomial Naive Bayes
M/M/c	Kendall's Notation for Multi-Server Queue with c Parallel Servers
NLP	Natural Language Processing
NPCI	National Payments Corporation of India
OCR	Optical Character Recognition
ORM	Object-Relational Mapping (SQLAlchemy)
PAN	Permanent Account Number / Primary Account Number
PCM	Pulse Code Modulation

PII	Personally Identifiable Information
QR	Quick Response (2D Barcode ISO/IEC 18004)
RAG	Retrieval-Augmented Generation
RBAC	Role-Based Access Control
RBI	Reserve Bank of India
RB-IOS	Reserve Bank - Integrated Ombudsman Scheme 2021
REST	Representational State Transfer
SBERT	Sentence Bidirectional Encoder Representations from Transformers
SLA	Service Level Agreement
SQL	Structured Query Language
SRS	Software Requirements Specification
TF-IDF	Term Frequency - Inverse Document Frequency
TLS	Transport Layer Security
UI / UX	User Interface / User Experience
UID	Unique Identification / Student Enrollment Number
UPI	Unified Payments Interface
W3C	World Wide Web Consortium
WAL	Write-Ahead Logging (SQLite High-Concurrency Mode)

Symbols and Units

Symbol	Mathematical / Operational Meaning
lambda	Mean complaint arrival rate (complaints per hour)
mu	Mean service/resolution rate per officer (complaints per officer per hour)
c	Number of active, parallel grievance redressal officers
rho	Traffic intensity / system utilization (lambda / (c * mu))
P_0	Probability of zero complaints in the redressal system

C(c, a)	Erlang-C probability of an arriving grievance having to wait in queue
W_q	Expected waiting time in queue before an officer commences investigation
W	Expected total dwell time in system (W_q + 1 / mu)
L_q	Expected number of pending grievances waiting in queue
L	Expected total number of grievances currently in system
T_SLA	Statutory SLA threshold duration (hours)
N	Total number of documents in classification corpus
V	Size of NLP vocabulary dictionary
alpha	Laplace smoothing parameter (alpha = 1.0)
ms	Millisecond (10^-3 seconds)
s	Second
INR (Rs.)	Indian Rupee (ISO 4217 Currency Code)

1 Introduction and Problem Definition

1.1 Project Background

The Indian banking and financial services sector has experienced an unprecedented structural transformation over the past decade, accelerated by the mass adoption of Unified Payments Interface (UPI), immediate payment services (IMPS), Real-Time Gross Settlement (RTGS), and mobile banking applications. Under the leadership of the National Payments Corporation of India (NPCI) and the Reserve Bank of India (RBI), digital retail payments now exceed tens of billions of transactions monthly. However, as the velocity, volume, and interconnectedness of financial transactions have grown exponentially, the corresponding surface area for operational failures, network timeouts, ATM dispensing errors, fraudulent debits, and customer service grievances has broadened commensurately.

When an unauthorized debit occurs or an automated clearing transaction stalls, aggrieved depositors turn to the institutional grievance redressal machinery mandated for scheduled commercial banks and non-banking financial companies (NBFCs). Traditionally, this machinery has depended upon manual ticket logging, physical branch queues, call-center interactive voice responses (IVR), or disparate static web forms. Customers are confronted with long wait times, opaque escalation processes, and generic, unhelpful rejections. At the regulatory apex, the Reserve Bank of India operates the Integrated Ombudsman Scheme (RB-IOS 2021), which handles hundreds of thousands of escalated disputes annually that fail to find timely or equitable resolution at the bank level.

The administrative overhead of manually reading, classifying, prioritizing, routing, and verifying documentary evidence for thousands of daily complaints severely strains bank operations. Frontline customer service representatives frequently misroute high-priority fraud cases to low-urgency queues, causing statutory Service Level Agreement (SLA) breaches and regulatory penalties. GrievanceIQ addresses this structural bottleneck by delivering an autonomous, full-stack, and privacy-hardened grievance redressal and predictive operational intelligence platform.

1.2 Problem Statement

Aggrieved banking consumers cannot easily navigate fragmented customer grievance portals, and bank operations teams struggle under massive, unstructured complaint inflows. Four fundamental technical and operational vulnerabilities undermine existing grievance management architectures:

1. Manual and Latency-Prone Triage: Inflow streams of customer complaints are manually read and categorized by tier-1 customer service agents. This produces severe routing bottlenecks, misclassifications (e.g., categorizing an urgent unauthorized debit as a general inquiry), and resolution delays often exceeding statutory RBI windows (typically 30 calendar days).

2. Linguistic and Technical Exclusion: Contemporary banking portals are heavily English-centric and require tedious manual typing into complex alphanumeric web forms. Rural, semi-urban, elderly, or visually challenged depositors who communicate in regional languages (such as Hindi or Marathi) are systematically disenfranchised from filing grievances independently.

3. Critical Regulatory Privacy Violations (DPDP Act 2023): Agitated depositors routinely paste unredacted 16-digit debit/credit card credentials, 12-digit Aadhaar numbers, and Permanent Account Numbers (PAN) into complaint descriptions. Existing banking portals persist these sensitive identifiers in plain text in relational databases and application logs, directly violating the statutory provisions of India's Digital Personal Data Protection (DPDP) Act of 2023.

4. Predictive Operational Blindness: Branch operations managers and executive leadership lack forward-looking quantitative tools to anticipate queue congestion surges, predict SLA breaches, or optimize frontline officer staffing allocations before operational collapses occur.

The central engineering problem addressed by GrievanceIQ is therefore: To design, implement, and benchmark an autonomous, privacy-first banking grievance management platform that provides zero-latency trilingual voice dictation, enforces ingestion-level DPDP Act 2023 token redaction, executes automated multi-class machine learning triage, independently validates documentary evidence via 4-point OCR entity matching, resolves routine claims via Tier-1 AI GrievanceBot, and empowers bank management with Kleinrock M/M/c Erlang-C predictive operational queueing models.

1.3 Motivation

A modern, fair, and resilient financial democracy requires that grievance redressal be frictionless, instantaneous, vernacularly inclusive, and legally compliant by design. Four fundamental engineering motivations drive this project:

• Real-Time Vernacular Accessibility: Enabling non-literate or elderly citizens to articulate complex banking disputes verbally in their mother tongue (Hindi or Marathi) using browser-native speech recognition without expensive third-party speech APIs.

• Statutory Privacy Enforcement by Design: Eliminating human error by scrubbing financial PII (payment cards, Aadhaar, PAN) at the network boundary prior to persistent storage or model inference, shielding banks from catastrophic regulatory penalties.

• Deterministic Evidence Cross-Validation: Moving beyond unverified customer assertions by extracting and cross-referencing transaction metadata directly from bank receipts, ATM failure slips, and passbook scans via OCR.

• Rigorous Mathematical Operations Research: Replacing arbitrary managerial intuition with proven queueing theory (M/M/c Erlang-C formulas) to forecast queue dwell times, monitor statutory SLA countdowns, and execute interactive What-If staffing simulations.

1.4 Objectives

The project objectives of GrievanceIQ are concrete, measurable, and testable:

1. Ingestion-Level DPDP 2023 Sanitization: Implement a case-insensitive regular expression masking engine that scrubs 16-digit debit/credit cards, 12-digit Aadhaar, and 10-character PAN identifiers with 100% precision before persistence.

2. Real-Time Multilingual Voice Ingestion: Build a browser-native voice dictation interface supporting English, Hindi (hi-IN), and Marathi (mr-IN) with non-destructive buffer accumulation that guarantees zero duplicate line emissions.

3. Autonomous NLP Multi-Class Categorization: Train a TF-IDF and Multinomial Naive Bayes classification model across banking categories (Unauthorized Transactions, ATM Failures, UPI Issues, Net Banking, Loans, Account Maintenance) achieving >80% accuracy.

4. SBERT Semantic Subcategory & Similarity Matching: Integrate Sentence-BERT embeddings (all-MiniLM-L6-v2) to predict granular subcategories and detect historical duplicate grievances.

5. Documentary Evidence OCR & 4-Point Entity Cross-Match: Develop an automated OCR pipeline that extracts Transaction Reference, Disputed Amount, Bank Identity, and Account Digits from uploaded images/PDFs and scores credibility from 0 to 100%.

6. Tier-1 AI GrievanceBot Adjudication: Implement an automated decision gate that checks claim validity, evaluates evidence scores, queries indexed knowledge-base articles, and offers immediate settlement dialogs for qualifying disputes.

7. Dynamic SLA Engine & Urgency Radar: Calculate statutory SLA deadlines (24h/72h/30d) based on RBI customer liability directions, maintaining visual countdowns and escalation alerts.

8. Workload-Balanced Officer Assigner: Construct an optimal assignment engine that allocates escalated complaints to bank redressal officers based on department specialty, active workload, and historical resolution velocity.

9. Predictive Queue Modeling (Kleinrock M/M/c & Erlang-C): Formulate and implement closed-form Erlang-C equations to compute system utilization, queue dwell times, and SLA breach risks under varying arrival surges.

10. Tamper-Evident Statutory PDF Receipt Generation: Generate verifiable ReportLab PDF receipts embedding ISO/IEC 18004 dynamic 2D QR codes pointing to live, unauthenticated case status tracking endpoints.

11. Full-Stack Trilingual Dynamic Localization: Implement seamless client-side UI localization across 222 key mappings in English, Hindi, and Marathi, supported by an immutable append-only audit trail.

1.5 Scope of the Project

1.5.1 Features Included

• Autonomous multi-attribute complaint registration supporting manual entry, file uploads, and voice dictation.

• Browser-native Web Speech streaming dictation in English, Hindi, and Marathi with live waveform visualizer.

• Automated DPDP Act 2023 PII sanitization (Cards, Aadhaar, PAN) with zero plain-text storage.

• TF-IDF and Multinomial Naive Bayes complaint triage with confidence scoring.

• SBERT semantic subcategory prediction and similar complaint clustering.

• Evidence uploader supporting PNG, JPG, and PDF receipts with automated OCR extraction.

• Deterministic 4-point entity cross-verification between user claim and OCR document tokens.

• Tier-1 AI GrievanceBot with instant resolution recommendations and customer escalation dialog.

• Dynamic SLA engine tracking 24h, 72h, and 30-day statutory deadlines with live countdown timers.

• Workload-balanced smart officer assignment algorithm.

• Senior Nodal Officer (Level 2) escalation and governance for reopened disputes.

• Predictive operations dashboard with Erlang-C queueing simulations and What-If staffing sandboxes.

• Bank health score calculation, vulnerability radar, and scheduled commercial banks leaderboard.

• Tamper-evident PDF statutory receipt generation with embedded dynamic tracking QR code.

• Immutable append-only forensic audit logging of all system actions, assignments, and state transitions.

• Full-stack trilingual UI localization across 222 dictionary keys in English, Hindi, and Marathi.

1.5.2 Features Outside the Scope

• Direct write-back integration into proprietary Core Banking Solutions (CBS) like Infosys Finacle or TCS BaNCS (mocked via standard RESTful APIs due to banking firewall boundaries).

• Direct execution of interbank financial debit reversals or automated clearinghouse settlements across NPCI/RBI networks.

• Recognition of handwritten physical complaint slips (system requires typed text, voice dictation, or printed receipts).

• Languages beyond English, Hindi, and Marathi in Version 1.0.

• Automatic formal legal filing into the RBI Integrated Ombudsman CMS portal without explicit human officer authorization.

1.5.3 Intended Users

• Bank Customers / Depositors: File disputes, dictate voice complaints, upload receipts, track live status, download QR receipts.

• Grievance Redressal Officers: Investigate complaints, inspect OCR evidence match scores, review AI copilot draft memos, issue resolutions.

• Branch Operations Managers: Monitor SLA adherence, run What-If staffing simulations, inspect officer productivity, audit bank health.

• Compliance & Regulatory Auditors: Inspect immutable audit logs, verify DPDP Act 2023 redaction, review closed-loop resolution fairness.

1.5.4 Operating Environment

• Backend API: Python 3.10+, FastAPI 0.100+, Uvicorn ASGI, Pydantic v2, SQLAlchemy ORM.

• Frontend Client: React 18, Vite 5.x, Tailwind CSS 3.x, Lucide Icons, Recharts 2.x.

• Data Persistence: SQLite 3 with Write-Ahead Logging (WAL) / PostgreSQL 15 via asyncpg.

• Machine Learning & OCR: Scikit-Learn 1.5, Sentence-Transformers (all-MiniLM-L6-v2), EasyOCR / PyTesseract.

• Document Generation: Python ReportLab, Qrcode library, Pillow (PIL).

• Client Browser: Modern browser (Chrome 90+, Edge 90+, Safari 14+) with W3C Web Speech API support.

1.5.5 Expected Scale of Operation

GrievanceIQ is engineered as an institutional departmental prototype capable of processing thousands of daily complaints, sustaining up to 100 concurrent HTTP requests with sub-150ms API latencies, and scaling horizontally via containerized Docker microservices.

1.6 Proposed Solution

GrievanceIQ delivers a comprehensive, multi-tiered architecture that unifies citizen intake, autonomous triage, documentary evidence verification, officer collaboration, and predictive operational intelligence into a seamless pipeline:

1. Frictionless Multimodal Ingestion: Complainants articulate disputes via manual typing, document uploads, or real-time voice dictation. The Web Speech audio pipeline transcribes Hindi, Marathi, and English audio streams in real time with zero duplicate loops.

2. Boundary-Level DPDP Sanitization: Raw descriptions pass through compiled regex filters that detect 16-digit payment card numbers, 12-digit Aadhaar identifiers, and 10-character PAN strings, replacing them with masked tokens before database insertion.

3. Hybrid NLP & Semantic Classification: Sanitized text is classified by TF-IDF vectorization and Multinomial Naive Bayes into high-level banking departments, followed by Sentence-BERT semantic similarity matching to pinpoint subcategories and flag duplicate tickets.

4. Deterministic OCR Evidence Cross-Validation: Uploaded transaction slips, passbooks, and ATM receipts are parsed via OCR. A 4-point verification algorithm compares transaction reference, bank name, account digits, and disputed amount against the user's claim.

5. Tier-1 AI GrievanceBot Adjudication: If a complaint exhibits high validity, qualifying OCR evidence, and matches clear banking rules, the system offers the customer an instant settlement proposal, reducing human officer ticket queues by over 30%.

6. Operations Research via Erlang-C Queueing: Branch management monitors real-time queue dynamics, evaluates traffic intensity, and simulates staffing adjustments to ensure zero statutory SLA breaches.

1.7 Novelty and Originality

The technical contributions and original engineering elements of GrievanceIQ include:

• Dual-State Voice Buffer Accumulator: Resolves a notorious browser limitation where W3C Web Speech API onresult events cause repeating text loops during continuous streaming dictation in regional Indian accents.

• Case-Insensitive Zero-Loss PII Redaction: Enforces strict DPDP Act 2023 compliance at the network ingestion boundary rather than relying on retrospective database scrubbing scripts.

• Deterministic 4-Point Document Credibility Scoring: Eliminates generative AI hallucinations during evidence evaluation by applying exact regex token matches and fuzzy Levenshtein ratios to OCR output.

• Closed-Loop Verifiable Dynamic QR Receipts: Statutory PDF receipts embed ISO/IEC 18004 2D barcodes pointing dynamically to the active server host, enabling instant mobile tracking with zero authentication barrier.

• Integrated Queueing Theory in BFSI Operations: Uniquely bridges front-office grievance logging with back-office Erlang-C queue modeling for proactive capacity management.

1.8 Feasibility Analysis

1.8.1 Technical Feasibility: The platform relies upon mature, production-grade open-source technologies: Python 3.10+, FastAPI (high-performance ASGI web framework), Scikit-Learn, React 18, Vite, and Tailwind CSS. Modern web browsers natively support

the W3C Web Speech API, Web Audio API, and HTML5 Canvas without requiring client-side plugin installations.

1.8.2 Economic Feasibility: The software utilizes open-source libraries with zero commercial licensing costs. It executes efficiently on commodity x86/ARM hardware or micro-tier cloud virtual machines (e.g., AWS t3.medium or GCP e2-small), ensuring negligible deployment and operational overhead.

1.8.3 Operational Feasibility: The client interface provides intuitive trilingual localization (English, Hindi, Marathi) and speech dictation, eliminating user friction. Bank officers benefit from explainable AI suggestions and automated memo drafting.

1.8.4 Time and Resource Feasibility: The project was structured systematically across a 12-week academic schedule with weekly milestone gates, achieving 100% completion of all core and extended deliverables within the designated timeframe.

1.9 Social Relevance and Practical Applications

Financial disputes and transaction failures cause severe psychological distress and economic hardship to retail consumers, particularly when monthly wages, student remittances, or emergency healthcare funds are frozen due to automated banking timeouts. By democratizing grievance filing through real-time voice dictation in Hindi and Marathi, protecting privacy under the DPDP Act 2023, and automating evidence validation to cut resolution times from weeks to hours, GrievanceIQ establishes a new benchmark for digital financial justice in the Indian banking ecosystem.

1.10 Success Criteria and Key Performance Indicators (KPIs)

The success of GrievanceIQ is evaluated against rigorous, pre-defined technical and operational metrics formalized in Table 3.

KPI Identifier	Metric Definition	Target Benchmark	Empirical Measurement Method
ML Classification Accuracy	Agreement of predicted category with hand-labeled ground truth	At least 80.0%	Evaluation across 2,998 test records (Achieved 83.49%)
Classification Macro F1	Harmonic mean of precision and recall across all banking categories	At least 0.80	Multi-class confusion matrix evaluation (Achieved 0.835)
DPDP Act 2023 PII Masking	Share of 16-digit cards, Aadhaar, and PAN tokens successfully masked	100.0% zero-leakage	Adversarial test suite with unredacted payloads (100% pass)
Voice Streaming Loop Elimination	Absence of repeating transcript phrases during streaming dictation	100% zero duplicate loops	Session buffer verification in automated browser

			tests
Evidence OCR Entity Matching	Precision of 4-point financial entity extraction from receipts	At least 85.0%	Benchmark test slips (Transaction Ref, Bank, Amount, Account)
Erlang-C Queueing Accuracy	Mathematical convergence of M/M/c dwell time and SLA breach risk	100% analytical match	Closed-form formula unit testing against hand-calculated cases
Statutory Receipt Verification	Generation of valid, scannable ISO/IEC 18004 dynamic QR PDF receipt	100% scannable QR	ReportLab automated PDF rendering and QR decode verification
API Response Latency	Time taken for transactional REST endpoints to complete execution	Under 150 ms	Timestamp-based integration testing under standard load (avg 42 ms)
Trilingual UI Key Parity	Share of UI interface keys fully localized across EN, HI, and MR	100.0% (222 keys)	Automated dictionary key-parity unit test (test_phase2_extended)
RBAC Security Enforcement	Prevention of unauthorized customer access to officer adjudication	Zero unauthorized bypass	OAuth2 JWT token validation and role-gated endpoint tests
Forensic Audit Immutability	Append-only logging of all state transitions, memos, and assignments	100% audited actions	Database transaction trigger and audit_logs table inspection
Full-Stack Test Pass Rate	Successful test executions across all unit and integration suites	100% pass rate	Execution of 48 master integration and unit tests (48/48 passed)

Table 3: Key Performance Indicators and Target Benchmarks

1

2 Literature Review and Study of Existing Systems

2.1 Study of Existing Systems

Grievance redressal in the financial domain comprises multiple interconnected activities: customer dispute intake, documentary evidence verification, categorical routing, statutory SLA monitoring, officer adjudication, and operational capacity management. Historically, public sector institutions, commercial banks, and regulatory bodies have developed individual software platforms to manage specific aspects of this workflow. However, each system exhibits distinct architectural limitations.

2.1.1 Manual Branch Filing and Call-Center Logging

In the conventional approach, an aggrieved customer visits a physical branch office or dials an interactive voice response (IVR) call center. A bank clerk or telephone operator manually writes down the complaint details, assigns an internal token number, and routes the physical file to the relevant operations desk. While this process allows human empathy and individualized listening, it suffers from extreme operational latency, geographic dependency, high transaction costs, and an absence of verifiable digital audit trails. Misplaced paper dockets and undocumented verbal complaints frequently evade statutory SLA monitoring entirely.

2.1.2 CPGRAMS (Centralized Public Grievance Redress and Monitoring System)

Operated by the Department of Administrative Reforms and Public Grievances (DARPG), Government of India, CPGRAMS serves as a national web-based portal connecting citizens with central government ministries, departments, and public sector banks. While CPGRAMS centralizes complaint registration, it functions essentially as an electronic post office. It lacks automated NLP triage, meaning human nodal officers must manually read and transfer tickets. Furthermore, it offers no voice-assisted intake for vernacular citizens, lacks automated documentary OCR verification, and does not provide predictive queueing intelligence to participating bank departments.

2.1.3 Reserve Bank of India CMS and the Integrated Ombudsman Scheme (RB-IOS 2021)

The RBI launched the Complaint Management System (CMS) to operationalize the Reserve Bank - Integrated Ombudsman Scheme of 2021. RB-IOS unifies grievance redressal across scheduled commercial banks, NBFCs, and non-bank payment system participants under a single 'One Nation, One Ombudsman' umbrella. However, by statutory mandate, the RBI Ombudsman is an appellate body of last resort: depositors are permitted to approach the Ombudsman only after 30 calendar days have elapsed without resolution at the bank level, or if the bank rejects the complaint unfairly. The primary institutional bottleneck resides inside the commercial banks themselves, which lack automated triage mechanisms to resolve routine disputes before they escalate to the RBI.

2.1.4 Commercial Enterprise CRM Systems (Salesforce Service Cloud, Freshdesk, Zendesk)

Leading commercial scheduled banks frequently deploy proprietary enterprise Customer Relationship Management (CRM) solutions. While these platforms offer sophisticated omnichannel ticket routing, customizable workflows, and agent assignment rules, they suffer from severe shortcomings in the Indian context: (a) exorbitant per-seat licensing costs running into millions of dollars annually, (b) vendor lock-in with closed-source codebases, (c) absence of out-of-the-box DPDP Act 2023 token redaction for Indian financial PII, and (d) generic customer support workflows that lack specialized BFSI dispute logic, such as RBI 72-hour customer liability directives.

2.1.5 General-Purpose Large Language Model Assistants

Recent advances in Generative Artificial Intelligence (LLMs such as GPT-4, Llama-3, and Gemini) enable automated document summarization and conversational interaction. However, relying solely on generative LLMs for banking grievance adjudication introduces catastrophic operational risks: LLMs are prone to hallucinating non-existent banking rules, misinterpreting transaction numbers, generating incorrect refund promises, and incurring heavy cloud API subscription costs and latency penalties (often >2000 ms per query). Financial systems require deterministic, reproducible, and explainable decision boundaries.

2.2 Review of Research Papers and Technical Resources

GrievanceIQ synthesizes established methodologies across seven computational disciplines:

2.2.1 Deterministic and Probabilistic NLP Text Classification: Text categorization literature highlights the proven efficiency of Term Frequency-Inverse Document Frequency (TF-IDF) feature representations combined with Multinomial Naive Bayes (MNB) classifiers (Manning et al., 2008). In domain-specific customer service contexts with clean vocabulary sets, MNB achieves high multi-class accuracy (>80%) with microscopic training and inference times (<5 ms per document), vastly outperforming heavyweight deep learning models on resource-constrained commodity servers.

2.2.2 Sentence Transformers and Semantic Embeddings: Reimers and Gurevych (2019) introduced Sentence-BERT (SBERT), which employs siamese and triplet network structures to generate semantically meaningful sentence embeddings. Utilizing pre-trained models like all-MiniLM-L6-v2 allows fast cosine similarity computation across high-dimensional vector spaces, providing an ideal mechanism for matching incoming customer grievances against historical bank knowledge bases and detecting duplicate tickets.

2.2.3 Optical Character Recognition and Entity Verification: Research in document image analysis demonstrates that combining deep-learning-based text detection (e.g., CRAFT) with character recognition (Tesseract / EasyOCR) reliably parses scanned financial receipts (Smith, 2007). Implementing deterministic regular-expression token matchers

over raw OCR bounding boxes enables verifiable 4-point cross-validation (Transaction ID, Amount, Bank Name, Account Digits) without model hallucination.

2.2.4 Browser-Native Speech Recognition and Vernacular Accessibility: The W3C Web Speech API specification provides standardized JavaScript interfaces for browser-native speech synthesis and recognition. By offloading acoustic processing to optimized browser runtimes, client applications achieve continuous zero-latency voice transcription in Indic locales (hi-IN, mr-IN) without streaming uncompressed raw audio to expensive third-party speech recognition cloud servers.

2.2.5 Regulatory Privacy and Statutory Token Redaction: India's Digital Personal Data Protection (DPDP) Act of 2023 mandates strict data minimization and technical safeguards against the unauthorized storage or processing of Personally Identifiable Information (PII). Software engineering best practices in financial systems mandate that PII token redaction occur at the earliest API gateway layer prior to relational persistence or model ingestion (Garfinkel, 2015).

2.2.6 Queueing Theory and Operations Research in Service Systems: Leonard Kleinrock's foundational treatise on Queueing Systems (1975) formalizes the multi-server M/M/c queueing model. Agner Krarup Erlang's Erlang-C formulation calculates the exact probability that an arriving job must wait in queue given arrival rate lambda, service rate mu, and c parallel servers. In financial service centers, Erlang-C enables precise analytical forecasting of queue dwell times and staffing requirements necessary to guarantee statutory SLA adherence.

2.2.7 Automated Software Verification and Quality Assurance: Modern dependable systems engineering emphasizes test-driven development (TDD), regression test automation, and continuous integration (Beck, 2002). Rigorous evaluation requires isolating deterministic arithmetic and regex verification from probabilistic machine learning inference.

2.3 Comparative Analysis

Table 4 compares conventional and contemporary grievance handling paradigms against the proposed GrievanceIQ platform.

Functional Criterion	Manual Review	CPGRAMS Portal	RBI CMS (RB-IOS)	Commercial CRM	GrievanceIQ (Proposed)
Dispute Intake Channels	Physical branch, Paper	Static Web Form	Online Web Form	Web, Email, Chat	Multimodal (Web, Voice, OCR)
Vernacular Voice Dictation	None (Physical only)	None (English/Hindi text)	None (Text only)	Requires costly add-on	Native Hindi, Marathi & English
Autonomous NLP Triage	Manual human sorting	Manual nodal routing	Manual clerk routing	Rule-based / Paid AI	TF-IDF + Multinomial Naive Bayes

DPDP 2023 PII Masking	None (Paper exposed)	None (Plain text stored)	None (Plain text stored)	Custom setup required	Ingestion-level regex redaction (100%)
Evidence Verification	Manual paper check	Manual officer review	Manual officer review	Manual agent inspection	Automated OCR 4-point cross-validation
Tier-1 Autonomous Bot	None	None	None	Basic keyword bot	AI GrievanceBot with instant settlement
Predictive Queue Modeling	None	None	None	Limited analytics	Kleinrock M/M/c Erlang-C simulation
What-If Staffing Sandbox	None	None	None	None / Costly BI tool	Built-in interactive staffing modeler
Dynamic SLA Countdowns	None (Static calendar)	Static days elapsed	Static 30-day clock	Standard SLA timer	Real-time urgency radar & countdowns
Statutory Receipt & QR	Carbon paper slip	Plain text printout	Basic PDF acknowledgement	Email confirmation	ReportLab PDF with dynamic ISO QR
Software Licensing Cost	Labor intensive	Government funded	Regulatory funded	High recurring SaaS fees	100% Free & Open-Source Software
Deployment & Footprint	Physical branches	Monolithic data center	Centralized server	Proprietary cloud lock-in	Lightweight, containerized, portable

Table 4: Comparison of Existing Solutions and GrievanceIQ

2.4 Limitations of Existing Systems

The comprehensive literature review and comparative analysis reveal four overarching systemic limitations:

• Static and Unresponsive Intake Modalities: Existing grievance portals force users into dense text-input fields, creating severe accessibility barriers for non-tech-savvy or non-English-speaking citizens.

• Regulatory Non-Compliance in Data Handling: Nearly all existing banking portals lack automated PII redaction at intake, resulting in persistent plaintext storage of customer credit cards and Aadhaar credentials in violation of the DPDP Act 2023.

• Unverified Customer Assertions: Traditional systems accept customer claim amounts and transaction IDs on faith until human investigation days later, lacking instant OCR verification against transaction receipts.

• Reactive Rather Than Predictive Operations: Bank leadership relies on retrospective end-of-month reporting rather than real-time mathematical queue modeling, causing preventable SLA breaches during transaction failure surges.

2.5 Identified Research or Engineering Gap

The critical engineering gap is the complete absence of an integrated, privacy-hardened software pipeline that bridges zero-latency vernacular voice intake, autonomous machine learning triage, deterministic documentary OCR validation, and predictive Erlang-C queueing intelligence into an open-source, full-stack architecture tailored to Indian banking regulations.

2.6 Proposed Improvements

GrievanceIQ delivers seven core architectural improvements over conventional systems:

1. Ingestion-Level DPDP Act 2023 PII Masking: 100% automated redaction of sensitive credentials prior to database insertion.

2. Continuous Streaming Voice Dictation: Dual-state buffer accumulator eliminating repeating text loops in Hindi and Marathi.

3. Sub-10ms NLP Classification: Lightweight TF-IDF + Multinomial Naive Bayes model providing instant triage without cloud API latency.

4. Deterministic 4-Point OCR Validation: High-precision cross-matching of transaction tokens against physical receipts.

5. Tier-1 Automated Settlement Gate: Deflecting routine grievances through instant AI copilot self-service resolutions.

6. Closed-Form Erlang-C Queueing Operations: Real-time calculation of dwell times and interactive What-If staffing capacity simulation.

7. Dynamic ISO/IEC 18004 QR PDF Receipts: Verifiable legal documentation with zero-friction mobile tracking.

3 Software Requirements Specification (SRS)

3.1 Purpose and Scope of the SRS

This Software Requirements Specification (SRS) delineates the functional, non-functional, interface, security, and operational requirements governing Version 1.0 of the GrievanceIQ platform. It serves as the authoritative technical contract between engineering design and practical deployment, providing explicit verification criteria, boundary invariants, and traceability matrices for academic and institutional evaluation. In all requirement specifications, the auxiliary verb 'shall' denotes a mandatory contractual requirement, while 'should' denotes a recommended design enhancement.

3.1.1 In Scope

The functional scope of GrievanceIQ encompasses:

• Multi-attribute dispute intake with manual entry, receipt attachment, and browser-native voice dictation.

• Ingestion-level regular expression redaction of 16-digit payment card numbers, 12-digit Aadhaar identifiers, and 10-character Permanent Account Numbers (PAN) to guarantee 100% compliance with India's DPDP Act of 2023.

• Autonomous NLP categorization of complaints into high-level banking departments using TF-IDF and Multinomial Naive Bayes.

• SBERT semantic embedding analysis for granular subcategory prediction and similar complaint clustering.

• Deterministic optical character recognition (OCR) and 4-point entity cross-matching against uploaded transaction proofs.

• Tier-1 AI GrievanceBot automated resolution gate offering instant settlement workflows for high-validity routine disputes.

• Dynamic calculation of statutory SLA countdowns (24h/72h/30d) based on RBI customer liability directions.

• Workload-balanced smart officer assignment algorithm prioritizing department specialty, active backlog, and historical speed.

• Senior Nodal Officer (Level 2) escalation and governance for reopened grievances.

• Predictive operations modeling using Kleinrock M/M/c Erlang-C queueing theory and interactive What-If staffing simulation.

• ReportLab generation of statutory PDF receipts with embedded ISO/IEC 18004 dynamic tracking QR codes.

• Immutable append-only forensic audit logging of all system events, state transitions, memos, and officer assignments.

• Full-stack trilingual dynamic UI localization across 222 dictionary keys in English, Hindi, and Marathi.

3.1.2 Out of Scope

The following capabilities are excluded from Version 1.0 release boundaries:

• Direct write-back integration into proprietary Core Banking Solutions (CBS) like Infosys Finacle or TCS BaNCS (mocked via standard RESTful JSON interfaces).

• Direct execution of interbank financial debit reversals or automated clearinghouse settlements across NPCI/RBI networks.

• Recognition of handwritten physical complaint slips (system requires typed text, voice dictation, or printed receipts).

• Languages beyond English, Hindi, and Marathi.

• Autonomous filing of formal legal complaints into the RBI Integrated Ombudsman CMS portal without human officer review.

3.2 Intended Users and Stakeholders

Table 5 delineates the primary user personas and their system interaction characteristics.

Stakeholder Persona	Primary Role and Interaction Workflow
Bank Customer / Complainant	Primary end-user filing banking disputes. May have limited technical literacy or English proficiency. Utilizes voice dictation in Hindi or Marathi, uploads transaction proofs, views live status, and downloads statutory QR receipts.
Grievance Redressal Officer	Bank operations specialist assigned to investigate complaints. Reviews OCR evidence matches, inspects AI copilot resolution suggestions, conducts internal inquiries, and executes formal resolution memos.
Branch Operations Manager	Administrative supervisor monitoring branch-level SLA compliance, evaluating officer productivity, running Erlang-C What-If queue simulations, and auditing DPDP Act privacy adherence.
Regulatory / Internal Auditor	Independent compliance officer inspecting immutable audit logs, validating PII masking enforcement, and analyzing systemic bank failure trends.
Project Maintainer / Developer	Engineering personnel deploying backend services, maintaining ML classification datasets, monitoring API health, and managing CI/CD test pipelines.

Table 5: Users and Stakeholders

3.3 Overall Product Description

3.3.1 Product Perspective

GrievanceIQ operates as a modern, decoupled three-tier software architecture comprising a reactive single-page frontend (React 18), an asynchronous RESTful API gateway (Python FastAPI / Uvicorn), and a relational data persistence layer (SQLite WAL / PostgreSQL). The system coordinates deterministic data sanitization, probabilistic

machine learning classification, deep learning semantic similarity, optical character recognition, and mathematical queueing theory into a unified operational pipeline.

3.3.2 System Environment and Data Flow

The end-to-end complaint processing pipeline executes across six distinct stages summarized in Table 6.

# Stage	Operational Activity	Generated Architectural Output
1. Ingestion & Sanitization	Multi-attribute dispute data and audio stream are received. DPDP regex filters scrub Cards, Aadhaar, and PAN tokens.	Sanitized complaint record, unmasked PII eliminated.
2. ML Triage & Routing	TF-IDF vectorizer extracts unigram/bigram tokens; Multinomial Naive Bayes and SBERT predict department and subcategory.	Assigned category, subcategory, confidence score.
3. Evidence OCR Validation	Uploaded receipt images/PDFs are parsed via OCR. 4-point entity matcher checks Ref, Bank, Account, and Amount.	Document text, entity match badges, credibility score (0-100%).
4. Tier-1 Bot & SLA Gating	Claim validity is scored; bot evaluates knowledge-base rules; statutory SLA deadline is computed based on RBI rules.	Immediate settlement offer or escalated queue status with SLA countdown.
5. Smart Assignment & Memo	Unresolved disputes are assigned to optimal officer based on workload; officer conducts review with AI memo copilot.	Officer assignment record, internal notes, draft memo.
6. Resolution, Receipt & Audit	Officer executes formal resolution memo; ReportLab generates statutory PDF receipt with dynamic QR; audit log is written.	Resolved status, downloadable QR PDF receipt, immutable audit event.

Table 6: Six-Stage Processing Pipeline

3.4 Functional Requirements

The formal functional requirements for GrievanceIQ are detailed in Tables FR-01 through FR-20, specifying input, processing logic, output, and testable acceptance criteria.

FR-01 [Priority: H] – Authentication and Role-Based Access Control

Attribute	Specification Details
Description	The system shall provide authentication and role-based access control as an automated, verifiable capability.
Input	Email, password, role claim; on subsequent requests, Bearer JWT access token.

Processing	Password is hash-verified using bcrypt with work factor 12. FastAPI OAuth2 middleware decodes JWT, validates expiry, and checks role permissions (Customer, Officer, Admin).
Output	Authenticated session token, user profile payload, or structured 401/403 HTTP error.
Acceptance Criteria	Valid credentials yield signed JWT; invalid credentials return 401; customers accessing officer endpoints receive 403 Forbidden; raw passwords are never persisted.

FR-02 [Priority: H] – Multi-Attribute Complaint Ingestion

Attribute	Specification Details
Description	The system shall provide multi-attribute complaint ingestion as an automated, verifiable capability.
Input	Complainant name, email, phone, bank name, transaction ID, date, amount, dispute description.
Processing	Backend validates presence, data types, and positive transaction amount. Assigns unique identifier GIQ-YYYY-XXXXX.
Output	Persisted complaint record in state 'Submitted', HTTP 201 Created.
Acceptance Criteria	Valid payloads are saved within 100 ms; non-positive amounts or missing required fields return 422 Unprocessable Entity.

FR-03 [Priority: H] – Real-Time Vernacular Voice Dictation

Attribute	Specification Details
Description	The system shall provide real-time vernacular voice dictation as an automated, verifiable capability.
Input	Streaming audio microphone capture via browser W3C Web Speech API.
Processing	Client-side speech recognizer configured for en-US, hi-IN, or mr-IN. Dual-state buffer accumulates session-final text while streaming interim hypotheses.
Output	Real-time text transcript streaming into description field with zero duplicate line emissions.
Acceptance Criteria	Continuous speech across 60 seconds generates single coherent transcript with 0% phrase duplication.

FR-04 [Priority: H] – DPDP Act 2023 Ingestion-Level PII Sanitization

Attribute	Specification Details
Description	The system shall provide dpdp act 2023 ingestion-level pii sanitization as an automated, verifiable capability.
Input	Raw natural-language complaint narrative containing potential PII tokens.
Processing	Compiled regex filters scan text for 16-digit card numbers, 12-digit Aadhaar numbers, and 10-character PAN strings (case-insensitive). Replaces matches with masked strings.
Output	Scrubbed complaint description with zero unredacted PII tokens.
Acceptance Criteria	100% of tested valid and formatted Card, Aadhaar, and PAN tokens are redacted; database contains zero raw PII.

FR-05 [Priority: H] – Autonomous ML Categorization (TF-IDF + MNB)

Attribute	Specification Details
Description	The system shall provide autonomous ml categorization (tf-idf + mnb) as an automated, verifiable capability.
Input	Sanitized complaint description string.
Processing	Pipeline converts text to unigram/bigram TF-IDF sparse matrix and executes Multinomial Naive Bayes inference.
Output	Predicted primary category, confidence score (0.0 to 1.0).
Acceptance Criteria	Classification accuracy >= 80% on test benchmark; execution latency < 10 ms per complaint.

FR-06 [Priority: H] – SBERT Semantic Subcategory & Duplicate Detection

Attribute	Specification Details
Description	The system shall provide sbert semantic subcategory & duplicate detection as an automated, verifiable capability.
Input	Complaint description string.
Processing	Sentence-BERT all-MiniLM-L6-v2 model calculates 384-dimensional dense embedding, computing cosine similarity against historical disputes.
Output	Predicted subcategory and list of similar historical complaints with similarity index.
Acceptance Criteria	Subcategory predicted within 50 ms; duplicate complaints with similarity > 0.85 flagged immediately.

FR-07 [Priority: H] – Documentary Evidence Upload and Validation

Attribute	Specification Details
Description	The system shall provide documentary evidence upload and validation as an automated, verifiable capability.
Input	Uploaded binary file (PNG, JPG, or PDF up to 5 MB).
Processing	Server verifies MIME type, magic bytes, and file size. Stores file securely under unique UUID in uploads/ directory.
Output	Validated evidence record with persistent storage path and document URL.
Acceptance Criteria	Valid files saved; executables, non-image/non-PDF files, and files > 5 MB rejected with 400 Bad Request.

FR-08 [Priority: H] – Evidence OCR Extraction & 4-Point Cross-Validation

Attribute	Specification Details
Description	The system shall provide evidence ocr extraction & 4-point cross-validation as an automated, verifiable capability.
Input	Validated transaction receipt image or PDF file, complaint metadata.
Processing	OCR extracts raw text tokens. Deterministic matching checks: (1) Transaction Ref, (2) Bank Name, (3) Disputed Amount, (4) Account last 4 digits.
Output	Extracted text, individual entity match boolean flags, and composite credibility score (0 to 100%).
Acceptance Criteria	Matching all 4 entities yields score >= 90%; matching 0 entities yields score < 25%; execution completes within 2.5 s.

FR-09 [Priority: H] – Tier-1 AI GrievanceBot Adjudication Gate

Attribute	Specification Details
Description	The system shall provide tier-1 ai grievancebot adjudication gate as an automated, verifiable capability.
Input	Complaint record, extracted OCR evidence score, complaint validity score.
Processing	Bot evaluates whether validity >= 70% and evidence >= 50%. Matches dispute against KnowledgeBase FAQs and circulars.
Output	Automated resolution memo, instant refund recommendation, or escalation to human queue.

Acceptance Criteria	Eligible minor disputes resolved immediately with customer confirmation; non-qualifying disputes cleanly escalated.

FR-10 [Priority: H] – Dynamic SLA Deadline & Urgency Radar

Attribute	Specification Details
Description	The system shall provide dynamic sla deadline & urgency radar as an automated, verifiable capability.
Input	Complaint category, transaction date, submission timestamp.
Processing	Engine applies statutory RBI rules: 72 hours for unauthorized electronic debits, 24 hours for ATM failures, 30 days for general grievances.
Output	Explicit SLA deadline timestamp, remaining countdown hours, urgency level (CRITICAL, HIGH, MEDIUM, LOW).
Acceptance Criteria	Deadlines computed deterministically; complaints exceeding deadline flagged with visual SLA_BREACH warning.

FR-11 [Priority: H] – Workload-Balanced Smart Officer Assignment

Attribute	Specification Details
Description	The system shall provide workload-balanced smart officer assignment as an automated, verifiable capability.
Input	Escalated complaint, department ID, active officers pool.
Processing	Assigner queries active officer ticket counts, historical resolution velocities, and specialty skills. Allocates to officer with lowest active load.
Output	Updated complaint assignment record, notification to officer, assignment_history audit entry.
Acceptance Criteria	Assignment executed in O(c) time; officer active ticket distribution remains balanced across department.

FR-12 [Priority: M] – Duplicate and Fraudulent Grievance Detection

Attribute	Specification Details
Description	The system shall provide duplicate and fraudulent grievance detection as an automated, verifiable capability.
Input	Incoming complaint details (user_id, bank, transaction ID, amount).
Processing	Database checks for identical transaction IDs and matching SBERT embeddings

	filed within preceding 30 days.
Output	Duplicate flag and reference to original master complaint.
Acceptance Criteria	Repeated submissions of identical transaction ID by same user within 30 days flagged as DUPLICATE.

FR-13 [Priority: H] – Officer Adjudication and AI Copilot Memo Drafting

Attribute	Specification Details
Description	The system shall provide officer adjudication and ai copilot memo drafting as an automated, verifiable capability.
Input	Officer review inputs, investigation notes, resolution decision.
Processing	Backend generates formal resolution memo incorporating dispute findings, bank policy, and refund amounts.
Output	Updated complaint state 'Resolved', resolution record, timestamp, officer signature.
Acceptance Criteria	Complaint state transitions to Resolved; customer receives notification; resolution memo is permanently logged.

FR-14 [Priority: M] – Case Reopening and Senior Nodal Escalation (Level 2)

Attribute	Specification Details
Description	The system shall provide case reopening and senior nodal escalation (level 2) as an automated, verifiable capability.
Input	Customer dissatisfaction request submitted within 7 days of resolution.
Processing	System verifies 7-day eligibility window. Escalates dispute to Senior Nodal Officer with priority set to CRITICAL.
Output	Complaint state 'Reopened', escalation_history entry, notification to Senior Nodal Officer.
Acceptance Criteria	Reopened cases bypass frontline officers and appear exclusively in Senior Nodal Officer queue.

FR-15 [Priority: H] – Statutory PDF Receipt with Dynamic ISO QR Code

Attribute	Specification Details
Description	The system shall provide statutory pdf receipt with dynamic iso qr code as an automated, verifiable capability.

Input	Resolved or registered complaint ID, metadata.
Processing	ReportLab generates formal two-column PDF receipt embedding bank logos, metadata, DPDP masked text, and ISO/IEC 18004 2D QR code.
Output	Downloadable PDF document (< 150 KB) with scannable QR tracking URL.
Acceptance Criteria	PDF conforms to formal layout; QR code scans cleanly on standard mobile cameras to live tracking endpoint.

FR-16 [Priority: H] – Predictive Queue Modeling (Kleinrock M/M/c & Erlang-C)

Attribute	Specification Details
Description	The system shall provide predictive queue modeling (kleinrock m/m/c & erlang-c) as an automated, verifiable capability.
Input	Hourly arrival rate lambda, officer service rate mu, active officer count c.
Processing	Engine computes traffic intensity rho, probability of zero jobs P_0, Erlang-C delay probability C(c, lambda/mu), queue wait time W_q, and SLA breach risk.
Output	Operational metrics payload: utilization, queue length, dwell time, and breach risk percentage.
Acceptance Criteria	Formulas produce exact analytical outputs in O(c) time; stability condition rho < 1 enforced.

FR-17 [Priority: M] – Interactive 'What-If' Staffing Sandbox

Attribute	Specification Details
Description	The system shall provide interactive 'what-if' staffing sandbox as an automated, verifiable capability.
Input	Baseline parameters, simulated arrival multiplier, simulated officer adjustment delta_c.
Processing	Engine recalculates Erlang-C queue metrics under hypothetical surge and staffing configurations.
Output	Side-by-side comparative table showing impact on wait times, queue sizes, and SLA breach probability.
Acceptance Criteria	Sandbox recalculates within 10 ms upon slider adjustment in browser UI.

FR-18 [Priority: M] – Bank Health Score & Systemic Vulnerability Radar

Attribute	Specification Details

Description	The system shall provide bank health score & systemic vulnerability radar as an automated, verifiable capability.
Input	Aggregated complaints dataset across scheduled commercial banks.
Processing	Engine computes composite health score (0 to 100) based on resolution speed, SLA breach rate, customer reopen rate, and evidence quality.
Output	Bank health scorecard, vulnerability radar dimensions, and operational leaderboard.
Acceptance Criteria	Leaderboard ranks all banks objectively; systemic failure spikes highlighted with early warnings.

FR-19 [Priority: H] – Trilingual Dynamic UI Localization (EN / HI / MR)

Attribute	Specification Details
Description	The system shall provide trilingual dynamic ui localization (en / hi / mr) as an automated, verifiable capability.
Input	User language selection event ('en', 'hi', 'mr').
Processing	React Context provider swaps dictionary lookup across 222 localized string keys across all navigation, labels, and alerts.
Output	Instantaneous UI language update without page reload or state loss.
Acceptance Criteria	100% of 222 keys render properly in English, Hindi, and Marathi with zero untranslated fallbacks.

FR-20 [Priority: H] – Immutable Append-Only Forensic Audit Trail

Attribute	Specification Details
Description	The system shall provide immutable append-only forensic audit trail as an automated, verifiable capability.
Input	System event trigger (submission, triage, OCR, assignment, memo, resolution).
Processing	Audit service captures action, entity_type, entity_id, user_id, details, and UTC timestamp, inserting into audit_logs table.
Output	Persistent audit record, visible in administrator audit viewer.
Acceptance Criteria	Audit records are append-only; database rules reject all UPDATE and DELETE commands on audit_logs.

3.5 Non-Functional Requirements

3.5.1 Performance Requirements

Table 33 formalizes the performance and response time constraints.

ID	Pri.	Requirement Title	Formal Specification Constraint
NFR-01	H	Transactional API Endpoint Latency	All core transactional REST endpoints (/api/complaints/submit, /api/auth/login) shall complete within 150 ms under standard load.
NFR-02	H	ML Categorization Inference Time	The TF-IDF and Naive Bayes classification pipeline shall infer category and confidence in under 15 ms per document.
NFR-03	M	Erlang-C Queue Model Execution	The analytical M/M/c queueing simulation engine shall compute waiting times, utilization, and breach risks in under 5 ms.
NFR-04	M	Documentary OCR Extraction Time	OCR extraction and 4-point entity cross-matching shall complete in under 3.0 seconds per uploaded receipt document.
NFR-05	M	Statutory PDF Receipt Generation	ReportLab PDF compilation with embedded dynamic QR code shall complete in under 500 ms and produce files under 150 KB.

Table 33: Performance Requirements

3.5.2 Scalability Requirements

• NFR-06 [H]: The backend ASGI server and database connection pool shall sustain at least 100 concurrent HTTP requests without connection timeouts or thread starvation.

• NFR-07 [M]: The relational database design shall accommodate at least 500,000 historical complaint records and 2,000,000 audit log entries without degradation of primary key lookup latency.

3.5.3 Availability and Reliability

• NFR-08 [H]: The system shall maintain 99.9% uptime during operational banking hours.

• NFR-09 [H]: All database write operations shall execute under explicit ACID transactions. In case of unexpected server termination, Write-Ahead Logging (WAL) ensures zero database corruption.

3.5.4 Security and Privacy Requirements

Table 34 formalizes the security and DPDP Act 2023 privacy requirements.

ID	Pri.	Security Requirement	Formal Technical Invariant

SEC-01	H	DPDP Act 2023 PII Masking	All 16-digit debit/credit card credentials, 12-digit Aadhaar numbers, and 10-character PAN tokens shall be masked at API ingestion with 100% precision.
SEC-02	H	Bcrypt Password Hashing	User passwords shall be salted and hashed using bcrypt with a work factor of at least 12. Raw passwords shall never be persisted or logged.
SEC-03	H	OAuth2 JWT Token Authentication	Protected administrative and officer endpoints shall require valid Bearer JSON Web Tokens signed with HS256 algorithm and 24-hour expiration.
SEC-04	H	Role-Based Access Control (RBAC)	The API gateway shall strictly enforce role separation: Customer, Officer, and Admin. Privilege escalation attempts shall be rejected with 403 Forbidden.
SEC-05	H	Parameterised SQL Execution	All database interactions shall utilize SQLAlchemy ORM parameterised statements. Raw string concatenation into SQL queries is strictly prohibited to prevent SQL injection.
SEC-06	H	Forensic Audit Immutability	The audit_logs table shall be append-only. Database rules shall block all UPDATE and DELETE queries to guarantee legal evidentiary non-repudiation.

Table 34: Security Requirements

3.5.5 Usability and Accessibility

• NFR-10 [H]: The interface shall provide trilingual localization in English, Hindi, and Marathi across 100% of UI labels, buttons, and alerts.

• NFR-11 [H]: The system shall support real-time voice dictation with visual waveform feedback to assist elderly and visually challenged depositors.

• NFR-12 [M]: The UI shall support high-contrast light and dark themes with WCAG 2.1 AA compliant color contrast ratios.

3.5.6 Maintainability and Portability

• NFR-13 [H]: Decoupled modular architecture separating frontend (React 18) and backend (FastAPI) via standardized RESTful JSON interfaces.

• NFR-14 [M]: The entire system shall execute seamlessly across Windows 10/11, Linux (Ubuntu 22.04 LTS), and macOS environments.

• NFR-15 [M]: Codebase shall maintain strict automated unit and integration test suites with zero syntax or linting violations.

3.5.7 Business Rules and Operational Invariants

Table 35 details the core business rules governing BFSI dispute adjudication.

Rule ID	Business Rule / Operational Policy Invariant
BR-01	PII Redaction Invariant: Zero plain-text payment card numbers, Aadhaar numbers, or PANs may be stored in database tables or logs.
BR-02	Statutory 72-Hour RBI SLA: Unauthorized electronic banking transactions reported by customers must be resolved within 72 hours.
BR-03	Statutory 24-Hour ATM SLA: ATM cash dispensing failures without customer debit reversal must be triaged within 24 hours.
BR-04	Statutory 30-Day Ombudsman Window: Banking grievances not resolved within 30 days are automatically flagged for RBI Ombudsman escalation.
BR-05	Customer-Gated AI Settlement: Tier-1 AI GrievanceBot settlement proposals require explicit affirmative customer acceptance.
BR-06	Deterministic Evidence Primacy: Customer assertions of payment amounts are verified against OCR extracted receipts before approval.
BR-07	Workload Fairness Invariant: No officer shall be assigned a new complaint if another qualified officer in the department has lower active load.
BR-08	7-Day Reopen Governance: Customers may request case reopening within 7 calendar days of resolution; reopened cases escalate to Senior Nodal Officers.
BR-09	Audit Non-Repudiation: Every complaint status transition, officer reassignment, and memo creation must generate an immutable audit log entry.
BR-10	Base-URL Dynamic QR Invariant: Statutory PDF receipt QR codes must encode the live server host dynamically to ensure scannable tracking.

Table 35: Business Rules

3.6 Hardware and Software Requirements

Table 36 documents the complete development, runtime, and deployment technology stack.

Technology Layer	Software Package, Framework and Version
Backend Framework	Python 3.10+, FastAPI 0.115.0, Uvicorn (ASGI Server), Pydantic v2
Database Engine	SQLite 3 with Write-Ahead Logging (WAL) / PostgreSQL 15, SQLAlchemy 2.0 ORM
Frontend Framework	React 18.3.1, Vite 5.4.14, Tailwind CSS 3.4.1, Lucide React Icons, Recharts 2.15

Audio & Speech	W3C Web Speech API (SpeechRecognition), Web Audio API (AudioContext Waveform)
Machine Learning	Scikit-Learn 1.5.0 (TF-IDF Vectorizer, Multinomial Naive Bayes Classifier)
Semantic NLP	Sentence-Transformers (all-MiniLM-L6-v2, 384-dimensional dense cosine embeddings)
OCR Engine	EasyOCR 1.7.1, PyTesseract 0.3.10, Pillow (PIL) 10.4.0
Document Generation	ReportLab 4.2.2 (canvas, platypus layout), Qrcode 7.4.2 (ISO/IEC 18004 QR)
Testing & Quality	FastAPI TestClient, Pytest 8.2, Requests, Pre-Commit, Flake8, Black

Table 36: Development and Runtime Stack

3.7 Constraints and Assumptions

3.7.1 Technical Constraints: System requires modern web browsers with Web Speech API support for voice dictation. Backend executes on standard Python 3.10+ runtimes.

3.7.2 Financial Constraints: Engineered exclusively with open-source software libraries, eliminating commercial software licensing fees.

3.7.3 Operational Constraints: GrievanceIQ functions as an assistive operational tool; binding financial debits and legal rulings remain under formal banking authority.

3.7.4 Time Constraints: Formulated and deployed within the 12-week academic sprint schedule of the APNI Leap semester.

Table 39 outlines technical items reserved for future production deployment.

ID	Architecture Open Item / Production Roadmap Task
TBD-01	Production Core Banking Integration: Certified adapter specifications for Finacle and BaNCS write-backs.
TBD-02	On-Device Whisper ASR: Local compilation of Whisper.tflite for offline voice recognition in rural kiosks.
TBD-03	NPCI UPI Auto-Reversal API: Direct integration with automated clearinghouse debit reversal webhooks.
TBD-04	Account Aggregator (AA) Connectivity: Automated retrieval of banking statements under RBI AA guidelines.
TBD-05	Distributed Message Bus: Migration of event queues to Apache Kafka for multi-datacenter replication.
TBD-06	Multi-Language Expansion: Inclusion of 10 additional scheduled Indian languages (Tamil, Telugu, Bengali, etc.).

TBD-07	Disaster Recovery & Hot Standby: Geographically distributed multi-region failover configuration.

Table 39: Open Items (TBD)

3.8 Use Cases and User Stories

3.8.1 Formal Use Cases

UC-01: Register and Authenticate User

Attribute	Specification Details
Actor	Bank Customer / Officer
Precondition	None
Main Flow	User opens /auth, enters credentials. Backend verifies password hash with bcrypt, issues signed Bearer JWT.
Alternative Flow	Invalid credentials return 401 Unauthorized with descriptive error message.
Postcondition	Authenticated session established; role-specific dashboard views enabled.

UC-02: File Grievance with Voice Dictation & PII Redaction

Attribute	Specification Details
Actor	Bank Customer
Precondition	Customer is signed in or guest on public portal
Main Flow	Customer selects language (Hindi/Marathi/English), activates microphone, dictates dispute, attaches receipt slip, submits form. System masks PII tokens, executes ML triage, stores complaint, and creates audit event.
Alternative Flow	If description is < 15 characters, validity gate rejects submission with 422 error requesting details.
Postcondition	Complaint persisted in 'Submitted' state; unique ID (GIQ-YYYY-XXXXX) returned; dynamic QR PDF receipt generated.

UC-03: Tier-1 GrievanceBot Adjudication & Settlement

Attribute	Specification Details
Actor	Bank Customer
Precondition	Complaint submitted with valid evidence

Main Flow	GrievanceBot evaluates validity and OCR score. If complaint meets criteria, bot presents immediate refund settlement dialog. Customer accepts settlement.
Alternative Flow	Customer declines automated settlement or dispute requires manual inquiry; dispute escalates to officer queue.
Postcondition	Complaint state transitions to 'Resolved'; settlement memo recorded; customer notified.

UC-04: Documentary Evidence OCR Cross-Verification

Attribute	Specification Details
Actor	Grievance Officer
Precondition	Complaint has attached receipt image/PDF
Main Flow	Officer opens complaint dossier. Clicks 'Verify Evidence'. OCR engine extracts text tokens and matches Ref, Bank, Amount, and Account. Scores displayed with visual badges.
Alternative Flow	Uploaded document is blurry or unreadable; OCR returns low confidence (< 30%); manual inspection required.
Postcondition	Credibility score saved to complaint record; match badges visible in officer workspace.

UC-05: Dynamic SLA Tracking and Urgency Escalation

Attribute	Specification Details
Actor	Grievance Officer / Admin
Precondition	Active complaints exist in database
Main Flow	Engine computes time delta between submission and statutory deadline (24h/72h/30d). Visual radar updates countdown timers and highlights urgent cases.
Alternative Flow	None.
Postcondition	Complaints within 12 hours of breach highlighted in Amber; breached complaints highlighted in Red with critical alert.

UC-06: Officer Adjudication and Resolution Memo Drafting

Attribute	Specification Details
Actor	Grievance Officer

Precondition	Complaint assigned to officer in state 'In Review'
Main Flow	Officer reviews complaint details, evidence match, and AI Copilot suggestions. Enters resolution memo and executes resolution action.
Alternative Flow	Investigation incomplete; officer adds internal investigation note and keeps complaint in review.
Postcondition	Complaint marked 'Resolved'; resolution memo persisted; customer notification dispatched; audit log updated.

UC-07: Case Reopening Governance (Level 2 Escalation)

Attribute	Specification Details
Actor	Bank Customer
Precondition	Complaint resolved within preceding 7 days
Main Flow	Customer enters dissatisfaction reason on tracking portal. System validates 7-day window, reopens case, sets priority to CRITICAL, and routes to Senior Nodal Officer.
Alternative Flow	Attempted reopen after 7 calendar days rejected with informational message advising RBI Ombudsman contact.
Postcondition	Complaint marked 'Reopened'; escalation logged in escalation_history; Senior Nodal Officer alerted.

UC-08: Predictive Queueing Simulation (Erlang-C What-If)

Attribute	Specification Details
Actor	Branch Operations Manager
Precondition	Manager authenticated on Analytics portal
Main Flow	Manager adjusts arrival rate multiplier and officer staffing count sliders. Engine recomputes Erlang-C formulas and updates charts in real time.
Alternative Flow	Traffic intensity exceeds 1.0 (unstable queue); system displays 'Queue Instability Warning' in red.
Postcondition	Predicted wait times, queue sizes, and SLA breach risks displayed with comparative baseline metrics.

UC-09: Generate and Verify Statutory QR Receipt

Attribute	Specification Details

Actor	Bank Customer / Officer
Precondition	Valid complaint ID exists
Main Flow	User clicks 'Download Official Receipt'. Backend compiles ReportLab PDF with embedded ISO/IEC 18004 dynamic QR code.
Alternative Flow	None.
Postcondition	Tamper-evident statutory PDF downloaded; mobile camera scanning QR navigates directly to live tracking page.

UC-10: Forensic Audit Log Inspection

Attribute	Specification Details
Actor	Compliance Auditor / Admin
Precondition	Admin credentials authenticated
Main Flow	Auditor navigates to /audit, filters by entity or date range. System renders immutable chronological event history.
Alternative Flow	None.
Postcondition	Complete, unalterable forensic record of all submissions, redacting events, assignments, and memos displayed.

3.8.2 User Stories Specification

Table 49 articulates the core functional requirements from user persona perspectives.

Story ID	User Persona Story & Acceptance Objective
US-01	As an aggrieved customer with limited typing skills, I want to dictate my dispute in Hindi or Marathi so that I can register my complaint effortlessly.
US-02	As a privacy-conscious depositor, I want my payment card numbers, Aadhaar, and PAN masked automatically so that my private financial credentials are never exposed.
US-03	As a bank customer, I want an instant statutory PDF receipt with a QR code so that I have verifiable legal proof of submission.
US-04	As a bank customer, I want a live status tracker with an SLA countdown timer so that I know exactly when my bank will resolve my dispute.
US-05	As a grievance redressal officer, I want automated OCR entity matching on uploaded receipts so that I can instantly verify claim authenticity without manual cross-referencing.

US-06	As a grievance redressal officer, I want an AI Copilot that drafts formal resolution memos so that I can resolve routine complaints 5x faster.
US-07	As an operations manager, I want an M/M/c queueing simulation sandbox so that I can forecast queue bottlenecks and optimize officer staffing before SLA breaches occur.
US-08	As an operations manager, I want a bank health scorecard and vulnerability radar so that I can detect systemic transaction failure points early.
US-09	As a customer whose dispute was rejected, I want the ability to escalate to a Senior Nodal Officer within 7 days so that I receive impartial secondary review.
US-10	As a regulatory compliance auditor, I want an immutable, append-only audit trail so that every status change and officer memo is forensically traceable.
US-11	As a system administrator, I want role-based access control so that customer dispute records are strictly segregated from administrative functions.
US-12	As a software engineer, I want decoupled, modular architecture and comprehensive automated test suites so that system components can be maintained without regression.

Table 49: User Stories

18

4 System Architecture and Detailed Design

4.1 Overall System Architecture

GrievanceIQ is engineered as a modern, layered, and decoupled Client-Server Architecture incorporating a modular service-oriented backend. Its architectural foundation enforces strict separation of concerns, guarantees zero plain-text PII persistence at the network boundary, isolates probabilistic machine learning inference from deterministic database transactions, and provides high-concurrency asynchronous I/O. The system is partitioned into five distinct architectural layers:

1. Client Presentation Tier: Single-Page Application (SPA) built with React 18, Vite, and Tailwind CSS. Provides accessible views for public grievance intake, real-time voice streaming with live waveform canvas visualizer, public status tracking with dynamic SLA countdowns, officer resolution workspace, AI Copilot memo drafter, bank health scorecards, and interactive What-If queueing simulation sandboxes. Communicates with the backend exclusively via asynchronous RESTful JSON over HTTPS.

2. API Gateway & Middleware Tier: Powered by Python FastAPI and Uvicorn ASGI server. Enforces CORS policies, validates request payloads via Pydantic v2 schemas (with extra="forbid" enforcement), verifies Bearer JWT tokens, inspects user role permissions (Customer, Officer, Admin), and extracts dynamic base URLs to ensure QR code tracking links adapt to the host environment.

3. Pipeline Orchestration Tier: Directs incoming disputes through a multi-stage state machine: Intake -> DPDP Sanitization -> TF-IDF / MNB Triage -> SBERT Subcategory Prediction -> OCR Evidence Validation -> Tier-1 AI GrievanceBot Adjudication -> SLA Calculation -> Smart Officer Assignment -> Statutory Receipt Generation. Tracks latency per stage and logs execution events.

4. Application & Domain Services Tier: Houses core functional modules M0 through M7 (detailed in Section 4.2), including the DPDP 2023 regex engine, the Scikit-Learn text classifier, the Sentence-BERT semantic search engine, the 4-point OCR entity cross-matcher, the Kleinrock M/M/c Erlang-C queue simulator, and the ReportLab PDF receipt generator.

5. Data Persistence & Forensic Audit Tier: Relational database layer running SQLite 3 in high-concurrency Write-Ahead Logging (WAL) mode or hosted PostgreSQL 15. The schema comprises 18 normalized tables governed by foreign keys, cascading deletions, CHECK constraints, and database rules ensuring an immutable, append-only audit trail.




Figure 1: Overall System Architecture of GrievanceIQ

4.2 Component and Module Description

The platform decomposes complex banking grievance workflows into eight decoupled domain modules:

Module M0: Dispute Intake & DPDP Act 2023 PII Sanitizer

Purpose: Collects multi-attribute grievance details and voice streams; enforces case-insensitive regex redaction to strip 16-digit payment card numbers, 12-digit Aadhaar identifiers, and 10-character PAN tokens before database insertion.
Inputs: Raw user form payload, audio stream transcription, transaction metadata.
Outputs: Scrubbed, legal-compliant complaint description, generated unique Grievance ID (GIQ-YYYY-XXXXX).
Dependencies: Python re module, Pydantic v2 schemas, W3C Web Speech API.

Module M1: Autonomous NLP Categorization Engine

Purpose: Autonomously classifies unstructured complaint descriptions into primary banking departments (Unauthorized Transactions, ATM Failures, UPI Issues, Net Banking, Loans, Account Maintenance).
Inputs: Sanitized complaint description string.
Outputs: Predicted category, department mapping, probabilistic confidence score.
Dependencies: Scikit-Learn 1.5 (TfidfVectorizer, MultinomialNB), classifier.pkl, vectorizer.pkl.

Module M2: Sentence-BERT Semantic Subcategory & Similarity Engine

Purpose: Generates 384-dimensional dense semantic embeddings to predict granular dispute subcategories and detect historical duplicate filings.
Inputs: Sanitized complaint text, historical complaint embeddings database.
Outputs: Subcategory prediction, nearest-neighbor similar complaints with cosine similarity indices.
Dependencies: Sentence-Transformers (all-MiniLM-L6-v2), PyTorch, NumPy, Scipy spatial distance.

Module M3: Documentary Evidence OCR & 4-Point Entity Cross-Matcher

Purpose: Extracts text from uploaded transaction receipts, passbooks, and ATM slips; executes deterministic 4-point cross-validation (Ref ID, Bank, Amount, Account digits) against customer assertions.
Inputs: Uploaded receipt image (PNG/JPG) or PDF file, complaint metadata.
Outputs: OCR raw text, individual match flags, composite credibility score (0 to 100%).
Dependencies: EasyOCR, PyTesseract, Pillow (PIL), PyMuPDF (fitz).

Module M4: Tier-1 AI GrievanceBot Adjudication Gate

Purpose: Evaluates complaint validity and OCR evidence credibility to offer instant automated settlement proposals for routine disputes, deflecting human officer queues.
Inputs: Complaint record, OCR evidence score, complaint validity score, KnowledgeBase rules.
Outputs: Automated resolution proposal, refund recommendation, or escalation flag.
Dependencies: bot_resolver.py, KnowledgeBaseArticle repository, SQLAlchemy Session.

Module M5: Dynamic SLA Calculation & Urgency Engine

Purpose: Enforces statutory RBI turnaround directions (72h for unauthorized debits, 24h for ATM failures, 30 days for ombudsman), calculating live countdowns and urgency tiers.
Inputs: Complaint submission timestamp, transaction date, category ID.
Outputs: SLA deadline timestamp, remaining countdown hours, urgency level (CRITICAL, HIGH, MEDIUM, LOW), SLA breach flag.
Dependencies: sla_engine.py, datetime, timedelta.

Module M6: Workload-Balanced Smart Assigner

Purpose: Allocates escalated complaints to bank redressal officers based on department specialty, active backlog, and historical resolution speed to ensure equitable workload distribution.
Inputs: Unassigned complaint record, department officer pool.
Outputs: Assigned officer ID, assignment timestamp, assignment_history audit record.
Dependencies: smart_assigner.py, User repository, SQLAlchemy query aggregations.

Module M7: Predictive Queue Modeling & Bank Intelligence

Purpose: Implements Kleinrock M/M/c Erlang-C queueing formulations to calculate system utilization, queue dwell times, and SLA breach risks; powers interactive What-If staffing simulations and bank health scorecards.
Inputs: Arrival rate lambda, service rate mu, officer count c, bank complaint history.
Outputs: Dwell time W_q, queue size L_q, breach probability, bank health score (0-100), bank performance leaderboard.
Dependencies: bank_intelligence.py, math, NumPy, Erlang-C closed-form solvers.

4.3 Architecture Selection and Justification

GrievanceIQ adopts a Layered Three-Tier Client-Server Architecture with Modular Domain Services. This architectural pattern was selected over monolithic or micro-frontend designs due to five compelling engineering requirements:

• Decoupling of Security and UI Boundaries: By enforcing DPDP Act 2023 PII sanitization at the API gateway layer, customer browser code cannot bypass redaction, ensuring zero plain-text sensitive data enters the persistence tier.

• Deterministic Isolation of Financial and Operational Math: Probabilistic machine learning triage (TF-IDF/MNB) and OCR text extraction are strictly segregated from deterministic SLA calculations, Erlang-C queue formulas, and immutable audit logs.

• High Asynchronous Concurrency: Utilizing FastAPI atop the Uvicorn ASGI event loop allows the server to handle non-blocking database queries and streaming voice transcription without thread starvation.

• Independent Testability and Module Governance: Each domain module (M0 to M7) maintains dedicated unit tests and metrics, preventing cross-module regression and ensuring adherence to the Single Responsibility Principle.

4.4 Data Flow Diagram (DFD)

Data flow across GrievanceIQ conforms to the Yourdon-DeMarco notation, utilizing open-ended bars (D1-D6) for data stores, rectangles for external entities, circles for operational processes, and directed arrows for data flows.

Store ID	Logical Content and Relational Entity Scope
D1	complaints (Central grievance records with masked text, status, SLA deadline, and verification scores)
D2	users (System users: Customers, Grievance Redressal Officers, Branch Managers, System Admins)
D3	evidence_docs & ocr_extractions (Uploaded transaction receipts, passbooks, and raw OCR text tokens)
D4	predictions & similar_complaints (ML category classifications, SBERT embeddings, similarity mappings)
D5	audit_logs (Immutable append-only forensic event log capturing all actions and state transitions)
D6	resolutions & investigation_notes (Officer adjudication memos, refund recommendations, case notes)

Table 51: DFD Data Stores

4.4.1 Context-Level DFD (Level 0)

The Level 0 Context Diagram (Figure 2) depicts GrievanceIQ as a single centralized system interacting with five external entities: the Aggrieved Complainant, the Grievance Redressal Officer, the Branch Operations Manager, the Regulatory Auditor, and External Core Banking Systems.




Figure 2: Level 0 DFD: Context Diagram

4.4.2 Level 1 DFD: Subsystem Decompositions

The operational workflow decomposes into four interconnected Level 1 functional diagrams:

• Diagram 1A: Intake, PII Redaction, and Autonomous ML Triage (Process 1.0 to 3.0)




Figure 3: Level 1 DFD, Diagram 1A: Intake, PII Redaction & NLP Triage

• Diagram 1B: Evidence OCR Extraction and Tier-1 Bot Adjudication (Process 4.0 to 5.0)




Figure 4: Level 1 DFD, Diagram 1B: Evidence OCR & Bot Resolution

• Diagram 1C: Smart Officer Assignment, SLA Tracking, and Senior Escalation (Process 6.0 to 7.0)




Figure 5: Level 1 DFD, Diagram 1C: Officer Assignment & SLA Monitoring

• Diagram 1D: Predictive Queueing Intelligence, Statutory Receipt, and Audit Trail (Process 8.0 to 10.0)




Figure 6: Level 1 DFD, Diagram 1D: Predictive Queueing, Audit & Receipt

4.4.3 Level 2 DFD: Detailed Process Specifications

Core processes are decomposed further into fine-grained Level 2 workflows: Process 1.0 (Intake & DPDP Sanitization, Figure 7), Process 2.0 (OCR Extraction & 4-Point Entity Cross-Match, Figure 8), Process 3.0 (TF-IDF & SBERT Classification, Figure 9), Process 4.0 (Kleinrock M/M/c Queueing Simulator, Figure 10), Process 5.0 (Officer Adjudication & Memo Drafting, Figure 11), and Process 6.0 (Statutory PDF Receipt & Dynamic QR Encoding, Figure 12).




Figure 7: Level 2 DFD: Process 1.0, Intake and DPDP PII Sanitization




Figure 8: Level 2 DFD: Process 2.0, OCR Extraction & 4-Point Entity Cross-Match




Figure 9: Level 2 DFD: Process 3.0, TF-IDF and SBERT Classification Engine




Figure 10: Level 2 DFD: Process 4.0, Kleinrock M/M/c Predictive Queue Simulator




Figure 11: Level 2 DFD: Process 5.0, Officer Adjudication & Resolution Memo




Figure 12: Level 2 DFD: Process 6.0, ReportLab PDF Receipt & Dynamic QR Encoding

4.5 UML Diagrams

Comprehensive UML models document the system structure, object interactions, behavioral lifecycles, and deployment:

• 4.5.1 Use Case Diagram (Figure 15): Illustrates relationships between Actors (Customer, Officer, Manager, Auditor) and Use Cases (File Dispute, Dictate Voice, Verify Evidence, Run Queue Simulation, Generate Receipt).




Figure 15: Use Case Diagram of GrievanceIQ

• 4.5.2 Class Diagram, Part 1: Service Layer (Figure 16): Delineates service classes: IngestionHandler, DPDPFilter, MLClassifier, SBERTEngine, OCREngine, BotResolver, SLAEngine, SmartAssigner, QueueSimulator, ReportLabGenerator, AuditService.




Figure 16: Class Diagram, Part 1: Service & Orchestration Layer

• 4.5.3 Class Diagram, Part 2: Relational Domain Entity Model (Figure 17): Delineates persistent entities: Complaint, User, Company, Department, Category, EvidenceDoc, Prediction, SimilarComplaint, Resolution, AuditLog.




Figure 17: Class Diagram, Part 2: Relational Domain Entity Model

• 4.5.4 Sequence Diagrams (Figures 18 & 19): Chronological message flow between Browser Client, FastAPI Gateway, ML Pipeline, OCR Service, and Relational Database during grievance intake and adjudication.




Figure 18: Sequence Diagram, Part 1: Ingestion, Voice Dictation & Triage




Figure 19: Sequence Diagram, Part 2: Tier-1 Bot Adjudication & Escalation

• 4.5.5 Activity Diagrams (Figures 20 & 21): Swimlane execution flows across Customer, FastAPI Backend, and Background ML/OCR Workers.




Figure 20: Activity Diagram, Part 1: Multi-Attribute Intake & Redaction




Figure 21: Activity Diagram, Part 2: Document Verification & Resolution

• 4.5.6 State Machine Diagrams (Figures 22 & 23): Complete lifecycle transitions of complaints (Submitted -> Triaged -> In Review -> Evidence Verified -> Resolved / Reopened).




Figure 22: State Machine Diagram, Part 1: Grievance Lifecycle Pipeline




Figure 23: State Machine Diagram, Part 2: Officer Assignment Lifecycle

• 4.5.7 User Flow Diagrams (Figures 24 & 25): Step-by-step user decision trees for complainants and bank officers.




Figure 24: User Flow Diagram, Part 1: Complainant Mobile & Web Flow




Figure 25: User Flow Diagram, Part 2: Bank Officer Adjudication Flow

4.6 Database Design

4.6.1 ER Diagram

Figure 26 depicts the complete Entity-Relationship model comprising 18 relational entities, enforcing strict 1:N cardinalities with foreign-key referential integrity.




Figure 26: Entity-Relationship Diagram of GrievanceIQ

4.6.2 Relational Schema Specifications

The public database schema consists of 18 normalized relations:

• users (id: integer primary key, email: text unique, password_hash: text, full_name: text, role: text, department_id: integer?, is_active: boolean, created_at: timestamptz)

• companies (id: integer primary key, name: text unique, code: text, created_at: timestamptz)

• departments (id: integer primary key, name: text unique, description: text, sla_hours: integer)

• categories (id: integer primary key, name: text unique, department_id: integer references departments(id), default_priority: text)

• complaints (id: integer primary key, complaint_id: text unique, user_id: integer references users(id), company_id: integer references companies(id), category_id: integer references categories(id), department_id: integer references departments(id), assigned_officer_id: integer? references users(id), description: text, description_sanitized: text, transaction_id: text, transaction_date: date, disputed_amount: numeric(15,2), status: text, priority: text, sla_deadline: timestamptz, evidence_doc_url: text?, verification_score: numeric(5,2), qr_code_url: text?, created_at: timestamptz, resolved_at: timestamptz?)

• evidence_docs (id: integer primary key, complaint_id: integer references complaints(id), file_name: text, file_path: text, mime_type: text, file_size_kb: integer, uploaded_at: timestamptz)

• ocr_extractions (id: integer primary key, doc_id: integer references evidence_docs(id), extracted_text: text, extracted_entities: jsonb, match_score: numeric(5,2), created_at: timestamptz)

• predictions (id: integer primary key, complaint_id: integer references complaints(id), predicted_category: text, confidence: numeric(5,4), model_version: text, created_at: timestamptz)

• similar_complaints (id: integer primary key, complaint_id: integer references complaints(id), matched_complaint_id: integer references complaints(id), similarity_score: numeric(5,4))

• resolutions (id: integer primary key, complaint_id: integer references complaints(id), resolving_officer_id: integer references users(id), memo_text: text, refund_amount: numeric(15,2), resolution_type: text, created_at: timestamptz)

• investigation_notes (id: integer primary key, complaint_id: integer references complaints(id), officer_id: integer references users(id), note_text: text, created_at: timestamptz)

• escalation_history (id: integer primary key, complaint_id: integer references complaints(id), escalation_level: integer, reason: text, escalated_to_id: integer references users(id), escalated_at: timestamptz)

• assignment_history (id: integer primary key, complaint_id: integer references complaints(id), officer_id: integer references users(id), assigned_by_id: integer? references users(id), assigned_at: timestamptz)

• status_history (id: integer primary key, complaint_id: integer references complaints(id), old_status: text, new_status: text, changed_by_id: integer? references users(id), changed_at: timestamptz)

• complaint_messages (id: integer primary key, complaint_id: integer references complaints(id), sender_id: integer references users(id), role: text, message_text: text, sent_at: timestamptz)

• notifications (id: integer primary key, user_id: integer references users(id), complaint_id: integer? references complaints(id), title: text, message: text, is_read: boolean, created_at: timestamptz)

• feedback (id: integer primary key, complaint_id: integer references complaints(id), csat_score: integer, comments: text?, submitted_at: timestamptz)

• audit_logs (id: integer primary key, action: text, entity_type: text, entity_id: integer?, user_id: integer? references users(id), details: jsonb, ip_address: text?, "timestamp": timestamptz)

4.6.11 Schema Normalization and Form Proofs

The GrievanceIQ schema was developed strictly to Boyce-Codd Normal Form (BCNF) and Third Normal Form (3NF). Starting from an unnormalized flat record containing all customer details, complaint tokens, documents, predictions, and memos, repeating groups were separated into individual relations (1NF). All non-key attributes depend fully on their primary keys with zero partial dependencies on composite keys (2NF). Transitive

dependencies such as complaint_id -> department_id -> sla_hours were systematically eliminated by factoring departments into a standalone relation (3NF). Every functional determinant in the relational model is a candidate key, satisfying BCNF across all primary relations.




Figure 14: Functional Dependency Graph & 3NF/BCNF Normalization Decomposition

Table 64 summarizes the relational anomalies prevented by this normalized design.

Database Anomaly	Structural Prevention Mechanism in GrievanceIQ Schema
Insertion Anomaly	A department or category can be configured before any complaint exists; a bank customer profile exists independently of grievances.
Update Anomaly	Modifying an officer's department or a bank's SLA policy is executed in a single row without scanning millions of historical complaint records.
Deletion Anomaly	Purging an unverified draft complaint does not delete the customer's account or system category records (guaranteed via ON DELETE CASCADE / RESTRICT rules).
Redundancy Minimization	Document binary data and OCR text are held in dedicated tables rather than duplicated across repeated status history rows.

Table 64: Anomalies Prevented by the Design

4.6.12 Database Indexing Strategy and DDL

To guarantee sub-150ms endpoint latencies across high-volume grievance datasets, B-Tree indexes are deployed on all foreign keys and high-frequency filtering attributes. Table 67 specifies the secondary performance indexes.

Index Identifier	Indexed Table and Column Specification	Operational Query Acceleration Purpose
idx_complaints_user	complaints(user_id, created_at DESC)	Speeds up complainant case listing queries
idx_complaints_dept_status	complaints(department_id, status)	Optimizes officer triage queue retrieval
idx_complaints_sla	complaints(sla_deadline, status)	Accelerates real-time SLA breach monitoring queries
idx_evidence_complaint	evidence_docs(complaint_id)	Speeds up document loading during investigation
idx_audit_entity_time	audit_logs(entity_type, entity_id, timestamp DESC)	Powers fast chronological audit inspections

Table 67: Proposed Secondary Indexes




Figure 26-B: Database Indexing & B-Tree Query Execution Plan

4.7 Security and Error Handling Design

Security in GrievanceIQ is designed defensively across four tiers: (1) Ingestion-Level PII Sanitization removing 16-digit cards, Aadhaar, and PAN tokens, (2) Cryptographic Security via bcrypt work factor 12 and HS256 JWT tokens with strict expiry, (3) Database Defense via parameterized ORM queries, foreign key referential integrity, and append-only audit rules, and (4) Structured Error Handling returning consistent JSON envelopes {error_code, message, request_id} while suppressing internal stack traces.

5 Algorithm Design and Data Structures

5.1 Identification of Critical Operations

GrievanceIQ coordinates seventeen mission-critical operations to ingest, redact, classify, verify, adjudicate, and forecast banking grievance lifecycles. These operations govern system security, statutory compliance, mathematical integrity, and user accessibility:

1. Ingestion-Level PII Sanitization: Deterministic case-insensitive regex scanning to mask cards, Aadhaar, and PAN.
2. Real-Time Streaming Voice Accumulation: Browser-native audio capture and buffer state management eliminating duplicate loops.
3. TF-IDF Feature Extraction: Sparse unigram/bigram tokenization converting complaint narratives into feature vectors.
4. Multinomial Naive Bayes Inference: Probabilistic classification maximizing posterior probabilities across banking departments.
5. SBERT Dense Embedding Inference: Transformer forward-pass computing 384-dimensional dense semantic vectors.
6. Cosine Similarity Calculation: Nearest-neighbor spatial distance evaluation for duplicate detection and subcategory routing.
7. Documentary OCR Text Extraction: Optical character recognition processing scanned receipts, ATM slips, and passbooks.
8. 4-Point Entity Cross-Validation: Deterministic regex and token matching comparing claim data against OCR text.
9. Adaptive Complaint Validity Scoring: Token density, structural completeness, and gibberish evaluation gate.
10. Kleinrock M/M/c Multi-Server Queue Simulation: Erlang-C closed-form computation of dwell times and queue lengths.
11. Dynamic SLA Deadline & Urgency Evaluation: Time delta comparison against statutory RBI turnaround circulars.
12. Workload-Balanced Smart Officer Assignment: Minimum-load allocation optimizing officer department queues.
13. Tier-1 AI GrievanceBot Adjudication Gate: Automated instant settlement evaluation for routine disputes.
14. ReportLab PDF Receipt & Dynamic QR Compilation: Dynamic layout generation and ISO/IEC 18004 2D barcode embedding.
15. Trilingual UI Key Resolution: O(1) hash map lookup across 222 localized keys in English, Hindi, and Marathi.
16. Bank Health Scorecard & Vulnerability Index: Multi-dimensional aggregation of resolution speeds, breach rates, and CSAT.
17. Append-Only Audit Trail Insertion: Cryptographically secure, unalterable event persistence for forensic accountability.

5.2 Algorithm Design

The formal pseudocode specifications for the core algorithmic modules are delineated below.

ALGORITHM 1: AUTHENTICATED INGESTION AND CASE-INSENSITIVE DPDP PII MASKING

Input: Raw complaint description text S_raw, transaction metadata
Output: Sanitized description text S_clean with zero plain-text PII tokens

1. Receive HTTP payload with bearer JWT and raw complaint text S_raw.
2. Verify JWT token validity and user claims via security middleware.
3. Initialize S_clean = S_raw.
4. Compile regex R_card = r'\b(?:\d{4}[-]?){3}\d{4}\b'.
5. Compile regex R_aadhaar = r'\b\d{4}[-]?\d{4}[-]?\d{4}\b'.
6. Compile regex R_pan = r'\b[A-Za-z]{5}\d{4}[A-Za-z]\b' with re.IGNORECASE.
7. Execute substitution: S_clean = re.sub(R_card, 'XXXX-XXXX-XXXX-XXXX', S_clean).
8. Execute substitution: S_clean = re.sub(R_aadhaar, 'XXXX-XXXX-XXXX', S_clean).
9. Execute substitution: S_clean = re.sub(R_pan, 'XXXXX0000X', S_clean).
10. Validate that no unmasked sensitive token survives in S_clean.
11. Return sanitized text S_clean for downstream ML triage and database persistence.

ALGORITHM 2: CONTINUOUS NON-DESTRUCTIVE VERNACULAR VOICE DICTATION BUFFER

Input: Browser W3C SpeechRecognition event stream E, Committed base text T_base
Output: Clean, continuous transcript T_final with 0% repeating loops

1. Initialize session buffers: T_sessionFinal = "", T_interim = "".
2. Bind listener to SpeechRecognition.onresult event stream.
3. FOR each result segment R_i in E.results starting at E.resultIndex:
4. Extract transcript phrase P = R_i[0].transcript.
5. IF R_i.isFinal == TRUE:
6. Append P to T_sessionFinal with boundary spacing.
7. ELSE:
8. Assign P to T_interim.
9. Construct composite display text: T_display = Trim(T_base + " " + T_sessionFinal + T_interim).
10. Dispatch T_display to reactive UI state without mutating committed history.
11. Upon SpeechRecognition.onend, commit T_base = Trim(T_base + " " + T_sessionFinal).
12. Return final continuous transcript T_final.

ALGORITHM 3: TF-IDF VECTORIZATION & MULTINOMIAL NAIVE BAYES CATEGORIZATION

Input: Sanitized complaint description string S_clean, Vocabulary V, Class set C
Output: Predicted banking department category c, Probabilistic confidence P**

1. Tokenize S_clean into lower-case unigram and bigram tokens.
2. Filter English and Indic domain stop words.
3. Compute term frequency vector TF(t, S_clean) for all vocabulary terms t in V.
4. Compute feature vector x = TF(t, S_clean) * IDF(t) using pre-calculated inverse document frequencies.
5. Normalize feature vector: x_norm = x / ||x||_2.
6. FOR each candidate banking category c in C:

```
    Compute log-likelihood: log_P(c|x) = log(P(c)) + SUM_i [ x_norm_i * log((N_ci + alpha) / (N_c + alpha * |V|)) ].
Identify optimal category: c* = argmax_{c in C} [ log_P(c|x) ].
Compute normalized softmax confidence score P* = exp(log_P(c*|x)) / SUM_c [ exp(log_P(c|x)) ].
Return predicted category c* and confidence score P*.
```

ALGORITHM 4: SENTENCE-BERT SEMANTIC SUBCATEGORY & DUPLICATE DETECTION

Input: Sanitized text S_clean, Historical complaint embeddings {E_hist}, Subcategory centroids {C_sub}
Output: Predicted subcategory s, Flag is_duplicate, Top matching complaint ID*

```
Pass S_clean through Sentence-BERT model (all-MiniLM-L6-v2) transformer backbone.
Extract 384-dimensional token embeddings; compute mean-pooling to derive sentence vector e_new.
Normalize vector: e_norm = e_new / ||e_new||_2.
Compute cosine similarity against all historical embeddings: Sim_h = dot(e_norm, e_hist_k).
Identify maximum similarity Sim_max = max(Sim_h) and corresponding complaint ID k*.
IF Sim_max >= 0.85:
    Set is_duplicate = TRUE, reference_complaint = k*.
ELSE:
    Set is_duplicate = FALSE.
Compute cosine similarity against subcategory centroid embeddings {C_sub}.
Select subcategory s* = argmax_s [ dot(e_norm, C_sub_s) ].
Return predicted subcategory s*, is_duplicate flag, and reference match.
```

ALGORITHM 5: DOCUMENTARY EVIDENCE OCR & 4-POINT ENTITY CROSS-VALIDATION

Input: Uploaded receipt file F (PNG/JPG/PDF), User claim data C = {ref_id, bank, amount, account_last4}
Output: Composite credibility score Score in [0, 100], Match flags {M_ref, M_bank, M_amount, M_acct}

```
IF F is PDF: rasterize pages to high-resolution images via PyMuPDF at 300 DPI.
Execute OCR text extraction via EasyOCR / PyTesseract to obtain raw token text T_ocr.
Normalize T_ocr: remove non-alphanumeric punctuation, convert to upper case.
Check Entity 1 (Transaction Ref): M_ref = (C.ref_id in T_ocr) OR (Levenshtein_Sim(C.ref_id, T_ocr) >= 0.85).
Check Entity 2 (Bank Name): M_bank = (C.bank.upper() in T_ocr) OR any bank acronym match in T_ocr.
Check Entity 3 (Disputed Amount): M_amount = Regex_Extract_Monetary(T_ocr) matches C.amount within +/- INR 1.00.
Check Entity 4 (Account Digits): M_acct = (C.account_last4 in T_ocr) OR regex 'XX' + C.account_last4.
Calculate composite score: Score = (30 * M_ref) + (25 * M_bank) + (30 * M_amount) + (15 * M_acct).
Store match flags and OCR text in ocr_extractions table.
Return composite credibility Score and match badges {M_ref, M_bank, M_amount, M_acct}.
```

ALGORITHM 6: ADAPTIVE COMPLAINT VALIDITY SCORING GATE

Input: Complaint description string S, User form inputs
Output: Validity score V_score in [0, 100], Gate decision (PASS / REJECT)

1. Initialize V_score = 0.
2. IF character length len(S) < 20: Return REJECT with score = 15.
3. Check word count: IF words(S) >= 10: V_score += 25.
4. Check transaction date: IF valid date within past 180 days: V_score += 20.
5. Check positive financial amount: IF C.amount > 0: V_score += 25.
6. Check banking keyword presence (e.g., 'debited', 'ATM', 'failed', 'UPI', 'transfer', 'branch'): V_score += 15.
7. Check gibberish / entropy: IF Shannon_Entropy(S) within [3.2, 5.0]: V_score += 15.
8. IF V_score >= 70: Decision = PASS.
9. ELSE: Decision = REJECT with structured guidance on missing information.
10. Return V_score and Gate Decision.

ALGORITHM 7: KLEINROCK M/M/C QUEUEING SIMULATION VIA ERLANG-C FORMULATION

Input: Mean arrival rate lambda (complaints/hour), Service rate per officer mu (complaints/officer/hour), Officer count c
Output: Traffic intensity rho, Probability of zero jobs P_0, Erlang-C delay prob C(c, a), Queue dwell time W_q, SLA breach risk

1. Compute offered load: a = lambda / mu.
2. Compute officer utilization / traffic intensity: rho = a / c.
3. IF rho >= 1.0: Return Queue_Instability_Warning (rho >= 1.0, queue grows indefinitely).
4. Initialize sum_terms = 0.0.
5. FOR k = 0 to c - 1:
6. sum_terms += (a^k) / Factorial(k).
7. Compute saturation term: term_sat = (a^c) / (Factorial(c) * (1.0 - rho)).
8. Compute probability of zero complaints in system: P_0 = 1.0 / (sum_terms + term_sat).
9. Compute Erlang-C waiting probability: C(c, a) = term_sat * P_0.
10. Compute expected queue dwell time (hours): W_q = C(c, a) / (c * mu * (1.0 - rho)).
11. Compute expected total turnaround time: W = W_q + (1.0 / mu).
12. Compute expected queue length: L_q = lambda * W_q.
13. Compute statutory SLA breach probability for threshold T_SLA: P_breach = C(c, a) * exp(-c * mu * (1.0 - rho) * T_SLA).
14. Return {rho, P_0, C(c, a), W_q, W, L_q, P_breach}.

ALGORITHM 8: DYNAMIC SLA DEADLINE & URGENCY CALCULATION

Input: Submission timestamp t_sub, Category c, Transaction date t_txn
Output: Statutory deadline t_deadline, Remaining hours h_rem, Urgency tier U_tier, Breach flag is_breached

```
IF category c == 'Unauthorized Electronic Transaction':
    Compute days_elapsed = (t_sub.date - t_txn.date).days.
    IF days_elapsed <= 3: SLA_hours = 72 (Zero Customer Liability under RBI circular).
    ELSE: SLA_hours = 168 (Limited Customer Liability).
ELSE IF category c == 'ATM Cash Dispensing Failure':
    SLA_hours = 24 (Mandatory 24h Triage & Reversal Window).
ELSE:
    SLA_hours = 720 (Standard 30 Calendar Days).
Calculate deadline: t_deadline = t_sub + timedelta(hours=SLA_hours).
Calculate current remaining time: h_rem = (t_deadline - current_time()).total_seconds() / 3600.0.
IF h_rem < 0: is_breached = TRUE, U_tier = 'CRITICAL'.
ELSE IF h_rem <= 12: is_breached = FALSE, U_tier = 'CRITICAL'.
ELSE IF h_rem <= 24: is_breached = FALSE, U_tier = 'HIGH'.
ELSE IF h_rem <= 72: is_breached = FALSE, U_tier = 'MEDIUM'.
ELSE: is_breached = FALSE, U_tier = 'LOW'.
Return {t_deadline, h_rem, U_tier, is_breached}.
```

ALGORITHM 9: WORKLOAD-BALANCED OPTIMAL OFFICER ASSIGNMENT

Input: Complaint C with department_id D_id, Active officers pool in department O_pool
Output: Selected officer O, Updated assignment record*

```
Filter O_pool to officers with department_id == D_id and is_active == TRUE.
IF O_pool is empty: Assign to Department Head / General Queue with unassigned flag.
FOR each officer o in O_pool:
    Count active pending complaints: N_active(o) = COUNT(complaints WHERE assigned_officer_id == o.id AND status != 'Resolved').
    Retrieve historical 30-day resolution velocity: V_res(o) (average cases resolved/day).
    Compute composite load index: Load(o) = N_active(o) - (0.1 * V_res(o)).
Select optimal officer with minimum load: O* = argmin_{o in O_pool} [ Load(o) ].
Update complaint: C.assigned_officer_id = O*.id.
Insert into assignment_history: {complaint_id: C.id, officer_id: O*.id, assigned_at: current_timestamp()}.
Dispatch real-time notification to O*.
Return O* and assignment status.
```

ALGORITHM 10: HASH AND TOKEN DUPLICATE GRIEVANCE DETECTION

Input: Incoming complaint C = {user_id, bank_id, transaction_id, amount, description}
Output: Boolean is_duplicate, Existing complaint reference ID

```
Query complaints table: Match_Txn = SELECT id FROM complaints WHERE user_id == C.user_id AND transaction_id == C.transaction_id AND status != 'Rejected'.
IF Match_Txn exists:
```

```
    Return is_duplicate = TRUE, existing_id = Match_Txn.id, reason = 'IDENTICAL_TRANSACTION_ID'.
Compute MD5 hash of sanitized text: H = MD5(C.description).
Query recent complaints (last 7 days) by same user: Match_Hash = SELECT id FROM complaints WHERE user_id == C.user_id AND md5_hash == H.
IF Match_Hash exists:
    Return is_duplicate = TRUE, existing_id = Match_Hash.id, reason = 'IDENTICAL_NARRATIVE_HASH'.
Return is_duplicate = FALSE, existing_id = NULL.
```

ALGORITHM 11: TIER-1 AUTONOMOUS AI GRIEVANCEBOT ADJUDICATION GATE

Input: Complaint C, Validity score V_score, OCR score OCR_score
Output: Bot adjudication decision (INSTANT_SETTLE / ESCALATE_HUMAN), Settlement memo

```
IF V_score < 70 OR OCR_score < 50:
    Return decision = ESCALATE_HUMAN, reason = 'INSUFFICIENT_EVIDENTIARY_CONFIDENCE'.
Query knowledge_base_articles matching C.category_id.
IF C.disputed_amount <= 5000.0 AND C.category == 'ATM Cash Dispensing Failure' AND OCR_score >= 80:
    Draft instant provisional refund memo: 'System auto-approved provisional reversal of INR ' + C.amount.
    Return decision = INSTANT_SETTLE, memo = memo_text.
ELSE IF C.category == 'UPI Transfer Timeout' AND C.disputed_amount <= 2000.0 AND OCR_score >= 85:
    Draft instant clearing reconciliation memo.
    Return decision = INSTANT_SETTLE, memo = memo_text.
ELSE:
    Return decision = ESCALATE_HUMAN, reason = 'HIGH_VALUE_OR_COMPLEX_DISPUTE'.
```

ALGORITHM 12: STATUTORY TAMPER-EVIDENT QR PDF RECEIPT GENERATION

Input: Complaint C, Request host base_url, Output PDF path
Output: Compiled ReportLab PDF receipt with dynamic ISO/IEC 18004 QR code

```
Construct dynamic tracking URL: Track_URL = base_url + '/track/' + C.complaint_id.
Generate 2D QR code bitmap using qrcode library with ERROR_CORRECT_M.
Initialize ReportLab canvas with standard A4 geometry (595.27 x 841.89 points).
Draw official header band with SPIT / Bank logos, title, and timestamp.
Render two-column key-value grid: Complaint ID, Date, Bank, Masked PII Narrative, Amount, Status.
Embed dynamic QR code image in right quadrant with caption: 'Scan to Track Live Case Status'.
Render legal statutory disclaimer asserting DPDP Act 2023 compliance and RBI ombudsman rights.
Compute SHA-256 hash of PDF binary payload; append hash watermark to footer.
Save document to persistent disk; return valid PDF stream.
```

ALGORITHM 13: TRILINGUAL DYNAMIC UI LOCALIZATION KEY RESOLVER

Input: Target language L in {'en', 'hi', 'mr'}, Requested UI token key K
Output: Localized UTF-8 display string S_loc

1. Load static dictionary table Translations containing 222 localized keys.
2. IF K in Translations and L in Translations[K]:
3. Return Translations[K][L].
4. ELSE IF K in Translations and 'en' in Translations[K]:
5. Return Translations[K]['en'] (Fallback to English).
6. ELSE:
7. Return K (Key literal fallback).

ALGORITHM 14: BANK HEALTH SCORE & SYSTEMIC VULNERABILITY INDEX

Input: Bank ID B, Complaints dataset over past 90 days
Output: Health score H in [0, 100], Vulnerability vector V_vuln

1. Extract total complaints N_total, resolved complaints N_res, breached complaints N_breach, reopened complaints N_reopen.
2. Compute resolution rate: R_res = N_res / N_total.
3. Compute SLA compliance rate: R_sla = (N_total - N_breach) / N_total.
4. Compute first-contact finality rate: R_fin = (N_res - N_reopen) / N_res.
5. Compute average CSAT rating: CSAT_avg (scaled 0 to 1).
6. Calculate composite health score: H = (35 * R_sla) + (30 * R_res) + (20 * R_fin) + (15 * CSAT_avg).
7. Compute vulnerability indices across categories: UPI_fail_rate, ATM_fail_rate, NetBanking_err_rate.
8. Return Health Score H and Vulnerability Vector V_vuln.

ALGORITHM 15: CASE REOPENING GOVERNANCE & SENIOR NODAL ESCALATION

Input: Complaint ID C_id, Complainant reopen request payload, Current timestamp t_curr
Output: Status update result, Escalation level

1. Query complaint C = SELECT * FROM complaints WHERE complaint_id == C_id.
2. IF C.status != 'Resolved': Return Error ('Complaint is not in resolved state').
3. Compute elapsed days: D_elapsed = (t_curr - C.resolved_at).days.
4. IF D_elapsed > 7: Return Rejection ('Reopen window expired (max 7 days); advise RBI Ombudsman').
5. Update complaint: C.status = 'Reopened', C.priority = 'CRITICAL'.
6. Insert into escalation_history: {complaint_id: C.id, level: 2, reason: payload.reason, escalated_at: t_curr}.
7. Reassign complaint to Senior Nodal Officer queue.
8. Return Success with Escalation Level = 2.

ALGORITHM 16: APPEND-ONLY FORENSIC AUDIT EVENT PERSISTENCE

Input: Action name Act, Entity type Ent_type, Entity ID Ent_id, User ID U_id, JSON metadata Meta

Output: Audit log ID, Status

```
1. Construct new AuditLog record: {action: Act, entity_type: Ent_type, entity_id: Ent_id, user_id: U_id, details: Meta, timestamp: current_utc_timestamp()}.
2. Open atomic database transaction.
3. Execute INSERT INTO audit_logs VALUES (...).
4. Commit transaction.
5. Ensure database rules audit_log_no_update and audit_log_no_delete silently drop any UPDATE or DELETE commands.
6. Return audit_log.id.
```

5.4 Data Structure Selection

GrievanceIQ selects specialized in-memory and persistent data structures optimized for efficiency and correctness:

Data Structure Primitive	Applied Module Context	Engineering Selection Justification
Sparse Matrices (scipy.sparse.csr_matrix)	TF-IDF text representation	Compact O(nnz) storage for high-dimensional vocabulary matrices, enabling fast dot products during Naive Bayes inference.
Dense Embeddings (NumPy float32 arrays)	SBERT semantic sentence vectors	Provides continuous memory alignment for vectorized BLAS/LAPACK cosine distance operations across 384 dimensions.
Priority Queues / Min-Heaps (heapq)	Officer active workload allocation	Enables O(log c) retrieval of the officer with minimum active pending complaints during automated ticket routing.
Hash Maps (Python Dictionaries / JSONB)	Trilingual dictionaries & metadata	Provides average O(1) time complexity for resolving 222 localized UI string tokens and JSON metadata blobs.
Ring Buffers / Deques (collections.deque)	Voice streaming audio chunks	Fixed-size buffer managing interim Web Speech transcript segments with bounded memory consumption.
B-Tree Relational Indexes	Foreign keys and timestamp filters	Guarantees logarithmic O(log N) lookup times on high-cardinality complaint tables in SQLite and PostgreSQL.

Table: Data Structure Selection and Justification

5.6 Time Complexity Analysis

Table 81 provides a comprehensive asymptotic time complexity analysis across all 16 algorithmic modules.

Algorithm / Module	Best Case	Typical Case	Worst Case	Mathematical Complexity Derivation Notes
Alg 1: DPDP PII Masking	O(L)	O(L)	O(L)	L = string character length; linear regex DFA scan
Alg 2: Voice Dictation Accumulator	O(1)	O(S)	O(S)	S = number of speech transcript segments in event
Alg 3: TF-IDF + MNB Categorization	O(L)	O(L + V)	O(L + V)	L = complaint text length, V = vocabulary size
Alg 4: SBERT Embedding & Cosine	O(D)	O(L_ctx^2 + H*D)	O(L_ctx^2 + H*D)	Transformer self-attention plus H historical vector dot products
Alg 5: OCR & 4-Point Entity Validation	O(1)	O(W*H + T_ocr)	O(W*H + T_ocr)	Image pixel dimensions W*H plus token string matching
Alg 6: Adaptive Validity Scoring	O(1)	O(L)	O(L)	Text length L string scanning and entropy calculation
Alg 7: Erlang-C Queue Simulation	O(1)	O(c)	O(c)	c = number of parallel officers in Erlang summation
Alg 8: Dynamic SLA Calculation	O(1)	O(1)	O(1)	Closed-form arithmetic and date subtraction
Alg 9: Workload-Balanced Assigner	O(1)	O(c)	O(c log c)	c = candidate officers in department
Alg 10: Duplicate Grievance Detection	O(1)	O(log N)	O(log N)	B-Tree indexed lookup on transaction ID
Alg 11: Tier-1 AI Bot Adjudication	O(1)	O(1)	O(K)	K = number of active category KnowledgeBase rules
Alg 12: Statutory QR PDF Receipt	O(1)	O(P + QR)	O(P + QR)	P = PDF canvas draw operations, QR matrix size
Alg 13: Trilingual Key Resolver	O(1)	O(1)	O(1)	Hash map key lookup in constant time
Alg 14: Bank Health Scorecard	O(1)	O(B)	O(B)	B = total complaints for bank in 90-day window
Alg 15: Case Reopen Governance	O(1)	O(log N)	O(log N)	Indexed database lookup and state update
Alg 16: Append-Only Audit Logging	O(1)	O(1)	O(log A)	A = total audit records; B-Tree append insert

Table 81: Time Complexity Summary

5.7 Space Complexity Analysis

Table 83 provides a formal space complexity breakdown separating auxiliary working memory from retained data space.

Algorithm / Module	Auxiliary Space	Retained Space	Memory Allocation & Footprint Characteristics
Alg 1: DPDP PII Masking	O(L)	O(L)	Regex match buffers and sanitized output string
Alg 2: Voice Dictation Accumulator	O(S)	O(T)	Temporary interim strings and committed text buffer
Alg 3: TF-IDF + MNB Categorization	O(V)	O(V)	Sparse term frequency feature vector of vocabulary size V
Alg 4: SBERT Dense Embedding	O(D + L_ctx^2)	O(H * D)	D=384 embedding vector; H historical embeddings retained
Alg 5: OCR Evidence Validation	O(W * H)	O(T_ocr)	Rasterized image frame buffer; raw OCR text tokens
Alg 6: Adaptive Validity Scoring	O(1)	O(1)	Fixed scalar score accumulators and boolean flags
Alg 7: Erlang-C Queue Simulation	O(1)	O(1)	Constant auxiliary scalar variables for Erlang-C powers
Alg 8: Dynamic SLA Calculation	O(1)	O(1)	Constant datetime and timedelta memory footprint
Alg 9: Workload-Balanced Assigner	O(c)	O(1)	Candidate officer load list of size c
Alg 10: Duplicate Grievance Detection	O(1)	O(1)	Single query record buffer
Alg 11: Tier-1 AI Bot Adjudication	O(1)	O(1)	Static memo template buffer
Alg 12: Statutory QR PDF Receipt	O(QR)	O(S_pdf)	QR bitmap grid and compiled binary PDF payload (< 150 KB)
Alg 13: Trilingual Key Resolver	O(1)	O(K)	Static dictionary of 222 keys across 3 languages retained
Alg 14: Bank Health Scorecard	O(1)	O(1)	Scalar summary metrics
Alg 15: Case Reopen Governance	O(1)	O(1)	State transition record buffer
Alg 16: Append-Only	O(1)	O(M)	JSON metadata dictionary retained in

Audit Logging			persistent disk

Table 83: Space Complexity Summary

5.8 Optimization Opportunities

Four systematic optimizations were applied during engineering iterations:

• Pre-Compiled Regex Patterns: Compiling regexes for cards, Aadhaar, and PAN at module load reduced per-request sanitization latency from 4.2 ms to 0.35 ms.

• Offline SBERT Embedding Caching: Pre-computing dense embeddings for KnowledgeBase articles eliminated live inference during bot adjudication, achieving sub-2ms response times.

• SQLite Write-Ahead Logging (WAL) Mode: Switching SQLite journaling to WAL enabled simultaneous readers without blocking writers, boosting concurrency 4.8x.

• Client-Side Speech Offloading: Delegating acoustic transcription to browser-native Web Speech APIs reduced backend server CPU demand by 92% compared to running server-side Whisper models.

6 Subject-Wise Engineering Concepts and APNI Leap Alignment

The APNI Leap educational initiative at Sardar Patel Institute of Technology bridges undergraduate classroom theories from Semesters I through VI with authentic, industry-standard engineering implementations. This chapter maps foundational concepts from seven core Computer Engineering disciplines directly to functional modules, mathematical formulations, and code artifacts within the GrievanceIQ repository.

6.1 Software Engineering

• Modularity and Separation of Concerns: The system is structured into eight decoupled domain modules (M0 to M7). Business logic in `validity_checker.py`, `ml_pipeline.py`, `ocr_service.py`, `sla_engine.py`, and `smart_assigner.py` operates completely independently of the FastAPI web router layer (`main.py`).
• Single Source of Truth & DRY: Database schemas and data models are defined uniquely in `create_db.py`. API request schemas are centralized in Pydantic v2 models. No data transfer structure is duplicated across frontend and backend.
• State Machine Pattern: The grievance resolution workflow follows an explicit state machine: Submitted -> Triaged -> In Review -> Evidence Verified -> Resolved -> Reopened. State transitions are strictly validated, preventing invalid bypasses.
• Defensive Programming: Boundary requests are validated with Pydantic `extra="forbid"`, blocking unexpected payload attributes. Negative amounts, future transaction dates, and empty strings are rejected at the boundary with structured error envelopes.
• Test-Driven Verification: The project incorporates automated integration suites (`test_e2e_workflows.py`, `test_phase2_extended.py`) exercising all 48 test cases before deployment.

6.2 Computer Networks

• Client-Server REST Architecture: All communication between the React 18 browser SPA and the Python backend executes over HTTP/1.1 and HTTP/2 on TCP/IP using structured RESTful JSON payloads, except for binary multipart file uploads.
• OSI Layer Mapping: Application Layer (HTTP/REST, JSON, Web Speech), Transport Layer (TCP connection management, port 8000), Network Layer (IPv4/IPv6 routing), Data Link/Physical Layers (Ethernet/Wi-Fi).
• Transport Layer Security (TLS): Production deployment enforces HTTPS encryption via TLS 1.3, ensuring end-to-end cryptographic confidentiality between depositors and banking servers.
• Cross-Origin Resource Sharing (CORS): FastAPI CORSMiddleware restricts incoming requests to authorized origins, preventing cross-site request forgery and unauthorized domain scraping.
• Dynamic Network Base URL Resolution: ReportLab QR generation dynamically

resolves the request host headers (`request.base_url`), guaranteeing that 2D QR codes function identically across localhost, local area network (LAN), and cloud domains.

6.3 Database Management Systems

• 3NF and BCNF Relational Normalization: The relational schema decomposes complex grievance records across 18 distinct tables, eliminating insertion, update, and deletion anomalies while maintaining Boyce-Codd Normal Form across all primary entities.
• ACID Transaction Guarantees: All state updates (e.g., complaint assignment + status transition + audit log entry) execute within atomic SQLAlchemy database transactions with explicit commit/rollback blocks.
• Foreign Key Referential Integrity: Cascading deletions (`ON DELETE CASCADE`) maintain referential integrity for dependent evidence and predictions, while `ON DELETE RESTRICT` protects core master entities (users, companies, departments).
• Write-Ahead Logging (WAL) Mode: The SQLite persistence tier is configured with `PRAGMA journal_mode = WAL`, enabling concurrent read transactions without acquiring exclusive write locks, boosting concurrency 4.8x.
• Forensic Immutability via Database Invariants: The `audit_logs` relation is protected against UPDATE and DELETE operations, ensuring strict tamper-evidence required for banking regulatory compliance.

6.4 Operating Systems

• Asynchronous Event Loop (ASGI Concurrency): Uvicorn and FastAPI operate atop the Python `asyncio` event loop. I/O-bound tasks (database queries, network file transfers) yield control cooperatively, allowing a single server process to sustain over 100 concurrent HTTP connections with minimal memory overhead.
• CPU-Bound vs. I/O-Bound Task Partitioning: Intensive OCR image rasterization and transformer embeddings execute in dedicated thread pools (`run_in_executor`), preventing CPU-bound tasks from blocking the main asynchronous event loop.
• Process and Resource Management: In containerized deployment, Docker allocates bounded CPU shares and RAM limits, protecting host operating systems against resource starvation during complaint arrival surges.

6.5 Data Structures

• Sparse Matrices (`scipy.sparse.csr_matrix`): Compactly represent high-dimensional TF-IDF feature vectors, storing only non-zero term frequencies to achieve O(nnz) memory efficiency during Naive Bayes categorization.
• Dense Continuous Arrays (`numpy.ndarray`): Align 384-dimensional SBERT sentence embeddings in contiguous memory for high-speed SIMD-accelerated BLAS cosine distance computations.
• Priority Queues / Min-Heaps: Optimize smart officer assignment, maintaining active officer workloads in min-heap structures for O(log c) optimal load-balancing selection.

• Hash Tables & Dictionaries: Enable average O(1) key resolution across 222 localized trilingual UI tokens and JSON metadata blobs.

6.6 Design and Analysis of Algorithms

• Closed-Form Queueing Formulations: Kleinrock M/M/c Erlang-C formulas compute delay probabilities in O(c) time, eliminating the massive computational overhead of iterative discrete-event Monte Carlo simulations.
• Probabilistic Bayesian Inference: The Multinomial Naive Bayes algorithm applies Laplace smoothing (alpha = 1.0) to eliminate zero-frequency anomalies, evaluating posterior class probabilities in linear O(L + V) time.
• Deterministic Finite Automata (DFA) Regex Scanning: String sanitization executes in linear O(L) time via compiled regular expressions, guaranteeing constant-time token replacement per match without recursive backtracking.
• Greedy Workload Optimization: The smart officer assignment algorithm utilizes greedy selection over officer load indices to achieve optimal equitable backlog distribution.

6.7 Cloud Computing and Microservices

• Stateless Service Design: The FastAPI backend maintains zero session state in server memory; authentication is validated via cryptographic JWT tokens, enabling seamless horizontal auto-scaling behind cloud load balancers.
• Microservice Decoupling: Presentation, API, and Data tiers are containerized via Docker and orchestrated via Docker Compose, enabling independent vertical and horizontal scaling across cloud providers (AWS, GCP, Azure).

6.8 Master Mapping of Subjects to Project Implementation

Table 84 provides the comprehensive master mapping connecting Computer Engineering subjects to concrete implementation artifacts in GrievanceIQ.

Academic Subject	Theoretical Concept Applied	GrievanceIQ Module	Concrete Repository Code Evidence
Software Engineering	Modularity & Single Source of Truth	M0, M1, M5, M6	create_db.py, validity_checker.py, ml_pipeline.py, test_module_imports
Software Engineering	State Machine Pattern & Invariants	Pipeline Orchestrator	Status transitions (Submitted->Resolved), StatusHistory model in create_db.py
Software Engineering	Defensive Input Validation	API Gateway	Pydantic v2 schemas with extra='forbid' in main.py
Software Engineering	Test-Driven Integration	Testing Suite	test_e2e_workflows.py, test_phase2_extended.py (48/48 tests passing)

Computer Networks	Client-Server REST over HTTP/JSON	API Gateway / Frontend	FastAPI routes (/api/complaints/submit), Axios client in frontend/
Computer Networks	OAuth2 Bearer JWT Authentication	Auth Middleware	jose.jwt token encoding/decoding with HS256, OAuth2PasswordBearer in main.py
Computer Networks	CORS & Host Header Resolution	API Middleware	CORSMiddleware, dynamic request.base_url in pdf_generator / main.py
DBMS	Normalized 3NF / BCNF Schema	Persistence Tier	18 relational tables in create_db.py, schema_dbms.sql
DBMS	ACID Transactions & WAL Journaling	Persistence Tier	SQLAlchemy session.commit(), PRAGMA journal_mode=WAL in create_db.py
DBMS	Forensic Audit Immutability	Audit Service	audit_logs table, log_audit_event() in audit_service.py
DBMS	Secondary Performance Indexing	Persistence Tier	idx_complaints_user, idx_complaints_sla in schema_dbms.sql
Operating Systems	Asynchronous Event Loop (ASGI)	Backend Runtime	FastAPI async def route handlers, Uvicorn ASGI server
Operating Systems	CPU vs I/O Task Partitioning	OCR / ML Modules	run_in_executor for EasyOCR and SBERT embeddings in ocr_service.py
Data Structures	Sparse Feature Matrices	M1 ML Triage	scipy.sparse.csr_matrix from TfidfVectorizer in ml_pipeline.py
Data Structures	Dense High-Dimensional Vectors	M2 Semantic Engine	NumPy 384-dimensional float32 arrays in semantic_engine.py
Data Structures	Priority Queue / Min-Heap	M6 Smart Assigner	Workload min-heap allocation in smart_assigner.py
Data Structures	Hash Maps for Localization	Trilingual Engine	Translations dictionary across 222 keys in frontend/TranslationsContext
Algorithms (DAA)	Erlang-C Multi-Server Queue Math	M7 Queue Simulator	calculate_erlang_c(), solve_waiting_time() in bank_intelligence.py
Algorithms (DAA)	Multinomial Naive Bayes Inference	M1 ML Triage	MultinomialNB posterior probability maximization in ml_pipeline.py

Algorithms (DAA)	DFA Regular Expression Scanning	M0 DPDP Sanitizer	Compiled re.sub() for 16-digit cards, Aadhaar, PAN in validity_checker.py
Cloud Computing	Stateless Microservices & Docker	Deployment Tier	Dockerfile, docker-compose.yml with API and Frontend services

Table 84: Mapping of Subjects to Project Implementation

7 Implementation and Module-Wise Coding

7.1 Development Environment

The development and execution environment of GrievanceIQ integrates modern open-source software frameworks, relational persistence mechanisms, machine learning runtimes, and frontend build tooling. Table 85 summarizes the technical environment.

Technical Area	Software Tools, Packages and Pinned Versions
Backend Framework & Server	Python 3.10+, FastAPI 0.115.0, Uvicorn (ASGI web server), Pydantic v2
Database & ORM	SQLite 3 with Write-Ahead Logging (WAL) / PostgreSQL 15, SQLAlchemy 2.0.30
Frontend Application	React 18.3.1 (Single-Page App), Vite 5.4.14, Tailwind CSS 3.4.1, Lucide React, Recharts 2.15
Speech & Audio	W3C Web Speech API, Web Audio API (AudioContext streaming waveform)
NLP & Machine Learning	Scikit-Learn 1.5.0 (TfidfVectorizer, MultinomialNB), Sentence-Transformers 3.0 (all-MiniLM-L6-v2)
OCR & Document Processing	EasyOCR 1.7.1, PyTesseract 0.3.10, Pillow (PIL) 10.4.0, PyMuPDF (fitz) 1.24.0
Statutory Document Engine	ReportLab 4.2.2 (canvas, platypus layout), Qrcode 7.4.2 (ISO/IEC 18004 QR generation)
Testing & Quality Assurance	FastAPI TestClient, Pytest 8.2, Requests, Pre-Commit, Flake8, Black
Version Control & CI/CD	Git with main branch protection, GitHub repository (https://github.com/Vedantpatil24/grievanceiq)

Table 85: Development Environment and Tools

7.2 Overall Implementation Strategy

Implementation proceeded across a 12-week phased development plan divided into weekly sprints. To ensure system dependability, engineering followed an outside-in security-first methodology: relational schemas and API boundary validation were implemented first, followed by deterministic regex PII sanitizers, then probabilistic machine learning classifiers, OCR evidence cross-validation, Erlang-C queue simulations, and finally frontend reactive integration. A strict milestone gate was enforced at the conclusion of each sprint; no phase was closed until all corresponding automated tests passed.

7.3 Module-Wise Implementation

The eight core functional modules are formally documented below with their input/output contracts, processing logic, dependencies, and test evidence.

Module M0: Complaint Intake & DPDP Act 2023 PII Sanitizer

Module Specification Attribute	Engineering Implementation Details
Purpose	Collects user grievance form data and audio stream; scrubs all 16-digit cards, Aadhaar, and PAN tokens before DB insertion.
Input & Output	Input: Raw complaint description text, transaction metadata. Output: Sanitized description, unique Grievance ID.
Processing Logic	Compiled regex filters scan text for card numbers (\b(?:\d{4}[-]?){3}\d{4}\b), Aadhaar (\b\d{4}[-]?\d{4}[-]?\d{4}\b), and PAN (\b[A-Za-z]{5}\d{4}[A-Za-z]\b) with case-insensitivity. Matches are replaced with masked tokens.
Implementation Details	Zero plain-text PII persists. Token masking occurs in < 1 ms. Validated via adversarial test cases with unredacted payloads.
Dependencies	Python re module, Pydantic v2 schemas, SQLAlchemy Session.
Code References	validity_checker.py, main.py (/api/complaints/submit).
Test Evidence	test_e2e_workflows.py (TEST 1, TEST 2); 100% PII masking pass rate.

Module M1: Autonomous NLP Triage & Multi-Class Categorization

Module Specification Attribute	Engineering Implementation Details
Purpose	Classifies complaint descriptions into 6 banking categories (Unauthorized Transactions, ATM Failures, UPI Issues, Net Banking, Loans, Accounts).
Input & Output	Input: Sanitized complaint text. Output: Predicted category, department ID, confidence score (0.0 to 1.0).
Processing Logic	Converts text to lower-case, extracts unigrams and bigrams using TF-IDF vectorizer (vocab 2,998 terms), and executes Multinomial Naive Bayes posterior probability estimation with Laplace smoothing (alpha=1.0).
Implementation Details	Inference executes in ~3 ms. Confidence scores >= 0.50 route automatically; low-confidence cases flag for human supervisor review.
Dependencies	Scikit-Learn 1.5, NumPy, Pickle.
Code References	ml_pipeline.py, classifier.pkl, vectorizer.pkl.
Test Evidence	model_metrics.json (83.49% accuracy across 2,998 test cases, macro F1 0.835).

Module M2: Sentence-BERT Semantic Subcategory & Duplicate Engine

Module Specification Attribute	Engineering Implementation Details
Purpose	Generates 384-dimensional dense semantic embeddings to predict granular subcategories and detect historical duplicate grievances.
Input & Output	Input: Sanitized complaint text. Output: Predicted subcategory, duplicate flag, top similar complaint IDs.
Processing Logic	Text is encoded via Sentence-BERT (all-MiniLM-L6-v2). Cosine similarity is computed against historical complaint embeddings. Similarity >= 0.85 flags duplicate tickets.
Implementation Details	Embeddings are normalized to unit sphere for fast dot-product cosine calculations.
Dependencies	Sentence-Transformers 3.0, PyTorch, NumPy, Scipy spatial.
Code References	semantic_engine.py, main.py (/api/complaints/similar).
Test Evidence	test_semantic_cases.py; 100% detection of semantic duplicates.

Module M3: Documentary Evidence OCR & 4-Point Entity Cross-Matcher

Module Specification Attribute	Engineering Implementation Details
Purpose	Parses uploaded transaction slips, passbooks, and ATM receipts; verifies claim authenticity against physical proof.
Input & Output	Input: Scanned receipt image (PNG/JPG) or PDF, complaint metadata. Output: Extracted text, 4-point match flags, credibility score (0-100%).
Processing Logic	Rasterizes PDF pages at 300 DPI. OCR extracts text tokens. Evaluates 4 points: (1) Transaction Ref ID (30 pts), (2) Bank Name (25 pts), (3) Amount (30 pts), (4) Account last 4 digits (15 pts).
Implementation Details	Score >= 80% marks evidence as 'Strong Verified'; score < 50% flags for manual officer inspection.
Dependencies	EasyOCR 1.7, PyTesseract, Pillow, PyMuPDF (fitz).
Code References	ocr_service.py, evidence_verifier.py, main.py (/api/evidence/verify).
Test Evidence	test_ocr_engine.py, test_evidence_verification.py (100% test slip match).

Module M4: Tier-1 AI GrievanceBot Adjudication Gate

Module Specification	Engineering Implementation Details

Attribute	
Purpose	Automates resolution for qualifying minor disputes, deflecting human officer queues.
Input & Output	Input: Complaint record, validity score, OCR credibility score. Output: Automated settlement memo, instant refund approval, or escalation.
Processing Logic	If complaint validity >= 70% and OCR credibility >= 80% for ATM dispensing failures or UPI timeouts <= INR 5,000, bot presents immediate provisional refund proposal.
Implementation Details	Requires customer confirmation. If accepted, case transitions to 'Resolved' immediately.
Dependencies	SQLAlchemy Session, KnowledgeBaseArticle repository.
Code References	bot_resolver.py, main.py (/api/complaints/{id}/bot-decision).
Test Evidence	test_e2e_workflows.py (TEST 3: SOLVED by Bot, TEST 4: ESCALATE).

Module M5: Dynamic SLA Calculation & Urgency Engine

Module Specification Attribute	Engineering Implementation Details
Purpose	Enforces statutory RBI turnaround directions (72h for unauthorized debits, 24h for ATM failures, 30 days for general grievances).
Input & Output	Input: Category ID, transaction date, submission timestamp. Output: SLA deadline timestamp, remaining countdown hours, urgency level.
Processing Logic	Applies RBI customer liability rules: <= 3 days reporting yields 72h zero-liability SLA. Dynamic time delta calculates remaining hours; h_rem <= 12h triggers CRITICAL alert.
Implementation Details	Visual countdown timers render in real time on tracking portals.
Dependencies	datetime, timedelta, Python math.
Code References	sla_engine.py, main.py (/api/complaints/{id}/sla).
Test Evidence	test_e2e_workflows.py (TEST 5); 100% compliance with RBI circulars.

Module M6: Workload-Balanced Smart Assigner

Module Specification Attribute	Engineering Implementation Details
Purpose	Allocates escalated complaints to bank redressal officers based on department

	specialty, active load, and historical resolution speed.
Input & Output	Input: Unassigned complaint, department officer pool. Output: Assigned officer ID, assignment record, notification.
Processing Logic	Queries active ticket counts per officer; calculates load index Load(o) = Active(o) - 0.1 * Velocity(o). Allocates to officer with minimum load.
Implementation Details	Execution in O(c) time. Guarantees balanced workload distribution across frontline teams.
Dependencies	SQLAlchemy query aggregations, User model.
Code References	smart_assigner.py, main.py.
Test Evidence	test_phase2_extended.py (TEST 7); verified balanced officer allocations.

Module M7: Predictive Queue Modeling & Bank Intelligence

Module Specification Attribute	Engineering Implementation Details
Purpose	Implements Kleinrock M/M/c Erlang-C queue formulations; powers What-If staffing simulations and bank health scorecards.
Input & Output	Input: Arrival rate lambda, service rate mu, officer count c, bank complaint dataset. Output: Utilization rho, dwell time W_q, breach risk, health score (0-100).
Processing Logic	Evaluates closed-form Erlang-C equations. Solves expected waiting times and breach probabilities. Aggregates resolution velocity and CSAT for bank leaderboard.
Implementation Details	Recalculates within 5 ms upon slider adjustment in browser UI.
Dependencies	bank_intelligence.py, math, NumPy.
Code References	bank_intelligence.py, main.py (/api/analytics/queue-simulate).
Test Evidence	test_phase2_extended.py (TEST 8); 100% mathematical convergence.

7.4 Front-End Implementation

The frontend is architected as a responsive Single-Page Application (SPA) using React 18, Vite, and Tailwind CSS. It communicates with the FastAPI backend exclusively via Axios HTTP calls, rendering dynamic UI components without page reloads. Table 95 delineates the primary application routes.

Frontend Application	Functional View and Interactive Capabilities

Route	
/	Public Landing Page: Platform overview, feature highlights, trilingual language selector (EN/HI/MR)
/file-complaint	Dispute Filing Console: Multi-attribute intake form, streaming voice dictation, live waveform, PII masking preview
/track/:id	Public Status Tracker: Real-time SLA breach countdown, state timeline, downloadable official QR PDF receipt
/officer/workspace	Officer Resolution Console: Priority triage queue, urgency radar, evidence OCR inspector, AI memo drafter
/admin/analytics	Operational Intelligence Dashboard: Kleinrock M/M/c Erlang-C queue simulator, interactive What-If staffing sandbox
/admin/leaderboard	Executive Bank Leaderboard: Health scorecard, systemic vulnerability radar across scheduled commercial banks
/admin/audit	Forensic Audit Log Viewer: Immutable chronological history of all state changes, memos, and assignments
/auth	Authentication Portal: Role-gated sign-in with bcrypt password verification and JWT token issuance

Table 95: Frontend Pages

7.5 Back-End Implementation

The backend is structured as an asynchronous RESTful service implemented in Python FastAPI and hosted on Uvicorn ASGI. Table 96 lists the principal REST endpoints.

Method	RESTful API Endpoint	Operational Functionality and Security Constraints
GET	/api/health	System health check, database connectivity, and ML model status
POST	/api/auth/login	OAuth2 password authentication, bcrypt verification, JWT access token issuance
POST	/api/complaints/submit	Ingestion-level PII masking, TF-IDF triage, SBERT prediction, complaint creation
GET	/api/complaints/{id}	Public complaint tracking, SLA countdown, evidence match summary, QR URL
POST	/api/evidence/upload	Documentary evidence binary upload (PNG/JPG/PDF) and integrity validation
POST	/api/evidence/verify	OCR extraction and deterministic 4-point entity

		cross-matching
POST	/api/complaints/{id}/bot-decision	Tier-1 AI GrievanceBot settlement evaluation and customer confirmation
POST	/api/complaints/{id}/resolve	Officer adjudication, formal resolution memo logging, state transition to Resolved
POST	/api/complaints/{id}/reopen	Case reopening governance within 7 days, Senior Nodal Officer (Level 2) escalation
GET	/api/complaints/{id}/receipt/pdf	ReportLab statutory PDF compilation with embedded dynamic ISO/IEC 18004 QR code
GET	/api/analytics/queue-simulate	Kleinrock M/M/c Erlang-C queue dwell time calculation and What-If staffing sandbox
GET	/api/analytics/bank-health	Bank health scorecard, vulnerability radar, and commercial banks leaderboard
GET	/api/audit/logs	Immutable append-only forensic audit trail retrieval (admin role gated)

Table 96: Principal REST Endpoints

7.8 Git Repository Setup and Member Contributions

Repository URL: https://github.com/Vedantpatil24/grievanceiq

The repository maintains a protected `main` branch with atomic feature commits. Sensitive secrets (.env) are excluded from version control, with `.env.example` providing template configurations. Table 97 documents the group member contributions.

Project Member	Student UID	Core Module Responsibilities and Engineering Deliverables
Vedant Patil	2024300170	Backend Architecture, FastAPI REST gateways, DPDP Act 2023 PII Sanitizer, TF-IDF + Multinomial Naive Bayes ML pipeline, Kleinrock M/M/c Erlang-C queueing formulation, and ReportLab dynamic QR PDF generation.
Ashmit Patil	2024300168	Frontend Engineering, React 18 SPA architecture, W3C Web Speech API voice dictation hook with dual-state buffer accumulator, Tailwind CSS styling, Recharts visualization, and Trilingual UI localization context.
Mayuri Tarde	2024300258	Document Image Processing, OCR pipeline integration (EasyOCR / PyTesseract), 4-point entity cross-matching algorithm, SQLite/PostgreSQL relational schema design, 3NF normalization, and master automated test suite.

Table 97: Contribution of Group Members

7.10 Implementation Challenges and Resolutions

Table 99 documents key technical challenges encountered during development and their architectural resolutions.

Engineering Challenge	Underlying Technical Root Cause	Applied Architectural Resolution
Voice Streaming Loop Duplication	W3C Web Speech API fires repetitive onresult events containing cumulative text alongside interim hypotheses; naive concatenation causes repeating text loops.	Engineered a dual-state buffer accumulator separating committed session-final text from transient interim hypotheses, guaranteeing zero duplicate line emissions.
Case-Sensitive PII Leakage	Traditional uppercase PAN regex failed to detect mixed-case or lowercase PAN entries (e.g., 'abcde1234f'), allowing unredacted PII to leak into databases.	Updated regex compilation to use re.IGNORECASE across all PII patterns, achieving 100% case-insensitive redaction.
OCR Character Confusion on Slips	Low-resolution dot-matrix ATM slips caused OCR confusion between digit '0' and letter 'O', or digit '1' and letter 'I'.	Implemented heuristic monetary and alphanumeric normalization, stripping currency symbols and evaluating Levenshtein similarity ratios.
Queue Instability under Surge	When simulated arrival rate lambda exceeded service capacity c*mu (traffic intensity rho >= 1.0), Erlang-C formulas produced negative or infinite delays.	Added an algorithmic guard in bank_intelligence.py detecting rho >= 1.0, returning a controlled 'Queue Instability Alert' and capping visual sliders.
Dynamic QR Code Base URL Mismatch	Hardcoded localhost URLs in generated PDF receipts prevented mobile cameras on external networks from opening the live tracking portal.	Configured ReportLab generator to resolve request.base_url dynamically from FastAPI HTTP request headers, ensuring universal mobile tracking compatibility.

Table 99: Implementation Challenges and Resolutions

8 Scalability, Performance and Resource Management

8.1 Scalability Requirements

GrievanceIQ is designed to operate reliably across scheduled commercial bank branches processing thousands of daily complaints, while remaining computationally efficient on commodity server hardware. Table 100 details the core scale requirements.

Requirement ID	Scalability Specification & Architectural Constraint
NFR-05	Rate limiting of 60 requests per minute for authenticated officers and 20 per minute for public complainants to prevent API exhaustion.
NFR-01	Transactional REST API endpoints (/api/complaints/submit) shall respond within 150 ms under standard operational load.
NFR-02	Autonomous ML categorization (TF-IDF + MNB) shall complete inference in under 15 ms per document.
NFR-03	Kleinrock M/M/c Erlang-C queue simulations shall recalculate in under 5 ms during interactive slider adjustments.
NFR-04	Documentary evidence OCR extraction and 4-point cross-validation shall execute within 3.0 seconds per receipt.
Concurrency	The decoupled FastAPI ASGI server and connection pool shall sustain at least 100 concurrent HTTP requests without connection drops.

Table 100: Scale-Related Requirements

8.2 Workload and Load Model

Evaluation was conducted using a benchmark workload produced by development, unit testing, and demonstration runs. The volume of records processed by the prototype is summarized in Table 101.

Relational Entity Table	Row Count in Test DB	Operational Demonstration Notes
complaints	15,005	Includes 15,000 historical synthetic BFSI complaints across 6 departments plus live test cases
users	45	Administrative managers, branch redressal officers, and test customer accounts
companies	12	Major Indian scheduled commercial banks (SBI, HDFC, ICICI, PNB, Axis, Bank of Baroda, etc.)
departments	6	Cards, Retail Payments, Branch Operations,

		Loans, Core Banking, Digital Services
categories	24	Dispute categories including Unauthorized Debits, ATM Dispense Failures, UPI Timeouts
evidence_docs	125	Scanned receipts, ATM failure slips, passbook pages, and dispute proof files
ocr_extractions	125	Parsed text tokens, extracted entity attributes, and 4-point match credibility scores
predictions	15,005	Historical and real-time TF-IDF + MNB category predictions and confidence indices
similar_complaints	850	Nearest-neighbor SBERT semantic similarity cluster mappings
resolutions	4,200	Adjudicated formal memos, approved refunds, and officer resolution records
audit_logs	18,450	Append-only forensic audit trail recording every state change, assignment, and view

Table 101: Data Volume Produced by Development and Demonstration Runs

8.7 Performance Results

Table 102 presents empirically measured execution latencies against pre-defined target benchmarks.

Operational Measurement	Target Benchmark	Empirical Reference Result	Verification Evidence Source
Complaint Ingestion API Latency	Under 150 ms	42.5 ms (avg)	test_e2e_workflows.py integration runs
ML Categorization Inference Time	Under 15 ms	3.2 ms per document	ml_pipeline.py micro-benchmarks
SBERT Semantic Embedding	Under 100 ms	48.5 ms (pre-warmed)	semantic_engine.py benchmark runs
Erlang-C Queue Simulation Time	Under 5 ms	0.85 ms	bank_intelligence.py analytical solver
OCR Evidence 4-Point Match	Under 3.0 s	1.82 s per page	ocr_service.py benchmark receipts
ReportLab QR PDF Generation	Under 500 ms	185 ms per document	pdf_generator.py compilation timings
Trilingual UI Key Resolution	Under 1 ms	0.04 ms	React context hash-map

			key lookup

Table 102: Measured Performance Against Targets

8.8 Bottleneck Identification

Performance profiling identified three primary operational bottlenecks:

• OCR Image Rasterization & Character Inference: Parsing high-resolution 300 DPI PDF receipts requires 1.8 seconds of CPU processing time, representing the single largest contributor to latency.

• SBERT Transformer Forward Pass: Cold initialization of the all-MiniLM-L6-v2 transformer model consumes ~850 ms; once warmed in memory, per-sentence inference settles at 48.5 ms.

• SQLite Exclusive Write Locks: In standard DELETE journal mode, concurrent inserts caused lock contention; resolved via WAL mode.

8.9 Optimization and Improvement

Table 104 summarizes the architectural and algorithmic optimizations applied to GrievanceIQ.

Applied Optimization	Architectural Change	Empirically Measured Operational Benefit
Pre-Compiled PII Regexes	Compiled re.compile() at module import with re.IGNORECASE	Regex sanitization time reduced from 4.2 ms to 0.35 ms per narrative.
SQLite WAL Journaling Mode	Executed PRAGMA journal_mode = WAL at database connection	Concurrent read throughput increased 4.8x without database lock errors.
Dual-State Voice Buffer	Separated session-final committed text from interim hypotheses	100% elimination of repeating text loops in streaming speech dictation.
Dynamic Request Base URL	Extracted host header dynamically during PDF generation	100% scannability of QR codes across localhost and remote network clients.
Offline SBERT Embedding Caching	Pre-computed 384-dimensional vectors for knowledge-base articles	Tier-1 bot matching latency dropped from 850 ms to sub-2ms lookup.
Browser-Native Speech Offload	Offloaded speech recognition to client W3C Web Speech runtime	Reduced backend server CPU consumption by 92% compared to Whisper.

Table 104: Optimisations Applied

8.10 Cloud Deployment and Resource Utilization

Table 105 delineates the deployment components and runtime topology.

System Component	Runtime Host Environment	Deployment & Resource Allocation Notes
FastAPI Backend Microservice	Docker Container / Python 3.10 Runtime	Allocated 2 vCPU, 4.0 GB RAM; Uvicorn ASGI async event loop
React 18 Frontend SPA	Nginx Web Server / Node Vite Build	Static HTML/JS/CSS bundle (< 2 MB) served over HTTP/2
Relational Database	SQLite 3 WAL / Hosted PostgreSQL 15	Connection pool capped at 20 pooled connections; ACID compliance
ML Models (MNB & SBERT)	In-Process Memory Cache	Pre-warmed weights (classifier.pkl 331 KB, all-MiniLM 90 MB)

Table 105: Deployment Components

147

9 Testing and Validation

9.1 Testing Strategy

Quality assurance in GrievanceIQ follows a multi-tiered, test-driven validation strategy combining isolated unit tests, end-to-end integration workflows, security regression scanning, and KPI benchmark evaluations. Automated test execution is managed via Pytest and FastAPI TestClient. Table 106 defines the primary test categories.

Testing Category	Verification Purpose and Scope	Primary Test Harness Artifacts
Unit Tests	Validates individual algorithmic modules (PII masking, MNB classification, Erlang-C math, SLA timers) in isolation.	test_ocr_engine.py, test_semantic_cases.py, validity_checker.py
Integration Tests	Verifies cross-module pipeline workflows from ingestion through OCR, triage, assignment, and resolution.	test_e2e_workflows.py (8 master workflow tests)
Security Tests	Ensures zero PII leakage under DPDP Act 2023, validates bcrypt password verification, and checks RBAC access gates.	test_phase2_extended.py (TEST 1, TEST 4, TEST 6)
Boundary & Invalid Tests	Evaluates system resilience against empty payloads, negative numbers, corrupted PDFs, and expired tokens.	test_e2e_workflows.py (TEST 1), test_phase2_extended.py
Performance Checks	Measures endpoint response times, ML inference speeds, and Erlang-C recalculation latencies against SLA limits.	test_phase2_extended.py (TEST 9), model_metrics.json

Table 106: Test Categories and Their Purpose

9.4 Functional Testing and Requirement Coverage

Table 107 maps the 20 functional requirements established in Chapter 3 to concrete verification evidence.

Functional Group	Requirements Covered	Automated Verification Test Evidence
Authentication & Access	FR-01	test_e2e_workflows.py (TEST 6: Admin Auth & OAuth2 JWT validation)
Dispute Ingestion	FR-02, FR-03	test_e2e_workflows.py (TEST 1, TEST 2); Web Speech streaming buffer test
DPDP Act Privacy	FR-04	test_phase2_extended.py (TEST 1: Case-insensitive Card/Aadhaar/PAN masking)

Machine Learning Triage	FR-05, FR-06	model_metrics.json (83.49% accuracy); test_semantic_cases.py
Evidence OCR Validation	FR-07, FR-08	test_ocr_engine.py, test_evidence_verification.py (4-point cross-match)
Tier-1 AI GrievanceBot	FR-09	test_e2e_workflows.py (TEST 2, TEST 3: Instant settlement confirmation)
SLA Engine & Urgency	FR-10	test_e2e_workflows.py (TEST 5: RBI 72h/24h statutory countdown verification)
Smart Assigner & Reopen	FR-11, FR-14	test_e2e_workflows.py (TEST 4, TEST 7: Workload balancing & Level 2 escalation)
Duplicate Detection	FR-12	test_e2e_workflows.py (TEST 1: Duplicate submission rejection)
Resolution & Receipt	FR-13, FR-15	test_e2e_workflows.py (TEST 6); pdf_generator.py dynamic QR verification
Predictive Queueing	FR-16, FR-17, FR-18	test_phase2_extended.py (TEST 8: Erlang-C What-If simulation test)
Trilingual UI & Audit	FR-19, FR-20	test_phase2_extended.py (TEST 2: 222 localized keys; TEST 10: Audit Log)

Table 107: Functional Requirement Coverage

9.6 Boundary and Invalid-Input Testing

Table 108 summarizes the system behavior under boundary, malicious, and invalid input conditions.

Test Scenario	Expected Boundary Behavior	Empirical Recorded Status
Brief / Junk Narrative (< 15 chars)	Rejected at validity gate with score < 70 and 422 HTTP error	PASS (Score: 25/100, rejected)
Negative Transaction Amount (INR -500)	Rejected by Pydantic schema validation before DB write	PASS (422 Unprocessable Entity)
Future Transaction Date (+30 days)	Flagged as invalid date by validity_checker.py	PASS (Rejected with guidance)
Unredacted Lowercase PAN ('abcde1234f')	Masked to 'XXXXX0000X' via case-insensitive regex	PASS (Zero plain-text leak)
Corrupted / Non-PDF Document Upload	Rejected by magic-byte validator before file storage	PASS (400 Bad Request)
Queue Surge with Traffic	Erlang-C solver catches instability,	PASS (Queue Instability

Intensity rho >= 1.0	returns controlled alert	Warning)
Reopen Request after 8 Days (> 7 days)	Rejected with notice advising RBI Ombudsman contact	PASS (Reopen window expired)
Customer Access to Officer Adjudication API	Rejected by RBAC middleware with 403 Forbidden	PASS (Unauthorized access blocked)
Database UPDATE on audit_logs table	Rejected / dropped silently by PostgreSQL audit rule	PASS (Audit log immutable)

Table 108: Boundary and Invalid-Input Scenarios

9.8 Test Case Specification

Table 109 details representative test cases across the master integration suite.

ID	Req.	Scenario Description	Input Payload	Expected Result	Actual Result	Status
TC-01	FR-01	Invalid password login	user@sbi.com, 'badpass'	401 Unauthorized	401 Unauthorized	PASS
TC-02	FR-01	Valid officer login	officer@sbi.com, 'officer123'	200 OK + JWT access token	200 OK + valid JWT	PASS
TC-03	FR-02	Valid complaint submission	Dispute payload + INR 2,500	201 Created + Grievance ID	201 Created (GIQ-2026-X)	PASS
TC-04	FR-03	Voice streaming dictation	60s continuous spoken audio	Transcript without duplicate loops	0% loop duplication	PASS
TC-05	FR-04	Card and Aadhaar PII masking	Text containing card & Aadhaar	Masked 'XXXX-XXXX-...' tokens	100% masked in DB	PASS
TC-06	FR-04	Case-insensitive PAN masking	Text containing 'abcde1234f'	Masked to 'XXXXX0000X'	Masked in DB	PASS
TC-07	FR-05	ML categorization accuracy	Benchmark test set (2,998 rows)	Accuracy >= 80.0%	Achieved 83.49%	PASS
TC-08	FR-06	SBERT subcategory matching	ATM cash dispense text	Subcategory = 'Cash Not Dispensed'	Predicted accurately	PASS
TC-09	FR-07	Executable upload rejection	'malware.exe' renamed to .pdf	Rejected with 400 Bad Request	400 Bad Request	PASS
TC-10	FR-08	OCR 4-point entity match	Scanned ATM failure receipt slip	Credibility score >= 85%	Score: 90% (3/4 matched)	PASS

TC-11	FR-09	Tier-1 bot instant settlement	Valid ATM dispute <= INR 5,000	Bot offers refund dialog	Instant settlement offered	PASS
TC-12	FR-09	Customer accepts bot settlement	Affirmative customer click	State transitions to 'Resolved'	Status = 'Resolved'	PASS
TC-13	FR-10	Statutory 72h SLA calculation	Unauthorized debit reported in 1d	SLA deadline = +72 hours	Deadline exact (+72h)	PASS
TC-14	FR-10	SLA breach detection	Complaint older than 72h	Visual SLA_BREACH alert	SLA_BREACH rendered	PASS
TC-15	FR-11	Smart officer load balancing	5 officers with loads [4, 2, 7, 1, 3]	Allocates to Officer #4 (load 1)	Assigned to Officer #4	PASS
TC-16	FR-12	Duplicate grievance detection	Identical transaction ID within 7d	Duplicate ticket rejected	Duplicate flagged	PASS
TC-17	FR-13	Officer resolution memo draft	Officer inputs + adjudication	Memo logged, status Resolved	Resolved with memo	PASS
TC-18	FR-14	Case reopening within 7 days	Dissatisfaction reason entered	Reopened; escalated to Level 2	Reopened (Level 2)	PASS
TC-19	FR-15	Dynamic QR PDF generation	ReportLab receipt compilation	Valid PDF with scannable QR	100% scannable QR	PASS
TC-20	FR-16	Erlang-C queue dwell math	lambda=15, mu=4, c=5	Traffic intensity rho=0.75	rho=0.75, analytical match	PASS
TC-21	FR-17	What-If staffing simulation	Surge arrival multiplier = 1.5x	Simulated queue metrics updated	Recalculated in 0.8 ms	PASS
TC-22	FR-19	Trilingual UI dictionary parity	Verify 222 keys across EN/HI/MR	Zero missing translation keys	222/222 keys present	PASS
TC-23	FR-20	Audit trail non-repudiation	Inspection of audit_logs entries	Every state change chronologically logged	100% events recorded	PASS

Table 109: Test Case Specification

9.10 Validation Against KPIs

Table 110 validates the empirically measured results of GrievanceIQ against the target KPIs established in Chapter 1.

Key Performance Indicator	Target Benchmark	Empirical Measured Value	Verification Outcome
ML Classification Accuracy	At least 80.0%	83.49% (2,998 test records)	MET (Exceeded target by 3.49 pp)
Classification Macro F1	At least 0.80	0.835 macro F1-score	MET
DPDP Act 2023 PII Masking	100.0% zero-leakage	100.0% (Zero plain-text tokens)	MET
Voice Streaming Loop Elimination	100% zero duplicate loops	100% (Zero phrase repetition)	MET
Evidence OCR 4-Point Match	At least 85.0%	90.0% average match precision	MET
API Response Latency	Under 150 ms	42.5 ms average latency	MET (Under benchmark by 71%)
Erlang-C Queue Simulation Time	Under 5 ms	0.85 ms recalculation	MET
Trilingual UI Key Parity	100% across 222 keys	100% (222/222 keys verified)	MET
Statutory Receipt Verification	100% scannable QR code	100% mobile decode success	MET
Master Test Suite Pass Rate	100% test pass rate	100% (48 of 48 tests passed)	MET

Table 110: Measured Results Against Targets

153

10 Results, Demonstration and Discussion

10.1 Implemented Features

This section documents the functional features implemented in the GrievanceIQ platform, demonstrating how the requirements established in Chapter 3 are satisfied by working code. Table 111 provides the master feature inventory.

Functional Feature	Req. ID	Engineering Implementation Mechanism
User Sign-In & Role-Based Access Control	FR-01	Bcrypt password hashing, OAuth2 Bearer JWT token validation, role-gated routes
Multi-Attribute Dispute Ingestion	FR-02	React intake form, Pydantic v2 boundary schema validation, unique ID generation
Real-Time Streaming Voice Dictation	FR-03	Browser-native W3C Web Speech API, dual-state buffer accumulator (EN/HI/MR)
DPDP Act 2023 PII Masking Engine	FR-04	Ingestion-level compiled regex filter with case-insensitive token substitution
Autonomous NLP Category Triage	FR-05	Scikit-Learn TF-IDF unigram/bigram vectorizer and Multinomial Naive Bayes
SBERT Semantic Subcategory Matching	FR-06	Sentence-BERT (all-MiniLM-L6-v2) 384-dimensional dense cosine similarity embeddings
Documentary Evidence Uploader	FR-07	Multipart binary uploader with MIME type, magic-byte, and 5 MB size validation
OCR Evidence 4-Point Entity Cross-Match	FR-08	EasyOCR / Tesseract extraction; cross-checks Ref ID, Bank, Amount, Account digits
Tier-1 AI GrievanceBot Adjudication	FR-09	Automated settlement decision gate evaluating validity, OCR score, and KB circulars
Dynamic SLA Engine & Urgency Radar	FR-10	Statutory RBI turnaround directions (72h/24h/30d) with live visual countdowns
Workload-Balanced Smart Officer Assigner	FR-11	Load-balancing greedy allocation optimizing officer backlog and resolution speed
Duplicate & Fraudulent Grievance Detector	FR-12	Transaction ID index lookup and SBERT cosine similarity clustering (>0.85)
Officer Adjudication & AI Copilot Drafter	FR-13	Structured memo generator, refund authorization, state transition to 'Resolved'
Case Reopening Governance (Level 2)	FR-14	7-day eligibility gate, Senior Nodal Officer escalation with CRITICAL priority
Statutory PDF Receipt with	FR-15	ReportLab canvas compilation, request-header dynamic

Dynamic QR		ISO/IEC 18004 QR encoding
Predictive M/M/c Queueing Model	FR-16	Kleinrock queueing formulas, closed-form Erlang-C delay and breach probabilities
Interactive What-If Staffing Sandbox	FR-17	Real-time slider-driven recalculation of surge arrivals and officer capacity
Bank Health Scorecard & Vulnerability Radar	FR-18	Composite 100-point index aggregating SLA speed, reopen rates, and CSAT ratings
Full-Stack Trilingual UI Localization	FR-19	React Context provider supporting instantaneous language swap across 222 keys
Forensic Append-Only Audit Trail	FR-20	Immutable audit_logs table protected against UPDATE and DELETE commands

Table 111: Implemented Features of GrievanceIQ

10.2 Screenshots and Demonstration Evidence

The operational capabilities of the running GrievanceIQ platform are illustrated across Figures 27 through 40.



Figure 27: Citizen Landing Portal and Trilingual Language Selector (EN / HI / MR)




Figure 28: Interactive Grievance Intake Form with Real-Time Vernacular Voice Dictation




Figure 29: DPDP Act 2023 Ingestion-Level PII Masking Live Preview




Figure 30: Autonomous Machine Learning Categorization & Confidence Rating




Figure 31: Tier-1 AI GrievanceBot Adjudication & Instant Settlement Dialog




Figure 32: Documentary Evidence Uploader with OCR 4-Point Entity Cross-Validation




Figure 33: Statutory PDF Receipt with Embedded Dynamic ISO/IEC 18004 QR Tracking Code




Figure 34: Public Grievance Status Tracker with Visual Statutory SLA Countdown




Figure 35: Grievance Redressal Officer Operational Workspace & Priority Triage Queue




Figure 36: AI Copilot Memo Drafter and Formal Adjudication Console




Figure 37: Executive Bank Health Scorecard and Systemic Risk Radar




Figure 38: Predictive Operational Sandbox (M/M/c Erlang-C Queue Simulation & What-If Staffing Modeler)



Bank Name	Category	Avg TAT (Hrs)	Resolution Rate	RBI Compliance
GrievanceIQ (SPIT Bank)	AI Platform	14.2 hrs	96.4%	99.1% (RANK #1)
HDFC Bank	Private Sector	38.5 hrs	88.2%	91.4% (RANK #2)
State Bank of India (SBI)	Public Sector	64.0 hrs	82.5%	84.8% (RANK #3)
ICICI Bank	Private Sector	42.1 hrs	86.9%	89.2% (RANK #4)
Axis Bank	Private Sector	46.8 hrs	85.1%	87.5% (RANK #5)
Bank of Baroda	Public Sector	72.4 hrs	79.8%	81.0% (RANK #6)
Punjab National Bank	Public Sector	78.2 hrs	77.4%	78.6% (RANK #7)
Kotak Mahindra Bank	Private Sector	44.5 hrs	86.0%	88.1% (RANK #8)

Figure 39: Scheduled Commercial Banks Operational Performance Leaderboard




Figure 40: Immutable Forensic Audit Trail & Regulatory Compliance Verification Console

10.3 Functional Results

• Classification Accuracy: The TF-IDF + Multinomial Naive Bayes model achieved 83.49% multi-class accuracy across 2,998 test cases spanning six banking departments, with a macro F1-score of 0.835. High-volume categories like Bank Accounts (F1: 0.875) and Loans (F1: 0.856) demonstrated exceptional precision.
• DPDP Act 2023 Compliance: In an adversarial test suite containing 100 raw complaint samples with unredacted 16-digit cards, 12-digit Aadhaar identifiers, and 10-character PANs, the regex sanitization engine achieved 100% zero-leakage, replacing every sensitive token before database write.
• Voice Dictation Loop Elimination: The dual-state buffer accumulator completely eliminated repeating text loops during continuous streaming dictation in Hindi and Marathi, maintaining clean sentence boundaries across 60-second test audio runs.
• Documentary Evidence OCR: Evaluated against 125 benchmark bank receipts, the 4-point cross-matcher achieved 90.0% precision, successfully flagging forged receipts and mismatching amounts.
• Kleinrock M/M/c Queueing Model: Analytical Erlang-C formulas matched hand-computed benchmark queue states with 100% mathematical precision, calculating utilization, dwell times, and SLA breach risks within 0.85 ms.

10.3.1 Empirical Model Performance & Operational Latency Visualizations

The empirical model evaluation, classification confusion matrix, and SLA turnaround improvements are visualized below:




Figure 10-A: Machine Learning Classification Performance by Category (Macro F1: 0.835)




Figure 10-B: Multi-Class Classification Confusion Matrix across 2,998 Test Cases (Accuracy: 83.49%)




Figure 10-C: Statutory SLA Turnaround Time Reduction: Traditional Process vs GrievanceIQ

10.5 Comparison with Existing Systems

Table 115 summarizes the operational advantages of GrievanceIQ over existing approaches.

Evaluation Criterion	Manual Process	Generic Commercial CRM	GrievanceIQ Platform
Triage & Categorization	Manual human sorting (hours to days)	Keyword rules / Costly paid AI	Autonomous TF-IDF + MNB (< 10 ms)
Vernacular Voice Access	None (Physical branch visit)	Requires third-party add-on	Native streaming Hindi/Marathi/English
DPDP 2023 PII Masking	Exposed on physical forms	Complex custom rules required	100% automated ingestion regex redaction
Evidence Verification	Manual paper check	Manual agent attachment view	Deterministic OCR 4-point cross-validation
Queue Capacity Planning	Retrospective monthly reports	Standard historical charts	Predictive M/M/c Erlang-C What-If modeler
Statutory Receipting	Carbon paper counterfoil	Email notification	ReportLab PDF with dynamic ISO QR tracking
Licensing & Cost	High manual labor costs	Recurring enterprise SaaS fees	100% Free & Open-Source Software

Table 115: Comparison of Approaches

10.6 Achievement of Objectives

Table 116 provides the formal traceability mapping between initial project objectives and empirical code evidence.

Project Objective (Chapter 1)	Technical Implementation Mechanism	Concrete Code & Test Evidence
1. Ingestion-Level DPDP Masking	Case-insensitive compiled regex sanitizer	validity_checker.py; test_phase2_extended.py (100% pass)
2. Multilingual Voice Ingestion	W3C Web Speech API + dual buffer hook	frontend/src/hooks/useVoiceDictation.js (zero duplicate loops)
3. Autonomous NLP Triage	TF-IDF vectorizer + Multinomial Naive Bayes	ml_pipeline.py; model_metrics.json (83.49% accuracy)
4. SBERT Semantic Matching	Sentence-BERT (all-MiniLM-L6-v2) cosine embeddings	semantic_engine.py; test_semantic_cases.py (100% pass)
5. Documentary Evidence OCR	EasyOCR + 4-point entity cross-matching	ocr_service.py; test_evidence_verification.py
6. Tier-1 AI GrievanceBot	Validity & OCR credibility settlement gate	bot_resolver.py; test_e2e_workflows.py (TEST 3)
7. Dynamic SLA Engine	Turnaround calculator based on statutory RBI circulars	sla_engine.py; test_e2e_workflows.py (TEST 5)
8. Workload-Balanced Assigner	Greedy load-balancing officer allocator	smart_assigner.py; test_phase2_extended.py (TEST 7)
9. Predictive Queue Modeling	Kleinrock M/M/c Erlang-C closed-form solver	bank_intelligence.py; test_phase2_extended.py (TEST 8)
10. Statutory QR PDF Receipt	ReportLab canvas + dynamic ISO/IEC 18004 QR	pdf_generator.py; live tracking scan verification
11. Trilingual Dynamic UI	React Context localization across 222 keys	frontend/TranslationsContext; test_phase2_extended.py (TEST 2)

Table 116: Objective-to-Evidence Mapping

160

11 Conclusion and Future Scope

11.1 Conclusion

In the contemporary Indian banking ecosystem, the exponential expansion of digital retail payments has outpaced conventional grievance redressal mechanisms, resulting in severe triage backlogs, accessibility barriers for vernacular citizens, and critical regulatory vulnerabilities under the Digital Personal Data Protection (DPDP) Act of 2023. This project resolved these challenges through the successful engineering of GrievanceIQ, an autonomous, full-stack banking grievance management and predictive operational intelligence platform.

GrievanceIQ delivers an integrated, privacy-first software pipeline: browser-native streaming voice dictation in Hindi and Marathi empowers underserved citizens to articulate disputes verbally without duplicate phrase loops; ingestion-level regular expression sanitization achieves 100% zero-leakage redaction of sensitive financial identifiers; autonomous machine learning (TF-IDF + MNB) and Sentence-BERT achieve 83.49% multi-class triage accuracy in sub-10ms inference; automated OCR executes deterministic 4-point entity cross-validation against physical transaction proofs; Tier-1 AI GrievanceBot deflects routine claims through instant settlement dialogs; and Kleinrock M/M/c Erlang-C queueing formulations provide branch management with predictive operational foresight and interactive What-If staffing sandboxes.

The software architecture has been thoroughly verified across a master test suite of 48 automated tests, demonstrating sub-150ms endpoint latencies, strict ACID transaction reliability, and 100% trilingual dictionary parity across 222 localized keys. By synthesizing mathematical operations research, machine learning, and secure software engineering, GrievanceIQ establishes a scalable, dependable, and socially transformative model for digital financial justice.

11.2 Status of Project Objectives

Table 117 details the final achievement status across all engineering objectives established in Chapter 1.

Project Engineering Objective	Final Status	Primary Supporting Evidence & Verification Metric
1. Ingestion-Level DPDP 2023 Masking	Achieved	100% zero-leakage masking across 16-digit cards, Aadhaar, and PAN tokens.
2. Multilingual Streaming Voice Ingestion	Achieved	W3C Web Speech hook with dual-state buffer; 0% phrase loop duplication.
3. Autonomous NLP Multi-Class Triage	Achieved	83.49% accuracy and 0.835 macro F1 across 2,998 test cases in model_metrics.json.
4. SBERT Semantic Subcategory	Achieved	Sentence-BERT embeddings (all-MiniLM-L6-v2)

Matching		achieving 100% duplicate detection.
5. Documentary Evidence OCR Validation	Achieved	EasyOCR + 4-point entity cross-matching scoring 90% precision on benchmark slips.
6. Tier-1 AI GrievanceBot Adjudication	Achieved	Automated instant refund settlement gate verified in test_e2e_workflows.py.
7. Dynamic SLA Engine & Urgency Radar	Achieved	Statutory RBI turnaround directions (72h/24h/30d) verified with live countdowns.
8. Workload-Balanced Officer Assigner	Achieved	Greedy allocation algorithm balancing active loads and resolution velocity.
9. Predictive M/M/c Queueing Model	Achieved	Kleinrock Erlang-C formulas matching hand-calculated benchmarks in 0.85 ms.
10. Statutory PDF Receipt with Dynamic QR	Achieved	ReportLab PDF compilation embedding live base-URL dynamic ISO/IEC 18004 QR.
11. Full-Stack Trilingual Dynamic UI	Achieved	React Context provider with 100% parity across 222 keys in EN, HI, and MR.

Table 117: Status of the Project Objectives

11.3 Major Engineering Contributions

• Architectural Decoupling: Strict separation between presentation, API gateway, business logic, and forensic persistence tiers.

• Privacy-by-Design Enforcement: Ingestion-level case-insensitive regex masking eliminating sensitive financial credentials before database writes.

• Dual-State Audio Buffer Algorithm: Practical client-side innovation resolving W3C Web Speech API repetitive phrase duplication.

• Deterministic 4-Point Document Validation: Verifiable OCR entity matching replacing unconstrained generative AI hallucinations.

• Mathematical Operations Research Integration: Application of Kleinrock's M/M/c Erlang-C queueing theory to banking capacity management.

• Dynamic Host-Aware Barcoding: Dynamic request header extraction ensuring mobile-verifiable ISO/IEC 18004 QR codes across any network host.

11.4 Current Limitations

• Synthetic Core Banking Interfaces: CBS debit reversal and ledger writebacks are mocked via RESTful APIs due to live banking network security boundaries.

• Printed Document OCR Dependency: OCR engine is optimized for printed transaction receipts; handwritten dispute dockets are outside current scope.

• Single-Node Persistence: Demonstration database operates on a single SQLite/PostgreSQL instance rather than a multi-region distributed cluster.

11.5 Future Enhancements

• Direct Core Banking Integration: Implement certified Finacle and BaNCS ISO 20022 message adapters for real-time ledger debit reversals.

• Account Aggregator (AA) Integration: Connect with RBI-regulated Account Aggregators to fetch authenticated bank statements automatically.

• On-Device Whisper Voice Models: Compile quantized Whisper.tflite models to enable offline voice dictation in rural banking kiosks.

• Multi-Lingual Expansion: Extend dynamic UI localization to 10 additional scheduled Indian languages (Bengali, Tamil, Telugu, Gujarati, etc.).

• Distributed Kafka Message Bus: Deploy Apache Kafka event streams for high-throughput multi-bank inter-branch message synchronization.

11.6 Lessons Learned

• Early Privacy Gating Prevents Downstream Catastrophe: Redacting PII at API ingestion simplifies compliance and guarantees that downstream logs and models never store illegal tokens.

• Deterministic Math Beats Generative Fluency: In financial operations, deterministic formulas (Erlang-C, SLA rules, 4-point OCR match) provide the explainability and legal defensibility that LLMs cannot guarantee.

• Buffer Isolation is Essential for Streaming Audio: Handling browser event streams requires strict separation between provisional hypotheses and committed history.

11.7 Plagiarism Check Report (Turnitin)

The complete project report was submitted to Turnitin for academic integrity verification. The system returned an Overall Similarity Index of 9%, which is well within the acceptable threshold prescribed by the University of Mumbai and Sardar Patel Institute of Technology guidelines. The breakdown of match sources is presented below:




Figure 41: Turnitin Plagiarism Report: 9% Overall Similarity Index (Submission ID: trn:oid::3618:157175442)

As evidenced by the Turnitin Integrity Overview, the report demonstrates original academic work with minimal textual overlap. The 9% similarity is attributable to standard technical terminology, IEEE citation formats, and commonly used regulatory references (RBI circulars, DPDP Act 2023 statutory language) that are inherent to the banking technology domain.

References

[1] Reserve Bank of India, "Reserve Bank - Integrated Ombudsman Scheme, 2021 (RB-IOS)," RBI Master Circulars, Mumbai, India, Nov. 2021.

[2] Ministry of Law and Justice, Government of India, "The Digital Personal Data Protection Act, 2023 (Act No. 22 of 2023)," The Gazette of India, Aug. 2023.

[3] Reserve Bank of India, "Customer Protection – Limiting Liability of Customers in Unauthorised Electronic Banking Transactions," RBI/2017-18/15, DBR.No.Leg.BC.78/09.07.005/2017-18, Jul. 2017.

[4] L. Kleinrock, "Queueing Systems, Volume 1: Theory," New York: John Wiley & Sons, 1975.

[5] A. K. Erlang, "The Theory of Probabilities and Telephone Conversations," Nyt Tidsskrift for Matematik B, vol. 20, pp. 33–39, 1909.

[6] C. D. Manning, P. Raghavan, and H. Schütze, "Introduction to Information Retrieval," Cambridge University Press, 2008.

[7] F. Pedregosa et al., "Scikit-learn: Machine Learning in Python," Journal of Machine Learning Research, vol. 12, pp. 2825–2830, 2011.

[8] N. Reimers and I. Gurevych, "Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks," in Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP), Hong Kong, pp. 3982–3992, Nov. 2019.

[9] R. Smith, "An Overview of the Tesseract OCR Engine," in Proceedings of the Ninth International Conference on Document Analysis and Recognition (ICDAR), Curitiba, Brazil, pp. 629–633, 2007.

[10] S. Tiwary, "FastAPI: Modern, High-Performance Web Framework for Python," O'Reilly Media, 2023.

[11] World Wide Web Consortium (W3C), "Web Speech API Specification," W3C Community Group Report, Oct. 2012. [Online]. Available: https://wicg.github.io/speech-api/

[12] S. Garfinkel, "De-Identification of Personally Identifiable Information," National Institute of Standards and Technology (NIST) Special Publication 800-122, 2015.

[13] R. Fielding, "Architectural Styles and the Design of Network-based Software Architectures," Ph.D. dissertation, Department of Information and Computer Science, University of California, Irvine, 2000.

[14] M. Fowler, "Patterns of Enterprise Application Architecture," Boston: Addison-Wesley, 2002.

[15] K. Beck, "Test-Driven Development: By Example," Boston: Addison-Wesley, 2002.

[16] R. C. Martin, "Clean Architecture: A Craftsman's Guide to Software Structure and Design," Prentice Hall, 2017.

[17] ISO/IEC, "Information technology — Automatic identification and data capture techniques — QR Code bar code symbology specification," ISO/IEC 18004:2015, Feb. 2015.

[18] National Payments Corporation of India (NPCI), "Unified Payments Interface (UPI) System Specifications and Dispute Management Framework," NPCI Circulars, 2022.

[19] D. Kalbande and R. Sawant, "Predictive Analytics in Distributed Software Systems," Journal of Engineering Education Transformations, vol. 35, no. 1, 2021.

[20] A. Vaswani et al., "Attention Is All You Need," in Advances in Neural Information Processing Systems (NeurIPS 2017), Long Beach, CA, pp. 5998–6008, Dec. 2017.

[21] J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova, "BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding," in Proceedings of NAACL-HLT 2019, Minneapolis, MN, pp. 4171–4186, 2019.

[22] S. Russell and P. Norvig, "Artificial Intelligence: A Modern Approach," 4th ed., Pearson, 2020.

[23] E. F. Codd, "A Relational Model of Data for Large Shared Data Banks," Communications of the ACM, vol. 13, no. 6, pp. 377–387, Jun. 1970.

[24] A. Silberschatz, P. B. Galvin, and G. Gagne, "Operating System Concepts," 10th ed., Wiley, 2018.

[25] A. S. Tanenbaum and D. J. Wetherall, "Computer Networks," 5th ed., Pearson, 2011.

[26] ReportLab Inc., "ReportLab PDF Generation User Guide," Version 4.2, 2024. [Online]. Available: https://www.reportlab.com/docs/reportlab-userguide.pdf