

DSIP – Lecturer 06

Image Enhancement in the Spatial Domain

Basic Relationships Between Pixels

- Neighborhood
- Adjacency
- Connectivity
- Paths
- Regions and boundaries

Contents

- Relationship between Pixels
- Distance Measures Operations
- Practice Examples

Image Enhancement :

- **Image Enhancement:** is the process that improves the quality of the image for a specific application
- Image enhancement:
 1. Improving the interpretability or perception of information in images for human viewers
 2. Providing `better' input for other automated image processing techniques.

Image Enhancement Methods

- **Spatial Domain Methods (Image Plane)**

Techniques are based on direct manipulation of pixels in an image

- **Frequency Domain Methods**

Techniques are based on modifying the Fourier transform of the image.

- **Combination Methods**

There are some enhancement techniques based on various combinations of methods from the first two categories


Spatial Domain Methods

- The term *spatial domain* refers to the aggregate of pixels composing an image. Spatial domain methods are procedures that operate directly on these pixels.
- Spatial domain processes will be denoted by the expression:

$$g(x,y) = \mathbf{T} [f(x,y)]$$

Where $f(x,y)$ is the input image, $g(x,y)$ is the processed image and \mathbf{T} is an operator on f , defined over some neighborhood of (x,y)

- In addition, \mathbf{T} can operate on a set of input images.



- The simplest form of T , is when the neighborhood of size 1×1 (that is a single pixel).
- In this case, g depends only on the value of f at (x, y) , and T becomes a *grey-level* (also called *intensity* or *mapping*) *transformation function* of the form:

$$s = T(r)$$

Where, r and s are variables denoting the grey levels of $f(x, y)$ and $g(x, y)$ at any point (x, y) .

Examples of Enhancement Techniques :

- **Contrast Stretching:**


If $T(r)$ has the form as shown in the figure below, the effect of applying the transformation to every pixel of f to generate the corresponding pixels in g would:

Produce higher contrast than the original image, by:

- Darkening the levels below m in the original image
- Brightening the levels above m in the original image

So, Contrast Stretching: is a simple image enhancement technique that improves the contrast in an image by 'stretching' the range of intensity values it to a desired range of values.


Typically, it uses a linear function



Examples of Enhancement Techniques

- **Thresholding**

Is a limited case of contrast stretching, it produces a two-level (binary) image.




Some fairly simple, yet powerful, processing approaches can be formulated with grey-level transformations. Because enhancement at any point in an image depends only on the gray level at that point, techniques in this category often are referred to as *point processing*.

Examples of Enhancement Techniques

Larger neighborhoods allow considerable more flexibility. The general approach is to use a function of the values of f in a predefined neighborhood of (x,y) to determine the value of g at (x,y) .

One of the principal approaches in this formulation is based on the use of so-called *masks* (also referred to as *filters*)

So, a **mask/filter**: is a small (say 3X3) 2-D array, such as the one shown in the figure, in which the values of the mask coefficients determine the nature of the process, such as **image sharpening**. Enhancement techniques based on this type of approach often are referred to as **mask processing** or **filtering**.



Some Basic Intensity (Gray-level) Transformation Functions


- Grey-level transformation functions (also called, intensity functions), are considered the simplest of all image enhancement techniques.
- The value of pixels, before and after processing, will be denoted by r and s , respectively. These values are related by the expression of the form:

$$s = T(r)$$

where T is a transformation that maps a pixel value r into a pixel value s .

Some Basic Intensity (Gray-level) Transformation Functions

Consider the following figure, which shows three basic types of functions used frequently for image enhancement:



Some Basic Intensity (Gray-level) Transformation Functions

- The three basic types of functions used frequently for image enhancement:
 - Linear Functions:
 - Negative Transformation
 - Identity Transformation
 - Logarithmic Functions:
 - Log Transformation
 - Inverse-log Transformation
 - Power-Law Functions:
 - n^{th} power transformation
 - n^{th} root transformation

Linear Functions

- **Identity Function**

- Output intensities are identical to input intensities
- This function doesn't have an effect on an image, it was included in the graph only for completeness
- Its expression:

$$s = r$$

Linear Functions

- **Image Negatives (Negative Transformation)**

- The negative of an image with gray level in the range $[0, L-1]$, where L = Largest value in an image, is obtained by using the negative transformation's expression:

$$s = L - 1 - r$$

Which reverses the intensity levels of an input image, in this manner produces the equivalent of a photographic negative.

- The negative transformation is suitable for enhancing white or gray detail embedded in dark regions of an image, especially when the black area are dominant in size

Logarithmic Transformations

- **Log Transformation**


The general form of the log transformation:

$$s = c \log (1+r)$$

Where c is a constant, and $r \geq 0$

- Log curve maps a narrow range of low gray-level values in the input image into a wider range of the output levels.
- Used to expand the values of dark pixels in an image while compressing the higher-level values.
- It compresses the dynamic range of images with large variations in pixel values.

Logarithmic Transformations



Logarithmic Transformations

- **Inverse Logarithm Transformation**
 - Do opposite to the log transformations
 - Used to expand the values of high pixels in an image while compressing the darker-level values.

Power-Law Transformations


- Power-law transformations have the basic form of:

$$s = c.r^v$$

Where c and v are positive constants

Power-Law Transformations

- Different transformation curves are obtained by varying γ (gamma)



Power-Law Transformations

- Variety of devices used for image capture, printing and display respond according to a power law. The process used to correct this power-law response phenomena is called ***gamma correction***.

Why power laws are popular?


- A cathode ray tube (CRT), for example, converts a video signal to light in a nonlinear way. The light intensity I is proportional to a power (γ) of the source voltage V $I \propto V^\gamma$
- For a computer CRT, γ is about 2.2
- Viewing images properly on monitors requires γ -correction

Gamma Correction

a b
c d

FIGURE 3.7

(a) Linear-wedge gray-scale image.
(b) Response of monitor to linear wedge.
(c) Gamma-corrected wedge.
(d) Output of monitor.




Gamma Measuring Applet:

<http://www.cs.cmu.edu/~efros/java/gamma/gamma.html>

Power-Law Transformation

- In addition to gamma correction, power-law transformations are useful for general-purpose contrast manipulation.



Power-Law Transformation

- Another illustration of Power-law transformation

a b
c d

FIGURE 3.9
(a) Aerial image.
(b)–(d) Results of applying the transformation in Eq. (3.2-3) with $c = 1$ and $\gamma = 3.0, 4.0$, and 5.0 , respectively. (Original image for this example courtesy of NASA.)






Piecewise-Linear Transformation Functions

- **Principle Advantage:** Some important transformations can be formulated only as a piecewise function.
- **Principle Disadvantage:** Their specification requires more user input than previous transformations
- **Types of Piecewise transformations are:**
 - Contrast Stretching
 - Gray-level Slicing
 - Bit-plane slicing

Contrast Stretching

- One of the simplest piecewise linear functions is a contrast-stretching transformation, which is used to enhance the low contrast images.
- Low contrast images may result from:
 - Poor illumination
 - Wrong setting of lens aperture during image acquisition.

Contrast Stretching



a b
c d

FIGURE 3.10

Contrast stretching.
(a) Form of transformation function. (b) A low-contrast image. (c) Result of contrast stretching. (d) Result of thresholding. (Original image courtesy of Dr. Roger Heady, Research School of Biological Sciences, Australian National University, Canberra, Australia.)

Contrast Stretching

- Figure 3.10(a) shows a typical transformation used for contrast stretching. The locations of points (r_1, s_1) and (r_2, s_2) control the shape of the transformation function.
- If $r_1 = s_1$ and $r_2 = s_2$, the transformation is a linear function that produces no changes in gray levels.
- If $r_1 = r_2$, $s_1 = 0$ and $s_2 = L-1$, the transformation becomes a *thresholding function* that creates a binary image. As shown previously.
- Intermediate values of (r_1, s_1) and (r_2, s_2) produce various degrees of spread in the gray levels of the output image, thus affecting its contrast.
- In general, $r_1 \leq r_2$ and $s_1 \leq s_2$ is assumed, so the function is always increasing.


Contrast Stretching

- Figure 3.10(b) shows an 8-bit image with low contrast.
- Fig. 3.10(c) shows the result of contrast stretching, obtained by setting $(r1, s1) = (r_{\min}, 0)$ and $(r2, s2) = (r_{\max}, L-1)$ where r_{\min} and r_{\max} denote the minimum and maximum gray levels in the image, respectively. Thus, the transformation function stretched the levels linearly from their original range to the full range $[0, L-1]$.
- Finally, Fig. 3.10(d) shows the result of using the *thresholding function* defined previously, with $r1=r2=m$, the mean gray level in the image.

Gray-level Slicing


- This technique is used to highlight a specific range of gray levels in a given image. It can be implemented in several ways, but the two basic themes are:
 - One approach is to display a high value for all gray levels in the range of interest and a low value for all other gray levels. This transformation, shown in Fig 3.11 (a), produces a binary image.
 - The second approach, based on the transformation shown in Fig 3.11 (b), brightens the desired range of gray levels but preserves gray levels unchanged.
 - Fig 3.11 (c) shows a gray scale image, and fig 3.11 (d) shows the result of using the transformation in Fig 3.11 (a).

Gray-level Slicing



Bit-plane Slicing

- Pixels are digital numbers, each one composed of bits. Instead of highlighting gray-level range, we could highlight the contribution made by each bit.
- This method is useful and used in image compression.



- Most significant bits contain the majority of visually significant data.

HW :

Assignment

- Write an M-function, that
 - inputs an image, a low value, a high value and a range of gray levels of interest
(f, low, high, from, to)
 - Outputs a two images (g, h)
 - Applies the two approaches of Gray-level slicing on image f, and produces images g and h respectively.