STEP 1: Import Libraries and Dataset

Double-click (or enter) to edit

```
from google.colab import files
uploaded = files.upload()
```

Choose files food_delivery.csv
food_delivery.csv(text/csv) - 883955 bytes, last modified: 24/03/2026 - 100% done
Saving food_delivery.csv to food_delivery.csv

```
import pandas as pd
from sklearn.model_selection import train_test_split
df = pd.read_csv('food_delivery.csv')
```

STEP 2: Statistical Summary

```
df.head()
```

	ID_Pesanan	Waktu_Transaksi	Kategori_Menu	Harga_Pesanan	Jarak_Kirim_KM	Waktu_Tunggu_Menit	Rating_Pelanggan	Ulasan_T
0	ORD-2024-000001	2024-03-22 13:15:14	Kopi	9000	NaN	27	4.0	Ses pesa
1	ORD-2024-000002	2024-01-14 17:05:37	Mie	21000	3.742238	37	NaN	N
2	ORD-2024-000003	2024-01-04 12:32:38	Martabak	33500	12.677149	49	NaN	N
3	ORD-2024-000004	2024-01-26 22:34:26	Kopi	13500	2.338085	20	5.0	Mantap g
4	ORD-2024-000005	2024-03-16 11:48:51	Ayam	47500	0.949764	27	4.0	Top kualitas

Next steps: Generate code with df New interactive sheet

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 8500 entries, 0 to 8499
Data columns (total 11 columns):
 #   Column              Non-Null Count  Dtype
---  ------              --------------  -----
 0   ID_Pesanan          8500 non-null   object
 1   Waktu_Transaksi     8500 non-null   object
 2   Kategori_Menu       8500 non-null   object
 3   Harga_Pesanan       8500 non-null   int64
 4   Jarak_Kirim_KM      7905 non-null   float64
 5   Waktu_Tunggu_Menit  8500 non-null   int64
 6   Rating_Pelanggan    6800 non-null   float64
 7   Ulasan_Teks         6800 non-null   object
 8   Status_Promo        8500 non-null   bool
 9   Tingkat_Keluhan     8500 non-null   object
 10  Status_Pesanan      8500 non-null   object
dtypes: bool(1), float64(2), int64(2), object(6)
memory usage: 672.5+ KB
```

```
df.size
```

```
93500
```

```
df.describe()
```

1 to 8 of 8 entries Filter

index	Harga_Pesanan	Jarak_Kirim_KM	Waktu_Tunggu_Menit	Rating_Pelanggan
count	8500.0	7905.0	8500.0	6800.0
mean	113473.88235294117	3.095437124322412	22.696941176470588	4.175294117647059
std	576441.8316031629	3.017151179338141	13.488615082651583	1.0127187498649945
min	0.0	0.5	5.0	1.0
25%	19000.0	0.9007725732044922	13.0	4.0
50%	29000.0	2.141931463160405	21.0	4.0
75%	45000.0	4.1569184074382335	30.0	5.0
max	8302000.0	25.0	112.0	5.0

Show 25 per page
Like what you see? Visit the data table notebook to learn more about interactive tables.

STEP 3: Selecting Features (X) and Target (y)

```
X = df[['Jarak_Kirim_KM', 'Harga_Pesanan',
        'Waktu_Tunggu_Menit', 'Rating_Pelanggan']]

y = df['Status_Pesanan']
```

STEP 4: Train-Test Split (80–20)

```
X_train_80, X_test_20, y_train_80, y_test_20 = train_test_split(
    X, y, test_size=0.2, random_state=42
)
```

STEP 5: Train-Test Split (70–30)

```
X_train_70, X_test_30, y_train_70, y_test_30 = train_test_split(
    X, y, test_size=0.3, random_state=42
)
```

STEP 6: Train-Test Split (60–40)

```
X_train_60, X_test_40, y_train_60, y_test_40 = train_test_split(
    X, y, test_size=0.4, random_state=42
)
```

STEP 7: Check Output Shapes

```
print("80-20 Split:", X_train_80.shape, X_test_20.shape)
print("70-30 Split:", X_train_70.shape, X_test_30.shape)
print("60-40 Split:", X_train_60.shape, X_test_40.shape)
```

```
80-20 Split: (6800, 4) (1700, 4)
70-30 Split: (5950, 4) (2550, 4)
60-40 Split: (5100, 4) (3400, 4)
```

Start coding or generate with AI.