

Orientation Measurement in Embedded Systems

Euler Angles, Quaternions, and Sensor Fusion in the MPU-9250 IMU

1. Measuring Orientation — Why It Is Not Trivial

To describe how an object is oriented in three-dimensional space, we need to know the direction of its three principal axes: the **X-axis**, **Y-axis**, and **Z-axis**. Together, these three directions fully define the object's rotational state relative to a fixed reference frame. The challenge lies in tracking these axes accurately as the object moves — and doing so without losing any information along the way.

In practice, two major mathematical frameworks are used for this purpose: **Euler angles** and **quaternions**. Both describe the same physical thing — orientation — but they go about it in very different ways, each with its own strengths and limitations. Understanding both is essential for anyone working with inertial measurement units (IMUs), robotics, drones, or any system that tracks rotational motion.

2. Euler Angles — The Intuitive Approach

2.1 Roll, Pitch, and Yaw

The most natural way for humans to describe the orientation of a body is through three angles, each corresponding to a rotation about one axis. These angles are known as **Euler angles** and are defined as follows:

- **Roll** — Rotation about the X-axis. Imagine an aircraft tilting one wing downward. Roll describes that side-to-side tilt.
- **Pitch** — Rotation about the Y-axis. This is the nose-up or nose-down motion of an aircraft, or the forward-backward tilt of a drone.
- **Yaw** — Rotation about the Z-axis. This is the left-right heading change, like a compass needle turning or a car steering left.

With these three angles — roll (ϕ), pitch (θ), and yaw (ψ) — any orientation in three-dimensional space can be described. This is an elegant and human-readable representation: engineers and pilots alike think naturally in terms of roll, pitch, and yaw.

2.2 The Rotation Sequence

An important but often overlooked property of Euler angles is that the **order of rotations matters**. Applying roll first and then pitch produces a different final orientation than applying pitch first and then roll. This is because rotations in three dimensions are not commutative. The most commonly used sequence is:

```
Final orientation = Rz(yaw) × Ry(pitch) × Rx(roll)
```

where R_x , R_y , R_z are rotation matrices about X, Y, and Z axes.

This ordered application means that each rotation is performed in the context of the axes that already exist after the previous rotations. The system is sequential and frame-dependent.

3. Gimbal Lock — The Fatal Flaw of Euler Angles

3.1 What Is Gimbal Lock?

Despite being intuitive, Euler angles suffer from a fundamental mathematical problem called **gimbal lock**. To understand this, consider the physical gimbal mechanism used in gyroscopes — three nested rings, each free to rotate about a different axis. Euler angles are essentially the mathematical equivalent of this physical gimbal system.

Gimbal lock occurs when the object rotates **90° about the pitch axis (Y-axis)**. At this exact angle, the first ring (roll, X-axis) and the third ring (yaw, Z-axis) become aligned — they now rotate about the *same* axis. The system has effectively lost one degree of freedom. No matter how much you vary roll or yaw independently, they produce exactly the same rotational change. The third dimension of orientation is gone.

3.2 Why This Is a Real Problem

In theory, gimbal lock only occurs at one specific angle (pitch = $\pm 90^\circ$). In practice, however, any motion *near* that angle introduces severe numerical instability, making Euler-based calculations unreliable. For applications like aircraft, rockets, drones, or robotic arms that routinely encounter these orientations, Euler angles alone are not a sufficient representation. A more robust approach is needed.

Key insight: Gimbal lock is not a sensor failure — it is a limitation of the three-parameter mathematical representation itself. The problem exists regardless of how good the hardware is.

4. Quaternions — The Robust Solution

4.1 What Is a Quaternion?

A **quaternion** is a four-component mathematical object developed by the mathematician William Rowan Hamilton in 1843. In the context of 3D rotation, a quaternion is written as:

```
q = w + xi + yj + zk
```

or equivalently as a vector: $q = (w, x, y, z)$

```
where  $i^2 = j^2 = k^2 = ijk = -1$ 
```

The four components carry a clear geometric meaning. If we imagine a rotation of angle θ about a unit axis vector $\hat{n} = (nx, ny, nz)$, then:

```
w = cos( $\theta$  / 2)           ← encodes how much rotation
x = nx × sin( $\theta$  / 2)      ← X-component of the rotation axis
y = ny × sin( $\theta$  / 2)      ← Y-component of the rotation axis
z = nz × sin( $\theta$  / 2)      ← Z-component of the rotation axis
```

4.2 The Role of w — Angle Encoding

The component w is the scalar part of the quaternion. It encodes the *cosine of half the rotation angle* — the total amount by which the body has rotated around its rotation axis. It is not directly the angle relative to any single fixed axis, but rather a measure of "how much" the body has turned as a whole. This is what makes the quaternion a *polar-form* representation of orientation, analogous to how a complex number can be expressed in rectangular form ($a + bi$) or polar form ($r \cdot e^{i\theta}$).

Analogy: Euler angles are like Cartesian coordinates (x, y, z) — three independent components, human-readable but prone to degeneracy. Quaternions are like polar coordinates — one magnitude (w) and a direction (x, y, z) — more abstract, but mathematically stable and singularity-free.

4.3 Why Quaternions Avoid Gimbal Lock

Quaternions represent orientation on the surface of a four-dimensional unit sphere (where $|q| = 1$ always). This 4D hypersphere has no singular points — every orientation maps to a unique, well-defined location. There is simply no configuration in which two axes collapse into one, because the representation does not use sequential axis rotations at all. It represents the entire rotation as a single operation around one axis.

Even when a body reaches the orientation that would cause gimbal lock in Euler angles (pitch = 90°), the quaternion representation continues smoothly without any loss of information. The fourth component w effectively acts as a safety net — if the spatial axes (x, y, z) approach a degenerate configuration, w carries the remaining orientation information to keep the full three degrees of freedom intact.

4.4 How the Raspberry Pi and MPU Work With Quaternions

Processing units like the Raspberry Pi compute orientation *internally* in quaternion form, because all matrix operations, interpolations (called **SLERP** — Spherical Linear Interpolation), and rotational updates are numerically well-behaved in this representation. However, quaternion values ($w = 0.707, x = 0.0, y = 0.707, z = 0.0$) are not immediately interpretable by a human operator.

The processor therefore performs a **quaternion-to-Euler conversion** before displaying data, presenting the familiar roll, pitch, and yaw angles on screen. This pipeline can be summarized as:

```
Sensor raw data → Quaternion (internal computation)
                  → Euler angles (converted for human display)

roll   = atan2( 2(wy + xz), 1 - 2(y² + x²) )
pitch  = arcsin( 2(wx - yz) )
yaw    = atan2( 2(wz + xy), 1 - 2(z² + y²) )
```

The sensor outputs that engineers read — gyroscope angular velocity in **rad/s**, accelerometer acceleration in **m/s²**, magnetometer field strength in **µT (microtesla)** — are all derived from this processing chain and presented in their respective physical units for ease of interpretation.

5. The MPU-9250 IMU — Hardware Overview

The **MPU-9250** is a nine-axis inertial measurement unit manufactured by InvenSense (now TDK). It integrates three distinct sensors into a single compact package, each measuring a different physical quantity:

Sensor	Measures	Unit	Axes
Gyroscope	Angular velocity (rate of rotation)	rad/s	X, Y, Z (Roll, Pitch, Yaw)
Accelerometer	Linear acceleration (including gravity)	m/s²	X, Y, Z (Roll, Pitch)
Magnetometer	Earth's magnetic field strength	µT (microtesla)	X, Y, Z (Yaw / heading)

Each of these sensors contributes differently to the final orientation estimate. Crucially, **no single sensor is sufficient on its own** — each has a blind spot, a drift problem, or a sensitivity limitation that the others can compensate for. This is the core motivation behind sensor fusion.

6. What Each Sensor Can and Cannot Do

6.1 The Gyroscope — Fast but Drifting

The gyroscope measures **angular velocity** — the rate at which the body is rotating about each axis, in radians per second. To get orientation from this, the readings must be *integrated over time*:

```
roll(t)    = roll(t0) + ∫ ωx dt  
pitch(t)   = pitch(t0) + ∫ ωy dt  
yaw(t)     = yaw(t0) + ∫ ωz dt
```

where ω_x , ω_y , ω_z are angular velocities measured by the gyroscope

The gyroscope is extremely responsive and accurate over **short time intervals**. It captures fast, dynamic motion cleanly. However, it suffers from a critical weakness called **gyroscope drift**.

Because orientation is obtained by integrating the velocity signal, any small constant error (called *bias*) in the raw sensor reading accumulates over time. Even a tiny error of 0.01 rad/s grows to a significant angle error after several seconds or minutes of operation. The gyroscope is excellent for tracking rapid movement, but it gradually loses its sense of absolute orientation due to this ever-accumulating drift.

Gyroscope summary: Excellent short-term accuracy, high responsiveness. Cannot determine absolute orientation independently. Drifts over time without correction.

6.2 The Accelerometer — Absolute but Noisy

The accelerometer measures **linear acceleration** acting on the device, including the constant downward pull of gravity (9.81 m/s²). When the body is stationary or in slow motion, the dominant signal is gravity, and its direction in the sensor frame tells us *how the sensor is tilted relative to the Earth's surface*.

```
roll    = atan2(ay, az)  
pitch   = atan2(-ax, √(ay2 + az2))
```

where a_x , a_y , a_z are the accelerometer readings on each axis

This gives accurate **roll** and **pitch** measurements — but only these two. Yaw (rotation about the vertical axis) cannot be determined from gravity alone, because gravity is a vertical vector; rotating the device horizontally does not change the gravity direction in the sensor frame at all.

The accelerometer provides an **absolute reference** — it does not drift over time because it measures a physical force rather than integrating a rate. However, it is highly sensitive to any external vibration or dynamic linear acceleration. When the body is in rapid motion, the true gravitational component becomes mixed with inertial forces, and the tilt estimate becomes unreliable. The accelerometer is best suited to **slow-moving or stationary conditions** and serves primarily as a corrective reference for the gyroscope's drift.

Accelerometer summary: Provides absolute roll and pitch reference. Cannot determine yaw. Unreliable during fast or vibrating motion. Does not drift over time.

6.3 The Magnetometer — Heading Without Drift

The magnetometer measures the strength and direction of the **Earth's magnetic field** along each axis. Since the Earth's magnetic field points approximately toward geographic north, the magnetometer acts as a digital compass — and its most important contribution is providing an absolute **yaw (heading) reference** that neither the gyroscope nor accelerometer can supply on their own.

```
yaw = atan2(-my_compensated, mx_compensated)

where mx, my are the magnetic field components after tilt compensation
using roll and pitch from the accelerometer
```

Notice that an accurate yaw estimate from the magnetometer requires *tilt compensation* — the roll and pitch from the accelerometer must first be applied to project the magnetic field measurements onto the horizontal plane. This shows the fundamental interdependence of all three sensors.

The magnetometer has its own limitations. It is highly sensitive to nearby ferromagnetic materials (iron, steel), electric currents, and other sources of magnetic interference. In environments with significant electromagnetic disturbance — near motors, power cables, or metallic structures — the magnetometer reading can become distorted. It also has relatively slow response dynamics compared to the gyroscope.

Magnetometer summary: Provides absolute yaw (heading) reference using Earth's magnetic field. Does not drift. Sensitive to magnetic interference and requires tilt compensation from the accelerometer.

7. Why No Single Sensor Is Enough

The limitations described above can be summarized as a fundamental trade-off across three dimensions:

Property	Gyroscope	Accelerometer	Magnetometer
Axes covered	Roll, Pitch, Yaw	Roll, Pitch	Yaw only
Absolute reference	No	Yes (gravity)	Yes (magnetic north)
Short-term accuracy	Excellent	Poor (vibration)	Moderate
Long-term accuracy	Poor (drift)	Good	Good (if clean)
Noise sensitivity	Low	High (vibration)	High (magnetic disturbance)

The solution is to combine all three sensors intelligently — taking the best of each at every moment in time — and using a mathematical framework to decide how much to trust each sensor at each instant. This approach is called **sensor fusion**.

8. Sensor Fusion — Combining All Three Sensors

8.1 The Core Idea

Sensor fusion is the process of combining data from multiple sensors in a principled, mathematically optimal way to produce a single, more accurate estimate of the system's state — in this case, the orientation (roll, pitch, yaw) of the body on which the MPU-9250 is mounted.

The central question sensor fusion must answer at every time step is: **"How much should I trust each sensor right now?"** The answer changes continuously. When the device is stationary, the accelerometer is highly trustworthy. When it is vibrating, the gyroscope should be weighted more heavily. When magnetic interference is low, the magnetometer provides a clean heading; when near a motor, it should be trusted less.

Quantifying and dynamically adjusting these trust levels is precisely what the **Kalman filter** does.

8.2 The Kalman Filter — Optimal State Estimation

The **Kalman filter**, developed by Rudolf E. Kálmán in 1960, is a recursive algorithm that estimates the true state of a system from a series of noisy measurements. It operates in a predict-and-correct cycle:

- **Predict:** Using the gyroscope's angular velocity and the current orientation estimate, project forward what the orientation should be at the next time step.
- **Update:** When a measurement from the accelerometer or magnetometer arrives, compare it to the prediction. Use the discrepancy to correct the estimate, weighted by how reliable each source is known to be.

The mathematics of this process involve two key quantities:

```
Process noise covariance  Q  →  how much we trust the gyroscope model
Measurement noise covariance  R  →  how much we trust the sensor
measurements
```

```
Kalman Gain  K  =  P- × HT × (H × P- × HT + R)-1
```

```
Updated estimate:  x^  =  x^- + K × (z - H × x^-)
```

```
where:  P- = predicted error covariance
         H  = observation matrix
         z  = actual sensor measurement
```

```
 $\hat{x}^-$  = predicted state
```

The **Kalman Gain K** is the heart of the filter. It is a value between 0 and 1 that determines how much the new measurement should shift the current estimate. If K is close to 1, the filter trusts the new measurement highly and shifts its estimate significantly. If K is close to 0, it trusts the model prediction more and largely ignores the new measurement.

Over time, the Kalman filter learns the characteristic noise patterns of each sensor and continuously refines how much weight to assign each one — a dynamic, self-correcting trust mechanism.

8.3 How Sensor Fusion Works in Practice

At the moment the MPU-9250 powers on, the system has no prior knowledge of orientation. It uses the **accelerometer as the initial reference**, reading the direction of gravity to establish a starting estimate of roll and pitch. This first reading establishes the baseline from which all subsequent tracking proceeds.

Step 1 — Gyroscope integration (high-frequency prediction)

At every sampling interval (typically every 1 to 10 milliseconds), the gyroscope angular velocity readings are integrated to update the orientation estimate. This step is fast and responsive — it captures even rapid rotations accurately. However, because of gyroscope bias and drift, this estimate slowly diverges from the true orientation over seconds to minutes.

Step 2 — Accelerometer correction (roll and pitch)

Simultaneously, the accelerometer continuously measures the direction of gravity in the sensor frame. By comparing the accelerometer-derived roll and pitch with the gyroscope-integrated estimates, the filter can detect drift. The Kalman filter computes how far the gyroscope estimate has drifted and applies a correction proportional to the Kalman Gain — pulling the estimate back toward the absolute reference provided by gravity.

During periods of high acceleration — for example, while a drone accelerates or a robot arm moves rapidly — the Kalman filter automatically reduces the weight given to the accelerometer (because the gravity assumption breaks down) and relies more on the gyroscope for that interval.

Step 3 — Magnetometer correction (yaw)

For yaw, the magnetometer provides the absolute reference. After tilt compensation using roll and pitch from the accelerometer, the projected magnetic field gives the heading direction relative to magnetic north. The Kalman filter compares this to the gyroscope-integrated yaw and applies the appropriate correction.

When the magnetometer detects anomalous readings — field strength significantly different from the known Earth-field magnitude — the filter reduces its weight and trusts the gyroscope more for that moment. This makes the system robust to transient magnetic interference.

Step 4 — Fused output

The result of each Kalman filter cycle is an updated, fused orientation estimate expressed as roll, pitch, and yaw (or internally as a quaternion). This estimate is more accurate than any single

sensor could provide alone: it has the **responsiveness of the gyroscope**, the **long-term stability of the accelerometer**, and the **absolute heading reference of the magnetometer**.

8.4 Percentage Contribution — Dynamic Trust Allocation

A useful way to visualize sensor fusion is to think of it as a dynamic blending of three sources. At any given moment:


- During fast rotation — gyroscope contributes ~90–95%, accelerometer ~5–10%, magnetometer ~5%.
- During slow, steady motion — accelerometer contributes more to roll/pitch correction (~30–40%), gyroscope integration still dominates ~60%.
- During stationary holds — accelerometer and magnetometer together dominate; the gyroscope contribution to correction falls near zero (though it still provides the primary tracking signal).
- Near magnetic disturbance — magnetometer weight drops toward 0%; gyroscope-integrated yaw is used instead.

These percentages are not fixed constants — they emerge naturally from the Kalman filter's ongoing calculation of noise covariances and prediction errors. The filter continuously re-evaluates which sensor is most trustworthy in the current operating conditions and adjusts the blend accordingly.

Sensor fusion in one sentence: At each moment in time, the Kalman filter decides how much to trust each sensor based on its current noise level and prediction accuracy — then combines them into one optimal orientation estimate that none of the sensors could achieve alone.

9. Complete Data Flow — From Raw Sensor to Orientation

The full processing pipeline from raw hardware readings to a usable orientation output can be summarized as follows:



10. Summary

The following points capture the essential concepts covered in this document:

- **Euler angles** (roll, pitch, yaw) describe orientation using three sequential rotations. They are human-readable but suffer from gimbal lock when pitch reaches $\pm 90^\circ$.
- **Quaternions** use four parameters (w, x, y, z) to represent orientation as a single rotation about one axis. They are immune to gimbal lock and are the preferred internal representation for all orientation computation.
- **The gyroscope** provides fast, responsive angular velocity data but drifts over time. It covers all three axes and is the primary source of orientation updates.
- **The accelerometer** provides an absolute gravitational reference for roll and pitch. It is noise-sensitive during dynamic motion but does not drift over time.
- **The magnetometer** provides an absolute heading (yaw) reference by detecting Earth's magnetic field. It is sensitive to electromagnetic interference and requires tilt compensation.
- **Sensor fusion** combines all three sensors, dynamically weighting each based on current noise conditions to produce an orientation estimate better than any sensor alone.
- **The Kalman filter** is the mathematical engine of sensor fusion. It operates in predict-and-correct cycles, computing the optimal Kalman Gain at each step to balance model prediction against sensor measurement.
- **The MPU-9250** computes orientation internally as a quaternion and outputs Euler angles for human readability — exactly as a processor outputs a decimal number after computing internally in binary.

End of Document