

GE23131-Programming Using C-2024

Quiz navigation



Show one page at a time

Finish review

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Friday, 25 October 2024, 1:11 PM
Duration	59 days 4 hours

Question 1

Correct

Marked out of 3.00

Flag question

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2
3 int main()
4 {
5     int a, b;
6     scanf("%d %d", &a, &b);
7     if(a % 10 == b % 10)
8     {
9         printf("true");
10    }
11    else
12    {
13        printf("false");
14    }
15    return 0;
16 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of
5.00

🚩 Flag question

Objective

In this challenge, we're getting started with conditional statements.

Task

Given an integer, ***n***, perform the following conditional actions:

- If ***n*** is odd, print **Weird**
- If ***n*** is even and in the inclusive range of **2** to **5**, print ***Not Weird***
- If ***n*** is even and in the inclusive range of **6** to **20**, print ***Weird***
- If ***n*** is even and greater than **20**, print ***Not Weird***

Complete the stub code provided in your editor to print whether or not ***n*** is weird.

Input Format

A single line containing a positive integer, ***n***.

Constraints

- $1 \leq n \leq 100$

Output Format

Print **Weird** if the number is weird; otherwise, print **Not Weird**.

Sample Input 0

3

Sample Output 0

Weird

Sample Input 1

24

Sample Output 1

Not Weird

Explanation

Sample Case 0: $n = 3$

n is odd and odd numbers are weird, so we print **Weird**.

Sample Case 1: $n = 24$

$n > 20$ and n is even, so it isn't weird. Thus, we print **Not Weird**.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2
3 int main()
4 {
5     int a;
6     scanf("%d", &a);
7     if (a % 2 != 0)
8     {
9         printf("Weird");
10    }
11    else if(a >= 2 && a <= 5)
12    {
13        printf("Not Weird");
14    }
15    else if(a >= 6 && a <= 20)
16    {
17        printf("Weird");
18    }
19    else if (a % 2 == 0 && a >= 20)
20    {
21        printf("Not Weird");
22    }
23    return 0;
24 }
```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Question 3

Correct

Marked out of 7.00

Flag question

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$. You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```

1 #include<stdio.h>
2
3 int main()
4 {
5     int a, b, c;
6     scanf("%d %d %d", &a, &b, &c);
7     if(a * a + b * b == c * c || c * c + a * a == b * b || c * c + b * b == a * a)
8     {
9         printf("yes");
10    }
11    else
12    {
13        printf("no");
14    }
15    return 0;
16 }
```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓

Finish review