CSS (Cascaded Style Sheet)

Introduction

- Styling of HTML (appearance, layout)
- Application
  - External: <link href="file.css">
  - Internal: <style></style>
  - Inline:
- Syntax: CSS Selector { property: value; …. }
  E.g. div { color: red; }

CSS Selector

- Simple
  - Name: div/*/div, p
  - Id: #myDiv
  - Class: div.chatbox
- Combinator
  - Descendent: div p
  - Child: div > p
  - Adjacent sibling: div + p
  - Any sibling: div ~ p
- Pseudo Class
  - :focus, :active, first-child, :not(p), :hover:, a:link, a:visited
- Pseudo Element
  - ::first-line, ::first-letter, ::before, ::after, ::selection
- Attribute Selector
  - input[type=“text”]
  - [attribute^="value"] starting with value
  - [attribute$="value"] end with value
  - [attribute*="value"] contains value
  - [attribute~="value"] contains word
  - [attribute|="value"] start with word

Properties

- Some CSS properties are inherited and some not
  - Text-related and list-related properties are inherited - `color`, `font-size`, `font-family`, `line-height`, `text-align`, `list-style` etc.
  - Box-related and positioning styles are not inherited - `width`, `height`, `border`, `margin`, `padding`, `position`, `float` etc.
  - `<a>` elements do not inherit color and text-decoration

Properties

- Background
  - background-color (hex, rgba, color)
  - background-image
- Border
  - border: 2px solid red;
  - border-radius, style, color, width (TRBL)
- Box
  - height, width, padding, border, outline, margin
- Text
  - color, text-align, vertical-align, text-transform, text-indent
  - Font: font-style, font-variant, font-weight, font-size/line-height, font-family
- Display: inline, block, none, inline-block
- Float: left, right