

Week 9 GDB

```
//seg1_string.c

#include <stdio.h>

#include <stdlib.h>

struct BSTNode{

    int data;

    struct BSTNode *left;

    struct BSTNode *right;

};

int insertnode(struct BSTNode **root, int data){

    if(!(*root)){

        struct BSTNode *newnode=(struct BSTNode *)malloc(sizeof(struct BSTNode));

        if(!newnode) return 0;

        newnode->data=data;

        newnode->left=newnode->right=NULL;

        *root=newnode;

        return 1;

    }

    else if((*root)->data>data){

        return insertnode(&(*root)->left, data);

    }

    else if((*root)->data<data){

        return insertnode(&(*root)->right, data);

    }

    else

        return 0;

}

int inorder(struct BSTNode *root){
```

```

if(root){
    inorder(root->left);
    printf("%d ", root->data);
    inorder(root->right);
    return 1;
}
return 1;
}

```

```

int findmin(struct BSTNode *root){
    while(root->left)
        root=root->left;
    return root->data;
}

```

```

int inordersuccessor(struct BSTNode *root, int key){
    struct BSTNode *succ=NULL;
    while(root!=NULL){
        if (root->data == key && root->right != NULL)
            return findmin(root->right);
        else if (key < root->data)
        {
            succ = root;
            root = root->left;
        }
        else if (key > root->data)
            root = root->right;
        else
            break;
    }
    return succ->data;
}

```

```
int main(){
    int n;
    printf("Enter the number of nodes in the BST");
    scanf("%d",&n);

    struct BSTNode *root=NULL;
    while(n--){
        int elem;
        printf("Enter node value: ");
        scanf("%d", &elem);

        insertnode(&root, elem);
    }

    int key;
    printf("Enter number to find successor of: ");
    scanf("%d",&key);

    int succ=inordersuccessor(root, key);
    printf("Successor: %d", succ);

    return 0;
}
```

Screenshots

```
veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/week9
veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/week9$ gdb ./seg1out
GNU gdb (Ubuntu 12.1-0ubuntu1~22.04) 12.1
Copyright (C) 2022 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.
Type "show copying" and "show warranty" for details.
This GDB was configured as "x86_64-linux-gnu".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<https://www.gnu.org/software/gdb/bugs/>.
Find the GDB manual and other documentation resources online at:
<http://www.gnu.org/software/gdb/documentation/>.

For help, type "help".
Type "apropos word" to search for commands related to "word"...
Reading symbols from ./seg1out...
(gdb) run
Starting program: /home/veeraja/Desktop/unix_lab/week9/seg1out
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
Enter the number of nodes in the BST: 5
Enter node value: 3
Enter node value: 4
Enter node value: 5
Enter node value: 1
Enter node value: 2
Enter number to find successor of: 4

Program received signal SIGSEGV, Segmentation fault.
0x00005555555552f6 in findmin (root=0x0) at seg1_string.c:42
42         return root->data;
```

```
veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/week9
veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/week9$ gdb ./seg1out
GNU gdb (Ubuntu 12.1-0ubuntu1~22.04) 12.1
Copyright (C) 2022 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.
Type "show copying" and "show warranty" for details.
This GDB was configured as "x86_64-linux-gnu".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<https://www.gnu.org/software/gdb/bugs/>.
Find the GDB manual and other documentation resources online at:
<http://www.gnu.org/software/gdb/documentation/>.

For help, type "help".
Type "apropos word" to search for commands related to "word"...
Reading symbols from ./seg1out...
(gdb) list
37     }
38
39     int findmin(struct BSTNode *root){
40         while(root!=NULL)
41             root=root->left;
42         return root->data;
43     }
44
45     int inordersuccessor(struct BSTNode *root, int key){
46         struct BSTNode *succ=NULL;
47     }
(gdb) break 81
Breakpoint 1 at 0x555555555400: file seg1_string.c, line 81.
(gdb) break 49
Breakpoint 2 at 0x555555555334: file seg1_string.c, line 49.
(gdb) break 40
Breakpoint 3 at 0x5555555552e2: file seg1_string.c, line 40.
(gdb) break 41
Breakpoint 4 at 0x5555555552e4: file seg1_string.c, line 41.
(gdb) break 42
Breakpoint 5 at 0x5555555552f7: file seg1_string.c, line 42.
(gdb) run
The program being debugged has been started already.
Start it from the beginning? (y or n) y
Starting program: /home/veeraja/Desktop/unix_lab/week9/seg1out
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
Enter the number of nodes in the BST: 5
Enter node value: 3
Enter node value: 4
Enter node value: 1
Enter node value: 5
Enter node value: 2
Enter number to find successor of: 4

Breakpoint 1, main () at seg1_string.c:81
81     int succ=inordersuccessor(root, key);
```

```
veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/week9
veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/week9$ gdb ./seg1out
GNU gdb (Ubuntu 12.1-0ubuntu1~22.04) 12.1
Copyright (C) 2022 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.
Type "show copying" and "show warranty" for details.
This GDB was configured as "x86_64-linux-gnu".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<https://www.gnu.org/software/gdb/bugs/>.
Find the GDB manual and other documentation resources online at:
<http://www.gnu.org/software/gdb/documentation/>.

For help, type "help".
Type "apropos word" to search for commands related to "word"...
Reading symbols from ./seg1out...
(gdb) break 81
Breakpoint 1 at 0x555555555400: file seg1_string.c, line 81.
(gdb) run
The program being debugged has been started already.
Start it from the beginning? (y or n) y
Starting program: /home/veeraja/Desktop/unix_lab/week9/seg1out
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
Enter the number of nodes in the BST: 5
Enter node value: 3
Enter node value: 4
Enter node value: 1
Enter node value: 5
Enter node value: 2
Enter number to find successor of: 4

Breakpoint 1, main () at seg1_string.c:81
81     int succ=inordersuccessor(root, key);
(gdb) print succ
$1 = 0
(gdb) print root
$2 = (struct BSTNode *) 0x555555559ac0
(gdb) print key
$3 = 4
(gdb) next

Breakpoint 2, inordersuccessor (root=0x555555559ae0, key=4) at seg1_string.c:49
49     return findmin(root->right);
(gdb) print root
$4 = (struct BSTNode *) 0x555555559ae0
(gdb) print root->data
$5 = 4
(gdb) print root->right
$6 = (struct BSTNode *) 0x555555559b20
(gdb) print root->right->data
$7 = 5
(gdb) print root->left->data
Cannot access memory at address 0x0
(gdb) next

Breakpoint 3, findmin (root=0x555555559b20) at seg1_string.c:40
40     while(root!=NULL)
(gdb) print root->data
$8 = 5
(gdb) next

Breakpoint 4, findmin (root=0x555555559b20) at seg1_string.c:41
41     root=root->left;
(gdb) print root->data
$9 = 5
(gdb) next
40     while(root!=NULL)
(gdb) print root->data
cannot access memory at address 0x0
```

```

(gdb) continue
Continuing.

Breakpoint 5, findmin (root=0x0) at seg1_string.c:42
42      return root->data;
(gdb) next

Program received signal SIGSEGV, Segmentation fault.
0x0000555555555276 in findmin (root=0x0) at seg1_string.c:42

```

```

0x000000000000130b <+5>: mov    %rsp,%rbp
0x000000000000130c <+6>: sub    $0x20,%rsp
0x000000000000130d <+8>: mov    %fs:0x28,%rax
0x000000000000130e <+12>: mov    %rax,-0x8(%rbp)
0x000000000000130f <+21>: mov    %eax,%eax
0x0000000000001310 <+25>: xor    %eax,%eax
0x0000000000001311 <+27>: lea    0xc50(%rip),%rax      # 0x2010
0x0000000000001312 <+34>: mov    %rax,%rdi
0x0000000000001313 <+37>: mov    $0x0,%eax
0x0000000000001314 <+42>: call   0x1000 <printf@plt>
0x0000000000001315 <+47>: lea    -0x1c(%rbp),%rax
0x0000000000001316 <+51>: mov    %rax,%rsi
0x0000000000001317 <+54>: lea    0xc02(%rip),%rax      # 0x2035
0x0000000000001318 <+61>: mov    %rax,%rdi
0x0000000000001319 <+64>: mov    $0x0,%eax
0x000000000000131a <+69>: call   0x1000 <_isoc99_scanf@plt>
0x000000000000131b <+74>: movq   $0x0,-0x10(%rbp)
0x000000000000131c <+82>: jmp     0x1022 <main+148>
0x000000000000131d <+84>: lea    0xc47(%rip),%rax      # 0x2038
0x000000000000131e <+91>: mov    %rax,%rdi
0x000000000000131f <+94>: mov    $0x0,%eax
0x0000000000001320 <+99>: call   0x1000 <printf@plt>
0x0000000000001321 <+104>: lea    -0x10(%rbp),%rax
0x0000000000001322 <+108>: mov    %rax,%rsi
0x0000000000001323 <+111>: lea    0xc29(%rip),%rax      # 0x2035
0x0000000000001324 <+118>: mov    %rax,%rdi
0x0000000000001325 <+121>: mov    $0x0,%eax
0x0000000000001326 <+126>: call   0x1000 <_isoc99_scanf@plt>
0x0000000000001327 <+131>: mov    -0x18(%rbp),%edx
0x0000000000001328 <+134>: lea    -0x10(%rbp),%rax
0x0000000000001329 <+138>: mov    %edx,%esi
0x000000000000132a <+140>: mov    %rax,%rdi
0x000000000000132b <+143>: call   0x11a0 <insertnode>
0x000000000000132c <+148>: mov    -0x1c(%rbp),%eax
0x000000000000132d <+151>: lea    -0x1(%rax),%edx
0x000000000000132e <+154>: mov    %edx,-0x1c(%rbp)
0x000000000000132f <+157>: test   %eax,%eax
0x0000000000001330 <+159>: jne     0x13ea <main+84>
0x0000000000001331 <+161>: lea    0xc12(%rip),%rax      # 0x2050
0x0000000000001332 <+168>: mov    %rax,%rdi
0x0000000000001333 <+171>: mov    $0x0,%eax
0x0000000000001334 <+176>: call   0x1000 <printf@plt>
0x0000000000001335 <+181>: lea    -0x18(%rbp),%rax
0x0000000000001336 <+185>: mov    %rax,%rsi
0x0000000000001337 <+188>: lea    0xbdc(%rip),%rax      # 0x2035
0x0000000000001338 <+195>: mov    %rax,%rdi
--Type <RET> for more, q to quit, c to continue without paging--

```

```
//gdb_prog2.c
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct node{
```

```
    int data;
```

```
    struct node *next;
```

```
};
```

```
struct node *head;
```

```
int initList(struct node **head){
```

```
    *head=NULL;
```

```
    return 1;
```

```
}
```

```

int search(struct node **head, int data, struct node **ptrToKey, int *pos){
    if (*head==NULL) return 0;
    *pos=1;
    struct node *ptr=*head;
    for (;ptr!=NULL && ptr->data!=data;ptr=ptr->next){
        *pos=(*pos)+1;
    }
    *ptrToKey=ptr;

    if (!ptr) return 0;
    return 1;
}

```

```

int insert(struct node **head, int position, int data){
    struct node *newnode=(struct node *)malloc(sizeof(struct node));
    if (newnode==NULL) return 0;

    newnode->data=data;
    if (position==1){
        newnode->next=*head;
        *head = newnode;
        return 1;
    }

```

//to make sure there are no duplicate insertions we search if given data is already present in linked list

```

    struct node *ptrToKey=NULL;
    int pos=0;
    if (!search(head, data,&ptrToKey, &pos)){
        struct node *ptr=*head;
        for (int i=1; i<position-1 && ptr!=NULL;i++)

```

```

        ptr=ptr->next;

    if (ptr==NULL) return 0;
    else{
        newnode->next=ptr->next;
        ptr->next=newnode;
        return 1;
    }
}
else{
    printf("Element already present in address: %p \n",ptrToKey);
    return 0;
}
}

```

```

int traverse(struct node *head){
    if (!head){
        printf("NULL \n");
        return 1;
    }

    for (struct node *ptr=head;ptr!=NULL;ptr=ptr->next)
        printf("%d -->",ptr->data);
    printf("NULL \n");
    return 1;
}

```

```

int kFromLast(struct node *head, int k ,int *data){
    if(!head) return 0;
    struct node *fast=head;
    struct node *slow=NULL;
    int i=1;

```

```

while(fast!=NULL && i<=k){
    fast=fast->next;
    i++;
}
if(fast==NULL && i<k) return 0;
slow=head;
while(fast!=NULL){
    slow=slow->next;
    fast=fast->next;
}
*data=slow->data;
return 1;
}

```

```

int main(){
    struct node *head;
    initList(&head);
    int n;

    printf("Enter no of nodes you want to enter data: ");
    scanf("%d",&n);
    int pos=1;
    while (n--){
        int data;
        printf("\nEnter data: ");
        scanf("%d",&data);
        if (!insert(&head,pos++,data)) return 0;
    }

    printf("\nThe current linked list is:\n");
    traverse(head);
}

```



```

int k, data;

printf("Enter kth position from last to find node data: ");

scanf("%d", &k);

kFromLast(head, k, &data);

printf("Data: %d\n",data);

return 0;

}

```

Outputs:

```

veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/w... x veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/w... x veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/w... x veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/w... x
(base) veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/week9$ gcc -g gdb_prog2.c
(base) veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/week9$ ./a.out
Enter no of nodes you want to enter data: 5
Enter data: 1
Enter data: 2
Enter data: 3
Enter data: 4
Enter data: 5
The current linked list is:
1 -->2 -->3 -->4 -->5 -->NULL
Enter kth position from last to find node data: 4
Segmentation fault (core dumped)

```

```

veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/w... x veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/w... x veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/w... x veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/w... x
(base) veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/week9$ gdb ./a.out
GNU gdb (Ubuntu 12.1-0ubuntu1~22.04) 12.1
Copyright (C) 2022 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.
Type "show copying" and "show warranty" for details.
This GDB was configured as "x86_64-linux-gnu".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<https://www.gnu.org/software/gdb/bugs/>.
Find the GDB manual and other documentation resources online at:
<http://www.gnu.org/software/gdb/documentation/>.
For help, type "help".
Type "apropos word" to search for commands related to "word"...
Reading symbols from ./a.out...
(gdb) run
Starting program: /home/veeraja/Desktop/unix_lab/week9/a.out
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
Enter no of nodes you want to enter data: 4
Enter data: 1
Enter data: 2
Enter data: 3
Enter data: 4
The current linked list is:
1 -->2 -->3 -->4 -->NULL
Enter kth position from last to find node data: 3
Program received signal SIGSEGV, Segmentation fault.
0x000055555555540b in kFromLast (head=0x555555559ac0, k=3, data=0xffffffffde40) at gdb_prog2.c:89
89          fast fast next;

```

```

veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/week9
(gdb) list
84         }
85         if(fast == NULL && t==k) return 0;
86         slow = head;
87         while(slow != NULL){
88             slow = slow->next;
89             fast = fast->next;
90         }
91         *data = slow->data;
92         return 1;
93     }
(gdb) break 75
Breakpoint 1 at 0x55555555442: file gdb_prog2.c, line 76.
(gdb) break 81
Breakpoint 2 at 0x5555555546a: file gdb_prog2.c, line 81.
(gdb) break 87
Breakpoint 3 at 0x555555554ab: file gdb_prog2.c, line 87.
(gdb) break 88
Breakpoint 4 at 0x555555554ab: file gdb_prog2.c, line 88.
(gdb) break 89
Breakpoint 5 at 0x555555554ab: file gdb_prog2.c, line 89.
(gdb) break 117
Breakpoint 6 at 0x555555554ee: file gdb_prog2.c, line 117.
(gdb) run
The program being debugged has been started already.
Start it from the beginning? (y or n) y
Starting program: /home/veeraja/Desktop/unix_lab/week9/a.out
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/lib/x86_64-linux-gnu/libthread_db.so.1".
Enter no of nodes you want to enter data: 4
Enter data: 1
Enter data: 2
Enter data: 3
Enter data: 4
The current linked list is:
1 --> 2 --> 3 --> 4 --> NULL
Enter kth position from last to find node data: 3

```

```

veeraja@veeraja-VirtualBox: ~/Desktop/unix_lab/week9
(gdb) next
81         while(fast != NULL && t==k){
(gdb) next
82             fast = fast->next;
(gdb) next
83             t++;
(gdb) next
84         }
(gdb) next
85         if(fast == NULL && t==k) return 0;
(gdb) next
86         slow = head;
(gdb) next
Breakpoint 3, kFromLast (head=0x555555559ac0, k=3, data=0x7fffffffde48) at gdb_prog2.c:87
87         while(slow != NULL){
(gdb) next
Breakpoint 4, kFromLast (head=0x555555559ac0, k=3, data=0x7fffffffde48) at gdb_prog2.c:88
88             slow = slow->next;
(gdb) next
Breakpoint 5, kFromLast (head=0x555555559ac0, k=3, data=0x7fffffffde48) at gdb_prog2.c:89
89             fast = fast->next;
(gdb) next
87         while(slow != NULL){
(gdb) next
Breakpoint 4, kFromLast (head=0x555555559ac0, k=3, data=0x7fffffffde48) at gdb_prog2.c:88
88             slow = slow->next;
(gdb) next
Breakpoint 5, kFromLast (head=0x555555559ac0, k=3, data=0x7fffffffde48) at gdb_prog2.c:89
89             fast = fast->next;
(gdb) next
Program received signal SIGSEGV, Segmentation fault.
0x5555555544b in kFromLast (head=0x555555559ac0, k=3, data=0x7fffffffde48) at gdb_prog2.c:89
89             fast = fast->next;
(gdb) next
^[[A
Program terminated with signal SIGSEGV, Segmentation fault.
The program no longer exists.
(nh) next

```

```

(gdb) disassemble main
Dump of assembler code for function main:
0x000000000014dd <+0>: endbr64
0x000000000014e1 <+4>: push    %rbp
0x000000000014e2 <+5>: mov     %rsp,%rbp
0x000000000014e5 <+8>: sub     $0x20,%rsp
0x000000000014e9 <+12>: mov     %fs:0x28,%rax
0x000000000014f2 <+21>: mov     %rax,-0x8(%rbp)
0x000000000014f6 <+25>: xor     %eax,%eax
0x000000000014f8 <+27>: lea     -0x10(%rbp),%rax
0x000000000014fc <+31>: mov     %rax,%rdi
0x000000000014ff <+34>: call    0x11c9 <initList>
0x00000000001504 <+39>: lea     0xb35(%rip),%rax    # 0x2040
0x00000000001506 <+40>: mov     %rax,%rdi
0x0000000000150a <+44>: mov     $0x0,%eax
0x00000000001513 <+54>: call    0x10b0 <printf@plt>
0x00000000001518 <+59>: lea     -0x20(%rbp),%rax
0x0000000000151c <+63>: mov     %rax,%rsi
0x0000000000151f <+66>: lea     0xb45(%rip),%rax    # 0x206b
0x00000000001526 <+73>: mov     %rax,%rdi
0x00000000001529 <+76>: mov     $0x0,%eax
0x0000000000152e <+81>: call    0x10b0 <scanf@plt>
0x00000000001533 <+86>: movl    $0x1,-0x14(%rbp)
0x00000000001534 <+87>: jmp     0x1175 <main+182>
0x0000000000153c <+95>: lea     0xb2b(%rip),%rax    # 0x206e
0x00000000001543 <+102>: mov     %rax,%rdi
0x00000000001548 <+105>: mov     $0x0,%eax
0x0000000000154b <+108>: call    0x1175 <printf@plt>
0x00000000001558 <+115>: lea     -0x18(%rbp),%rax
0x0000000000155d <+119>: mov     %rax,%rsi
0x00000000001562 <+122>: lea     0xb0d(%rip),%rax    # 0x206b
0x00000000001568 <+129>: mov     %rax,%rdi
0x0000000000156b <+132>: mov     $0x0,%eax
0x0000000000156e <+137>: call    0x10b0 <scanf@plt>
0x0000000000157b <+142>: mov     -0x18(%rbp),%edx
0x0000000000157e <+145>: mov     -0x14(%rbp),%eax
0x0000000000157f <+146>: lea     0x1(%rax),%ecx
0x00000000001584 <+151>: mov     %ecx,-0x14(%rbp)
0x00000000001577 <+154>: lea     -0x10(%rbp),%rcx
0x0000000000157b <+158>: mov     %eax,%esi
--Type <RET> for more, q to quit, c to continue without paging--

```