

```

mysql> use cg_mysql;
Database changed
mysql> -- MySQL Operators
mysql> /* Where clause: It is a fundamental element of select, update, and delete
statements in mysql */
mysql> /* Operator: They are symbols which perform specific task.
/*> Syntax: operand operator operand
/*> Types of Operators:
/*> 1. Arithmetic operators
/*> 2. Comparison operators
/*> 3. Logical operators */
mysql> CREATE TABLE Products (
-> id INT,
-> name VARCHAR(100),
-> price DECIMAL(10,2),
-> qty INT
-> );
Query OK, 0 rows affected (0.13 sec)

```

```

mysql>
mysql>
mysql> INSERT INTO Products VALUES
-> (1, 'Pen', 10.00, 100),
-> (2, 'Notebook', 25.00, 50),
-> (3, 'Pencil', 5.00, 200),
-> (4, 'Eraser', 3.00, 300),
-> (5, 'Marker', 15.00, 80),
-> (6, 'Scale', 20.00, 150),
-> (7, 'Sharpener', 8.00, 120),
-> (8, 'Geometry Box', 120.00, 40),
-> (9, 'Sketch Pen', 60.00, 75),
-> (10, 'Crayons', 90.00, 55);
Query OK, 10 rows affected (0.05 sec)
Records: 10 Duplicates: 0 Warnings: 0

```

```

mysql> show tables;
+-----+
| Tables_in_cg_mysql |
+-----+
| backup_emp          |
| company_staff       |
| departments         |
| doctors             |
| emp                 |
| employees           |
| products            |
| staff               |
| students            |
+-----+
9 rows in set (0.07 sec)

```

```
mysql> select * from tables;
ERROR 1146 (42S02): Table 'cg_mysql.tables' doesn't exist
mysql> select * from products;
```

id	name	price	qty
1	Pen	10.00	100
2	Notebook	25.00	50
3	Pencil	5.00	200
4	Eraser	3.00	300
5	Marker	15.00	80
6	Scale	20.00	150
7	Sharpener	8.00	120
8	Geometry Box	120.00	40
9	Sketch Pen	60.00	75
10	Crayons	90.00	55

10 rows in set (0.00 sec)

```
mysql> -- add 12% tax to the price
mysql> select name,price,price+(price * 0.12) as price_after_tax from products;
```

name	price	price_after_tax
Pen	10.00	11.2000
Notebook	25.00	28.0000
Pencil	5.00	5.6000
Eraser	3.00	3.3600
Marker	15.00	16.8000
Scale	20.00	22.4000
Sharpener	8.00	8.9600
Geometry Box	120.00	134.4000
Sketch Pen	60.00	67.2000
Crayons	90.00	100.8000

10 rows in set (0.04 sec)

```
mysql> select *, price-5 as price_after_discount from products;
```

id	name	price	qty	price_after_discount
1	Pen	10.00	100	5.00
2	Notebook	25.00	50	20.00
3	Pencil	5.00	200	0.00
4	Eraser	3.00	300	-2.00
5	Marker	15.00	80	10.00
6	Scale	20.00	150	15.00
7	Sharpener	8.00	120	3.00
8	Geometry Box	120.00	40	115.00

9	Sketch Pen	60.00	75	55.00
10	Crayons	90.00	55	85.00

10 rows in set (0.00 sec)

```
mysql> select name,price,qty,price*qty as total_inventory_value from products;
```

name	price	qty	total_inventory_value
Pen	10.00	100	1000.00
Notebook	25.00	50	1250.00
Pencil	5.00	200	1000.00
Eraser	3.00	300	900.00
Marker	15.00	80	1200.00
Scale	20.00	150	3000.00
Sharpener	8.00	120	960.00
Geometry Box	120.00	40	4800.00
Sketch Pen	60.00	75	4500.00
Crayons	90.00	55	4950.00

10 rows in set (0.00 sec)

```
mysql> select name,price,price*10 as price_of_10_units from products;
```

name	price	price_of_10_units
Pen	10.00	100.00
Notebook	25.00	250.00
Pencil	5.00	50.00
Eraser	3.00	30.00
Marker	15.00	150.00
Scale	20.00	200.00
Sharpener	8.00	80.00
Geometry Box	120.00	1200.00
Sketch Pen	60.00	600.00
Crayons	90.00	900.00

10 rows in set (0.00 sec)

```
mysql> select * from table where qty%50 != 0;
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'table where qty%50 != 0' at line 1

```
mysql> select * from products where qty%50 != 0;
```

id	name	price	qty
5	Marker	15.00	80
7	Sharpener	8.00	120
8	Geometry Box	120.00	40

9	Sketch Pen	60.00	75
10	Crayons	90.00	55

5 rows in set (0.00 sec)

```
mysql> update table products set qty=qty+2;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that
corresponds to your MySQL server version for the right syntax to use near 'table
products set qty=qty+2' at line 1
mysql> update products set qty=qty+2;
Query OK, 10 rows affected (0.05 sec)
Rows matched: 10  Changed: 10  Warnings: 0
```

```
mysql> select * from products;
```

id	name	price	qty
1	Pen	10.00	102
2	Notebook	25.00	52
3	Pencil	5.00	202
4	Eraser	3.00	302
5	Marker	15.00	82
6	Scale	20.00	152
7	Sharpener	8.00	122
8	Geometry Box	120.00	42
9	Sketch Pen	60.00	77
10	Crayons	90.00	57

10 rows in set (0.00 sec)

```
mysql> update products set price=price-5;
Query OK, 10 rows affected (0.04 sec)
Rows matched: 10  Changed: 10  Warnings: 0
```

```
mysql> select * from products;
```

id	name	price	qty
1	Pen	5.00	102
2	Notebook	20.00	52
3	Pencil	0.00	202
4	Eraser	-2.00	302
5	Marker	10.00	82
6	Scale	15.00	152
7	Sharpener	3.00	122
8	Geometry Box	115.00	42
9	Sketch Pen	55.00	77
10	Crayons	85.00	57

10 rows in set (0.00 sec)

```
mysql> update products set qty=qty*2 where name = 'Eraser';
Query OK, 1 row affected (0.06 sec)
Rows matched: 1  Changed: 1  Warnings: 0
```

```
mysql> select * from products;
```

id	name	price	qty
1	Pen	5.00	102
2	Notebook	20.00	52
3	Pencil	0.00	202
4	Eraser	-2.00	604
5	Marker	10.00	82
6	Scale	15.00	152
7	Sharpener	3.00	122
8	Geometry Box	115.00	42
9	Sketch Pen	55.00	77
10	Crayons	85.00	57

```
10 rows in set (0.00 sec)
```

```
mysql> update products set qty=qty/2 where name = 'Marker';
Query OK, 1 row affected (0.06 sec)
Rows matched: 1  Changed: 1  Warnings: 0
```

```
mysql> select * from products;
```

id	name	price	qty
1	Pen	5.00	102
2	Notebook	20.00	52
3	Pencil	0.00	202
4	Eraser	-2.00	604
5	Marker	10.00	41
6	Scale	15.00	152
7	Sharpener	3.00	122
8	Geometry Box	115.00	42
9	Sketch Pen	55.00	77
10	Crayons	85.00	57

```
10 rows in set (0.00 sec)
```

```
mysql> -- delete from products where qty<100; this results in deletion of rows
where name='Notebook','Marker','Geometry Box','Sketch Pen','Crayons'
```

```
mysql> delete from products where qty<100;
Query OK, 5 rows affected (0.05 sec)
```

```
mysql> select * from products;
```

id	name	price	qty
1	Pen	5.00	102
3	Pencil	0.00	202
4	Eraser	-2.00	604
6	Scale	15.00	152
7	Sharpener	3.00	122

5 rows in set (0.00 sec)

```
mysql> -- Comparison Operators
mysql> -- <,>,<=,>=,==,!=
mysql> -- STEP 1: Create Table
mysql> CREATE TABLE StudentScores (
  -> id INT,
  -> name VARCHAR(100),
  -> subject VARCHAR(50),
  -> marks INT
  -> );
Query OK, 0 rows affected (0.06 sec)
```

```
mysql>
mysql> -- STEP 2: Insert Records
mysql> INSERT INTO StudentScores VALUES
  -> (1, 'Alice', 'Math', 95),
  -> (2, 'Bob', 'Math', 76),
  -> (3, 'Charlie', 'Math', 59),
  -> (4, 'Diana', 'Math', 88),
  -> (5, 'Eve', 'Math', 40),
  -> (6, 'Frank', 'Math', 95),
  -> (7, 'Grace', 'Science', 67),
  -> (8, 'Henry', 'Science', 82),
  -> (9, 'Ivy', 'English', 91),
  -> (10, 'Jack', 'English', 55),
  -> (11, 'Kevin', 'Math', 73),
  -> (12, 'Lily', 'Science', 48),
  -> (13, 'Mia', 'English', 100),
  -> (14, 'Noah', 'Math', 64),
  -> (15, 'Olivia', 'Science', 79);
Query OK, 15 rows affected (0.04 sec)
Records: 15 Duplicates: 0 Warnings: 0
```

```
mysql> select * from StudentScores;
```

id	name	subject	marks
1	Alice	Math	95
2	Bob	Math	76
3	Charlie	Math	59

4	Diana	Math	88
5	Eve	Math	40
6	Frank	Math	95
7	Grace	Science	67
8	Henry	Science	82
9	Ivy	English	91
10	Jack	English	55
11	Kevin	Math	73
12	Lily	Science	48
13	Mia	English	100
14	Noah	Math	64
15	Olivia	Science	79

+-----+
15 rows in set (0.00 sec)

mysql> select * from StudentScores where marks > 80;

id	name	subject	marks
1	Alice	Math	95
4	Diana	Math	88
6	Frank	Math	95
8	Henry	Science	82
9	Ivy	English	91
13	Mia	English	100

+-----+
6 rows in set (0.00 sec)

mysql> select * from StudentScores where marks >= 60;

id	name	subject	marks
1	Alice	Math	95
2	Bob	Math	76
4	Diana	Math	88
6	Frank	Math	95
7	Grace	Science	67
8	Henry	Science	82
9	Ivy	English	91
11	Kevin	Math	73
13	Mia	English	100
14	Noah	Math	64
15	Olivia	Science	79

+-----+
11 rows in set (0.00 sec)

mysql> select * from StudentScores where marks < 50;

id	name	subject	marks
----	------	---------	-------

5	Eve	Math	40
12	Lily	Science	48

2 rows in set (0.00 sec)

```
mysql> select * from StudentScores where marks == 95;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that
corresponds to your MySQL server version for the right syntax to use near '== 95'
at line 1
```

```
mysql> select * from StudentScores where marks = 95;
```

id	name	subject	marks
1	Alice	Math	95
6	Frank	Math	95

2 rows in set (0.00 sec)

```
mysql> select * from StudentScores where marks != 95;
```

id	name	subject	marks
2	Bob	Math	76
3	Charlie	Math	59
4	Diana	Math	88
5	Eve	Math	40
7	Grace	Science	67
8	Henry	Science	82
9	Ivy	English	91
10	Jack	English	55
11	Kevin	Math	73
12	Lily	Science	48
13	Mia	English	100
14	Noah	Math	64
15	Olivia	Science	79

13 rows in set (0.00 sec)

```
mysql> select * from StudentScores where marks <= 60;
```

id	name	subject	marks
3	Charlie	Math	59
5	Eve	Math	40
10	Jack	English	55
12	Lily	Science	48

4 rows in set (0.00 sec)

```
mysql> update StudentScores set marks+10 where marks<50;
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '+10 where marks<50' at line 1

mysql> update StudentScores set marks=marks+10 where marks<50;

Query OK, 2 rows affected (0.03 sec)

Rows matched: 2 Changed: 2 Warnings: 0

mysql> select * from StudentScores;

id	name	subject	marks
1	Alice	Math	95
2	Bob	Math	76
3	Charlie	Math	59
4	Diana	Math	88
5	Eve	Math	50
6	Frank	Math	95
7	Grace	Science	67
8	Henry	Science	82
9	Ivy	English	91
10	Jack	English	55
11	Kevin	Math	73
12	Lily	Science	58
13	Mia	English	100
14	Noah	Math	64
15	Olivia	Science	79

15 rows in set (0.00 sec)

mysql> update StudentScores set marks=marks+15 where marks<=60;

Query OK, 4 rows affected (0.03 sec)

Rows matched: 4 Changed: 4 Warnings: 0

mysql> select * from StudentScores;

id	name	subject	marks
1	Alice	Math	95
2	Bob	Math	76
3	Charlie	Math	74
4	Diana	Math	88
5	Eve	Math	65
6	Frank	Math	95
7	Grace	Science	67
8	Henry	Science	82
9	Ivy	English	91
10	Jack	English	70
11	Kevin	Math	73
12	Lily	Science	73
13	Mia	English	100

14	Noah	Math	64
15	Olivia	Science	79

15 rows in set (0.00 sec)

```
mysql> update StudentScores set marks=marks-10 where marks<=60;
Query OK, 0 rows affected (0.00 sec)
Rows matched: 0  Changed: 0  Warnings: 0
```

```
mysql> select * from StudentScores;
```

id	name	subject	marks
1	Alice	Math	95
2	Bob	Math	76
3	Charlie	Math	74
4	Diana	Math	88
5	Eve	Math	65
6	Frank	Math	95
7	Grace	Science	67
8	Henry	Science	82
9	Ivy	English	91
10	Jack	English	70
11	Kevin	Math	73
12	Lily	Science	73
13	Mia	English	100
14	Noah	Math	64
15	Olivia	Science	79

15 rows in set (0.00 sec)

```
mysql> update StudentScores set marks=marks+2 where marks>90;
Query OK, 4 rows affected (0.04 sec)
Rows matched: 4  Changed: 4  Warnings: 0
```

```
mysql> select * from StudentScores;
```

id	name	subject	marks
1	Alice	Math	97
2	Bob	Math	76
3	Charlie	Math	74
4	Diana	Math	88
5	Eve	Math	65
6	Frank	Math	97
7	Grace	Science	67
8	Henry	Science	82
9	Ivy	English	93
10	Jack	English	70
11	Kevin	Math	73

12	Lily	Science	73
13	Mia	English	102
14	Noah	Math	64
15	Olivia	Science	79

15 rows in set (0.00 sec)

```
mysql> update StudentScores set marks=marks+3 where marks>=80;
```

Query OK, 6 rows affected (0.03 sec)

Rows matched: 6 Changed: 6 Warnings: 0

```
mysql> select * from StudentScores;
```

id	name	subject	marks
1	Alice	Math	100
2	Bob	Math	76
3	Charlie	Math	74
4	Diana	Math	91
5	Eve	Math	65
6	Frank	Math	100
7	Grace	Science	67
8	Henry	Science	85
9	Ivy	English	96
10	Jack	English	70
11	Kevin	Math	73
12	Lily	Science	73
13	Mia	English	105
14	Noah	Math	64
15	Olivia	Science	79

15 rows in set (0.00 sec)

```
mysql> update StudentScores set marks=marks-1 where marks=95;
```

Query OK, 0 rows affected (0.00 sec)

Rows matched: 0 Changed: 0 Warnings: 0

```
mysql> update StudentScores set marks=marks-1 where marks!=95;
```

Query OK, 15 rows affected (0.01 sec)

Rows matched: 15 Changed: 15 Warnings: 0

```
mysql> update StudentScores set marks=100 where marks=95;
```

Query OK, 1 row affected (0.03 sec)

Rows matched: 1 Changed: 1 Warnings: 0

```
mysql> select * from StudentScores;
```

id	name	subject	marks
1	Alice	Math	99

2	Bob	Math	75
3	Charlie	Math	73
4	Diana	Math	90
5	Eve	Math	64
6	Frank	Math	99
7	Grace	Science	66
8	Henry	Science	84
9	Ivy	English	100
10	Jack	English	69
11	Kevin	Math	72
12	Lily	Science	72
13	Mia	English	104
14	Noah	Math	63
15	Olivia	Science	78

+-----+
15 rows in set (0.00 sec)

mysql> delete from StudentScores where marks<50;
Query OK, 0 rows affected (0.00 sec)

mysql> select * from StudentScores;

id	name	subject	marks
1	Alice	Math	99
2	Bob	Math	75
3	Charlie	Math	73
4	Diana	Math	90
5	Eve	Math	64
6	Frank	Math	99
7	Grace	Science	66
8	Henry	Science	84
9	Ivy	English	100
10	Jack	English	69
11	Kevin	Math	72
12	Lily	Science	72
13	Mia	English	104
14	Noah	Math	63
15	Olivia	Science	78

+-----+
15 rows in set (0.00 sec)

mysql> delete from StudentScores where marks<=60;
Query OK, 0 rows affected (0.00 sec)

mysql> select * from StudentScores;

id	name	subject	marks
1	Alice	Math	99

2	Bob	Math	75
3	Charlie	Math	73
4	Diana	Math	90
5	Eve	Math	64
6	Frank	Math	99
7	Grace	Science	66
8	Henry	Science	84
9	Ivy	English	100
10	Jack	English	69
11	Kevin	Math	72
12	Lily	Science	72
13	Mia	English	104
14	Noah	Math	63
15	Olivia	Science	78

+-----+
15 rows in set (0.00 sec)

mysql> delete from StudentScores where marks>90;
Query OK, 4 rows affected (0.06 sec)

mysql> select * from StudentScores;

id	name	subject	marks
2	Bob	Math	75
3	Charlie	Math	73
4	Diana	Math	90
5	Eve	Math	64
7	Grace	Science	66
8	Henry	Science	84
10	Jack	English	69
11	Kevin	Math	72
12	Lily	Science	72
14	Noah	Math	63
15	Olivia	Science	78

+-----+
11 rows in set (0.00 sec)

mysql> delete from StudentScores where marks!=95;
Query OK, 11 rows affected (0.07 sec)

mysql> select * from StudentScores;
Empty set (0.00 sec)

mysql> delete from StudentScores where marks=76;
Query OK, 0 rows affected (0.00 sec)

mysql> select * from StudentScores;
Empty set (0.00 sec)

```

mysql> -- Logical Operators
mysql> /* logical and : if both true return true or else false
/*>    logical or  : if both false return false or else true
/*>    logical not : if true return false (negation)
/*> */
mysql> show tables;
+-----+
| Tables_in_cg_mysql |
+-----+
| backup_emp          |
| company_staff       |
| departments         |
| doctors             |
| emp                 |
| employees            |
| products            |
| staff               |
| students            |
| studentscores       |
+-----+
10 rows in set (0.01 sec)

mysql> CREATE TABLE Employees (
-> id INT,
-> name VARCHAR(100),
-> department VARCHAR(100),
-> salary INT,
-> isactive BOOLEAN
-> );
ERROR 1050 (42S01): Table 'employees' already exists
mysql>
mysql> -- STEP 2: Insert Records
mysql> INSERT INTO Employees VALUES
-> (1, 'Rahul Sharma', 'IT', 50000, TRUE),
-> (2, 'Priya Reddy', 'HR', 30000, TRUE),
-> (3, 'Amit Kumar', 'Finance', 45000, FALSE),
-> (4, 'Sneha Patel', 'IT', 35000, TRUE),
-> (5, 'Vikram Singh', 'Finance', 28000, TRUE),
-> (6, 'Anjali Mehta', 'HR', 32000, FALSE),
-> (7, 'Kiran Rao', 'IT', 60000, TRUE),
-> (8, 'Pooja Verma', 'Marketing', 27000, TRUE),
-> (9, 'Ramesh Naidu', 'Sales', 38000, TRUE),
-> (10, 'Deepika Joshi', 'Finance', 52000, TRUE),
-> (11, 'Suresh Babu', 'Marketing', 29000, FALSE),
-> (12, 'Neha Kapoor', 'HR', 41000, TRUE),
-> (13, 'Arjun Reddy', 'IT', 55000, FALSE),
-> (14, 'Lakshmi Devi', 'Sales', 33000, TRUE),
-> (15, 'Nikhil Jain', 'IT', 47000, TRUE);
ERROR 1136 (21S01): Column count doesn't match value count at row 1
mysql> drop table employees;

```

Query OK, 0 rows affected (0.10 sec)

```
mysql> CREATE TABLE Employees (  
-> id INT,  
-> name VARCHAR(100),  
-> department VARCHAR(100),  
-> salary INT,  
-> isactive BOOLEAN  
-> );
```

Query OK, 0 rows affected (0.10 sec)

mysql>

mysql> -- STEP 2: Insert Records

```
mysql> INSERT INTO Employees VALUES  
-> (1, 'Rahul Sharma', 'IT', 50000, TRUE),  
-> (2, 'Priya Reddy', 'HR', 30000, TRUE),  
-> (3, 'Amit Kumar', 'Finance', 45000, FALSE),  
-> (4, 'Sneha Patel', 'IT', 35000, TRUE),  
-> (5, 'Vikram Singh', 'Finance', 28000, TRUE),  
-> (6, 'Anjali Mehta', 'HR', 32000, FALSE),  
-> (7, 'Kiran Rao', 'IT', 60000, TRUE),  
-> (8, 'Pooja Verma', 'Marketing', 27000, TRUE),  
-> (9, 'Ramesh Naidu', 'Sales', 38000, TRUE),  
-> (10, 'Deepika Joshi', 'Finance', 52000, TRUE),  
-> (11, 'Suresh Babu', 'Marketing', 29000, FALSE),  
-> (12, 'Neha Kapoor', 'HR', 41000, TRUE),  
-> (13, 'Arjun Reddy', 'IT', 55000, FALSE),  
-> (14, 'Lakshmi Devi', 'Sales', 33000, TRUE),  
-> (15, 'Nikhil Jain', 'IT', 47000, TRUE);
```

Query OK, 15 rows affected (0.01 sec)

Records: 15 Duplicates: 0 Warnings: 0

mysql> select * from employees;

id	name	department	salary	isactive
1	Rahul Sharma	IT	50000	1
2	Priya Reddy	HR	30000	1
3	Amit Kumar	Finance	45000	0
4	Sneha Patel	IT	35000	1
5	Vikram Singh	Finance	28000	1
6	Anjali Mehta	HR	32000	0
7	Kiran Rao	IT	60000	1
8	Pooja Verma	Marketing	27000	1
9	Ramesh Naidu	Sales	38000	1
10	Deepika Joshi	Finance	52000	1
11	Suresh Babu	Marketing	29000	0
12	Neha Kapoor	HR	41000	1
13	Arjun Reddy	IT	55000	0
14	Lakshmi Devi	Sales	33000	1

15	Nikhil Jain	IT	47000	1
----	-------------	----	-------	---

15 rows in set (0.00 sec)

```
mysql> select * from employees where department='IT' and salary>40000;
```

id	name	department	salary	isactive
1	Rahul Sharma	IT	50000	1
7	Kiran Rao	IT	60000	1
13	Arjun Reddy	IT	55000	0
15	Nikhil Jain	IT	47000	1

4 rows in set (0.00 sec)

```
mysql> select * from employees where department='HR' or salary<35000;
```

id	name	department	salary	isactive
2	Priya Reddy	HR	30000	1
5	Vikram Singh	Finance	28000	1
6	Anjali Mehta	HR	32000	0
8	Pooja Verma	Marketing	27000	1
11	Suresh Babu	Marketing	29000	0
12	Neha Kapoor	HR	41000	1
14	Lakshmi Devi	Sales	33000	1

7 rows in set (0.00 sec)

```
mysql> select * from employees where department not 'HR';
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near ''HR'' at line 1

```
mysql> select * from employees where department != 'HR';
```

id	name	department	salary	isactive
1	Rahul Sharma	IT	50000	1
3	Amit Kumar	Finance	45000	0
4	Sneha Patel	IT	35000	1
5	Vikram Singh	Finance	28000	1
7	Kiran Rao	IT	60000	1
8	Pooja Verma	Marketing	27000	1
9	Ramesh Naidu	Sales	38000	1
10	Deepika Joshi	Finance	52000	1
11	Suresh Babu	Marketing	29000	0
13	Arjun Reddy	IT	55000	0
14	Lakshmi Devi	Sales	33000	1
15	Nikhil Jain	IT	47000	1

12 rows in set (0.00 sec)

```
mysql> select * from employees where not department='HR';
```

id	name	department	salary	isactive
1	Rahul Sharma	IT	50000	1
3	Amit Kumar	Finance	45000	0
4	Sneha Patel	IT	35000	1
5	Vikram Singh	Finance	28000	1
7	Kiran Rao	IT	60000	1
8	Pooja Verma	Marketing	27000	1
9	Ramesh Naidu	Sales	38000	1
10	Deepika Joshi	Finance	52000	1
11	Suresh Babu	Marketing	29000	0
13	Arjun Reddy	IT	55000	0
14	Lakshmi Devi	Sales	33000	1
15	Nikhil Jain	IT	47000	1

12 rows in set (0.00 sec)

```
mysql> select * from employees where department='Finance' or (salary>30000 and isactive=1);
```

id	name	department	salary	isactive
1	Rahul Sharma	IT	50000	1
3	Amit Kumar	Finance	45000	0
4	Sneha Patel	IT	35000	1
5	Vikram Singh	Finance	28000	1
7	Kiran Rao	IT	60000	1
9	Ramesh Naidu	Sales	38000	1
10	Deepika Joshi	Finance	52000	1
12	Neha Kapoor	HR	41000	1
14	Lakshmi Devi	Sales	33000	1
15	Nikhil Jain	IT	47000	1

10 rows in set (0.00 sec)

```
mysql> notee
```