Gemma 4 Gives Its Failing Patches Full Marks

Sugam Panthi University of Southern Mississippi

github.com/Vein05/gemma4-paper-track Supplement: `rubber-stamp-supplement.pdf` Kaggle paper track

Abstract

Coding agents often decide whether a patch is finished by asking the model that wrote it. This check assumes that the model judges its own patches as well as other models' patches. Earlier work found that most judges favor their own contest programs, but Gemma 3 12B and 27B do not. In this work, we ask Gemma 4 31B and other models to score SWE-bench Verified patches without naming their writer, and we compare each judge with judges from other model families on the same patch. Gemma gives its top score to 52 of its 85 failing patches, while the other judges score the same patches lower. Most small open models we tested are also lenient on their own contest programs. Five large models show no leniency on their own repository patches. On one of two data sets, Gemma also trusts other models' failing patches that make the same edit. The trust stays when Gemma thinks before scoring, tests the patch in a shell, or is fine-tuned on labeled patches. When an agent shows Gemma the repository tests that its patch breaks, Gemma repairs 9 of the 52, but it also breaks 4 correct patches. Gemma's score alone should not decide whether its patch is finished. We release everything we ran, including every agent and judge trace, on GitHub and Hugging Face.

1 Introduction

In matplotlib issue 24570, Gemma 4 31B wrote a patch that fixes the reported alignment bug but also swaps the left and right cases of a shared helper. When we later asked Gemma whether this patch would pass the project's hidden tests, it gave the highest score on our 0 to 100 scale and called the patch "a simple swap" that "correctly implements the expected behavior". GLM-4.5 scored the same patch 20 because it "breaks VPacker by reversing left and right", and the hidden tests for left and right alignment fail. Coding agents make this call at the end of every task, and many make it by asking the model that wrote the patch.

We call this failure rubber-stamping: a judge gives its own failing patch the top score. On LiveCodeBench contest programs, Pombal et al. (2026) found that most judges favor their own programs, but Gemma 3 12B and 27B do not. On the same benchmark, Gemma 4 31B gives the top score to half of its failing programs and to 8% of other writers'. It also rubber-stamps on SWE-bench Verified issues it attempted with mini-SWE-agent, and on another team's Gemma run on SWE-bench Lite. We compare Gemma with outside judges, models from families other than Gemma that score the same patches, and they do not share this trust.

Gemma is not lenient in general, since it scores other writers' failing patches below the outside judges. On Lite, it also trusts failing patches from other models that make the same edit as its own. One reading is that Gemma trusts the fix itself, but we cannot rule out that it recognizes its own patches. Checks that Gemma runs itself mostly leave the trust in place. Showing Gemma the repository tests its patch breaks repairs more patches than a plain second look.

We make the following contributions:

- **Gemma 4 31B rubber-stamps its failing patches.** On held-out SWE-bench Verified issues, it gives the top score to 52 of its 85 failing patches, while outside judges score the same patches lower. Five of six other

small open models are also lenient on their own contest programs. Five large models show no leniency on their own repository patches (Section 3.1).

- **Gemma's trust reaches other writers' patches that make its edit.** On SWE-bench Lite, Gemma's extra trust in those patches over other failing patches is 20 points. The same test on our held-out issues is inconclusive (Section 3.2).
- **Tests that Gemma did not write let it repair some patches.** Shown the repository tests its patch breaks, Gemma repairs 9 of the 52 rubber-stamped failing patches, against 3 after a plain second look. The same step breaks 4 correct patches (Section 3.4).

2 Setup

Patches. The main data set is 193 held-out issues, a random sample of SWE-bench Verified issues (Jimenez et al., 2023) outside SWE-bench Verified Mini (MariusHobbhahn). We call the model that wrote a patch its writer. The 4-bit competition checkpoint of Gemma 4 31B made one attempt per issue in mini-SWE-agent v1.7.0 (SWE-agent) at temperature 0, and we graded its patches with SWE-bench's grading code. We kept an issue only if its reference patch passes in our environment, which kept 193 of 200. Other writers' patches are public mini-SWE-agent submissions (SWE-bench experiments) by GLM-4.5, gpt-oss-120b, Kimi-K2, Llama-4-Maverick and Qwen3-Coder, with their official labels. We removed test files from every patch and dropped very long patches.

Two more data sets test whether the result depends on our run. Another team ran Gemma 4 31B on the 300 SWE-bench Lite issues, in mini-SWE-agent 2.2.1 at full precision with thinking on. LiveCodeBench is a different kind of task: our checkpoint wrote one program per contest problem with no agent. On the 50 Mini issues, Gemma's patches from four public harnesses (n-pelleriti), including SWE-agent (Yang et al., 2024), give the same picture (Supplement, Section C).

Judges. Nine models scored every held-out patch: Gemma 4 31B, gpt-oss-20b, Qwen3.5-9B, GLM-4.7-Flash and the five writers above. Each judge saw the issue and one patch, without its writer, and scored the chance that the patch passes the hidden tests from 0 to 100. Calls went through OpenRouter at temperature 0 with reasoning off, except for gpt-oss, which always reasons and ran at low effort. Credit limits left fewer judges on Lite and LiveCodeBench, before any score was read.

Measures. A judge's score on a failing patch says little alone, because some failing patches look right to everyone. We therefore measure how far a judge scores each patch above the outside judges' mean on that patch. Extra trust is how much further above them a judge scores one group of failing patches than other writers' failing patches, unless we name another comparison group. A judge with extra trust in its own failing patches is lenient on them. We report 95% intervals from 2,000 bootstrap resamples of issues. The rubber-stamp rate is the share of a judge's own failing patches that it scores 100.

Plans. We committed a written plan, with the rule for reading its result, before computing each test. We mark as exploratory every analysis chosen after we saw a result.

3 Results




Figure 1. (a) Gemma's scores on failing patches, its own and other writers', on three data sets. (b) Extra trust in failing patches, in score points with 95% intervals. In the two same-edit rows, the comparison is other writers' failing patches without Gemma's edit.

3.1 Gemma rubber-stamps its failing patches

Gemma gives 100 to about half or more of its failing patches on all three data sets, and to far fewer of other writers' failing patches (Figure 1a). The outside judges do not share this trust. On the held-out issues, Gemma's extra trust in its own failing patches is 16.6 points [10.3, 23.1]. The same holds on Lite and LiveCodeBench, where both intervals lie above zero. Gemma's failing patches do look a little better to everyone, so we also compared them only with other writers' failing patches that the outside judges score the same. The held-out extra trust is still +13.6, and its interval stays above zero (exploratory, Supplement, Sections C and D).

The failure reaches beyond this one model. On LiveCodeBench, five of six other usable small open models, including Gemma 4 12B and 26B-A4B, are lenient on their own failing programs, and Gemma 4 31B has the largest estimate (Figure 2). These models share no outside panel, so Qwen3-32B is the only reference judge here. Seed-OSS-36B gives 100 to most failing programs, its own or not.

Five large models judged their own held-out patches in the same way, and none shows extra trust like Gemma's (exploratory, Figure 1b, Supplement, Section C).

3.2 The trust reaches other writers' patches that make Gemma's edit

Gemma could trust its patches because it recognizes them as its own, or because it believes in the edit they make. We fixed a test before computing it, and it needed support from both data sets. We split other writers' failing patches by whether they change nearly the same lines as Gemma's failing patch for that issue. On Lite, Gemma's extra trust in the same-edit patches over the others is 20.0 points (Figure 1b). On the held-out issues the estimate is smaller, and its interval reaches zero. We detect no extra trust in Gemma's own patch beyond these same-edit patches on either set, but few issues have both kinds of patch. The edit explanation




Figure 2. Extra trust (exploratory) is own failing minus other writers' failing programs, in score points above Qwen3-32B. We set aside GLM-4-9B and Phi-4-mini after reading their results, because they pass almost no problems (Supplement, Section C).

is therefore supported on Lite and inconclusive on the held-out issues (Supplement, Section D).

Gemma 4 12B and 26B-A4B scored the 31B's held-out patches. We find no measurable extra trust in the 31B's failing patches over other writers' failing patches (Figure 1b). These two models are lenient on their own contest programs (Figure 2), so the two results answer different questions (Supplement, Section D).

The trust is not limited to Gemma's own fixes. On Lite, Gemma trusts failing patches by Claude 4 Sonnet, one of that data set's other writers, about as much as its own (Supplement, Section C). Our data cannot tell the fix Gemma would write from the fix most strong models would write. We also never varied the writer with the patch held fixed, so we cannot rule out that Gemma recognizes its own patches.

3.3 Checking harder through Gemma leaves the trust in place

A check that Gemma runs itself may inherit this trust. We tested four such checks.

Check run by Gemma	What happens to Gemma's failing patches
Thinking before scoring (Mini issues)	still scores 62% of its failing patches 100, against 61% without thinking
Its own reproduction script, written while fixing the issue	the last run ends without an error in almost all failing runs that ran one
A shell with the patch applied; Gemma must write a test that fails without it	on the 52 failing held-out patches it had scored 100, still scores 80% at 100
LoRA fine-tuning on labeled patches from other issues	on separate held-out and Lite issues, still accepts almost all the failing patches it had scored 100

Gemma had a working environment, and in most of its runs on failing patches it wrote a test that fails without the patch and passes with it. The shell lowers Gemma's score more often on failing patches than on passing ones, but it separates them only slightly (AUROC 0.58). The LoRA adapter did not reduce the failing patches Gemma accepts on new issues by a measurable amount (one seed, Supplement, Section E).

3.4 Tests that Gemma did not write let it repair some patches

The repository's existing tests encode what the project's developers expected. We gave the agent a check that needs no hidden test and no second model. It picks the existing tests whose files or functions match the changed code, runs them twice before the patch and once after, and holds back the patch if a test that passed both times now fails or disappears. A held-back patch gets one more Gemma run in mini-SWE-agent. In one condition Gemma sees the broken tests and their output, and in the other it gets a plain second look at its patch. We graded every result with the hidden tests (Supplement, Section F).




Figure 3. Showing Gemma the tests its patch breaks repairs 9 of its 52 rubber-stamped failing patches and breaks 4 of its 81 correct ones. Each dot is one of the 133 held-out patches Gemma scored 100: filled if it passes the hidden tests, hollow if it fails. The grey band marks the patches the check held back, and only these got a repair run.

The check holds back 15 of the 52 failing patches Gemma scored 100. In almost all of these, the broken test passes with the reference patch, so these are real regressions that Gemma missed.

On all held-back failing patches, the tests repair more than a second look (one-sided sign test, $p = 0.004$), which meets the reading we fixed before the run. Among the 52 patches it scored 100, the tests repair nine and a second look repairs three.

The repair has a cost. Some existing tests assert the old behavior that the issue asks to change, so the check also holds back about one in ten correct patches. By our plan, that is too many to count the check alone as a fix. Shown such a test, Gemma often obeys it. In 3 of the 4 correct patches it broke, the broken test also fails with the reference patch, and Gemma restored the old behavior to make it pass. On sympy issue 12481 it wrote that it had "re-introduced the disjointness check to make `test_args` pass, although this contradicts the PR description". Among the 133 patches Gemma scored 100, the repair fixes nine and breaks four, so five fewer fail.

4 Related work

The closest work is Pombal et al. (2026). They asked judges whether a LiveCodeBench program passes each unit test, and most judges wrongly pass their own programs more often than other families' programs. Gemma 3 4B does too, while 12B and 27B do not. We score whole programs and did not run Gemma 3, so we cannot say whether the model or the measure explains the difference from Gemma 4 31B. In their data, gpt-oss-120b and Llama-4-Maverick do this too, yet we detect no extra trust in either on its own repository

patches. On contest programs, our measure finds Llama-4-Maverick lenient and gpt-oss-120b not (exploratory, Supplement, Section C).

Other work on judges that favor their own outputs uses mostly text and short programs. Panickssery et al. (2024) link this self-preference to how well a model recognizes its own summaries. Roytburg et al. (2026) compare a judge's own wrong answers with other models' wrong answers to the same question, and much of the measured self-preference goes away.

Khullar et al. (2026) find that one model rates a SWE-bench patch as more correct when it is framed as its own earlier answer. In our setting, the judge sees no authorship cue, and the patches come from full agent runs. SWE-Gym (Pan et al., 2024) and R2E-Gym (Jain et al., 2025) fine-tune verifiers that choose among attempts at one issue.

5 Limitations

All our data are Python code. The repair covers Gemma 4 31B only, and its result comes from one run per patch with one seed. In our held-out runs the repository's Python environment was not active, so Gemma often could not import the code while writing its patch. This lowers its resolve rate, but its rubber-stamp rate is similar on the runs without this problem and on the Lite and Mini runs, which were made elsewhere.

6 Conclusion

Gemma 4 31B gives its top score to 52 of its 85 failing patches, and the outside judges score the same patches lower. Checks that Gemma runs itself mostly leave this trust in place. The repository's existing tests catch some of these patches, and seeing the broken tests lets Gemma repair nine of the 52, at the cost of four correct patches. An agent built on Gemma should not let Gemma's score alone decide that a patch is finished. It should run the project's existing tests, and someone other than Gemma should decide when such a test conflicts with the issue.

7 Data, code and compute

The GitHub repository holds the paper, the supplement, all code, every analysis plan, every judge answer and the summary behind each number. The Hugging Face dataset holds the raw runs, including every agent run and judge prompt. The project used about 74 GPU-hours. At RunPod on-demand prices this compute costs about $122.

References

Naman Jain, Jaskirat Singh, Manish Shetty, Liang Zheng, Koushik Sen and Ion Stoica. 2025. *R2E-Gym: Procedural Environments and Hybrid Verifiers for Scaling Open-Weights SWE Agents*. https://arxiv.org/abs/2504.07164.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press and Karthik Narasimhan. 2023. *SWE-bench: Can Language Models Resolve Real-World GitHub Issues?* https://arxiv.org/abs/2310.06770. ICLR 2024 (arXiv comment, https://openreview.net/forum?id=VTF8yNQM66).

Dipika Khullar, Jack Hopkins, Rowan Wang and Fabien Roger. 2026. *Self-Attribution Bias: When AI Monitors Go Easy on Themselves*. https://arxiv.org/abs/2603.04582.

MariusHobbhahn. *swe-bench-verified-mini*. https://huggingface.co/datasets/MariusHobbhahn/swe-bench-verified-mini. Hugging Face dataset; revision b316c349; accessed 2026-10-05.

n-pelleriti. *AlphaDiana Gemma 4 agent-run datasets*. https://huggingface.co/n-pelleriti. Six Hugging Face datasets; accessed 2026-10-05.

Jiayi Pan, Xingyao Wang, Graham Neubig, Navdeep Jaitly, Heng Ji, Alane Suhr and Yizhe Zhang. 2024. *Training Software Engineering Agents and Verifiers with SWE-Gym*. https://arxiv.org/abs/2412.21139. ICML 2025 (arXiv comment).

Arjun Panickssery, Samuel R. Bowman and Shi Feng. 2024. *LLM Evaluators Recognize and Favor Their Own Generations*. https://arxiv.org/abs/2404.13076.

José Pombal, Ricardo Rei and André F. T. Martins. 2026. *Self-Preference Bias in Rubric-Based Evaluation of Large Language Models*. https://arxiv.org/abs/2604.06996.

Dani Roytburg, Matthew Bozoukov, Matthew Nguyen, Jou Barzdukas, Mackenzie Puig-Hall and Narmeen Oozeer. 2026. *Are LLM Evaluators Really Narcissists? Sanity Checking Self-Preference Evaluations*. https://arxiv.org/abs/2601.22548. ICML 2026 Main.

SWE-agent. *mini-SWE-agent*. https://github.com/SWE-agent/mini-swe-agent. GitHub repository; accessed 2026-10-05.

SWE-bench. *SWE-bench experiments*. https://github.com/SWE-bench/experiments. GitHub repository; patches from the swe-bench-submissions bucket; revision 40f164d5; accessed 2026-10-05.

John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan and Ofir Press. 2024. *SWE-agent: Agent-Computer Interfaces Enable Automated Software Engineering*. https://arxiv.org/abs/2405.15793.