ARCH LINUX INSTALLATION AND CONFIGURATION

Veit Karpf

December 9, 2018

Contents

1	BASIC SYSTEM INSTALL 1.1 Load keyboard	2
	1.2 Disk partitioning and mounting	2
	1.3 setup network connection (wifi-menu)	2
	1.4 install base system	2
	1.5 exit chroot and boot into new system	3
2	add user and choose group	3
3	CUSTOMIZE SYSTEM	3
	3.1 install packages	3
	3.2 install yay (aur helper)	3
	3.3 aur packages	3
	3.4 install configs	4
	3.5 install lightdm greeter (login/display manager)	4
4	LAPTOP/NOTEBOOK SPECIFIC	4
5	DUAL BOOTING WITH WINDOWS	4
	5.1 setting windows to UTC instead of localtime:	4
	5.2 disable fast startup	4
	5.3 Mount Windows partition on boot	4
6	ADDITIONAL SETTINGS	5
	6.1 pacman stuff:	5
	6.2 vim stuff:	5
	6.3 have a look at tlp	5
	6.4 pywal:	5
	6.5 Fixing Invalid MIT-MAGIC-COOKIE-1:	5
7	PROGRAMMS FOR CERTAIN TASKS	5
8	USEFULL COMMANDS	5

1 BASIC SYSTEM INSTALL

1.1 Load keyboard

loadkeys de_CH-latin1

1.2 Disk partitioning and mounting

```
(gpt -> gdisk, mbr -> fdisk)
gdisk /dev/sdx
# code root: 8300
# code home: 8300
# code swap: 8200

(mkfs.fat -F 32 -n EFIBOOT /dev/sdx#)
mkfs.ext4 -L ARCH_ROOT /dev/sdx#
mkfs.ext4 -L ARCH_HOME /dev/sdx#
mkswap -L ARCH_SWAP /dev/sdx#
mount -L ARCH_SWAP /dev/sdx#
mount -L ARCH_HOME /mnt/home
mount -L ARCH_HOME /mnt/home
mount -L ARCH_BOOT /mnt/boot
swapon -L ARCH_SWAP
```

1.3 setup network connection (wifi-menu)

git clone https://github.com/Veit96/dotfiles.git dotfiles

wifi-menu

get scripts

1.4 install base system

launch second script

choose hostname, default "arch"

```
# launch first script
# choose mirror
./script_install1.sh

# configure fstab, the options should be like this (for SSD):
root: rw,defaults,noatime,discard 0 1
boot: rw,noatime,fmask=0022,dmask=0022,codepage=437,iocharset=iso8859-1,shortname=mixed,utf8,error home: rw,defaults,noatime,discard 0 2
swap: defaults,noatime,discard,pri=-2 0 0
# change root to new system
arch-chroot /mnt/
```

```
# in /etc/locale.gen uncomment all en_US, de_CH, de_DE
./script_install2.sh
```

1.5 exit chroot and boot into new system

```
exit
umount -R /mnt
reboot
# login as root
```

2 add user and choose group

```
useradd -m -g users -s /bin/bash user_name
passwd user_name
vim /etc/sudoers
%wheel ALL=(ALL) ALL
gpasswd -a user_name wheel
gpasswd -a user_name audio
# add to audio, video, games, power too?
pacman -S acpid dbus avahi cronie
systemctl enable acpid
systemctl enable avahi-daemon
systemctl enable cronie
systemctl enable org.cups.cupsd.service
systemctl enable NetworkManager.service
systemctl enable systemd-timesyncd.service
systemctl start systemd-timesyncd.service
hwclock -w
```

3 CUSTOMIZE SYSTEM

3.1 install packages

```
pacman -S $(< my_packages.txt)</pre>
```

3.2 install yay (aur helper)

```
git clone https://aur.archlinux.org/yay.git
cd yay
makepkg -si
cd ..
rm -rf yay
```

3.3 aur packages

• urxvt-resize-font-git

- polybar
- mons
- spotify
- popcorntime
- arch-silence-grub-theme

3.4 install configs

```
pacman -S git
mkdir .dotfiles
git clone https://github.com/Veit96/dotfiles.git .dotfiles
cd .dotfiles
./install
```

3.5 install lightdm greeter (login/display manager)

```
systemctl enable lightdm.service
/etc/lightdm/lightdm.conf
[Seat:*]
...
greeter-session=lightdm-webkit2-greeter
...
/etc/lightdm/lightdm-webkit2-greeter.conf
...
webkit-theme = litarvan
```

4 LAPTOP/NOTEBOOK SPECIFIC

5 DUAL BOOTING WITH WINDOWS

5.1 setting windows to UTC instead of localtime:

reg add "HKEY_LOCAL_MACHINE\System\CurrentControlSet\Control\TimeZoneInformation" /v RealTimeIsUniversal /d 1 /t REG_DWORD /f

5.2 disable fast startup

- 1. go to windows power settings
- 2. go to additional settings
- 3. go to what power buttons do
- 4. uncheck fast startup

5.3 Mount Windows partition on boot

Add the following to your /etc/fstab, where /dev/sdxy is the ntfs windows partition to be mounted: # /dev/sdxy UUID=... LABEL=share /home/veit/share ntfs-3g utf8,uid=1000,gid=1000,dmask=027,fmask=137 0 2

6 ADDITIONAL SETTINGS

6.1 pacman stuff:

uncomment "#Color" for color pacman add aur

6.2 vim stuff:

- vim-jedi
- vim-jellybeans
- vim-latexsuite
- vim-spell-de
- vim-supertab

6.3 have a look at tlp

6.4 pywal:

wal -i image.png

6.5 Fixing Invalid MIT-MAGIC-COOKIE-1:

This was needed to launch the graphical matlab installer from terminal with sudo privileges uncomment Defaults env_keep += "HOME" in /etc/sudoers

7 PROGRAMMS FOR CERTAIN TASKS

- display manager / login manager -> lightdm
- window manager -> i3
- $shell \rightarrow zsh$
- terminal -> rxvt-unicode
- app launcher -> rofi, dmenu
- aur helper -> yay
- file manager \rightarrow ranger
- \bullet browser -> qutebrowser
- wallpaper setter -> nitrogen, wal
- image viewer -> sxiv
- pdf viewer -> zathura, okular
- office ->
- video/audo player -> smplayer, mpv
- \bullet system monitoring -> deepin-system-monitor
- offline docs browser \rightarrow zeal
- firewall -> ufw
- BitTorrent client -> transmission
- Screenshot -> deepin-screenshot

8 USEFULL COMMANDS

• connect to ethernet:

```
sudo systemctl enable dhcpcd@enp3s0.service
sudo systemctl enable netctl-auto@wlo1.service
sudo systemctl stop/disable netctl/NetworkManager/...
  • this app handles monitor setup
mons
  • stuff
i3lock-blur replaced i3lock as a screenlocker
wicd connman wpa_supplicant_gui
  • search disk an list memory usage
ncdu -x
  • list packages sorted by size
expac -H M "%011m\t%-20n\t%10d" $(comm -23 <(pacman -Qqen | sort) <(pacman -Qqg
base base-devel | sort)) | sort -n
  • remove orphant packages
sudo pacman -Rns $(pacman -Qtdq)
  • check for errors
sudo systemctl --failed sudo journalctl -p 3 -xb
  • wifi settings with nmcli
nmcli radio wifi on/off nmcli con nmcli dev
```