

```

/* Microchip Technology Inc. and its subsidiaries.  You may use this software
 * and any derivatives exclusively with Microchip products.
 *
 * THIS SOFTWARE IS SUPPLIED BY MICROCHIP "AS IS".  NO WARRANTIES, WHETHER
 * EXPRESS, IMPLIED OR STATUTORY, APPLY TO THIS SOFTWARE, INCLUDING ANY IMPLIED
 * WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A
 * PARTICULAR PURPOSE, OR ITS INTERACTION WITH MICROCHIP PRODUCTS, COMBINATION
 * WITH ANY OTHER PRODUCTS, OR USE IN ANY APPLICATION.
 *
 * IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE,
 * INCIDENTAL OR CONSEQUENTIAL LOSS, DAMAGE, COST OR EXPENSE OF ANY KIND
 * WHATSOEVER RELATED TO THE SOFTWARE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS
 * BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE.  TO THE
 * FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS
 * IN ANY WAY RELATED TO THIS SOFTWARE WILL NOT EXCEED THE AMOUNT OF FEES, IF
 * ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THIS SOFTWARE.
 *
 * MICROCHIP PROVIDES THIS SOFTWARE CONDITIONALLY UPON YOUR ACCEPTANCE OF THESE
 * TERMS.
 */

/*
 * File:
 * Author: velmurugan
 * Comments:
 * Revision history:
 */

// This is a guard condition so that contents of this file are not included
// more than once.
#ifndef LCD_H
#define LCD_H

void Lcd_Data(unsigned char);    //Sending data to the LCD

void Lcd_Cmd(unsigned char);    //Sending command to the LCD

void Lcd_Configuration(void);    //Configuring the LCD

void Lcd_Print(unsigned char*);    //Display print

void Lcd_Print(unsigned char* x){    //Printing the Data on LCD

    while(*x){
        Lcd_Data(*x);
        x++;
    }
}

//initial Configuration

void Lcd_Configuration()
{
    TRISD=0x00;

    PORTD=0x00;

    TRISC=(TRISC&0x3F);

    //Lcd Configuration
    Lcd_Cmd(0x0C); //Display on cursor off

    __delay_ms(10);

    Lcd_Cmd(0x01); //clear the display;

    __delay_ms(10);
}

```

```

    Lcd_Cmd(0x38); //Selecting 5X7 dots

    __delay_ms(10);

    Lcd_Cmd(0x06); //Cursor Auto move

    __delay_ms(10);

    Lcd_Cmd(0x81); //Selecting the first row

    __delay_ms(10);

}

//Write the Data to the LCD by character by character

void Lcd_Data(unsigned char data) {
    //enable bit RC7
    //RS bit RC6;

    PORTD = data; //Load the register with character

    PORTC |= 0x40;

    PORTC |= 0x80;

    PORTC &= ~0x80;

    __delay_ms(10);

}

//Sending the Instruction to the LCD

void Lcd_Cmd(unsigned char cmd) {

    PORTD = cmd; //Load the register with character

    PORTC &= ~0x40;

    PORTC |= 0x80;

    PORTC &= ~0x80;

    __delay_ms(10);

}
#ifdef __cplusplus
extern "C" {
#endif /* __cplusplus */

    // TODO If C++ is being used, regular C code needs function names to have C
    // linkage so the functions can be used by the c code.

#ifdef __cplusplus
}
#endif /* __cplusplus */

#endif /* XC_HEADER_TEMPLATE_H */

```