

What is the command to start Django's built-in development server?

- A. manage.py runserver
- B. manage.py --start
- C. manage.py run
- D. manage.py startserver --dev
- E. manage.py --run

Ans: A

Given a model named 'User' that contains a DateTime field named 'last_login', how do you query for users that have never logged in?

- A. User.objects.filter(last_login=None)
- B. User.objects.filter(last_login__null=True)
- C. User.objects.filter(last_login__isnull=False)
- D. User.objects.filter(last_login__isnull=True)
- E. User.objects.filter(last_login=Never)

Ans: D

What does the Django command 'manage.py shell' do?

- A. Starts a command line in whatever \$SHELL your environment uses.
- B. Starts a Django command prompt with your Python environment pre-loaded.
- C. Starts a Python command prompt with your Django environment pre-loaded.
- D. Loads a special Pythonic version of the Bash shell.
- E. Loads a Python command prompt you can use to sync your database schema remotely.

Ans: C

Assuming you've imported the proper Django model file, how do you add a 'User' model to the Django admin?

- A. admin.register(Users)
- B. admin.site(self, User)
- C. user.site.register(Admin)
- D. users.site.register(Admin)
- E. admin.site.register(User)

Ans: E

What is the Django command to start a new app named 'users' in an existing project?

- A. manage.py --newapp users
- B. manage.py newapp users
- C. manage.py --startapp users
- D. manage.py startapp users
- E. manage.py start users

Ans: D

What does a urls.py file do in Django?

- A. This file contains site deployment data such as server names and ports.
- B. It contains a site map of Django-approved URLs.
- C. It contains URL matching patterns and their corresponding view methods.
- D. You run this file when you get obscure 404 Not Found errors in your server logs.
- E. This file provides an up to date list of how-to URLs for learning Django more easily.

Ans: C

What is the command to run Django's development server on port 8080 on IP address 12.34.56.78?

- A. `manage.py --run 12.34.56.78 8080`
- B. `manage.py --dev 12.34.56.78:8080`
- C. `manage.py runserver 12.34.56.78:8000`
- D. `manage.py run 12.34.56.78:8080`
- E. `manage.py runserver 12.34.56.78:8080`

Ans: E

Django is written using what programming language?

- A. PHP
- B. Ruby
- C. Javascript
- D. Java
- E. Python

Ans: E

After you make a new 'app' in your existing Django project, how do you get Django to notice it?

- A. No additional action is required, Django notices new apps automatically.
- B. Run the `'manage.py validate'` command, and then start a new shell.
- C. Run the `'manage.py syncdb'` command.
- D. In `settings.py`, add the app to the `PROJECT_APPS` variable.
- E. In `settings.py`, add the new app to the `INSTALLED_APPS` variable.

Ans: E

What is the purpose of `settings.py`?

- A. To configure settings for the Django project
- B. To configure settings for an app
- C. To set the date and time on the server
- D. To sync the database schema

Ans: A

How do you define a 'name' field in a Django model with a maximum length of 255 characters?

- A. `name = models.CharField(max_len=255)`
- B. `model.CharField(max_length=255)`
- C. `name = models.CharField(max_length=255)`
- D. `model = CharField(max_length=255)`
- E. `name = model.StringField(max_length=auto)`

Ans: C

What is the definition of a good Django app?

- A. A good Django app provides a small, specific piece of functionality that can be used in any number of Django projects.
- B. A good Django app is a fully functioning website that has 100% test coverage.
- C. A good Django app is highly customized and cannot be used in multiple projects.

Ans: A

What is the most easiest, fastest, and most stable deployment choice in most cases with Django?

- A. FastCGI
- B. `mod_wsgi`
- C. SCGI
- D. AJP

Ans: B

How do you exclude a specific field from a ModelForm?

- A. Create a new Form, don't use a ModelForm
- B. Use the exclude parameter in the Meta class in your form
- C. Set the field to hidden
- D. You can not do this

Ans: B

Assuming you have a Django model named 'User', how do you define a foreign key field for this model in another model?

- A. model = new ForeignKey(User)
- B. user = models.IntegerKey(User)
- C. user = models.ForeignKey(User)
- D. models.ForeignKey(self, User)

Ans: C

What preferred method do you add to a Django model to get a better string representation of the model in the Django admin?

- A. __unicode__
- B. to_s(self)
- C. __translate__
- D. __utf_8__

Ans: A

What is ModelForm used for?

- A. To model an input form for a template
- B. To specify rules for correct form when writing Django code
- C. To define a form based on an existing model

Ans: C

What happens if MyObject.objects.get() is called with parameters that do not match an existing item in the database?

- A. The Http404 exception is raised.
- B. The DatabaseError exception is raised.
- C. The MyObject.DoesNotExist exception is raised.
- D. The object is created and returned.

Ans: C

A set of helpful applications to use within your Django projects is included in the official distribution. This module is called what?

- A. django.extras
- B. django.helpers
- C. django.utilities
- D. django.ponies
- E. django.contrib

Ans: E

What is the correct syntax for including a class based view in a URLconf?

- A. (r'^pattern/\$', YourView.as_view()),
- B. (r'^pattern/\$', YourView.init()),
- C. (r'^pattern/\$', YourView),
- D. (r'^pattern/\$', YourView()),

Ans: A

What is the command to start a new Django project called 'myproject'?

- A. django-admin.py startproject myproject
- B. django-admin.py --start myproject
- C. django.py startproject myproject
- D. django.py --new myproject
- E. django.py new myproject

Ans: A

How to make django timezone-aware?

- A. In settings.py: USE_L10N=True
- B. in views.py, import timezone
- C. in views.py, import tz
- D. in urls.py, import timezone
- E. In settings.py: USE_TZ=True

Ans: E

In Django how would you retrieve all the 'User' records from a given database?

- A. User.objects.all()
- B. Users.objects.all()
- C. User.all_records()
- D. User.object.all()
- E. User.objects

Ans: A

How can you define additional behavior and characteristics of a Django class?

- A. def setUp():
- B. class Meta:
- C. class __init__:
- D. def Meta():
- E. def __init__():

Ans: B

What is the Django shortcut method to more easily render an html response?

- A. render_to_html
- B. render_to_response
- C. response_render
- D. render

Ans: B

What does the Django command `manage.py validate` do?

- A. Checks for errors in your views.
- B. Checks for errors in your templates.
- C. Checks for errors in your controllers.
- D. Checks for errors in your models.
- E. Checks for errors in your settings.py file.

Ans: D

What is the correct way to include django's admin urls? from django.contrib import admin') from django.conf.urls import patterns, include, url urlpatterns = patterns("", _____)

- A. url(r'^admin/', admin.as_view(), name='admin'),
- B. url(r'^admin/', include(admin)),
- C. url(r'^admin/', include(admin.site.urls)),

- D. url(r'^admin/', admin.urls),
- E. admin.autodiscover()

Ans: C

Where is pre_save signal in Django

- A. from django.db.models import pre_save
- B. from django.db.models.signals import pre_save
- C. There is no pre_save signal
- D. from django.db.models.signal import pre_save

Ans: B

Given the Python data: mydata = [[0, 'Fred'], [1, 'Wilma']] How do you access the data in a Django template?

- A. {% for d in mydata %}

[{% d.1 %}](#)

{% endfor %}

- B. {% for d in mydata -%}

[{{ d.1 }}](#)

{% end -%}

- C. {% for d in mydata %}

[{{ d.1 }}](#)

{% endfor %}

- D. {{ for d in mydata }}

[{{ d\[1\] }}](#)

{{ endfor }}

- E. {% mydata.each |d| %}

[{{ d.2 }}](#)

{% end %}

Ans: C

What is the purpose of the STATIC_ROOT setting?

- A. Defines the URL prefix where static files will be served from .
- B. Defines the location where all static files will be copied by the 'collectstatic' management command, to be served by the production webserver.
- C. A project's static assets should be stored here to be served by the development server.
- D. Defines the location for serving user uploaded files.

Ans: B

How to create a DateTimeField named created and filled in only on the creation with the current time?

- A. created = models.CreationTimeField()
- B. created = models.DateTimeField(default=datetime.datetime.now())
- C. created = models.DateTimeField(auto_now_add=True, auto_now=True)
- D. created = models.DateTimeField(auto_now=True)
- E. created = models.DateTimeField(auto_now_add=True)

Ans: E

Given an IntegerField named 'widgets' in the Django model 'User' , how do you calculate the average number of widgets per user?

- A. User.objects.avg('widgets')
- B. Widget.objects.all().aggregate(Avg('users'))
- C. User.all().aggregate(Avg('widgets')).count()
- D. User.objects.all().aggregate(Avg('widgets'))
- E. User.objects.all().aggregate(Sum('widgets'))

Ans: D

What is the Django command to view a database schema of an existing (or legacy) database?

- A. manage.py legacydb
- B. django-admin.py schemadump
- C. manage.py inspect
- D. manage.py inspectdb
- E. django-admin.py inspect

Ans: D

What is the Django command to retrieve the first 10 'User' records from your database sorted by name descending?

- A. User.all().order_by('-name')[10:]
- B. User.objects.all().order('-name')[:10]
- C. User.objects.all().order_by('-name')[10]
- D. User.objects.all().order_by('name')[:10]
- E. User.objects.all().order('-name')[10:]

Ans: C

What is the definition of a Django Project?

- A. A specific piece of functionality that can be used in multiple Django apps.
- B. A fork of the official Django repo.
- C. A web site that uses the Django framework.
- D. A collection of configuration files and individual apps that form a web site.

Ans: D

Given a model named 'User' that contains a field named 'email', how do you perform a case-insensitive exact match for the email 'fred@aol.com'?

- A. User.objects.filter(email__icontains='fred@aol.com')
- B. User.objects.filter(email__iexact='fred@aol.com')
- C. User.objects.filter(email__contains='fred@aol.com')
- D. User.objects.filter(email__exact='fred@aol.com')
- E. User.objects.filter(email__matches='fred@aol.com')

Ans: B

Given a form with field foo, what should the validation method for this field be called?

- A. foo_clean

- B. `foo_is_valid`
- C. `clean_foo`
- D. `validate_foo`

Ans: C

You have created a Form class and wish to provide custom logic for validating the input in the "foo" field. What would you name your custom validation method?

- A. `clean_foo`
- B. `foo_clean`
- C. `clean_foo_field`
- D. `sanitize_foo`
- E. `validate_foo`

Ans: A

When customizing validation in a Form subclass named `MyForm`, how do you add an error message that is displayed as a form-wide error?

- A. Add the error to `MyForm.errors` in `MyForm.clean()`
- B. Raise `ValidationError` in `MyForm.clean_()`
- C. Raise `ValidationError` in `MyForm.clean()`
- D. Add the error to `MyForm._errors` in `MyForm.clean()`

Ans: C

Which class is a model field representing a path to a server-based image file?

- A. `django.db.models.fields.files.ImageFieldFile`
- B. `django.db.models.fields.files.ImageField`
- C. `django.db.models.fields.files.ImageField`
- D. `django.db.models.fields.files.ImageFieldField`
- E. `django.db.models.fields.files.ImageFieldDescriptor`

Ans: C

In `settings.py`, when `DEBUG` is set to _____, Django will email unhandled exceptional conditions.

- A. `False`
- B. `1`
- C. `Always`
- D. `True`
- E. `Never`

Ans: A

What is the command used to print the CREATE TABLE SQL statements for the given app name?

- A. `./manage.py sql myapp`
- B. `./manage.py schema myapp`
- C. `./manage.py showsql myapp`
- D. `django-admin.py dumpdata myapp`
- E. `./manage.py showschema myapp`

Ans: A

How do you create a recursive relationship in a model class named 'Company' in Django?

- A. `models.ForeignKey(Company)`
- B. `models.ForeignKey('self')`
- C. `models.ForeignKey('me')`
- D. `models.ForeignKey('Company')`

Ans: B

You have a Form defined with “password” and “confirm_password” fields. In what method of the “form” object would you validate that the values supplied in these fields match?

- A. form.clean_confirm_password
- B. form.clean
- C. form.validate
- D. form.sanitize_data
- E. form.clean_password

Ans: B

What command do you use to alter the fields Django displays for a given model in the Django admin ListView?

- A. auto_list_fields
- B. list_filter
- C. list_display
- D. fields_display
- E. fields_list

Ans: C

You can handle multiple Django forms with what keyword argument when creating forms?

- A. suffix
- B. prefix
- C. name
- D. infix

Ans: B

Which of these can be used to retrieve a setting from the settings module, and provide a default if the setting is not defined?

- A. get_setting(“SETTING_NAME”, default=default_value)
- B. getattr(“SETTING_NAME”, settings, default=default_value)
- C. settings.get(“SETTING_NAME”, default_value)
- D. getattr(settings, “SETTING_NAME”, default_value)

Ans: D

The Benevolent Dictators for Life of the Django Project are:

- A. Ian Bicking and Jannis Leidel
- B. Jacob Kaplan-Moss and Adrian Holovaty
- C. and Armando De La Veloper
- D. Guido van Rossum and Linus Torvalds
- E. Eric S. Raymond and Larry Wall

Ans: B

The django.contrib.contenttypes application provides

- A. functionality for working with varied file formats
- B. mimetypes used for returning http responses
- C. a generic interface for working with models
- D. none of the others

Ans: C

In your django template, if you need to get the content of the block from the django parent template, what do you need to add? {% block my_block %} _____ {% endblock %}

- A. {% super %}
- B. {{ extends block }}

- C. `super(block, self).__init__()`
- D. `{{ block.super }}`
- E. `{% block.super %}`

Ans: D

Which type of custom template tag returns a string?

- A. `inclusion_tag`
- B. `assignment_tag`
- C. `string_tag`
- D. `simple_tag`

Ans: D

What command compile Django's translation files?

- A. `./manage.py translate_files`
- B. `./manage.py compilei18n`
- C. `./manage.py compilemessages`
- D. `./manage.py i18n_update`
- E. `./manage.py compiletranslation`

Ans: C

A model's "full_clean()" method is called automatically when you call your model's "save()" method.

- A. True
- B. False

Ans: B

How would you perform a lookup on a model against a database aside from the default?

- A. `Model.objects.using('other').all()`
- B. `Model.objects.database('other').all()`
- C. `Model.objects.all(using='other')`
- D. `Model.objects.all(database='other')`

Ans: A

Given a model named 'User' that contains a CharField 'name', how do you query for users whose name starts with 'Fred' or 'Bob'?

- A. `User.objects.filter( name__regex=r'^(fred|bob)+' )`
- B. `User.objects.filter( name__iregex=r'^(fred|bob)+' )`
- C. `User.objects.filter( name__like=r'^(fred|bob)*' )`
- D. `User.objects.filter( name__iregex=r'^(fred|bob).+' )`
- E. `User.objects.filter( name__iregex=r'^(fred|bob)$' )`

Ans: D

Which model field type does NOT exist in Django?

- A. `CommaSeparatedIntegerField`
- B. `LargeIntegerField`
- C. `IPAddressField`
- D. `SlugField`
- E. `SmallIntegerField`

Ans: B

What datetime formatting would you apply in a template to display the following: 2013/03/20 8:00:06 AM ?

- A. `Y/m/d H:i`

- B. m/d/Y h:m:s
- C. Y/m/d g:i:s A
- D. Y-m-d H:m:s
- E. Y/m/d H:i:s A

Ans: C

How would you create a ForeignKey from a model named Transaction, to a model named Product, with no reverse relation?

- A. class Transaction(models.Model): product = models.ForeignKey(Product, related_name=None)
- B. class Transaction(models.Model): product = models.ForeignKey(Product, related_name='+')
- C. class Transaction(models.Model): product = models.ForeignKey(Product, related_name=False)
- D. class Transaction(models.Model): product = models.ForeignKey(Product, related_name="")

Ans: B

How to set a default order by in your Django model ? YourModel.objects.all() will be ordered by default without calling order_by() method

- A. Using META default_order attribute
- B. Using META order attribute
- C. Using META order_by attribute
- D. Using META ordering attribute
- E. Using META default_order_by attribute

Ans: D

What is the name of the Django decorator that hides sensitive info from error reports?

- A. @secret_variables
- B. @sensitive_variables
- C. @hide_fields
- D. @secret_fields
- E. @sensitive_fields

Ans: B

By using django.contrib.humanize, you can use the following filter in your template to display the number 3 as three.

- A. apnumber
- B. intcomma
- C. intword
- D. ordinal
- E. naturaltime

Ans: A