UL Product **iQ**™



UQGS.S36306 - Heat-automatic Fire Detectors

Heat-automatic Fire Detectors

See General Information for Heat-automatic Fire Detectors

MTECH FIRE DETECTION SYSTEMS LTD

S36306

KIBBUTZ HASOLELIM 17905 D.N HAMOVIL, ISRAEL

					Spacing (Ft)		
Model No.	Туре	Compatibility Restrictions	Contact Arrangement	Temp Range (°F)	Smooth Ceiling	to Wall or Partition	
MA-330(**)	FT/ROR	D2	-	135, 194	50	25	
MA-340	FT	D2	-	135	50	25	
MB-230	FT	D2	-	135	50	25	
MB-240	FT	D2	-	135	50	25	

Base ModelRelated DetectorControl Unit Compatibility RestrictionsMA-300MA-320, MA-340B2MB-300MB-220, MB-240B2

- B2 For connection to Listed control units with which compatibility was determined by test or a review of circuit parameters. Interconnection and compatible models indicated on installation wiring diagram for detector (base) and/or control unit.
- D2 For connection to Listed control units with which compatibility was determined by test or a review of circuit parameters. Interconnection and compatible models indicated on installation wiring diagram for detector (base) and/or control unit.

FT/ROR - Fixed temperature/rate of rise combination

- FT Fixed temperature
- $(\ensuremath{^{\star\star}})$ Temperature rating is programmble at the Listed compatible control unit

Note - Detectors MB-230, MB-240 is Compatible with Detector Base MB-300 and Detectors MA-330, MA-340 is Compatible with Base MA-300

Last Updated on 2020-06-18

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"