

```
1 default
10 hr active Et0/2, Et0/3
20 sales active Et0/0
1002 fddi-default active Et0/1
1003 token-ring-default act/unsup
1004 fddinet-default act/unsup
1005 trnet-default act/unsup
SW1#conf t act/unsup
```

Enter configuration commands, one per line. End with CNTL/Z.

```
SW1(config)#int e0/2
SW1(config-if)#switchport trunk encapsulation dot1q
```

% Invalid input detected at '^' marker.

```
SW1(config-if)#switchport trunk encapsulation dot1q
SW1(config-if)#switchport mode trunk
SW1(config-if)#exit
SW1(config)#exit
SW1#s
```

*Aug 10 09:25:48.855: %SYS-5-CONFIG_I: Configured from console by console

```
SW1#show int trunk

Port      Mode      Encapsulation  Status      Native vlan
Et0/2     on        802.1q         trunking    1

Port      Vlans allowed on trunk
Et0/2     1-4094

Port      Vlans allowed and active in management domain
Et0/2     1,10,20
```

SW1 x SW2 x

```


SW2(config)#int e0/0
SW2(config-if)#switchport access vlan 10
SW2(config-if)#exit
SW2(config)#int e0/1
SW2(config-if)#switchport access vlan 20
SW2(config-if)#exit
SW2(config)#int e0/2
SW2(config-if)#switch
*Aug 10 09:30:42.923: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)
SW2(config-if)#switchport trunk encapsulation dot1q
SW2(config-if)#switchport mode trunk
SW2(config-if)#exit
SW2(config)#exit
SW2#sh
*Aug 10 09:32:39.309: %SYS-5-CONFIG_I: Configured from console by console
SW2#show mac table
^
% Invalid input detected at '^' marker.

SW2#
SW2#show mac address-table
      Mac Address Table
-----
Vlan    Mac Address      Type      Ports
----
1       aabb.cc00.0120   DYNAMIC   Et0/2
10      aabb.cc00.0120   DYNAMIC   Et0/2
20      aabb.cc00.0120   DYNAMIC   Et0/2
Total Mac Addresses for this criterion: 3
SW2#


```





VLAN 10
10.0.0.10




VLAN 20
20.0.0.10



VLAN 10
10.0.0.20



VLAN 20
20.0.0.20



TERMINAL (2)

Physical