VENKATESH MOGILI

#Web Guru

తెలుగు లో

PART - 1

React JS Crash Course

Introduction

Applications of

Virtual DOM

#Jobs

#Trendy

Create Project

node
JS
®

Contents

- ReactJS Introduction
- Applications of React
- Virtual DOM
- Popularity of React
- Create Project
- Display “Hello World!”



Before Proceeding to React JS…

You should be familiar with the following languages.

- HTML
- CSS
- JavaScript (including ES6 features)



What is React JS?

- React JS is UI **Library**
- Developed By Facebook
- It's Open Source
- It's released on 2013
- Current Stable Version 17.0.1



Applications of React JS

- React JS can be used to develop Single Page Web Applications.
- React Native with the similar React JS syntax can be used to develop Cross Platform Mobile Applications.
- It uses Virtual DOM for updating the DOM changes.

Virtual DOM



- It takes lightweight copy of Real DOM and keeps in memory and syncs with the Real DOM by using ReactDOM Library.
- It improves lot of performance.

Popularity Of React JS



- Current Trending Technology for frontend developers.

VENKATESH MOGILI
#Web Guru

Let's Start Coding...



VENKATESH MOGILI
#Web Guru

How to Create React JS Project?

- npm install create-react-app –g
- create-react-app myproject

OR

- npx create-react-app myproject



Naming Convention for Project?

- Project Name should be URL Friendly.
- It should not contain any special characters except hyphen(-) and underscore(_)
- It should not contain any Capital Letters.

Hello World!



VENKATESH MOGILI

#Web Guru

తెలుగు లో

PART - 2

React JS

Crash Course

Contents

- JSX?
- Components
- Props
- State
- LifeCycle Methods
- Event Handling
- Rendering
- Lists
- Forms
- Todo Management Application



VENKATESH MOGILI
#Web Guru

Useful VS Code Extensions

- Prettier Now
- ES7/React Snippets



What is JSX?

- JSX stands for JavaScript XML which means combination of both JavaScript and XML syntax.
- JavaScript syntax:
  - let button;
- XML syntax:
  - <button>Click here</button>
- JSX syntax:
  - let button = <button>Click here</button>;



Is JSX Mandatory?

- It's recommended to use JSX for React Applications.
- It's not mandatory, We can use babel syntax instead of JSX.
- Babel syntax:
- import React from 'react';
- let button = React.createElement('button',null,'Hello');
- Equivalent syntax in JSX:
- let button = <button>Hello</button>;

HTML Tag/React Component

Children

Properties



Any extra syntax changes?

- class → className
- onclick → onClick
- onchange → onChange
- checked → defaultChecked
- selected → defaultValue
- for → htmlFor
- style="normal css" → style={ {camel case css}}

```
<div className="col-md-12"></div>
```

```
<button onClick={}>Click here</button>
```

```
<select onChange={}>Click here</select>
```

```
<input type='checkbox' defaultChecked />
```

```
<select type='checkbox' defaultValue></select>
```

```
<label htmlFor="firstname">FirstName</label>
```

```
<button style={{backgroundColor:"blue",fontSize:"30px"}}>Stylish Button</button>
```

Stylish Button

JSX Summary

- JSX is a special syntax for creating user interface using React Library.
- JSX stands for JavaScript XML.
- It's not mandatory to use but recommended to use for learning React fast.
- Babel is the compiler for JSX Syntax.
- Few attribute changes such as className,onClick….



What is Component?

- Any UI block can be considered as a Component.
- It can be reusable. Create once use anywhere.





Types of Components in React?

- There are 2 types of components available in React.

- 1.Functional Component

```
import React from 'react'

export default function Button() {
    return (
        <div>
            <button>Submit</button>
        </div>
    )
}
```

- 2.Class Component

```
import React, { Component } from 'react'

export default class Button extends Component {
    render() {
        return (
            <div>
                <button>Submit</button>
            </div>
        )
    }
}
```



Component Naming Convention?

- React Component Name should start with Capital Letter.

```
import React from 'react'

export default function Button() {
    return (
        <div>
            <button>Submit</button>
        </div>
    )
}
```

```
import React from 'react'

export default function button() {
    return (
        <div>
            <button>Submit</button>
        </div>
    )
}
```

VENKATESH MOGILI
#Web Guru

Components Summary

- Any UI block can be considered as a Component.
- It can be reusable. Create once use anywhere.
- There are 2 types of components available in React.
  1.Functional Components & 2.Class Components
- React Component Name should start with Capital Letter.



Props in React?

- Props full form is Properties, which means simply attributes.
- Props will be used to pass the data between the components.
- We can pass any valid JavaScript expression as prop.

App Component → Button Component

```
import React from 'react';
import Button from './components/Button';

function App() {
    return (
        <div>
            <Button title='Click here' />
        </div>
    );
}
export default App;
```

```
import React from 'react';

export default function Button(props) {
    return (
        <div>
            <button>{props.title}</button>
        </div>
    );
}
```

Output: Click here



Props in React?

- Data can be passed in one way only. Unidirectional or top-down.
- From the below example, title is passed from App component, but Button component won't know whether it's value is typed manually or passed from state variable or passed from it's parent component.

App Component → Button Component

```
import React from 'react';
import Button from './components/Button';

function App() {
    return (
        <div>
            <Button title='Click here' />
        </div>
    );
}
export default App;
```

```
import React from 'react';

export default function Button(props) {
    return (
        <div>
            <button>{props.title}</button>
        </div>
    );
}
```

Output: Click here



State in React?

- State is a local variable for the component.
- Any state in one component won't be accessible to other components, which means by default states are encapsulated in components.

App Component

```
import React, { useState } from 'react';
import Button from './components/Button';

function App() {
    const [ title ] = useState('Click here');
    return (
        <div>
            <button>{title}</button>
            <Button />
        </div>
    );
}
export default App;
```

Output: Click here

Submit

Button Component

```
import React, { Component } from 'react';

export default class Button extends Component {
    state = {
        title: 'Submit',
    };
    render() {
        return (
            <div>
                <button>{this.state.title}</button>
            </div>
        );
    }
}
```

Output: Submit

Props and State Summary

- Properties are nothing but attributes, which can be used to pass the data from one component and another component.
- Any valid JavaScript expression can be passed a prop.
- State is local variable of the component, which is by default encapsulated to it's own component.
- setState method can be used to update the state values.



VENKATESH MOGILI

#Web Guru

తెలుగు లో

PART - 3

React JS

Crash Course

Contents

- **Project Structure**
- Styles
- LifeCycle Methods
- Event Handling
- Rendering
- Lists
- Forms

Contents

- ✓ Project Structure
- ➢ **Styles**
- ➢ LifeCycle Methods
- ➢ Event Handling
- ➢ Rendering
- ➢ Lists
- ➢ Forms

Contents

- ✓ Project Structure
- ✓ Styles
- ➢ **LifeCycle Methods**
- ➢ Event Handling
- ➢ Rendering
- ➢ Lists
- ➢ Forms



LifeCycle methods in Class Component?

React component has three lifecycle methods.

- ✓ 1.Mounting (Putting elements into the DOM)
- ✓ 2.Updating (when component is updated)
- ✓ 3.Unmounting (when component is removed from the DOM)

I) Mounting has the below order of execution.

1.constructor() →optional

2.getDerivedStateFromProps() →optional

3.render() →Mandatory

4.componentDidMount() →optional



LifeCycle methods in Class Component?

II) Updating has the below order of execution.

1.getDerivedStateFromProps() →optional

2.shouldComponentUpdate() →optional

3.render() →Mandatory

4.getSnapshotBeforeUpdate() →optional

5.componentDidUpdate() →optional

III) Unmounting will run the below lifecycle method.

1.componentWillUnmount()



LifeCycle methods in Functional Component?

- The below useEffect hook will be used for all the three lifecycle phases.

```
useEffect(()=>{
},[ ])
```



Contents

- ✓ Project Structure
- ✓ Styles
- ✓ LifeCycle Methods
- ➢ **Event Handling**
- ➢ Rendering
- ➢ Lists
- ➢ Forms

Event Handling

- When user performs any action, it should be considered as an event.
- onClick button, onChange dropdown values, onCheck checkbox etc.,

```
import React, { Component } from 'react';

export default class Button extends Component {
    constructor(props) {
        super(props);
        this.state = {
            title: 'Submit',
        };
        this.submit = this.submit.bind(this);
    }
    submit() {
        console.log('Submitted');
    }
    render() {
        return (
            <div>
                <button onClick={this.submit}>{this.state.title}</button>
            </div>
        );
    }
}
```

Event Handling

- Inline Binding

```
import React, { Component } from 'react';

export default class Button extends Component {
    constructor(props) {
        super(props);
        this.state = {
            title: 'Submit',
        };
    }
    submit() {
        console.log('Submitted');
    }
    render() {
        return (
            <div>
                <button onClick={this.submit.bind(this)}>{this.state.title}</button>
            </div>
        );
    }
}
```



Event Handling

- ES6 Arrow Function

```
import React, { Component } from 'react';

export default class Button extends Component {
    constructor(props) {
        super(props);
        this.state = {
            title: 'Submit',
        };
    }
    submit = () => {
        console.log('Submitted');
    };
    render() {
        return (
            <div>
                <button onClick={this.submit}>{this.state.title}</button>
            </div>
        );
    }
}
```



Event Handling

- ES6 Inline Arrow Function

```
import React, { Component } from 'react';

export default class Button extends Component {
    constructor(props) {
        super(props);
        this.state = {
            title: 'Submit',
        };
    }
    submit() {
        console.log('Submitted');
    }
    render() {
        return (
            <div>
                <button onClick={() => this.submit()}>{this.state.title}</button>
            </div>
        );
    }
}
```

VENKATESH MOGILI
#Web Guru

Event Handling

- Passing the arguments to the function from the event.

```
import React, { Component } from 'react';

export default class Button extends Component {
    constructor(props) {
        super(props);
        this.state = {
            title: 'Submit',
        };
    }
    submit(e) {
        console.log('Submitted', e);
    }
    render() {
        return (
            <div>
                <button onClick={(e) => this.submit(e)}>{this.state.title}</button>
            </div>
        );
    }
}
```

VENKATESH MOGILI
#Web Guru

LifeCycle methods and Event Handling Summary

- React has 3 lifecycle methods, which are Mounting, Updating, Unmounting and render method is mandatory to display the output in DOM.
- Any event can be performed by user action such as onClick,onChange etc.,



LifeCycle methods and Event Handling Summary

Break



Contents

- ✓ Project Structure
- ✓ Styles
- ✓ LifeCycle Methods
- ✓ Event Handling
- ➢ **Rendering**
- ➢ Lists
- ➢ Forms

Conditional Rendering

JavaScript conditions will be executed like below.

```
If(a && b && c){
        console.log("output");
}
```

- If a is true, then only b will be executed, similarly c.
- We can use the same condition for elements whichever we want to display, we will write a condition before it.
- Example:

```
{this.state.user && <h1>{this.state.username}</h1>}
```



Using Ternary Operator

JavaScript Ternary operation looks like below code.

a?"display":"won't display";

- If a is true, then it will display, otherwise it won't display.
- We can use the same operation for elements whichever we want to display, we will write the ternary operator before it. If condition is false, we should pass null or '' (empty string) or any false value.
- Example:

{this.state.user?<h1>{this.state.username}</h1>:null}



Contents

- ✓ Project Structure
- ✓ Styles
- ✓ LifeCycle Methods
- ✓ Event Handling
- ✓ Rendering
- ➢ **Lists**
- ➢ Forms

Displaying List of Items

JavaScript ES6 has map function which iterates the loop and returns the new values.

- Example:

```
this.state={
        users : [{name:"Venkatesh"},{name:"Chinni"}];
    }
{this.state.users.map((user)=>(
        <p>{user.name}</p>
        )
)}
```



List without keys

Add Item to end

```
<ul>
    <li>Venkatesh</li>
    <li>Chinni</li>
</ul>
```

```
<ul>
    <li>Venkatesh</li>
    <li>Chinni</li>
    <li>Vivek</li>
</ul>
```

Add Item to start

```
<ul>
    <li>Venkatesh</li>
    <li>Chinni</li>
</ul>
```

```
<ul>
    <li>Vivek</li>
    <li>Venkatesh</li>
    <li>Chinni</li>
</ul>
```



List with keys

Add Item to end

```
<ul>
    <li key="0">Venkatesh</li>
    <li key="1">Chinni</li>
</ul>
```

```
<ul>
    <li key="0">Venkatesh</li>
    <li key="1">Chinni</li>
    <li key="2">Vivek</li>
</ul>
```

Add Item to start

```
<ul>
    <li key="0">Venkatesh</li>
    <li key="1">Chinni</li>
</ul>
```

```
<ul>
    <li key="2">Vivek</li>
    <li key="0">Venkatesh</li>
    <li key="1">Chinni</li>
</ul>
```

VENKATESH MOGILI
#Web Guru

Displaying List of Items

JavaScript ES6 has map function which iterates the loop and returns the new values.

- Example:

```
this.state={
    users : [{name:"Venkatesh"},{name:"Chinni"}];
 }
{this.state.users.map((user,index)=>(
    <p key={index}>{user.name}</p>
    )
 )}
```

Contents

- ✓ Project Structure
- ✓ Styles
- ✓ LifeCycle Methods
- ✓ Event Handling
- ✓ Rendering
- ✓ Lists
- ➢ **Forms**

Forms

- Forms can be used as we use in html.
- When we do onSubmit, we can prevent reload the page by using event.preventDefault() which won't reload the page and output will be displayed.



Lifting State Up

- When we implement individual components with their own functionalities, there can a situation to use those functionalities in it's parent component or in it's sibling component.
- In this case, we will completely move the functionalities to it's parent component. Which is called State Lifting.



VENKATESH MOGILI

#Web Guru

తెలుగు లో

Part-4
Todo App

React JS
Crash Course

File Upload using React & Cloudinary

Choose Files No file chosen

Upload

File Upload (Multi and Single)

తెలుగు లో



Don't forget to SUBSCRIBE

Like Share Comment

Thank you for watching...

Venkatesh Mogili

#WebGuru

React JS

Crash Course

తెలుగు లో

PART – 5

Routing

Contents

- **Routing Introduction**
- Routers
- Route Matchers
- Route Navigation
- Routing with Hooks
- Authentication with route
- Lazy Loading/Code splitting Components
- Example Scenarios
- Summary

Prerequisites and Project Setup

- ✓ Before learning Routing concept, better to have basic knowledge on React concepts like props, components, children, JSX syntax.

- ➢ Create a react project.

  npx create-react-app routing-crash-course

- ➢ Install react-router-dom package.

  npm i react-router-dom

- ➢ Install Bootstrap and import in index.css file

  npm i bootstrap@next

```
@import 'bootstrap/dist/css/bootstrap.min.css';
```

Routing

- Routing means simply navigating from one URL to another URL without refreshing the application every time.

Primary Components:

There are three primary categories of components in React Router:

1) **routers**, like <BrowserRouter> and <HashRouter>
2) **route matchers**, like <Route> and <Switch>
3) **navigation**, like <Link>, <NavLink>, and <Redirect>

- All of the components that you use in a web application should be imported from **react-router-dom**

- **react-router-dom (for web)**
- **react-router-native (for mobile)**

Contents

- ✓ Routing Introduction
- ➢ **Routers**
- ➢ **Route Matchers**
- ➢ **Route Navigation**
- ➢ Routing with Hooks
- ➢ Authentication with route
- ➢ Lazy Loading/Code splitting Components
- ➢ Example Scenarios
- ➢ Summary

Browser Router VS Hash Router

1) Browser Router:

When we have big production-ready applications which serve backend, it is recommended to use <BrowserRouter>

Example: http://localhost:3000/about

As server supports normal url system, it will take the complete path for server side api calls for GET requests.

2) Hash Router:

When we have small client side applications which doesn't need backend we can use <HashRouter> because when we use hashes in the URL/location bar browser doesn't make a server request.

Example: http://localhost:3000/#/about

Server will ignore about as it appended after #, server only takes the url till / (slash).



---

forceRefresh can imitate the normal url functionality.

basename can be used to give a global app url for our application.

getUserConfirmation Prompt before moving to another page can be checked

Switch

Switch:

- When a <Switch> is rendered, it searches through its children <Route> elements to find one whose path matches the current URL.
- When it finds one, it renders that <Route> and ignores all others.
- This means that you should put <Route>s with more specific (typically longer) paths **before** less-specific ones.
- If no <Route> matches, the <Switch> renders nothing (null).

Example:
/projects/:id
/projects
/about
/home
/dashboard



Route

Route:

***path** - (/projects, /home, /dashboard etc.,)

Every route has props (match, location, history)
component – we can pass component to render for particular route. (it will create a new React component whenever we render it)

render – we can use inline rendering for particular route. (it won't create new react component, instead it will take previous route props).

children – we can pass JSX elements to render for particular route. (similar to render but it works even if there is no match).

children>component>render

exact – to match exact url.(browser location. Works for **/about** also **/about/)**
strict – to match exact url including slash. (works for /about/ but not /about)
sensitive – to match url with case sensitive. (works for /About but not /about)



Navigation

Navigation:

It used to change navigations by using components like <Link>, <NavLink> and <Redirect>

<Link>: uses **to** prop to navigate to specified path.
<NavLink>: it will do the same like Link but also having extra feature like active link or not.
<Redirect>: it redirects to specified path.



Link, NavLink, Redirect

Link:

to - string (/home)
to - object ({to:"/home"})
to - function (location=>({...location,pathname:"/home"})

NavLink:

to – string
activeClassName – className
activeStyle – object styling.
exact – style applies only if url matches exactly
strict - style applies only if url matches exactly including slash (/)

Redirect:

to - string (/home)
to - object ({pathname:"/home"})
from – string



Contents

- ✓ Routing Introduction
- ✓ Routers
- ✓ Route Matchers
- ✓ Route Navigation
- ➢ **Routing with Hooks**
- ➢ Authentication with route
- ➢ Lazy Loading/Code splitting Components
- ➢ Example Scenarios
- ➢ Summary

Using Hooks

We can use hooks to do the similar things which can be done with Switch and Route.
useHistory, useLocation, useParams, useRouteMatch

1.useHistory: it handles push, pop etc., history functionality. (history.push("/home"))

2.useLocation: we can get location details by using this. (location.pathname)

3.useParams: it provides the params of the matched url. ({id})

4.useRouteMatch: we can do whatever things can be done with <Route> by using this hook.

Contents

- ✓ Routing Introduction
- ✓ Routers
- ✓ Route Matchers
- ✓ Route Navigation
- ✓ Routing with Hooks
- ➢ **Authentication with route**
- ➢ **Lazy Loading/Code splitting Components**
- ➢ **Example Scenarios**
- ➢ Summary

Example Scenarios

1. Default Homepage if url has only slash.
2. 404 Not Found! (if none of the paths are matching)
3. url parameters (by using useParams())
4. Auth redirects based on conditions.
5. Redirect from old site url to new site url
6. Nested routing
7. Sidebar routing
8. Query parameters

Contents

- ✓ Routing Introduction
- ✓ Routers
- ✓ Route Matchers
- ✓ Route Navigation
- ✓ Routing with Hooks
- ✓ Authentication with route
- ✓ Lazy Loading/Code splitting Components
- ✓ Example Scenarios
- ➢ **Summary**

Summary

1. Routing is very useful while developing single page applications or any kind of web/mobile applications which has lot of page transitions from one page to another.

2. Primary components in react-router-dom package are three.
   1. Routers
   2. Route matchers
   3. Navigation

3. We can use hooks to do the same functionalities as Switch, Route components.

4. We can use routing for many applications for many scenarios.

Exercise and References

Exercise:

1. Display either login or logout by checking with user data stored in local storage.

2. Try to add routing to todo-app which we built in this series. Or make a new app with any of your idea and add routing to it along with authentication.

References:

https://www.freecodecamp.org/news/how-to-optimize-react-applications-with-lazy-loading-232183e02768/

https://reactjs.org/docs/code-splitting.html

https://reactrouter.com/web/guides/quick-start

Venkatesh Mogili

#WebGuru

React JS

Crash Course

Next Video

తెలుగు లో

PART – 6

Hooks

Sharing is caring 😃

SUBSCRIBE

LIKE

SHARE

COMMENT

Welcome back

Subscribe

and

Stay Tuned

For more updates...

VENKATESH MOGILI

#Web Guru

Venkatesh Mogili

#WebGuru

React JS

Crash Course

తెలుగు లో

PART – 6

Hooks



Contents

- **Hooks Introduction**
- Rules Of Hooks
- Basic Hooks:
- useState, useEffect, useContext, customHooks
- Additional Hooks:
- useReducer,
- useMemo,
- useCallback,
- useRef,
- useImperativeHandle,
- useLayoutEffect,
- useDebugValue
- Summary

Introduction

- Hooks are a new addition in **React 16.8 version.**

1) **Hooks don't replace your knowledge of React concepts.** Instead, Hooks provide a more direct API to the React concepts you already know: props, state, context, refs, and lifecycle.

2) **100% backwards-compatible.** Hooks don't contain any breaking changes.

3) **There are no plans to remove classes from React.**

- It does not work inside classes.

Rules of Hooks

❖ Hooks are JavaScript functions, but they impose two additional rules:

1. Only call Hooks **at the top level**. Don't call Hooks inside loops, conditions, or nested functions.

2. Only call Hooks **from React function components**. Don't call Hooks from regular JavaScript functions.

✓ one other valid place to call Hooks — your own custom Hooks.

Contents

- ✓ Hooks Introduction
- ✓ Rules Of Hooks
- ➢ **Basic Hooks:**
- ➢ **useState, useEffect, useContext, customHooks**
- ➢ Additional Hooks:
- ➢ useReducer,
- ➢ useMemo,
- ➢ useCallback,
- ➢ useRef,
- ➢ useImperativeHandle,
- ➢ useLayoutEffect,
- ➢ useDebugValue
- ➢ Summary

useState

❖ Let's understand Object and Array De-structuring before hooks.

1) **useState** returns a pair: **the current state value** and a **function** that lets you update it.

2) It's similar to this.setState in a class, except it doesn't merge the old and new state together.

3) We can use single and many useState hooks.

4) Hooks execute one after another in a sequence.

useEffect

- useEffect, adds the ability to perform side effects from a function component.

1) It serves the same purpose as componentDidMount, componentDidUpdate, and componentWillUnmount in React classes, but unified into a single API

2) By default, React runs the effects after every render — including the first render.

3) Just like with useState, you can use more than a single effect in a component.

Custom Hooks

- Custom Hooks are more of a convention than a feature. If a function's name starts with "use" and it calls other Hooks, we say it is a custom Hook.

- The state of each component is completely independent. Hooks are a way to reuse stateful logic, not state itself. In fact, each call to a Hook has a completely isolated state — so you can even use the same custom Hook twice in one component.

useContext

- useContext hook makes it easy to pass data throughout your app without manually passing props down the tree.

- Context can make a nice simple alternative to Redux when your data is simple or your app is small.

Contents

- ✓ Hooks Introduction
- ✓ Rules Of Hooks
- ✓ Basic Hooks:
- ✓ useState, useEffect, useContext, customHooks
- ➢ **Additional Hooks:**
- ➢ **useReducer,**
- ➢ **useMemo,**
- ➢ **useCallback,**
- ➢ **useRef,**
- ➢ **useImperativeHandle,**
- ➢ **useLayoutEffect,**
- ➢ **useDebugValue**
- ➢ Summary

useReducer

- ✓ convenient for dealing with more complex state changes in React components.
- ✓ useReducer borrows some theory from **Redux**, namely the concepts of reducers, action, and dispatch.

useMemo

❖ Returns a **memoized value**.

1) Whenever a huge computation is involved, then we can use useMemo hook.

2) Whenever there is no need of re-rendering If the respective state is not changed.

useCallback

❖ Returns a **memoized callback** instead of a single value like useMemo.

1) We use the result as a function, so that if it is required, we can pass parameters to it for doing operations.

2) Both useMemo and useCallback are equivalent but with the small difference.

useRef

- ✓ The useRef Hook is a function that returns a mutable ref object whose .current property is initialized with the passed argument (initialValue). The returned object will persist for the full lifetime of the component.

- ✓ A ref created with useRef will be created only when the component has been mounted and preserved for the full lifecycle.

useImperativeHandle

- ✓ **useImperativeHandle** customizes the instance value that is exposed to parent components when using ref.

useLayoutEffect

- ✓ Updates scheduled inside useLayoutEffect will be flushed synchronously, before the browser has a chance to paint.



useDebugValue

- ✓ **useDebugValue** can be used to display a label for custom hooks in React DevTools.

Contents

- ✓ Hooks Introduction
- ✓ Rules Of Hooks
- ✓ Basic Hooks:
- ✓ useState, useEffect, useContext, customHooks
- ✓ Additional Hooks:
- ✓ useReducer,
- ✓ useMemo,
- ✓ useCallback,
- ✓ useRef,
- ✓ useImperativeHandle,
- ✓ useLayoutEffect,
- ✓ useDebugValue
- ➢ **Summary**

Summary

- ✓ Hooks are introduced in React 16.8 version.
- ✓ We have basic hooks such as useState,useEffect, useContext etc., and additional hooks and customHooks that we can create by our own.
- ✓ We can use hooks in functional components only.
- ✓ We can't use in class components.
- ✓ We should follow 2 rules to use hooks:
  1. Only call Hooks **at the top level**
  2. Only call Hooks **from React function components**
  3. We can call in **custom hooks as well**

Venkatesh Mogili
#WebGuru

తెలుగు లో

PART – 7

API Calls, Import Export, JEST Unit Testing

React JS
Crash Course

Sharing is caring 😃

SUBSCRIBE

LIKE

SHARE

COMMENT

Thank you for watching

Subscribe

and

Stay Tuned

For more updates...

VENKATESH MOGILI

#Web Guru