

R1

```
Ethernet0/2          20.0.0.1      YES manual down      down
Ethernet0/3          unassigned    YES TFTP  down      down
R1#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
R1(config)#int e0/2
R1(config-if)#no ip address 20.0.0.1 255.0.0.0
R1(config-if)#shu
*Jul 15 06:34:14.054: %LINK-3-UPDOWN: Interface Ethernet0/2, changed state to up
*Jul 15 06:34:15.054: %LINEPROTO-5-UPDOWN: Line protocol on Interface Ethernet0/2, changed state to up
R1(config-if)#shut
R1(config-if)#exit
R1(config)#
*Jul 15 06:34:23.358: %LINK-5-CHANGED: Interface Ethernet0/2, changed state to administratively down
*Jul 15 06:34:24.362: %LINEPROTO-5-UPDOWN: Line protocol on Interface Ethernet0/2, changed state to down
R1(config)#do sh ip int br
Interface            IP-Address      OK? Method Status              Protocol
Ethernet0/0          10.0.0.1        YES manual up                  up
Ethernet0/1          unassigned      YES TFTP  up                  up
Ethernet0/2          unassigned      YES unset administratively down down
Ethernet0/3          unassigned      YES TFTP  down               down
R1(config)#int e0/1
R1(config-if)#ip add 20.0.0.1 255.0.0.0
R1(config-if)#no shut
R1(config-if)#exit
R1(config)#exit
R1#
*Jul 15 06:35:25.760: %SYS-5-CONFIG_I: Configured from console by console
R1#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PBR

Gateway of last resort is not set

  10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       10.0.0.0/8 is directly connected, Ethernet0/0
L       10.0.0.1/32 is directly connected, Ethernet0/0
  20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       20.0.0.0/8 is directly connected, Ethernet0/1
L       20.0.0.1/32 is directly connected, Ethernet0/1
S       30.0.0.0/8 [1/0] via 20.0.0.2
S       40.0.0.0/8 [1/0] via 20.0.0.2
R1#
```



R2

```
R2#
R2#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
R2(config)#int e0/0
R2(config-if)#ip add 20.0.0.2 255.0.0.0
R2(config-if)#no shut
R2(config-if)#exit
R2(config)#int e0/1
R2(config-if)#ip add 30.0.0.1 255.0.0.0
R2(config-if)#no shut
R2(config-if)#exit
R2(config)#
*Jul 15 06:19:50.795: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)
R2(config)#ip route 40.0.0.0 255.0.0.0 30.0.0.2
R2(config)#exit
R2#
*Jul 15 06:27:43.189: %SYS-5-CONFIG_I: Configured from console by console
R2#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
R2(config)#ip route 10.0.0.0 255.0.0.0 20.0.0.1
R2(config)#exit
R2#
*Jul 15 06:28:20.510: %SYS-5-CONFIG_I: Configured from console by console
R2#
```



R3

```
R3#conf t
Enter configuration commands, one per line. End with CNTL/Z.
R3(config)#int e0/1
R3(config-if)#ip add 30.0.0.2 255.0.0.0
R3(config-if)#no shut
R3(config-if)#exit
R3(config)#int e0/0
R3(config-if)#ip add 40.0.0.1 255.0.0.0
R3(config-if)#no shut
R3(config-if)#exit
R3(config)#
*Jul 15 06:19:42.251: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)
R3(config)#ip route 10.0.0.0 255.0.0.0 30.0.0.1
R3(config)#exit
R3#
*Jul 15 06:29:27.010: %SYS-5-CONFIG_I: Configured from console by console
R3#conf t
Enter configuration commands, one per line. End with CNTL/Z.
R3(config)#ip route 20.0.0.0 255.0.0.0 30.0.0.1
R3(config)#exit
R3#
*Jul 15 06:29:49.005: %SYS-5-CONFIG_I: Configured from console by console
R3#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

S    10.0.0.0/8 [1/0] via 30.0.0.1
S    20.0.0.0/8 [1/0] via 30.0.0.1
     30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C     30.0.0.0/8 is directly connected, Ethernet0/1
L     30.0.0.2/32 is directly connected, Ethernet0/1
     40.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C     40.0.0.0/8 is directly connected, Ethernet0/0
L     40.0.0.1/32 is directly connected, Ethernet0/0
R3#
```

ENG
IN12:21 PM
15-Jul-26

